Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

	Expires:	July	3
Lease	Serial No.		
NMN	M14124		

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use th	is form for proposals to	drill or to re-enter an	6. If In	idian, Allottee or Tribe Name
abandoned we	II. Use form 3160-3 (AP	טן זor such proposals.		
SUBMIT IN TRI	PLICATE - Other instruc	ctions on reverse side.	7. If U	nit or CA/Agreement, Name and/or No.
Type of Well			8. Well MĄ	Name and No. RQUARDT 1 FEDERAL 015H
Name of Operator CIMAREX ENERGY CO OF O	Contact: COLORA B0 /ail: tstathem@	TERRI STATHEM cimarex.com		Well No. 015-42471
3a. Address 600 N. MAREIENFELD STRE MIDLAND, TX 79701	3b. Phone No. (include area c Ph: 432-620-1936		eld and Pool, or Exploratory TTONWOOD DRAW; BONE SPG	
4. Location of Well (Footage, Sec., T)	11. Co	ounty or Parish, and State	
Sec 1 T25S R26E SESW 200 32.152356 N Lat, 104.250275		ED	DY COUNTY, NM	
12. CHECK APP	ROPRIATE BOX(ES) TO	O INDICATE NATURE C	F NOTICE, REPORT	, OR OTHER DATA
TYPE OF SUBMISSION .		TYPE	OF ACTION	
C Nation Cl. 1994	☐ Acidize	□ Deepen	☐ Production (Sta	rt/Resume)
Notice of Intent	☐ Alter Casing	☐ Fracture Treat	☐ Reclamation	☐ Well Integrity
☐ Subsequent Report	Casing Repair	New Construction	□ Recomplete	Other
☐ Final Abandonment Notice	☐ Change Plans	. Plug and Abandon	□ Temporarily Ab	pandon ,
	Convert to Injection	☐ Plug Back	■ Water Disposal	
If the proposal is to deepen direction Attach the Bond under which the wo	peration (clearly state all pertine sally or recomplete horizontally, ork will be performed or provide d operations. If the operation re bandonment Notices shall be fil	, give subsurface locations and me the Bond No. on file with BLM, sults in a multiple completion or	easured and true vertical dep BIA. Required subsequent recompletion in a new inter	pths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once
If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final A determined that the site is ready for the Cimarex Energy Co of Colora Propose to construct 852.9' of an operating pressure of 100 pressure gas line (MAOP of 1 to our 12" Triple Crown Line f	peration (clearly state all pertine tally or recomplete horizontally, ork will be performed or provided operations. If the operation rebandonment Notices shall be fil final inspection.) Indo respectfully requests performed for low pressure steel gapsi) into our Hunter 1 gas psi) into our Hunter 1 gas and operating preor high pressure gas lift.	, give subsurface locations and me the Bond No. on file with BLM, sults in a multiple completion or led only after all requirements, in opermission to lay two buries s line for gas sales (MAOPs pipeline and 885.1' of 4" sessure of 1100 psi) to an 8' They will both be buried in	easured and true vertical dq BIA. Required subsequent recompletion in a new inter cluding reclamation, have b d steel gas lines. of 250 psi with teel high valve connecting the same	pths of all pertinent markers and zones, reports shall be filed within 30 days val, a Form 3160-4 shall be filed once een completed, and the operator has
If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involve testing has been completed. Final A determined that the site is ready for the Cimarex Energy Co of Colora Propose to construct 852.9' of an operating pressure of 100 pressure gas line (MAOP of 1 to our 12" Triple Crown Line for the ditch and will run South down will run approximately 475.8 fline will run approximately 40 total of 885.1 feet, 53.65 rods	peration (clearly state all pertine lally or recomplete horizontally, ork will be performed or provided operations. If the operation rebandonment Notices shall be fil final inspection.) ado respectfully requests performed or provided operation in the person of the fill of the person of the fill of the person of the fill operating present the fill operating present performed by the fill of the fill operating present performed by the fill operation of the fill operation	, give subsurface locations and me the Bond No. on file with BLM, sults in a multiple completion or led only after all requirements, in permission to lay two buriers line for gas sales (MAOF) appeline and 885.1 of 4" sessure of 1100 psi) to an 8' They will both be buried in quardt 1 Federal 15H batte the SE/SW quarter of Section approximately 377.1 feet, 2	easured and true vertical de BIA. Required subsequent recompletion in a new inter cluding reclamation, have b d steel gas lines. of 250 psi with teel high valve connecting the same ry pad. Both lines tion 1. The 4" HP 12 and will be a	pths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once een completed, and the operator has
If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final A determined that the site is ready for the Cimarex Energy Co of Colora Propose to construct 852.9' of an operating pressure of 100 pressure gas line (MAOP of 1 to our 12" Triple Crown Line for ditch and will run South down will run approximately 475.8 for line will run approximately 405 total of 885.1 feet, 53.65 rods the NE/NW quarter of Section	peration (clearly state all pertine tally or recomplete horizontally, ork will be performed or provided operations. If the operation rebandonment Notices shall be fill final inspection.) ado respectfully requests performed or pressure steel gappsi) into our Hunter 1 gas 440 psi and operating presor high pressure gas lift. The East side of the Marceet, 28.84 rods per line in 9.3 feet, 24.81 rods in the The 6" LP line will run at 12 and will be a total of 8	, give subsurface locations and me the Bond No. on file with BLM, sults in a multiple completion or led only after all requirements, in permission to lay two buriers line for gas sales (MAOF) appeline and 885.1 of 4" sessure of 1100 psi) to an 8' They will both be buried in quardt 1 Federal 15H batte the SE/SW quarter of Section approximately 377.1 feet, 2	easured and true vertical dq BIA. Required subsequent recompletion in a new intercluding reclamation, have but steel gas lines. Tof 250 psi with teel high valve connecting the same y pad. Both lines tion 1. The 4" HP 12 and will be a 2.85 rods in	pths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once een completed, and the operator has NM OIL CONSERVATIO ARTESIA DISTRICT AUG 3 1 2015 RECEIVED
If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involve testing has been completed. Final A determined that the site is ready for the Cimarex Energy Co of Colora Propose to construct 852.9' of an operating pressure of 100 pressure gas line (MAOP of 1 to our 12" Triple Crown Line for ditch and will run South down will run approximately 475.8 for line will run approximately 40 total of 885.1 feet, 53.65 rods	peration (clearly state all pertine tally or recomplete horizontally, ork will be performed or provided operations. If the operation rebandonment Notices shall be fill final inspection.) ado respectfully requests performed or pressure steel gappsi) into our Hunter 1 gas 440 psi and operating presor high pressure gas lift. The East side of the Marceet, 28.84 rods per line in 9.3 feet, 24.81 rods in the The 6" LP line will run at 12 and will be a total of 8	, give subsurface locations and me the Bond No. on file with BLM, sults in a multiple completion or led only after all requirements, in permission to lay two buriers line for gas sales (MAOF) appeline and 885.1 of 4" sessure of 1100 psi) to an 8' They will both be buried in quardt 1 Federal 15H batte the SE/SW quarter of Section approximately 377.1 feet, 2	easured and true vertical de BIA. Required subsequent recompletion in a new inter cluding reclamation, have b d steel gas lines. of 250 psi with teel high valve connecting the same ry pad. Both lines tion 1. The 4" HP 12 and will be a	phs.of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once een completed, and the operator has NM OIL CONSERVATIO ARTESIA DISTRICT AUG 3 1 2015 RECEIVED
If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involved testing has been completed. Final A determined that the site is ready for the Cimarex Energy Co of Colora Propose to construct 852.9' of an operating pressure of 100 pressure gas line (MAOP of 1 to our 12" Triple Crown Line for ditch and will run South down will run approximately 475.8 for line will run approximately 475.8 for line will run approximately 405 total of 885.1 feet, 53.65 rods the NE/NW quarter of Section	peration (clearly state all pertine lally or recomplete horizontally, ork will be performed or provided operations. If the operation rebandonment Notices shall be fill final inspection.) Ido respectfully requests performed or provided operations. If the operation rebandonment Notices shall be fill final inspection.) Ido respectfully requests performed for low pressure steel gas psi) into our Hunter 1 gas 440 psi and operating provided for high pressure gas lift. In the East side of the Marched for East side of the Marched for East side of the Marched for East side of the East sid	give subsurface locations and methe Bond No. on file with BLM, sults in a multiple completion or led only after all requirements, in permission to lay two buries line for gas sales (MAOF) appeline and 885.1 of 4" sessure of 1100 psi) to an 8' They will both be buried in quardt 1 Federal 15H batte the SE/SW quarter of Section approximately 377.1 feet, 2852.9 feet, 51.69 rods.	easured and true vertical de BIA. Required subsequent recompletion in a new intercluding reclamation, have be disteel gas lines, of 250 psi with teel high valve connecting the same ry pad. Both lines tion 1. The 4" HP 12 and will be a 2.85 rods in	nths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once een completed, and the operator has NM OIL CONSERVATIO ARTESIA DISTRICT AUG 3 1 2015 RECEIVED 9/3/15
If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involvet testing has been completed. Final A determined that the site is ready for the Cimarex Energy Co of Colora Propose to construct 852.9' of an operating pressure of 100 pressure gas line (MAOP of 1 to our 12" Triple Crown Line for ditch and will run South down will run approximately 475.8 for line will run approximately 405 total of 885.1 feet, 53.65 rods the NE/NW quarter of Section	peration (clearly state all pertine tally or recomplete horizontally, ork will be performed or provided operations. If the operation rebandonment Notices shall be fill final inspection.) Ido respectfully requests performed or provided operations. If the operation rebandonment Notices shall be fill final inspection.) Ido respectfully requests performed for low pressure steel gapsi) into our Hunter 1 gas 440 psi and operating prevor high pressure gas lift. It the East side of the Marched For State of the Marched For	give subsurface locations and methe Bond No. on file with BLM, sults in a multiple completion or led only after all requirements, in permission to lay two buries in line for gas sales (MAOF) pipeline and 885.1' of 4" sessure of 1100 psi) to an 8'. They will both be buried in quardt 1 Federal 15H batte the SE/SW quarter of Section approximately 377.1 feet, 2852.9 feet, 51.69 rods.	easured and true vertical de BIA. Required subsequent recompletion in a new intercluding reclamation, have be disteel gas lines, of 250 psi with teel high valve connecting the same ry pad. Both lines tion 1. The 4" HP 12 and will be a 2.85 rods in	nths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once een completed, and the operator has NM OIL CONSERVATIO ARTESIA DISTRICT AUG 3 1 2015 RECEIVED 9/3///5 n 50
If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involventesting has been completed. Final A determined that the site is ready for the Cimarex Energy Co of Colorar Propose to construct 852.9' of an operating pressure of 100 pressure gas line (MAOP of 1 to our 12" Triple Crown Line for ditch and will run South down will run approximately 475.8 fine will run approximately 475.8 fine will run approximately 40 total of 885.1 feet, 53.65 rods the NE/NW quarter of Section This is all on lease NMNM014. I hereby certify that the foregoing in Name (Printed/Typed) TERRIST	peration (clearly state all pertine cally or recomplete horizontally, ork will be performed or provided operations. If the operation rebandonment Notices shall be fill final inspection.) Ido respectfully requests performed or provided operations. If the operation rebandonment Notices shall be fill final inspection.) Ido respectfully requests performed for low pressure steel gapsi) into our Hunter 1 gas 440 psi and operating provided for high pressure gas lift. In the East side of the Marciel for the East side of the East side of the East side of the Marciel for the East side of the Eas	give subsurface locations and me the Bond No. on file with BLM, sults in a multiple completion or led only after all requirements, in permission to lay two buries line for gas sales (MAOF) spipeline and 885.1 of 4" sessure of 1100 psi) to an 8' They will both be buried in quardt 1 Federal 15H batte the SE/SW quarter of Section approximately 377.1 feet, 2852.9 feet, 51.69 rods. 1308392 verified by the BLM RGY CO OF COLORADO, sprocessing by DEBORAH M	easured and true vertical de BIA. Required subsequent recompletion in a new intercluding reclamation, have be disteel gas lines. of 250 psi with teel high valve connecting the same ry pad. Both lines tion 1. The 4" HP 12 and will be a 2.85 rods in Well Information Systement to the Carlsbad CKINNEY on 07/10/2015	nths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once een completed, and the operator has NM OIL CONSERVATIO ARTESIA DISTRICT AUG 3 1 2015 RECEIVED 9/3///5 n 50
If the proposal is to deepen direction Attach the Bond under which the wo following completion of the involventesting has been completed. Final A determined that the site is ready for the Cimarex Energy Co of Colora Propose to construct 852.9' of an operating pressure of 100 pressure gas line (MAOP of 1 to our 12" Triple Crown Line for ditch and will run South down will run approximately 475.8 fline will run approximately 475.8 fline will run approximately 40total of 885.1 feet, 53.65 rods the NE/NW quarter of Section This is all on lease NMNM014. I hereby certify that the foregoing in Name (Printed/Typed) TERRI STATES	cration (clearly state all pertine tally or recomplete horizontally, ork will be performed or provided operations. If the operation rebandonment Notices shall be filfinal inspection.) Ido respectfully requests performed or provided operations. If the operation rebandonment Notices shall be filfinal inspection.) Ido respectfully requests performed for low pressure steel gapsi) into our Hunter 1 gas 440 psi and operating preor high pressure gas lift. The East side of the Marcet, 28.84 rods per line in 9.3 feet, 24.81 rods in the The 6" LP line will run and 12 and will be a total of 8 for CIMAREX ENE Committed to AFMSS for TATHEM Submission)	give subsurface locations and me the Bond No. on file with BLM, sults in a multiple completion or led only after all requirements, in permission to lay two buries line for gas sales (MAOF) spipeline and 885.1 of 4" sessure of 1100 psi) to an 8' They will both be buried in quardt 1 Federal 15H batte the SE/SW quarter of Section approximately 377.1 feet, 2852.9 feet, 51.69 rods. 1308392 verified by the BLM RGY CO OF COLORADO, sprocessing by DEBORAH M	easured and true vertical de BIA. Required subsequent recompletion in a new intercluding reclamation, have be a steel gas lines. Tof 250 psi with teel high valve connecting the same y pad. Both lines tion 1. The 4" HP 12 and will be a 2.85 rods in Well Information Systement to the Carlsbad CKINNEY on 07/10/2015 NAGER REGULATOR'	nths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once een completed, and the operator has NM OIL CONSERVATIO ARTESIA DISTRICT AUG 3 1 2015 RECEIVED 9/3///5 n 50
Attach the Bond under which the wo following completion of the involved testing has been completed. Final A determined that the site is ready for a Cimarex Energy Co of Colora Propose to construct 852.9' on operating pressure of 100 pressure gas line (MAOP of 1 to our 12" Triple Crown Line for ditch and will run South down will run approximately 475.8 f line will run approximately 475.8 f line will run approximately 400 total of 885.1 feet, 53.65 rods the NE/NW quarter of Section This is all on lease NMNM014. Thereby certify that the foregoing in Name (Printed/Typed) TERRI ST	cration (clearly state all pertine tally or recomplete horizontally, ork will be performed or provided operations. If the operation rebandonment Notices shall be filfinal inspection.) Ido respectfully requests performed or provided operations. If the operation rebandonment Notices shall be filfinal inspection.) Ido respectfully requests performed for low pressure steel gapsi) into our Hunter 1 gas 440 psi and operating preor high pressure gas lift. The East side of the Marcet, 28.84 rods per line in 9.3 feet, 24.81 rods in the The 6" LP line will run and 12 and will be a total of 8 for CIMAREX ENE Committed to AFMSS for TATHEM Submission)	give subsurface locations and me the Bond No. on file with BLM sults in a multiple completion or led only after all requirements, in permission to lay two buries in line for gas sales (MAOF) pipeline and 885.1 of 4" sessure of 1100 psi) to an 8 They will both be buried in quardt 1 Federal 15H batte the SE/SW quarter of Section NE/NW quarter of Section NE/NW quarter of Section NE/NW quarter of Section Sproximately 377.1 feet, 2852.9 feet, 51.69 rods.	easured and true vertical de BIA. Required subsequent recompletion in a new intercluding reclamation, have be a steel gas lines. Tof 250 psi with teel high valve connecting the same y pad. Both lines tion 1. The 4" HP 12 and will be a 2.85 rods in Well Information Systement to the Carlsbad CKINNEY on 07/10/2015 NAGER REGULATOR'	nths of all pertinent markers and zones. reports shall be filed within 30 days val, a Form 3160-4 shall be filed once een completed, and the operator has NM OIL CONSERVATIO ARTESIA DISTRICT AUG 3 1 2015 RECEIVED 9/3///5 n 50

BLM LEASE NUMBER: NMNM14124

COMPANY NAME: Cimarex Energy Company

ASSOCIATED WELL NAME: Marquardt 1 Federal 15H

BURIED PIPELINE STIPULATIONS

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

- 1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
- 2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
- 3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C.6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.
- 4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. All construction and maintenance activity will be confined to the authorized right-of-way.
6. The pipeline will be buried with a minimum cover of <u>36</u> inches between the top of the pipe and ground level.
7. The maximum allowable disturbance for construction in this right-of-way will be $\underline{30}$ feet:
• Blading of vegetation within the right-of-way will be allowed: maximum width of blading operations will not exceed 20 feet. The trench is included in this area. (Blading is defined as the complete removal of brush and ground vegetation.)
• Clearing of brush species within the right-of-way will be allowed: maximum width of clearing operations will not exceed 30 feet. The trench and bladed area are included in this area. (Clearing is defined as the removal of brush while leaving ground vegetation (grasses, weeds, etc.) intact. Clearing is best accomplished by holding the blade 4 to 6 inches above the ground surface.)
• The remaining area of the right-of-way (if any) shall only be disturbed by compressing the vegetation. (Compressing can be caused by vehicle tires, placement of equipment, etc.)
8. The holder shall stockpile an adequate amount of topsoil where blading is allowed. The topsoil to be stripped is approximately6 inches in depth. The topsoil will be segregated from other spoil piles from trench construction. The topsoil will be evenly distributed over the bladed area for the preparation of seeding.
9. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
10. Vegetation, soil, and rocks left as a result of construction or maintenance activity will be randomly scattered on this right-of-way and will not be left in rows, piles, or berms, unless otherwise approved by the Authorized Officer. The entire right-of-way shall be recontoured to match the surrounding landscape. The backfilled soil shall be compacted and a 6 inch berm will be left over the ditch line to allow for settling back to grade.
11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.
12. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.
(X) seed mixture 1 () seed mixture 3 () seed mixture 2 () seed mixture 4 () seed mixture 2/LPC () Aplomado Falcon Mixture

- 13. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be color which simulates "Standard Environmental Colors" **Shale Green**, Munsell Soil Color No. 5Y 4/2.
- 14. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. All signs and information thereon will be posted in a permanent, conspicuous manner, and will be maintained in a legible condition for the life of the pipeline.
- 15. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder before maintenance begins. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway. As determined necessary during the life of the pipeline, the Authorized Officer may ask the holder to construct temporary deterrence structures.
- 16. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.
- 17. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes associated roads, pipeline corridor and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.
- 18. <u>Escape Ramps</u> The operator will construct and maintain pipeline/utility trenches that are not otherwise fenced, screened, or netted to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:
 - a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
 - b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.
- 19. Special Stipulations: Installation of silt fencing on either side of the work area for the installation of the 4-inch and 6-inch buried lines. Silt fencing will remain until trench has been backfilled and vegetation has been established. Topsoil will be stockpiled to enhance reclamation.

- <u>Cave Karst</u> In the event that any underground voids are encountered during construction activities, construction activities will be halted and the BLM will be notified immediately.
- No Blasting to prevent geologic structure instabilities.

BLM LEASE NUMBER: NMNM14124

COMPANY NAME: Cimarex Energy Company

ASSOCIATED WELL NAME: Marquardt 1 Federal 15H

STANDARD STIPULATIONS FOR SURFACE INSTALLED PIPELINES

A copy of the application (Grant, Sundry Notice, APD) and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

- 1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
- 2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
- 3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to activity of the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.
- 4. The holder shall be liable for damage or injury to the United States to the extent provided by 43 CFR Sec. 2883.1-4. The holder shall be held to a standard of strict liability for damage or injury to the United States resulting from pipe rupture, fire, or spills caused or substantially aggravated by any of the following within the right-of-way or permit area:
 - a. Activities of the holder including, but not limited to construction, operation, maintenance,

and termination of the facility.

- b. Activities of other parties including, but not limited to:
 - (1) Land clearing.
 - (2) Earth-disturbing and earth-moving work.
 - (3) Blasting.
 - (4) Vandalism and sabotage.
- c. Acts of God.

The maximum limitation for such strict liability damages shall not exceed one million dollars (\$1,000,000) for any one event, and any liability in excess of such amount shall be determined by the ordinary rules of negligence of the jurisdiction in which the damage or injury occurred.

This section shall not impose strict liability for damage or injury resulting primarily from an act of war or from the negligent acts or omissions of the United States.

- 5. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil, salt water, or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil, salt water, or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any responsibility as provided herein.
- 6. All construction and maintenance activity will be confined to the authorized right-of-way width of ______ feet. If the pipeline route follows an existing road or buried pipeline right-of-way, the surface pipeline must be installed no farther than 10 feet from the edge of the road or buried pipeline right-of-way. If existing surface pipelines prevent this distance, the proposed surface pipeline must be installed immediately adjacent to the outer surface pipeline. All construction and maintenance activity will be confined to existing roads or right-of-ways.
- 7. No blading or clearing of any vegetation will be allowed unless approved in writing by the Authorized Officer.
- 8. The holder shall install the pipeline on the surface in such a manner that will minimize suspension of the pipeline across low areas in the terrain. In hummocky of duney areas, the pipeline will be "snaked" around hummocks and dunes rather then suspended across these features.
- 9. The pipeline shall be buried with a minimum of <u>24</u> inches under all roads, "two-tracks," and trails. Burial of the pipe will continue for 20 feet on each side of each crossing. The condition of the road, upon completion of construction, shall be returned to at least its former state with no bumps or dips remaining in the road surface.