, r	•			
Submit 3 Copies To Appropriate District	State of New 1	Mexico		Form C-103
Office District I	Energy, Minerals and Na	atural Resources	TITLE ADDAG	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240 District II	011 00\/d=n*//=n*/		WELL API NO 30-015-3	
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATIO		5. Indicate Ty	
<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. F		STATE	
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM	8/303	i e	CGas Lease No. 3756
87505	THE REPORT OF THE PARTY OF THE	× 6		
(DO NOT HER THIS FORM FOR BRODG	FICES AND REPORTS ON WEL DSALS TO DRILL OR TO DEEPEN OR I	I LIG DACK TO A		e or Unit Agreement Name FANK ST COM
DIFFERENT RESERVOIR. USE "APPLI	CATION FOR PERMIT" (FORM C-101)	FORRECEIVED	KED I	TANK ST COM
PROPOSALS.) 1. Type of Well: Oil Well	Gas Well 🛛 Other		8. Well Numb	per 1
2. Name of Operator		DEC _ 9 2005	9. OGRID Nu	ımber 015363
	CHISON OIL & GAS, INC.	dou-wateria		
3. Address of Operator	MIRA VISTA BLVD., PLANO,	TY 75093_4698	10. Pool name	e or Wildcat SCO DRAW, MORROW
4. Well Location	WINCA VISTA BEVD., I LANO,	1A. 75075-4076	FENA	SCO DRAW, MORROW
Unit Letter D	: 660 feet from the NOR	ΓH line and 66	60 feet from	the WEST line
Section 35	Township 18S Ran			County EDDY
Section 33	11. Elevation (Show whether I			County EDD 1
<u></u>	<u> </u>			
Pit or Below-grade Tank Application .				
Pit typeDepth to Grounds			nce from nearest s	urface water
Pit Liner Thickness: mil	Below-Grade Tank: Volume		truction Material	
12. Check	Appropriate Box to Indicate	Nature of Notice,	Report or Oth	ner Data
NOTICE OF I	NTENTION TO:	SUBS	SEQUENT F	REPORT OF:
PERFORM REMEDIAL WORK		REMEDIAL WOR		ALTERING CASING
TEMPORARILY ABANDON		OCMMENCE DO		
I FINIT OLYVICE ADVIADOIA	CHANGE PLANS	COMMENCE DRI	LLING OPNS.L] PANDA 🗌
-	J CHANGE PLANS ☐ MULTIPLE COMPL ☐	CASING/CEMENT		-
PULL OR ALTER CASING	-	CASING/CEMENT		-
PULL OR ALTER CASING COTHER:	MULTIPLE COMPL	CASING/CEMENT OTHER:	JOB 🗵	_
OTHER: 13. Describe proposed or compost of starting any proposed w	-	CASING/CEMENT OTHER: Il pertinent details, and	JOB Significant Specificant	dates, including estimated date
OTHER: 13. Describe proposed or compost of starting any proposed wor recompletion.	MULTIPLE COMPL pleted operations. (Clearly state a work). SEE RULE 1103. For Mu	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At	JOB Example 1 give pertinent tach wellbore di	dates, including estimated date agram of proposed completion
OTHER: 13. Describe proposed or compostarting any proposed wor recompletion. Drill 12-1/4" hole from both	pleted operations. (Clearly state a work). SEE RULE 1103. For Mu	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At	JOB Example 1 give pertinent tach wellbore di	dates, including estimated date agram of proposed completion
OTHER: 13. Describe proposed or compost of starting any proposed wor recompletion.	pleted operations. (Clearly state a work). SEE RULE 1103. For Mu	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At	JOB Example 1 give pertinent tach wellbore di	dates, including estimated date agram of proposed completion
OTHER: 13. Describe proposed or compostarting any proposed wor recompletion. Drill 12-1/4" hole from both	pleted operations. (Clearly state a work). SEE RULE 1103. For Mule ottom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Late to a depth of 1163'.	JOB Example 1 give pertinent tach wellbore di	dates, including estimated date agram of proposed completion
PULL OR ALTER CASING OTHER: 13. Describe proposed or composed or composed or composed or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as follows: 1 1 JT	pleted operations. (Clearly state a work). SEE RULE 1103. For Mule ottom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let 1' 31' 1'	JOB Example 1 give pertinent tach wellbore di	dates, including estimated date agram of proposed completion
OTHER: 13. Describe proposed or composed or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as follows:	pleted operations. (Clearly state a work). SEE RULE 1103. For Mule ottom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Late to a depth of 1163'.	JOB Example 1 give pertinent tach wellbore di	dates, including estimated date agram of proposed completion
PULL OR ALTER CASING OTHER: 13. Describe proposed or composed or composed or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as followed by the second of the second or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as followed by the second of the sec	pleted operations. (Clearly state a work). SEE RULE 1103. For Mustom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let 1' 31' 1' 1130'	I give pertinent tach wellbore di	dates, including estimated date agram of proposed completion 492' and drilled dry to 1163'
PULL OR ALTER CASING OTHER: 13. Describe proposed or composed or composed or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as followed by the second of	pleted operations. (Clearly state a work). SEE RULE 1103. For Mustom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C went w/ 180 SXS Fixotropic + 1% feet w/	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let 1' 31' 1' 1130' CACL + ¼ #/SX Cello Class "C" + 2% CACI	I give pertinent tach wellbore di ost all returns @	dates, including estimated date agram of proposed completion 492' and drilled dry to 1163' S Class "C" 35/65 + 2% CACL pp plug at 24:05 HRS and
PULL OR ALTER CASING OTHER: 13. Describe proposed or composed was or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as followed by the second of the secon	pleted operations. (Clearly state a work). SEE RULE 1103. For Mustom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C attent w/ 180 SXS Fixotropic + 1% fixed with the state of	CASING/CEMENT OTHER: Ill pertinent details, and tiple Completions: At to a depth of 1163'. Let 1' 31' 1' 1130' CACL + 1/4 #/SX Cello Class "C" + 2% CACI of cement @ 512' with	I give pertinent tach wellbore di ost all returns @	dates, including estimated date agram of proposed completion 492' and drilled dry to 1163' Class "C" 35/65 + 2% CACL pp plug at 24:05 HRS and pp 150 SXS Class "C" neat
PULL OR ALTER CASING OTHER: 13. Describe proposed or composed was or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as followed by the second of the secon	pleted operations. (Clearly state a work). SEE RULE 1103. For Multitom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C tent w/ 180 SXS Fixotropic + 1% fixed with the state of	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS 14.8 PPG Bun 1" tubing. Pun and pump 300	dates, including estimated dates agram of proposed completion at 492' and drilled dry to 1163'. S Class "C" 35/65 + 2% CACL ap plug at 24:05 HRS and ap 150 SXS Class "C" neat SXS Class "C" neat. TOH w.
PULL OR ALTER CASING OTHER: 13. Describe proposed or composed was or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as followed by the second of the secon	pleted operations. (Clearly state a work). SEE RULE 1103. For Multitom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C tent w/ 180 SXS Fixotropic + 1% float w/ 180 SXS Fixotropic + 1% flowed by 200 SXS surface and no returns. Tag top of CC 3 HRS. Tag top of cement w/ 1 w/ 1" and tag TOC @ 325'. TIF	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS 14.8 PPG Bun 1" tubing. Pun " and pump 300 SXS Class "C"	dates, including estimated date agram of proposed completion 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL ap plug at 24:05 HRS and anp 150 SXS Class "C" neat SXS Class "C" neat. TOH w. Circualte 25 SXS to surface.
OTHER: 13. Describe proposed or compost of starting any proposed wor recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as follows: 1 1 JT 36 JTS Set casing @ 1163'. Cem + 25 #/SX Celloflake + 5 floats held. No cement to through 1" and pull out Wal" and WOC 3 HRS. TIH WOC 4 HRS. ND BOP set	pleted operations. (Clearly state a work). SEE RULE 1103. For Mule of the pletest of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C ent w/ 180 SXS Fixotropic + 1% of the pletest with the pletest wit	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS 14.8 PPG Bun 1" tubing. Pun " and pump 300 SXS Class "C" and test to 300	dates, including estimated date agram of proposed completion 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL applug at 24:05 HRS and applug at 24:05 HRS and applug at 25 Class "C" neat SXS Class "C" neat TOH w. Circualte 25 SXS to surface. O PSI. NU 11" 5K BOP. Test
PULL OR ALTER CASING OTHER: 13. Describe proposed or composed was or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as following as	pleted operations. (Clearly state a work). SEE RULE 1103. For Multitom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C tent w/ 180 SXS Fixotropic + 1% float w/ 180 SXS Fixotropic + 1% flowed by 200 SXS surface and no returns. Tag top of CC 3 HRS. Tag top of cement w/ 1 w/ 1" and tag TOC @ 325'. TIF	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS 14.8 PPG Bun 1" tubing. Pun " and pump 300 SXS Class "C" and test to 300	dates, including estimated date agram of proposed completion 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL applug at 24:05 HRS and applug at 24:05 HRS and applug at 25 Class "C" neat SXS Class "C" neat TOH w. Circualte 25 SXS to surface. O PSI. NU 11" 5K BOP. Test
PULL OR ALTER CASING OTHER: 13. Describe proposed or composed was or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as following as	pleted operations. (Clearly state a work). SEE RULE 1103. For Mule ottom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C ent w/ 180 SXS Fixotropic + 1% feet	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS 14.8 PPG Bun 1" tubing. Pun " and pump 300 SXS Class "C" and test to 300	dates, including estimated date agram of proposed completion 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL applug at 24:05 HRS and applug at 24:05 HRS and applug at 25 Class "C" neat SXS Class "C" neat TOH w. Circualte 25 SXS to surface. O PSI. NU 11" 5K BOP. Test
PULL OR ALTER CASING OTHER: 13. Describe proposed or composed was or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as following as	pleted operations. (Clearly state a work). SEE RULE 1103. For Mule ottom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C ent w/ 180 SXS Fixotropic + 1% feet	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS 14.8 PPG Bun 1" tubing. Pun " and pump 300 SXS Class "C" and test to 300	dates, including estimated date agram of proposed completion 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL applug at 24:05 HRS and applug at 24:05 HRS and applug at 25 Class "C" neat SXS Class "C" neat TOH w. Circualte 25 SXS to surface. O PSI. NU 11" 5K BOP. Test
OTHER: 13. Describe proposed or compost of starting any proposed wor recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as follows: 1	pleted operations. (Clearly state a work). SEE RULE 1103. For Mule of the pletest of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C tent w/ 180 SXS Fixotropic + 1% of the pletest w/ 180 SXS Fixotropic + 1% of the plete	CASING/CEMENT OTHER: Ill pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS 14.8 PPG Bum 1" tubing. Pum " and pump 300 SXS Class "C" and test to 300 at collar. Test collar.	dates, including estimated date agram of proposed completion at 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL applug at 24:05 HRS and applug at 24:05 HRS and applug at 25 SXS Class "C" neat S
PULL OR ALTER CASING OTHER: 13. Describe proposed or composed was or recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as follows: 1	pleted operations. (Clearly state a work). SEE RULE 1103. For Mule of the pletest of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C tent w/ 180 SXS Fixotropic + 1% of the pletest w/ 180 SXS Fixotropic + 1% of the plete	CASING/CEMENT OTHER: Ill pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS 14.8 PPG Bum 1" tubing. Pum " and pump 300 SXS Class "C" and test to 300 at collar. Test collar.	dates, including estimated date agram of proposed completion at 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL applug at 24:05 HRS and applug at 24:05 HRS and applug at 25 SXS Class "C" neat S
OTHER: 13. Describe proposed or compost of starting any proposed wor recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as follows: 1	pleted operations. (Clearly state a work). SEE RULE 1103. For Multitom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C and which will be surface and no returns. Tag top of comment which will be surface and no returns. Tag top of comment will will be surface and resume drilling 8 above is true and complete to the closed according to NMOCD guidelines	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS 14.8 PPG Bun 1" tubing. Pun " and pump 300 SXS Class "C" and test to 300 at collar. Test co	dates, including estimated date agram of proposed completion at 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL applug at 24:05 HRS and applug at 24:05 HRS and applug at 25 SXS Class "C" neat S
OTHER: 13. Describe proposed or compost of starting any proposed wor recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as follows: 1	pleted operations. (Clearly state a work). SEE RULE 1103. For Multitom of surface casing set at 382' ows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C and which will be surface and no returns. Tag top of comment which will be surface and no returns. Tag top of comment will will be surface and resume drilling 8 above is true and complete to the closed according to NMOCD guidelines	CASING/CEMENT OTHER: Ill pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS 14.8 PPG Bun 1" tubing. Pun " and pump 300 SXS Class "C" and test to 300 at collar. Test co	dates, including estimated date agram of proposed completion at 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL applug at 24:05 HRS and applug at 24:05 HRS and applug at 25 SXS Class "C" neat S
OTHER: 13. Describe proposed or compost of starting any proposed wor recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as follows: 1	pleted operations. (Clearly state a work). SEE RULE 1103. For Multitom of surface casing set at 382' lows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C ent w/ 180 SXS Fixotropic + 1% left state and no returns. Tag top of COC 3 HRS. Tag top of cement w I w/ 1" and tag TOC @ 325'. Tilet slips cut casing. LD 13-5/8" Bolly valves, TIW to 5000 PSI. OK. In above is true and complete to the closed according to NMOCD guidelines. "ITTLE"	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS flake + 400 SX	dates, including estimated date agram of proposed completion at 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL applug at 24:05 HRS and applug at 24:05 HRS and applug at 25 SXS Class "C" neat S
OTHER: 13. Describe proposed or compost of starting any proposed wor recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as follows: 1	pleted operations. (Clearly state a work). SEE RULE 1103. For Mule of the pletest operations. (Clearly state a work). SEE RULE 1103. For Mule of the pletest operation of surface casing set at 382' lows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C ment w/ 180 SXS Fixotropic + 1% for the pletest of the pletest operation operation operation of the pletest operation of the pletest operation o	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS flake + 400 SX	dates, including estimated date agram of proposed completion at 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL applug at 24:05 HRS and applug at 24:05 HRS and applug at 25 SXS Class "C" neat S
OTHER: 13. Describe proposed or compost of starting any proposed wor recompletion. Drill 12-1/4" hole from both Run 9-5/8" casing as follows: 1	pleted operations. (Clearly state a work). SEE RULE 1103. For Multitom of surface casing set at 382' lows: Float Shoe 9-5/8" 43.5 #/FT N-80 LT&C Float Collar 9-5/8" 43.5 #/FT N-80 LT&C ent w/ 180 SXS Fixotropic + 1% left state and no returns. Tag top of COC 3 HRS. Tag top of cement w I w/ 1" and tag TOC @ 325'. Tilet slips cut casing. LD 13-5/8" Bolly valves, TIW to 5000 PSI. OK. In above is true and complete to the closed according to NMOCD guidelines. "ITTLE"	CASING/CEMENT OTHER: Il pertinent details, and tiple Completions: At to a depth of 1163'. Let	flake + 400 SXS flake + 400 SX	dates, including estimated date agram of proposed completion at 492' and drilled dry to 1163'. Class "C" 35/65 + 2% CACL applug at 24:05 HRS and applug at 24:05 HRS and applug at 25 SXS Class "C" neat S