Form 3160-5 (April 2004)

OCD-ARTESIA

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT** FORM APPROVED OMB No. 1004-0135

SHADDY NOTICES AND DEDODTS ON WELLS

Expires March 31, 2007 E Lagge Cariel No.

Do not use this form for proposals to drill or re enter an abandoned well. Use Form 3160-3 (APD) for such proposals. SUBMIT IN TRIPLICATE - Other instructions on reverse side 1. Type of Well					NM-103594 6. If Indian, Allottee or Tribe Name 7. If Unit or CA/Agreement, Name and/or No.			
					1. Type of Well Oil Well A Gas Well Other JAN 1 8 2006			
2. Name of Operator					Koonunga Hill BGX Federal #1			
Yates Petroleum Corporation				9. API Well No.				
		3b. Phone No. (include area code)			30-015-34380			
105 S. 4th Str., Artesia, NM 88210	dia a \	505-748-1471			10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., OR Survey Description)					Undes. McIver Ranch Morrow 11. County or Parish, State			
1838'FNL & 1072'FWL of Section 19-T22S-R25E (Unit E, SWNW)								
990'FNL & 660'FWL of Section 19-T22S-R25E (Unit D, NWNW) 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, RI					EDORT OR OTHER DATA			
	b) IO INDICA	· · · · ·	 		PORT, OR OT	HER DATA		
TYPE OF SUBMISSION TYPE OF ACTION								
Acidize		Deepen		Production (S	tart/Resume)	Water Shut-Off	;	
Notice of Intent Alter Casing		Fracture Treat		Reclamation		Well Integrity		
X Casing Rep.		New Construction		Recomplete		X Other Surfa	ace and	
Subsequent Report Change Pla	ns	Plug and Abandor		Temporarily A	Abandon	intermedia	ate	
Final Abandonment Notice Convert to Injection		Plug Back Water Dis			osal <u>casing</u>			
testing has been completed. Final Abandonment Notices shall be fill determined that the site is ready for final inspection.) 12/14/05 Resumed drilling at 12:00 PM. 12/20/05 Set 13-3/8" 48# H-40 casing at 150 200 sx "C" + 2% CaCl2. Cement d surface with 880 sx Class "C" with Reduced hole to 12-1/4" and resum 12/27/05 Set 9-5/8" 36# J-55 ST&C casing a .25#/sx Cellophane flake + 10#/sx .25#/sx Cellophane flakes + 5#/sx (yld 1.34, wt 14.8). Cement circula 30 min. Reduced hole and resume	07'. Cemented lid not circulat 2% CaCl. Te ned drilling. at 2724'. Cem LCM-1 (yld 1. LCM-1 (yld 1.	d with 180 sie. Ran tem sted casing lented with 1 50, wt 14.6) 96, wt 12.5).	x Thixotro perature to 1000 p 80 sx Cla and 540 Tailed i	opic and survey - osi for 30 ass "H" + sx 35:65 n with 20	1000 sx BJ L TOC 1300'. F min. WOC 6 10% A-10 + :6 Poz "C" + 0 sx "C" + 2%	ite. Tailed in v Ran 1" cement 69 hrs 15 min. 1% CaCl2 + 1% CaCl2 + 6 CaCl2		
14. I hereby certify that the foregoing is true and correct								
Name (Printed/Typed) Tina Huerta		Title Regulatory Compliance Supervisor						
Signature (Sina) Luerta)	Date Ja	inuary 3,	2005	ACCEPTE	ED FOR REC	ORD	
THIS S	PACE FOR FED	ERAL OR STA	TE OFFIC	E USE				
Approved by					JA Date	1 3 2006		
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.						S C. SWOBÓD	Ā	

certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

ALEXIS C. SWOBODA

PETROLEUM ENGINEER

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willbully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction