	UNITED STATE DEPARTMENT OF THE I BUREAU OF LAND MANA	INTERIOR		M APPROVED NO. 1004-0135 es: July 31, 2010	
SUNDRY NOTICES AND REPORTS ON WELLSA1 Do not use this form for proposals to drill or to re-enter an		ORTS ON WELLSArtes	5 Lease Serial No.		
Do not use t	his form for proposals to ell. Use form 3160-3 (AF	o drill or to re-enter an	6. If Indian, Allotte	e or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.			7. If Unit or CA/Ag	7. If Unit or CA/Agreement, Name and/or No	
I. Type of Well S Oil Well Gas Well Other			8. Well Name and No. GANT 7 G FEDERAL 2		
2. Name of Operator Contact: MIKE PIPPIN LIME ROCK RESOURCES II A LP		9. API Well No. 30-015-42447	9. API Well No. 30-015-42447-00-X1		
^{3a.} Address 1111 BAGBY STREET SUITE 4600 HOUSTON, TX 77002		3b. Phone No. (include area code) Ph: 505.327.4573	10. Field and Pool, RED LAKE	or Exploratory	
. Location of Well (Footage, Sec.,	T., R., M., or Survey Description	n)	11. County or Paris	h, and State	
Sec 7 T18S R27E SWNE 1400FNL 2180FEL 32.76\$706 N Lat, 104.315606 W Lon			EDDY COUNTY,		
12. СНЕСК АРІ	PROPRIATE BOX(ES) T	O INDICATE NATURE OF N	OTICE, REPORT, OR OTH	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
□ Notice of Intent		🗖 Deepen	Production (Start/Resume)	U Water Shut-Of	
Subsequent Report	Alter Casing	Fracture Treat	Reclamation	U Well Integrity	
Final Abandonment Notice	Casing Repair	New Construction Plug and Abandon	Recomplete Temporarily Abandon	🛛 Other Well Spud	
	Convert to Injection	— , •	Water Disposal		
Attach the Bond under which the w following completion of the involve testing has been completed. Final 2 determined that the site is ready for	nally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re <i>bandonment Notices shall be fil</i> final inspection.)	, give subsurface locations and measure the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements, includi	 Required subsequent reports shall 1 mpletion in a new interval, a Form 3 ing reclamation, have been completed 	tinent markers and zones. be filed within 30 days 160-4 shall be filed once	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt to tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4523 production csg @ 4513'. Cm LCM1, 0.2% R-3, & 6% gel. cmt to pit. Released drilling	nally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re <i>(bandonment Notices shall be fil final inspection.)</i> rilled 12-1/4" hole to 440'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. 'yon 8/17/14. Ran open ho need w/lead 200 sx (381 cf) Tailed w/715 sx (951 cf) c rig on 8/19/14. Plan to pre	, give subsurface locations and measure the Bond No. on file with BLM/BIA esults in a multiple completion or reco led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 43i Circ 33 sx cmt to pit. On 8/12 ble logs. On 8/18/14, set 5-1/2") 35:65 poz "C" cmt w/5% salt, I "C" cmt w/6% R-3 & 0.25# CF issure test 5-1/2" csg during cc	red and true vertical depths of all per . Required subsequent reports shall 1 mpletion in a new interval, a Form 3 ng reclamation, have been completed 8'. Cmted 2/14, pressure ' 17# J-55 0.25# CF, 5#	tinent markers and zones. be filed within 30 days 160-4 shall be filed once 1, and the operator has	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt y tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4521 production csg-@ 4513'. Cm LCM1, 0.2% R-3, & 6% gel.	nally or recomplete horizontally, ork will be performed or provide ad operations. If the operation re bandoment Notices shall be fil final inspection.) rilled 12-1/4" hole to 440'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. 'en 8/17/14. Ran open ho thed w/lead 200 sx (381 cf) Tailed w/715 sx (951 cf) c rig on 8/19/14. Plan to pre	, give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 430 Circ 33 sx cmt to pit. On 8/12 ole logs. On 8/18/14, set 5-1/2" 35:65 poz "C" cmt w/5% salt, t "C" cmt w/6% R-3 & 0.25# CF essure test 5-1/2" csg during co L CONSERVATION.	red and true vertical depths of all per . Required subsequent reports shall 1 mpletion in a new interval, a Form 3 ng reclamation, have been completed B'. Cmted 2/14, pressure 177# J-55 0.25# CF, 5# 5. Circ 141 sx completion	tinent markers and zones. be filed within 30 days 160-4 shall be filed once I, and the operator has	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt v tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4523 production csg1@ 4513'. Cm LCM1, 0.2% R-3, & 6% gel. cmt to pit/ Released drilling	nally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re handonment Notices shall be fil final inspection.) rilled 12-1/4" hole to 4240'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. 'on 8/17/14. Ran open ho hed w/lead 200 sx (381 cf) Tailed w/715 sx (951 cf) c rig on 8/19/14. Plan to pre NM OI	, give subsurface locations and measure the Bond No. on file with BLM/BIA esults in a multiple completion or reco- led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 438 Circ 33 sx cmt to pit. On 8/12 ole logs. On 8/18/14, set 5-1/2" 35:65 poz "C" cmt w/5% salt, I "C" cmt w/6% R-3 & 0.25# CF essure test 5-1/2" csg during co L CONSERVATION RTESIA DISTRICT	red and true vertical depths of all per . Required subsequent reports shall i mpletion in a new interval, a Form 3 ng reclamation, have been completed B'. Cmted 2/14, pressure 7 17# J-55 0.25# CF, 5# 5. Circ 141 sx completion SIO	tinent markers and zones. be filed within 30 days 160-4 shall be filed once l, and the operator has JANIBOBA 2 0 6 100	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt v tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4521 production csg @ 4513'. Cm LCM1, 0.2% R-3, & 6% gel. cmt to pit/ Released drilling to operations.	nally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re handonment Notices shall be fil final inspection.) rilled 12-1/4" hole to 4240'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. 'on 8/17/14. Ran open ho hed w/lead 200 sx (381 cf) Tailed w/715 sx (951 cf) c rig on 8/19/14. Plan to pre NM OI	, give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 430 Circ 33 sx cmt to pit. On 8/12 ole logs. On 8/18/14, set 5-1/2" 35:65 poz "C" cmt w/5% salt, t "C" cmt w/6% R-3 & 0.25# CF essure test 5-1/2" csg during co L CONSERVATION.	red and true vertical depths of all per . Required subsequent reports shall i mpletion in a new interval, a Form 3 ng reclamation, have been completed B'. Cmted 2/14, pressure 7 17# J-55 0.25# CF, 5# 5. Circ 141 sx completion SIO	tinent markers and zones. be filed within 30 days 160-4 shall be filed once l, and the operator has	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt or tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4521 production csgr@ 4513'. Cr LCM1, 0.2% R-3, & 6% gel. cmt to pit/ Released drilling to operations.	nally or recomplete horizontally, ork will be performed or provide ed operations. If the operation re handoment Notices shall be fil final inspection.) rilled 12-1/4" hole to 440'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. 'on 8/17/14. Ran open ho hed w/lead 200 sx (381 cf) Tailed w/715 sx (951 cf) c rig on 8/19/14. Plan to pre NM OI A d	, give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 430 Circ 33 sx cmt to pit. On 8/12 ble logs. On 8/18/14, set 5-1/2" 35:65 poz "C" cmt w/5% salt, 1 "C" cmt w/6% R-3 & 0.25# CF essure test 5-1/2" csg during co L CONSERVATION RTESIA DISTRICT OCT 3 0 2015 RECEIVED 257430 verified by the BLM Well	red and true vertical depths of all per . Required subsequent reports shall i mpletion in a new interval, a Form 3 ng reclamation, have been completed B'. Crnted 2/14, pressure 17# J-55 0.25# CF, 5# 5. Circ 141 sx completion SIO NOILENES Information System	tinent markers and zones. be filed within 30 days 160-4 shall be filed once 1, and the operator has	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt v tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4521 production csg1@ 4513'. Cr LCM1, 0.2% R-3, & 6% gel. cmt to pit/ Released drilling to operations.	nally or recomplete horizontally, ork will be performed or provide d operations. If the operation re <i>bandonment Notices shall</i> be fil final inspection.) rilled 12-1/4" hole to 440'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. 'yon 8/17/14. Ran open ho fred w/lead 200 sx (381 cf) Tailed w/715 sx (951 cf) c rig on 8/19/14. Plan to pre NM OI d is true and correct. Electronic Submission # For LIME ROCK	, give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 430 Circ 33 sx cmt to pit. On 8/12 ole logs. On 8/18/14, set 5-1/2" 35:65 poz "C" cmt w/5% salt, t "C" cmt w/6% R-3 & 0.25# CF essure test 5-1/2" csg during co L CONSERVATION RTESIA DISTRICT OCT 3 0 2015	red and true vertical depths of all per . Required subsequent reports shall 1 mpletion in a new interval, a Form 3 ng reclamation, have been completed 8'. Cmted 2/14, pressure 17# J-55 0.25# CF, 5# 5. Circ 141 sx completion SIO NOILENE Information System ie Calisbad	tinent markers and zones. be filed within 30 days 160-4 shall be filed once l, and the operator has JANIBOBA 2 0 6 100	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt or tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4521 production csgr@ 4513'. Crf LCM1, 0.2% R-3, & 6% gel. cmt to pit/ Released drilling to operations.	nally or recomplete horizontally ork will be performed or provide d operations. If the operation re handonment Notices shall be fil final inspection.) rilled 12-1/4" hole to 440'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. 'on 8/17/14. Ran open ho need w/lead 200 sx (381 cf) Tailed w/715 sx (951 cf) c rig on 8/19/14. Plan to pre NM OI d is true and correct. Electronic Submission # For LIME ROCK mmitted to AFMSS for proc	, give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 434 Circ 33 sx cmt to pit. On 8/12 ble logs. On 8/18/14, set 5-1/2") 35:65 poz "C" cmt w/5% salt, 1 "C" cmt w/6% R-3 & 0.25# CF assure test 5-1/2" csg during co L CONSERVATION. RTESIA DISTRICT 0CT 3 0 2015 RECEIVED 257430 verifield by the BLM Well RESOURCES II A LP, sent to th essing by MARISSA KLEIN.on g	red and true vertical depths of all per . Required subsequent reports shall 1 mpletion in a new interval, a Form 3 ng reclamation, have been completed 8'. Cmted 2/14, pressure 17# J-55 0.25# CF, 5# 5. Circ 141 sx completion SIO NOILENE Information System ie Calisbad	tinent markers and zones. be filed within 30 days 160-4 shall be filed once 1, and the operator has 2 0 8 100 SIG VISELAU SNOD TIO WW	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt ny tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4521 production csgr@ 4513'. Cm LCM1, 0.2% R-3, & 6% gel. cmt to pit. Released drilling operations. Accepted for recor NMOCD 11 k 15 thereby certify that the foregoing Name (Printed/Typed) MIKE PIF	nally or recomplete horizontally ork will be performed or provide d operations. If the operation re handonment Notices shall be fil final inspection.) rilled 12-1/4" hole to 440'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. '. on 8/17/14. Ran open ho need w/lead 200 sx (381 cf) Tailed w/715 sx (951 cf) c rig on 8/19/14. Plan to pre NM OI d is true and correct. Electronic Submission # For LIME ROCK mmitted to AFMSS for proc PPIN	, give subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or reco led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 433 Circ 33 sx cmt to pit. On 8/12 ble logs. On 8/18/14, set 5-1/2" 0 35:65 poz "C" cmt w/5% salt, 1 "C" cmt w/6% R-3 & 0.25# CF assure test 5-1/2" csg during co L CONSERVATION RTESIA DISTRICT 0 CT 3 0 2015 RECEIVED 257430 verified by the BLM Well RESOURCES II A LP, sent to th essing by MARISSA KLEIN on a Title PE TRO	red and true vertical depths of all per . Required subsequent reports shall 1 mpletion in a new interval, a Form 3 ng reclamation, have been completed 8'. Cmted 2/14, pressure 17# J-55 0.25# CF, 5# 5. Circ 141 sx completion SIO NOLLANE information System re Carlsbad 7/24/2015 (15MGK02475F) IF DED (AGENTRECO 14	tinent markers and zones. be filed within 30 days 160-4 shall be filed once 1, and the operator has 2 0 8 100 SIG VISELAU SNOD TIO WIN	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt ty tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4521 production csgr@ 4513'. Cm LCM1, 0.2% R-3, & 6% gel. cmt to pit. Released drilling operations. Accepted for recor NMOCD II be 15- 4. Thereby certify that the foregoing Co Name (Printed/Typed) MIKE PIF	nally or recomplete horizontally ork will be performed or provide d operations. If the operation re handonment Notices shall be fil final inspection.) rilled 12-1/4" hole to 440'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. '. on 8/17/14. Ran open ho need w/lead 200 sx (381 cf) Tailed w/715 sx (951 cf) c rig on 8/19/14. Plan to pre NM OI d is true and correct. Electronic Submission # For LIME ROCK mmitted to AFMSS for proc PPIN	, give subsurface locations and measu the Bond No. on file with BLM/BIA soults in a multiple completion or reco led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 43i Circ 33 sx cmt to pit. On 8/12 ble logs. On 8/18/14, set 5-1/2") 35:65 poz "C" cmt w/5% salt, 1 "C" cmt w/6% R-3 & 0.25# CF essure test 5-1/2" csg during co L CONSERVATION RTESIA DISTRICT OCT 3 0 2015 RECEIVED 257430 verified by the BLM Well RESOURCES II A LP, sent to th essing by MARISSA KLEIN on a Title PETRO	red and true vertical depths of all per . Required subsequent reports shall 1 mpletion in a new interval, a Form 3 ng reclamation, have been completed 8'. Cmted 2/14, pressure 17# J-55 0.25# CF, 5# 5. Circ 141 sx completion SIO NOLLANE information System re Carlsbad 7/24/2015 (15MGK02475F) IF DED (AGENTRECO 14	tinent markers and zones. be filed within 30 days 160-4 shall be filed once 1, and the operator has 2 0 8 100 SIG VISELAU SNOD TIO WIN	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt v tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4521 production csg @ 4513'. Cm LCM1, 0.2% R-3, & 6% gel. cmt to pit/ Released drilling to operations. Accepted for recor NMOCD II le 15- t. Thereby certify that the foregoing Co Name (Printed/Typed) MIKE PIF Signature (Electronic	nally or recomplete horizontally ork will be performed or provide d operations. If the operation re handonment Notices shall be fil final inspection.) rilled 12-1/4" hole to 440'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. '. on 8/17/14. Ran open ho need w/lead 200 sx (381 cf) Tailed w/715 sx (951 cf) c rig on 8/19/14. Plan to pre NM OI d is true and correct. Electronic Submission # For LIME ROCK mmitted to AFMSS for proc PPIN	, give subsurface locations and measu the Bond No. on file with BLM/BIA soults in a multiple completion or reco led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 43i Circ 33 sx cmt to pit. On 8/12 ble logs. On 8/18/14, set 5-1/2") 35:65 poz "C" cmt w/5% salt, 1 "C" cmt w/6% R-3 & 0.25# CF essure test 5-1/2" csg during co L CONSERVATION RTESIA DISTRICT OCT 3 0 2015 RECEIVED S7430 verified by the BLM Well RESOURCES II A LP, sent to th essing by MARISSA KLEIN on a Title PE TRO Date 08 19/20 DR FEDERAL OR STATE O	red and true vertical depths of all per Required subsequent reports shall 1 mpletion in a new interval, a Form 3 ng reclamation, have been completed 8'. Cmted 2/14, pressure 17# J-55 0.25# CF, 5# Circ 141 sx information System re Carlsbad 2/24/2015 (15MGK02475F) FFICE USE/D 2010 14 FFICE USE/D 2010 14 FFICE USE/D 2010	tinent markers and zones. be filed within 30 days 160-4 shall be filed once 1, and the operator has 2 0 8 130 SIQ VISELAV ISNO2 JIO WW RD	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt v tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4521 production csg @ 4513'. Cm LCM1, 0.2% R-3, & 6% gel. cmt to pit. Released drilling to operations. Accepted for recor NMOCD 11 / 6 / 15 4. Thereby certify that the foregoing Co Name (Printed/Typed) MIKE PII Signature (Electronic	nally or recomplete horizontally, ork will be performed or provide ad operations. If the operation re bhandonment Notices shall be fil final inspection.) rilled 12-1/4" hole to 440'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. 'on 8/17/14. Ran open ho hed wilead 200 sx (381 cf) Tailed w/T15 sx (951 cf) c rig on 8/19/14. Plan to pre NM OI d is true and correct. Electronic Submission # For LIME ROCK mmitted to AFMSS for proc PPIN Submission) THIS SPACE FO	, give subsurface locations and measu the Bond No. on file with BLM/BIA soults in a multiple completion or reco led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 431 Circ 33 sx cmt+orpit. On 8/12 ole logs. On 8/18/14, set 5-1/2" 35:65 poz "C" cmt w/5% salt, 1"C" cmt w/6% R-3 & 0.25# CF essure test 5-1/2" csg during cc L CONSERVATION RTESIA DISTRICT OCT 3 0 2015 RECEIVED 257430 verified by the BLM Well RESOURCES II A LP, sent to the essing by MARISSA KLEIN on 6 Title PETRO Date 08 19/20 DR FEDERAL OR STATE C	red and true vertical depths of all per Required subsequent reports shall 1 mpletion in a new interval, a Form 3 ng reclamation, have been completed 8'. Cmted 2/14, pressure 17# J-55 0.25# CF, 5# 5. Circ 141 sx completion SIO NOILVAN Information System re Catisbad 724/2015 (15MGK02475F) FICE USE/D 2010 14 FFICE USE/D 2010	tinent markers and zones. be filed within 30 days 160-4 shall be filed once 1, and the operator has 2 0 8 130 SIQ VISELAV ISNOS TIO WIN RD	
Attach the Bond under which the w following completion of the involve testing has been completed. Final / determined that the site is ready for Spudded well on 8/10/14. D w/300 sx (405 cf) cl "C" cmt v tested 8-5/8" csg to 1500 psi Drilled 7-7/8" hole to TD4521 production csg @ 4513'. Cf LCM1, 0.2% R-3, & 6% gel. cmt to pit. Released drilling to operations. Accepted for recor NMOCD II le 13- 4. Thereby certify that the foregoing Co Name (Printed/Typed) MIKE PIF Signature (Electronic pproved By	nally or recomplete horizontally, ork will be performed or provide ad operations. If the operation re bandonment Notices shall be fil final inspection.) rilled 12-1/4" hole to 440'. w/2% Cacl2 & 0.125# C/F. for 30 min-OK. 'yon 8/17/14. Ran open ho hed w/lead 200 sx (381 cf) Tailed w/715 sx (951 cf) c rig on 8/19/14. Plan to pre NM OI d is true and correct. Electronic Submission # For LIME ROCK mmitted to AFMSS for proc PIN Submission) THIS SPACE FO	, give subsurface locations and measu the Bond No. on file with BLM/BIA soults in a multiple completion or reco led only after all requirements. includi Set 8-5/8" 24# J-55 csg @ 436 Circ 33 sx cmt+orpit. On 8/12 ole logs. On 8/18/14, set 5-1/2" 35:65 poz "C" cmt w/5% salt, 1"C" cmt w/6% R-3 & 0.25# CF essure test 5-1/2" csg during cc L CONSERVATION RTESIA DISTRICT OCT 3 0 2015 RECEIVED 257430 verified by the BLM Well RESOURCES II A LP, sent to the essing by MARISSA KLEIN on 6 Title PETRO Date 08/19/20 Date 08/19/20 CR FEDERAL OR STATE C Title Bl Title Bl Conservation Conse	red and true vertical depths of all per Required subsequent reports shall 1 mpletion in a new interval, a Form 3 ng reclamation, have been completed 8'. Cmted 2/14, pressure 17# J-55 0.25# CF, 5# Circ 141 sx impletion SIO NOILVAL Information System ac Carlsbad 124/2015 (15MGK0247SE) If PED(AGENTRECO 14 FFICE USED 2010 IREAL OF LAND MAIN GEMENY CARL SBAL FILLU FITUEAN	tinent markers and zone be filed within 30 days 160-4 shall be filed once 1, and the operator has 2 0 8 100 SIG VISELUV ISNOS TIO WIN RD RD	

. .

.

.