NM OIL CONSERVATION		
District I 1625 N. French Dr., Hobbs, NM 88240 N 17 2016 Energy, M 2015 Strict II 2016 Energy, M	State of New Mexico Inerals and Natural Resources Department	Submit Original to Appropriate
811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Road, Aztec, NM 87 RECEIVED <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505	Oil Conservati 1220 South St. Francis Dr. Santa Fe. NM 87505 NMOCD	

GAS CAPTURE PLAN

Date: 06/15/2016

Original □ Amended

Reason for Amendment:

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Clydesdale 1 Fee #6H	30-015- 43396	UL-I Sec1, T198, R25E	1650 FSL & 150 FEL	300	0	

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Agave Energy Company and will be connected to Agave's low/high pressure gathering system located in Eddy County, New Mexico. It will require <500'of pipeline to connect the facility to low/high pressure gathering system. COG Operating, LLC provides (periodically) to Agave a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, COG Operating, LLC and Agave have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Agave's Dagger Draw Processing Plant located in Sec. 25, TWN 18-S, RNG 25E, Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Agave's system at that time. Based on current information, it is COG Operating, LLC belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease •
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - \circ Plants are expensive residue cas is still flared, and uneconomical to operate when cas volume declines