Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT RY NOTICES AND DECEMBER.

	OMB NO. 1004-0135 Expires: July 31, 2010
5.	Lease Serial No. NMNM98122

SUNDRY NOTICES AND REPORTS ON WELLS JUN 2 0 2010 Do not use this form for proposals to drill or to re-enter an bandoned well. Use form 3160-3 (APD) for such proposals. RECEIVED
UBMIT IN TRIPLICATE - Other instructions on reverse side.

6.	If Indian, Allottee or	Tribe Name	
	•		

	1							
SUBMIT IN TRI	7. If Unit or CA/Agree 8920002760	ement, Name and/or No.						
1. Type of Well	1. Type of Well							
Oil Well Gas Well 🗷 Oth					SKENVA	TION		
2. Name of Operator LINN OPERATING INCORPO	DRENO		9. API Well No 30-015-05426-0	0-S1				
3a. Address 600 TRAVIS STREET SUITE HOUSTON, TX 77002	3b. Phone No. (include area code) Ph: 713.904.6657 Fx: 832.209.4316			10. Field and Pool, or Exploratory GRAYBURG				
4. Location of Well (Footage, Sec. 17.	, R., M., or Survey Description) .			11. County or Parish,	and State		
Sec 28 T17S R31E NENE 660	-			EDDY COUNTY, NM				
12. CHECK APPI	ROPRIATE BOX(ES) TO	O INDICATE	NATURE OF	NOTICE, R	EPORT, OR OTHE	R DATA		
TYPE OF SUBMISSION			TYPE	OF ACTION				
Notice of Intent ■ Notice of Intent Notice of Inten	☐ Acidize	☐ Dee	pen	☐ Produc	tion (Start/Resume)	□ Water Shut-Off		
A Profice of Michi	☐ Alter Casing	☐ Frac	ture Treat	Reclam	ation	□ Well Integrity		
☐ Subsequent Report	☐ Casing Repair	□ New	Construction	☐ Recom	plete	☐ Other		
☐ Final Abandonment Notice	☐ Change Plans	— ☑ Plug			rarily Abandon			
	☐ Convert to Injection			■ Water I	Disposal			
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) LINN RESPECTFULLY REQUESTS TO PA THIS WELL. THE SUBJECT WELL IS DOWN WITH A SHALLOW CASING LEAK. THE WELL HAS NOT INJECTED SINCE 2005 AND SUPPORTS MINIMAL OFFSET PRODUCTION. THIS WELL HAS NO UTILITY IN THE CURRENT ECONOMIC ENVIRONMENT. PROPOSED PA PROCEDURE: 1. MIRU PLUGGING EQUIPMENT 2. SET 4 1/2 CIBP @ 3678* W/25 SX CMT 3. CIRCULATE HOLE WITH MUD LADEN FLUID 4. PERF & SQZ 40 SX CMT @ 3495*. WOG & TAG 5. PERF & SQZ 25 SX CMT @ 3660*. WOG & TAG 6. PERF & SQZ 25 SX CMT @ 300 & CIRCULATE TO SURFACE 7. CUT OFF WELLHEAD & WELD ON DRY HOLE MARKER CONDITIONS OF APPROVAL PROPOSED FOR APPROVAL								
14. I hereby certify that the foregoing is true and correct. Electronic Submission #341417 verified by the BLM Well Information System For LINN OPERATING INCORPORATED, sent to the Carlsbad Committed to AFMSS for processing by CHRISTOPHER WALLS on 06/09/2016 (16CRW0053SE)								
Name (Printed/Typed) LAURA A	MORENO		Title REG	COMPLIANC	E ADVISOR TO IN	<u>~</u> 0		
Signature (Electronic S	Submission)		Date 0 6/08/	/2016	VCCEL VIVIC)Co		
THIS SPACE FOR FEDERAL OR STATE OFFICE USE								
Approved By Wa	L		Title Eng)		Date 6/16/16		
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent to conduct the applicant the applicant to conduct the applicant to conduc	Office (F	\sim						

Additional data for EC transaction #341417 that would not fit on the form

32. Additional remarks, continued

PLEASE SEE ATTACHED CURRENT & PROPOSED WBD's

ПЙЙ NM Schematic Encryy Well Name: SKELLY UNIT 088 3001505426 PBNM PBSKEULY BEddy Township Range | Street | Stre NM 250 280 Ground Elevation (R) Ong KB Elev (ft) 3,804.00 103,52754715W 8/1/1942 3,804.00 0.00 6/29/1942 Original Hole Data Original Hole, 5/17/2016 11:47:05 AM MD Wellbores Vertical schematic (actual) (fiKB) EW Fing North-South Distance [f] East-West Distance (it) 660.0 FNL 660.0 Casing Strings 20 Cso Des Set Dept. OD: Noma Run Date Surface 609.0 32.00 H-40L 6/27/1942 815/81 7:921 8 5/8; 0.0-609.0 Csq Des Set Dept DD Nom WALER (U Billing Grade 20100∰ U-55∰ / Run Date Wellbore; 12.250; 0.0-Production 3,145.0 6:4561 9/2/1942 290 9 Witten (in Burng Grade 1,1160 N-80 Csg Des Set Dept. DD Nomi Run Date 6/7/1983 3,707.0 411/2: Liner 585.0 Cement Stages 569.6 Description Top (fKB; Bim (fixB) Eval Method 8 5/8 0.0 609.0 Returns to Surface 32.1 Description Eval Mathod Top (RKB) Surface; Casing: 0.0-300.0 3,145.0 CBL 607 1 609.0 Description Top (INE Bun (NKB) Eval Method Comment Sqz Csg Leak; 597.0-Plug back 3,728.0 4,105.0 tD0 t 628.0 Ten (MKB) Bbm (ftKB) Eval Method Comment 4 1/2; 0.0-3,078 0 Sqz Csg Leak 597.0 628.0 7, 300.0-3,145.0 Top (ftKB Eval Method Comment Wellbore; 8,750; 609.0-Sqz Csg Leak 2,899.0 2,928.0 2,1200 Seven Rivers (final) 3,145.0 Description 4 1/2 0.0 3,078.0 Returns to 27349 Surface **Tubing Strings** 2 552 0 Sqz Csg Leak, 2,899.0-Tubing Description 2.928.0 9/28/1942 Tubing 3,727.0 4/1/1943 **Tubing Description** Set Depth. 3,727.0 Pul Date Tubing 4/9/1943 10/1/1957 3 078.1 Set Depth. Pul Cate Tub na Descriptor Run Date **Tubing - Production** 9/11/1995 3,650.0 6/11/1983 1000.1 Tubing Descriptor Set Death Run Date Pus Date 3,660.0 9/11/1995 4/9/1997 **Tubing - Production** Tubing Description Set Death Run Date Pull Date Tubing 3.099.0 4/10/1997 Perforations 3 140 1 Grayburg (final) Top (fiKB) Bom (RKB) Comment 3,690.0 3,625,0 3 147 7 Formations Formation Comment 31434 San Andres 3,612.0 3,724.0 Final Otm Final Too Comment Production; Casing 0.0 31450 Seven Rivers 2,123.0 | 2,735.0 3,145,0 Formation First Otto 3.140.0 Grayburg 3.610.0 3 500.9 3518.0 2 585.E 1602.0 3 611.9 San Andres (final) Wellbore, 6.250; 3 145.0-36250 4.105.0 Open Hole, 3,625 0-3.690.0 3 673.9 1600.0 3 660 0 3 707 0 Liner Casing 0.0-3,707.0 Plug back 3,728.0-3 728.D 4.105.0

Wallbore: 4,105.0

Page 1/1

Report Printed: 5/17/2016

www.peloton.com

NM Schematic Eiengy Well Name: SKELLY UNIT 088 3001505426 400 MI PBINM PBISKELLY Eddy Steral/Province | Gecton | Township | Range | Survey | Blob | NM | 28 2 1 017-SV | 031-E Ground Elevation (ft) Ong KB Elev (ft) 3.804.00 KB-Grd (N) Indial Soud Date TD Date 8/1/1942 3.804.00 6/29/1942 Original Hole, 6/6/2016 2:45:21 PM Original Hole Data MD Wellbores Vertical schematic (actual) (ftKB) North-South Distance (fl) East-West Distance (f) FNL 660.0 660.0 FEL Casing Strings άo Cement Plug; 0.0-200 0 Cag Des PROPOSED Perfs; 200.0 Wellbore; 12,250, 0,0-200 1 Surface 6.09.0 815/8 7.921 32:00 H-40 6/27/1942 Cag Des D(Nom:: Willen (13 Binng Grade 6.456 20100 以555 Run Date 220.0 -8 5/8 0.0-609.0 Production 3.145.0 9/2/1942 Cement Plug; 470.0-Wiften (68 Buing Grade Csa Des Set Dept... DD Nom." D 1 3,707.0 4\$1/2 41 D Nom Run Date 470 1 Liner 1,1.60 N-80 6/7/1983 675 505.0 Cement Stages . Description Top (fIXB) 3,225.0 Birm (ftKB) Eval Method Cement Plug 3,575.0 PROPOSED: Cap CIBP with 25 sks cmt. नवा । Description Top (ftKB) Bun (ftKB) Eval Method TUS - 625 Surface, Casing; 0.0-Cement Plug PROPOSED: Perf and 2.900.0 3.078.0 609.0 Sqz 40 sks cmt at 3195'. Bos - 1575 Sqz Csg Leak, 597.0-600.9 WOC and Tag. Yts- 1735 675 Description Top (MKB) Eval Method 8tm (ftK8) Cement Plug 47D.0 660.0 PROPOSED: Perf and 4 1/2; 0,0-3,078.0 Saz 25 sks cmt at 660'. PROPOSED Perfs: 669-6 4011 -7; 300.0-3,145.0 WOC and Tag. Wellbore 8.750; 609 0-- Seven Rivers (final) Eval Method 3,145.0 Cement Plug PROPOSED: Perf and 0.0 200.0 2,734 8 Sqz 55 sks cmt at 200'. Circ cmt to surface 2 899 0 Cement Plug 2,900.0-Description Fyal Mathod Parto Saz from 3 078.0 Cement Plua 3.078.0 3.195.0 PROPOSED: Perf and 2 429 1 Sqz Csg Leak; 2,899,0-Sqz 40 sks cmt at 3195. 1785-1595 2,928 0 WOC and Tag. 2,925.1 Description Top (ftKB) Bun (taka) Eval Method Cement Plug: 3-978-0-3 078 1 8 5/8 0.0 609.0 Returns to 3,405.0 [7.85- IS95 Surface Description Eval Method Comment 3.145.0 300.0 CBL 3 140 1 - Grayburg (final) Eval Method Top (fIKB 3 141 7 Plug back 3.728.0 4,105.0 Top (RKB) Birn (ftKB) Eval Method Description Comment 3143.4 Soz Csg Leak 597.0 628,0 Production, Casing; 0.0-Too INKB Eval Method Description Ban IRKE Comment 3,145.0 Sqz Csg Leak 2,928.0 3,145.0 2.899.0 PROPOSED Perfs; Top (RKB) Birm (ftKB) Eval Method 31949 4 1/2 3.078.0 Returns to Cement Plug; 3 225 0-3.225.1 Surface 3.575.0 **Tubing Strings** 3 500.9 Tubing Description Sei Depti. 3,727.0 Run Date 9/28/1942 Pul Date 4/1/1943 Tubing 35160 Set Depth 3,727.0 Run Date 4/9/1943 Pul Date 10/1/1957 Tubing Description Tubing 3 578.1 Bridge Plug - Permanent; 2:575:0-3:580.0; 4:000 Set Depth 3.650.0 Pull Date 9/11/1995 Tubing Descriptor 6/11/1983 3 540 1 Tubing - Production 3050 Tubing Description Pull Date Set Depth 3,660.0 2.588.E Tubing - Production 9/11/1995 4/9/1997 41/2 Slotted CSq Rur: Date 4/10/1997 Pull Date Tubing Description Set Depth. 3,099.0 3 999 1 Com 3145-3707 6/1/2016 Tubing Perforations 3 611.9 - Şan Andres (final) -200 0 200.0 Top (ffKB) Stm (NKB) Comment Wellbore; 6,250, 3,145 0-1625.0 660.0 660.0 Open Hole: 3,625.0-4,105.0 Top (ftKB) Bitm (fiXB) Comment 3 690 0 3 673 0 3, 195.0 3,195.0 'n Btm (ftKB) 3444.0 Top (fiXB) Comment 3.690.0 3,625.0 Other In Hole · Des Top (ftKB) Btm (ftKB) Run Date 3 707.0 Liner, Casing, 0.0-3,707.0 Bridge Plug -3,575.0 3,580,0 PROPOSED: Set CIBP Plug back, 3,728 0-Permanent at 3575' and cap with 25 4 105 0 sks cmt. 4 105 0 Wellbore, 4,105.0 www.peloton.com Page 1/2 Report Printed: 6/6/2016

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

<u>Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:</u>
From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. -Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
 Operations must include adequate measures for stabilization and reclamation of disturbed lands.
 Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
 process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.

- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Linda Denniston Environmental Protection Specialist 575-234-5974

Henryetta Price Environmental Protection Specialist 575-234-5951

Dara Glass
Environmental Protection Specialist
575-234-5924

Shelly Tucker Environmental Protection Specialist 575-234-5979