

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

NM OIL CONSERVATION AND Natural Resources
ARTESIA DISTRICT
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505
OCT 21 2016 RECEIVED

WELL API NO. 30-005-61962
5. Indicate Type of Lease STATE [ ] FEE [X]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Spool SU Com
8. Well Number 5
9. OGRID Number 025575
10. Pool name or Wildcat Pecos Slope; Abo
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3670'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [ ] PLUG AND ABANDON [ ]
TEMPORARILY ABANDON [ ] CHANGE PLANS [ ]
PULL OR ALTER CASING [ ] MULTIPLE COMPL [ ]
DOWNHOLE COMMINGLE [ ]
CLOSED-LOOP SYSTEM [ ]
OTHER: [ ]
SUBSEQUENT REPORT OF:
REMEDIAL WORK [ ] ALTERING CASING [ ]
COMMENCE DRILLING OPNS. [ ] P AND A [X]
CASING/CEMENT JOB [ ]
OTHER: [ ]

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

9/22/16 - Loaded annulus and tested. Pumped 20 bbls fresh water down tubing. ND wellhead and NU BOP.
9/23/16 - Set a 4-1/2" CIBP at 3621'. Tagged CIBP. Pumped mud and tested casing to 500 psi. Spotted 25 sx Class "C" cement. Calc TOC 3258'. WOC.
9/26/16 - Tagged plug at 3445'. Perforated 4 holes at 1505'. Pumped through perfs and circulated out 8-5/8" x 4-1/2". Pumped 45 sx Class "C" cement in/out plug. WOC. Tagged plug at 1305'. Perforated 4 holes at 950'. Pumped through perfs, circulating, then plugged off 1500 psi. Pumped down 8-5/8", circulated up tubing. Plugged off 300 psi and pumped down 4-1/2". Displaced 15 bbls. Pumped down tubing again. Started circulating. Plugged off 1500 psi. Had scale in returns. Re-perforated at 950'. Same results.
9/27/16 - RIH open ended to 970'. Circulated and displaced 4-1/2" with clean brine. Opened 8-5/8" x 4-1/2" valve. Pumped and circulated. Displaced with 50 bbls. Pumped 30 sx Class "C" cement at 650' (10-3/4" shoe plug). WOC 4 hrs. Tagged at 736'. Perforated at 452'. Pumped through perfs and circulated out 8-5/8" x 4-1/2". ND BOP. Pumped 125 sx Class "C" cement. Displaced with 6 bbls brine. Calc TOC 375'.
9/28/16 - Tagged at 260'. Pumped 18 sx Class "C" cement. Filled to surface. Topped well bore only.
10/7/16 - Dug out cellar. Busted up cement in cellar. Cut off wellhead. Installed well head and filled cellar. WELL IS PLUGGED AND ABANDONED.

Approved for plugging well bore only.
Liability under bond is retained by providing receipt of Case Date.
Subsequent Report of Well Plugging
Form is: www.enr.state.nm.us/ocd.

Accepted for record
NMOCD

Spud Date: [ ]

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Tina Huerta] TITLE Regulatory Reporting Supervisor DATE October 18, 2016

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only
APPROVED BY: [Signature] TITLE COMPLIANCE OFFICER DATE 10/21/2016
Conditions of Approval (if any):