

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103  
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-03432
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator J CLEO THOMPSON		6. State Oil & Gas Lease No. C058127
3. Address of Operator 325 NORTH SAINT PAUL, SUITE 4300 DALLAS, TX 75201		7. Lease Name or Unit Agreement Name R TRAVIS JR
4. Well Location Unit Letter _____ : 330 _____ feet from the NORTH _____ line and 330 _____ feet from the EAST _____ line Section 17 _____ Township 18S _____ Range 29E _____ NMPM _____ County EDDY		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3488 GT		9. OGRID Number 11181
		10. Pool name or Wildcat

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. 25SX @ 2585-2592
2. 3. CIRCULATE HOLE W/ MUD LADEN FLUID.
4. P&SQZ 45 SX @ 1460-1360. WOC & TAG
5. P&SQZ 45SX @ 620-520. WOC & TAG
6. 7. P&SQZ 45 SX @ 100' TO SURFACE.
8. WELD ON DRY HOLE MARKER

2492 TOE ← SET CMT TOP HIGHER  
SET CIBP @ 2580' ADD THIS  
SPOT 25 SX - WOC 2 TAG

PERF 2 SQ @ 350'  
WOC 2 TAG

ADD THIS

NM OIL CONSERVATION  
ARTESIA DISTRICT

NOV 01 2016

RECEIVED

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Form: www.emnrd.state.nm.us/ocd.

Spud Date: 01/27/1940

Rig Release Date: 03/14/1940

WELL MUST BE PLUGGED BY 11/3/2017

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Shelly Bilberry*

TITLE REGULATORY SPECIALIST

DATE 10/26/2016

Type or print name SHELLY BILBERRY

E-mail address: SBILBERRY@JCLEO.COM

PHONE: (432)550-8887

For State Use Only

APPROVED BY:

*Robert 2 Bynd*

TITLE COMPLIANCE OFFICER

DATE 11/3/2016

Conditions of Approval (if any):

SEE ATTACHED COA-S

# Travis R #1

Field: LOCO HILLS

API: 30-015-03432

Spud Date: 01/27/40

Comp. Date: 03/14/40

**PRIOR TO P&A  
NOT TO SCALE  
Wellbore Diagram**


Location:	
Footage:	330 FNL & 330 FEL
Section:	17
Township:	18S
Range:	29E
Meridian:	NMP
County:	EDDY
Lat (NAD83):	32.7537575
Long (NAD83):	-104.0894241

Hole Size:		ID	
Surface Csg:	8 1/4	OD	ppf
Set @:	346.0	ft	
TOC:	Surface		
Cement:	50	sx	ppg
			Yield

Hole Size:	8	ID	
Prod. Csg:	7	OD	ppf
Set @:	2,300.0	ft	
TOC:	Circulated		
Lead Cement:	100	sx	ppg
			Yield
Tail Cement:		sx	ppg
			Yield

8" OPEN HOLE 2,301' - 2,585'

03/10/40: 2,542' - 2,565' Shot w/210 qts



BBTR 2,541' ft  
TR 2,585' ft

# Travis R #1

## PLUG & ABANDONED

Field: LOCO HILLS

API: 30-015-03432

Spud Date: 01/27/40

Comp. Date: 03/14/40

### CURRENT NOT TO SCALE Wellbore Diagram


Hole Size:	8	ID	
Surface Csg:	8 1/4	OD	ppf
Set @:	346.0	ft	
TOC:	Surface		
Cement:	50	sx	ppg
			Yield

350' PERF & SQUEEZE  
WOL & TAG

Hole Size:	8	ID	
Prod. Csg:	7	OD	ppf
Set @:	2,300.0	ft	
TOC:	Circulated		
Lead Cement:	100	sx	ppg
			Yield
Tail Cement:		sx	ppg
			Yield

8" OPEN HOLE 2,301' - 2,585'

03/10/40: 2,542' - 2,565' Shot w/210 qts



Location:	
Footage:	330 FNL & 330 FEL
Section:	17
Township:	18S
Range:	29E
Meridian:	NMP
County:	EDDY
Lat (NAD83):	32.7537575
Long (NAD83):	-104.0894241

SURFACE - 100' P&SQZ 45SX CMT

520' - 620' P&SQZ 45SX CMT

1,360' - 1,460' P&SQZ 45SX CMT

CIBP @ 2580-5101 25SKS PLUG  
WOL & TAG

2492

2,542' - 2,585' DUMP 25SX CMT

PBTD 4.4 ft  
TD 2,585 ft

## CONDITIONS FOR PLUGGING AND ABANDONMENT

### District II / Artesia N.M.

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, **Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. **Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.**
7. Produced water **will not** be used during any part of the plugging operation.
8. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
9. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
10. **Class 'C' cement will be used above 7500 feet.**
11. **Class 'H' cement will be used below 7500 feet.**
12. **A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged**
13. **All Casing Shoes Will Be Perforated and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing**
14. **A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.**
15. **If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing**

16. **When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set**
17. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, **(WOC 4 hrs and tag).**
18. **No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.**
19. Any Production Formations will be isolated with cement plugs: Some of these are:
  - A) **Strawn, Fusselman, Devonian, Marrow, Atoka, Wolfcamp, Bone springs, Delaware, Abo, Glorieta, Any Salt Section, (Potash), Grayburg, Queen, Yates, Tubb, 7-Rivers**
  - B) **Potash---** (In the R-111-P Area (Potash Mine Area), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, **WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.**
20. **If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing**

#### **DRY HOLE MARKER REQUIRMENTS**

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

**1. Operator name 2. Lease and Well Number 3.API Number 4. Unit Letter 5. Quarter Section (feet from the North, South, East or West) 6. Section, Township and Range 7. Plugging Date 8. County**

#### **(SPECIAL CASES)**

##### **AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS**

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)