<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe NM 87505

NM OIL CONSERVATION

			Santa I C, IV	111 07505		ARTESIA DISTRICT
Dotae 11 5 TC	GAS CAPTURE PLAN			· , · · · · · · · · · · · · · · · · · ·	NOV 0 3 2016	
Date: 11-3-16   RECEIVED  ☐ Original   Operator & OGRID No.: Mewbourne Oil Company - 14744    ☐ Amended - Reason for Amendment:						
This Gas Capture Plan on the completion (new dri	ll, recomplete t	o new zone, re-fra	ac) activity.			facility flaring/venting f
Well(s)/Production Fac	ility – Name of	<u>facility</u>	·			1 by 12.13.10.12 (Marie).
The well(s) that will be leave Well Name	API	oduction facility a Well Location (ULSTR)	Footages	the table be Expected MCF/D	Flared or Vented	Comments
Yardbirds 3 WOAP Fee #2H	30-015-	A 3-24S-28E	185' FNL 450' FEL		3	Online after frac
place. The gas produce  Crestwood low  100 'of pipeline to  (periodically) to Cresty  be drilled in the foresees	I to a production of from production of from product of from pressure connect the factorial of the from the fro	on facility after flation facility is de gathering system icility to low/high drilling, completion addition, Mewbord drilling and complete in Seattle in S	edicated to n located in pressure gan and estima ourne Oil Completion scheme. 29, Two	Cresty  1 Eddy ( athering system ted first produmny and edules. Gas 71. 245, Rn	cood. County, New em. Mewbo luction date fo Crestwoo from these g. 28E, Ed.	gas transporter system is and will be connected Mexico. It will requi urne Oil Company provid or wells that are scheduled have period wells will be processed dy County, New Mexic pressures.
flared or vented. During the sand, the wells will be to	flowback, the fl rned to product s there are oper	uids and sand cor ion facilities. Ga ational issues on _	ntent will be a s sales shoul Crestwood	monitored. \ Id start as so system at	When the proc on as the we	uction tanks and gas will l duced fluids contain minim lls start flowing through t sed on current information,

al e it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

## Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines