

NM OIL CONSERVATION  
ARTESIA DISTRICT  
NOV 09 2016

Form 3160-3  
(March 2012)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED  
OMB No. 1004-0137  
Expires October 31, 2014


APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NM-125008
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other / <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator Yates Petroleum Corporation		7. If Unit or CA Agreement, Name and No.
3a. Address 105 South Fourth St. Artesia, NM 88210		8. Lease Name and Well No. Roy AET Com #10H
3b. Phone No. (include area code) 575-748-4120		9. API Well No. 30-015- <del>1222</del> 43955
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface 1935' FNL & 15' FEL At proposed prod. zone 2310' FNL & 330' FWL		10. Field and Pool, or Exploratory N. Seven Rivers; Glorieta-Yeso 97565
14. Distance in miles and direction from nearest town or post office* 15 miles		11. Sec., T. R. M. or Blk. and Survey or Area Section 17, T19S-R25E
15. Distance from proposed* 15' FEL location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)	16. No. of acres in lease 960 80 NM-125008	12. County or Parish Eddy County
17. Spacing Unit dedicated to this well S2N2 160 arces	13. State NM	
18. Distance from proposed location* 945' to nearest well, drilling, completed, applied for, on this lease, ft.	19. Proposed Depth 7392' TD 2400' TVD	20. BLM/BIA Bond No. on file NMB000434 NMB000920
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3516'	22. Approximate date work will start*	23. Estimated duration 15 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- |  |   |
|--|---|
| 1. Well plat certified by a registered surveyor.   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan.  | 5. Operator certification   |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the BLM.             |

25. Signature 	Name (Printed/Typed) Travis Hahn	Date 06/05/2015
---	-------------------------------------	--------------------

Title  
Land Regualtory Agent

Approved by (Signature) <b>/s/Cody Layton</b>	Name (Printed/Typed)	Date <b>NOV 1 - 2016</b>
Title <b>FIELD MANAGER</b>	Office <b>CARLSBAD FIELD OFFICE</b>	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

**APPROVAL FOR TWO YEARS**

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

\*(Instructions on page 2)

**Roswell Controlled Water Basin**

**SEE ATTACHED FOR  
CONDITIONS OF APPROVAL**

**Approval Subject to General Requirements  
& Special Stipulations Attached**

## DISTRICT I

1625 N. French Dr., Hobbs, NM 88240  
Phone (575) 393-8161 Fax: (575) 393-0720

## DISTRICT II

811 S. First St., Artesia, NM 88210  
Phone (575) 748-1283 Fax: (575) 748-9720

## DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410  
Phone (505) 334-6178 Fax: (505) 334-6170

## DISTRICT IV

1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone (505) 476-3480 Fax: (505) 476-3482

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-102

Revised August 1, 2011

Submit one copy to appropriate  
District Office

## OIL CONSERVATION DIVISION

1220 South St. Francis Dr.  
Santa Fe, New Mexico 87505

## WELL LOCATION AND ACREAGE DEDICATION PLAT

☐ AMENDED REPORT

API Number 30-015- <del>41204</del> 43955	Pool Code 97565	Pool Name N. Seven Rivers; Glorieta - Yeso
Property Code 40227 40480	Property Name ROY AET COM	Well Number 10H
OGRID No. 025575	Operator Name YATES PETROLEUM CORPORATION	Elevation 3517

## Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
H	17	19 S	25 E		1935'	NORTH	15'	EAST	EDDY

## Bottom Hole Location If Different From Surface


UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
E	17	19 S	25 E		2260'	NORTH	330'	WEST	EDDY

Dedicated Acres	Joint or Infill	Consolidation Code	Order No.
160			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED  
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION


<p>N.: 606938.3 E.: 485258.3 (NAD83)</p> <p>2260'</p> <p>NM-125008</p> <p>330' B.H.</p> <p>PROPOSED BOTTOM HOLE LOCATION Lat - N 32°39'43.82" Long - W 104°30'52.36" NMSPCE- N 604676.5 E 485571.4 (NAD-83)</p> <p>N.: 606923.1 E.: 487920.1 (NAD83)</p> <p>1945' + 507' FEL</p> <p>Penetration Point</p> <p>15'</p> <p>S.L.</p> <p>15'</p> <p>330'</p> <p>N.: 601622.4 E.: 485218.7 (NAD83)</p>	<p>N.: 606908.0 E.: 490581.9 (NAD83)</p> <p>OPERATOR CERTIFICATION</p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unLEASEd mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</p> <p>Signature <u>Travis Hahn</u> Date <u>4/28/14</u></p> <p>Printed Name <u>Travis Hahn</u></p> <p>Email Address <u>thahn@yatespetroleum.com</u></p> <p>SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p>Date Surveyed <u>4/28/14</u></p> <p>Signature &amp; Seal of Professional Surveyor <u>[Signature]</u></p> <p>Certificate No. <u>7977</u></p> <p>Scale: 1" = 2000'</p> <p>WO Num.: 30184</p>
--	--

SECTION 17, TOWNSHIP 19 SOUTH, RANGE 25 EAST. N.M.P.M.,  
EDDY COUNTY, NEW MEXICO.



YATES PETROLEUM CORPORATION  
ROY AET STATE COM #10H  
ELEV. - 3517'  
Lat - N 32°39'46.83"  
Long - W 104°29'54.10"  
NMSPCE- N 604973.1  
E 490552.3  
(NAD-83)

ARTESIA, NM IS ±17 MILES TO THE NORTHEAST OF LOCATION.



PETROLEUM  
CORPORATION

REF: ROY AET STATE COM #10H / WELL PAD TOPO


THE ROY AET STATE COM #10H LOCATED 1935' FROM  
THE NORTH LINE AND 15' FROM THE EAST LINE OF  
SECTION 17, TOWNSHIP 19 SOUTH, RANGE 25 EAST.

N.M.P.M., EDDY COUNTY, NEW MEXICO.

**basin**  
**surveys**  
focused on excellence  
in the oilfield


P.O. Box 1786  
1120 N. West County Rd.  
Hobbs, New Mexico 88241  
(575) 393-7316 - Office  
(575) 392-2206 - Fax  
basinsurveys.com

SECTION 17, TOWNSHIP 19 SOUTH, RANGE 25 EAST. N.M.P.M.,  
EDDY COUNTY, NEW MEXICO.



YATES PETROLEUM CORPORATION  
ROY AET STATE COM #10H  
ELEV. - 3517'

Lat - N 32°39'46.83"  
Long - W 104°29'54.10"  
NMSPCE- N 604973.1  
E 490552.3  
(NAD-83)



YATES PETROLEUM CORPORATION


REF: ROY AET STATE COM #10H / WELL PAD TOPO

THE ROY AET STATE COM #10H LOCATED 1935' FROM  
THE NORTH LINE AND 15' FROM THE EAST LINE OF  
SECTION 17, TOWNSHIP 19 SOUTH, RANGE 25 EAST.

N.M.P.M., EDDY COUNTY, NEW MEXICO.

**basin**  
**surveys**  
focused on excellence  
in the oilfield

P.O. Box 1786 (575) 393-7316 - Office  
1120 N. West County Rd. (575) 392-2206 - Fax  
Hobbs, New Mexico 88241 basin-surveys.com



## ROY AET STATE COM #10H

Located 1935' FNL and 15' FEL

Section 17, Township 19 South, Range 25 East,  
N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786  
1120 N. West County Rd.  
Hobbs, New Mexico 88241  
(575) 393-7316 - Office  
(575) 392-2206 - Fax  
basinsurveys.com


0' 1000' 2000' 3000' 4000'  
SCALE: 1" = 2000'

W.O. Number: KAN 30184


Survey Date: 03-06-2014

YELLOW TINT - USA LAND  
BLUE TINT - STATE LAND  
NATURAL COLOR - FEE LAND





**ROY AET STATE COM #10H**  
 Located 1935' FNL and 15' FEL  
 Section 17, Township 19 South, Range 25 East,  
 N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786  
 1120 N. West County Rd.  
 Hobbs, New Mexico 88241  
 (575) 393-7316 - Office  
 (575) 392-2206 - Fax  
 basinsurveys.com

0 1 MI 2 MI 3 MI 4 MI


SCALE: 1" = 2 MILES

W.O. Number: KAN 30184


Survey Date: 03-06-2014

YELLOW TINT - USA LAND  
 BLUE TINT - STATE LAND  
 NATURAL COLOR - FEE LAND





**ROY AET STATE COM #10H**  
 Located 1935' FNL and 15' FEL  
 Section 17, Township 19 South, Range 25 East,  
 N.M.P.M., Eddy County, New Mexico.



P.O. Box 1786  
 1120 N. West County Rd.  
 Hobbs, New Mexico 88241  
 (575) 393-7316 - Office  
 (575) 392-2206 - Fax  
[basinsurveys.com](http://basinsurveys.com)

0' 1000' 2000' 3000' 4000'

SCALE: 1" = 2000'

W.O. Number: KAN 30184

Survey Date: 03-06-2014

YELLOW TINT - USA LAND  
 BLUE TINT - STATE LAND  
 NATURAL COLOR - FEE LAND





# YATES PETROLEUM CORPORATION

Roy AET Com #10H

1935' FNL & 15' FEL, Section 17 -T19S-R25E, Surface Hole  
2260' FNL & 330' FWL, Section 17 - T19S-R25E, Bottom Hole  
Eddy County, New Mexico

1. The estimated tops of geologic markers are as follows:

San Andres	700'	Oil	Target Yeso	2772'	Oil
Gloriet	2173'	Oil	TVD: 2400'	MD:7392	
Yeso	2261'	Oil			

2. The estimated depths at which anticipated water, oil or gas formations are expected to be encountered:

Water: Approx.: 0' - 7392'

Oil or Gas: See above--All Potential Zones

3. Pressure Control Equipment: A 3000 PSI BOP will be installed on the 9 5/8" casing. Test will be conducted by an independent tester, utilizing a test plug in the well head. BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes on each segment of the system tested if test is done with a test plug and 30 minutes without a test plug. Blind rams and pipe rams will be tested to the rated pressure of the BOP. Any leaks will be repaired at the time of the test. Annular preventers will be tested to 50% of rated pressure. Accumulator system will be inspected for correct pre charge pressures, and proper functionality, prior to connection to the BOP system. Tests will be conducted before drilling out from under all casing strings, which are set and cemented in place. Blowout Preventer controls will be installed prior to drilling the surface plug and will remain in use until the well is completed or abandoned. Preventers will be inspected and operated at least daily to ensure good mechanical working order, and this inspection recorded on the daily drilling report. See Exhibit.

4. Auxiliary Equipment:

A. Auxiliary Equipment: Kelly cock, pit level indicators, flow sensor equipment and a sub with full opening valve to fit the drill pipe and collars will be available on the rig floor in the open position at all times for use when kelly is not in use.

5. THE PROPOSED CASING AND CEMENTING PROGRAM:

A.

Hole Size	Casing Size	Wt./Ft	Grade	Coupling	Interval	Length
26"	20"	94#	H-40	ST&C	0'-57'	57'
14.75"	9.625"	36#	J-55	LT&C	0'-800'	800'
8.75"	5.5"	17#	P-110	Buttress Thread	0'-2772'	2772'
8.5"	5.5"	17#	P-110	Buttress Thread	2772'-7392'	4620'

Minimum Casing Design Factors: Burst 1.0, Tensile 1.8, Collapse 1.125



**B. CEMENTING PROGRAM:**

Conductor Cement (0'-85'): Lead with Ready Mix cement.

Surface Cement (0'-800'): Lead with 410 sacks of Class PozC 35:65:6 (WT 12.5, YLD 2.0, H2O 11.0 gal/sack). Tail with 205 sacks of Class C (WT 14.8, YLD 1.34, H2O 6.20 gal/sack) designed with 100% excess, TOC is surface. Additives for Class C are 2% CaCl2.

Production Cement (0'-7392'): Lead with 340 sacks of Class 35:65:6PzC (WT. 12.5, YLD 2.00, H2O 11. gal/sack); tail in with 930 sacks of Pecos Valley Lite (WT. 13.0, YLD 1.82, H2O 9.3 gal/sack). 30% CaCO3 Weight, 3.2% Expansion additive, 2% Antifoam, .8% Retarder, 15 Fluid loss. TOC is surface, designed with 35% excess.

Well will be drilled vertically to 2013', then be kicked off at approximately 2013', and the directionally drilled at 12 degrees per 100' with an 8 3/4 hole to 2772' MD (TVD 2490'). Hole size will then be reduced to 8 1/2 and drilled to 7392' (2400' TVD) where 5 1/2 casing will be set and cemented. Production string will be cemented to surface. Penetration point of producing zone will be encountered at 1972' FNL and 386' FEL, Section 17-T19S-R25E. Deepest TVD in the well is 2490' in the lateral hole.

Mud Program and Auxiliary Equipment:

Interval	Type	Weight	Viscosity	Fluid Loss
0'-800'	Fresh Water	8.6-8.7	32-34	N/C
800'-7392'	Fresh Water	8.5-8.7	28-32	N/C

Sufficient mud material(s) to maintain mud properties, control lost circulation and contain a blow out will be available at the well site during drilling operations. After surface casing is set an electronic PVT system will be installed as our primary mud level monitoring system. A secondary system will also be implemented as to insure the PVT system is functioning properly. The secondary system will be comprised of a derrick hand checking the fluid level in the pits hourly using a nut on the end of a rope hanging just above the fluid level in the pit.

**5. EVALUATION PROGRAM:**

Samples: 10' samples to 800 - TD.

Logging: No logs

Horizontal – MWD - GR- Horizontal

Coring: None

DST's: None

Mud logging: Yes from kickoff through lateral.

6. Abnormal Conditions, Bottom hole pressure and potential hazards:

Anticipated BHP:

From: 0	TO: 800'	Anticipated Max. BHP:	362 PSI
From: 800'	TO: 2490'	Anticipated Max. BHP:	1126 PSI

No abnormal pressures or temperatures are anticipated.

H2S is Anticipated → See COA

7. ANTICIPATED STARTING DATE:

Plans are to drill this well as soon as possible after receiving approval. It should take approximately 65 days to drill the well with completion taking another 30 days.



Project: Eddy County, NM (NAD83 NM1)  
Site: Roy AET State Com  
Well: #10H  
Wellbore: WB1/Job #1410492  
Design: Plan #2B 03-21-14  
Rig: Silver Oak 11

Phoenix  
TECHNOLOGY SERVICES

North Arrow  
Azimuth to Grid North  
True North: 0.99°  
Magnetic North: 7.79°  
Magnetic Field  
Strength: 48500.5 nT  
Dip Angle: 80.37°  
Date: 03/21/2014  
Model: IGRF2010\_14

WELL DETAILS			
Well Name	3517.00	Latitude	32° 38' 46.3109 N
Well ID	40552.30	Longitude	104° 29' 54.1007 W
Well Depth	60497.10		


SECTION DETAILS			
Sec	MD	Inc	Asl
1	0.00	0.00	0.00
2	2070.25	0.00	0.00
3	2833.17	91.55	2537.70
4	2833.30	91.55	2537.82
5	2833.14	91.55	2537.82
6	2833.14	91.55	2537.82

DESIGN TARGET DETAILS			
Name	TD	MD	Inc
PBH-Roy AET #10H	2425.00	-296.63	48501.46
Plan this target center			

Map System: US State Plane 1983  
Datum: North American Datum 1983  
Zone Name: New Mexico Eastern Zone  
Local Origin: Well #10H, Grid North  
Latitude: 32° 38' 46.3109 N  
Longitude: 104° 29' 54.1007 W  
Grid East: 40552.30  
Grid North: 60497.10  
Scale Factor: 1.000  
Geographic Model: IGRF2010\_14  
Magnetic Declination: 7.79°  
Dip Angle from Horizontal: 80.37°  
Magnetic Field Strength: 48501

FORMATION TOP DETAILS			
Formation	MD	Inc	Asl
2188.72	2170.46	0.00	2170.46
2249.08	2233.55	91.55	2233.55
2547.64	2511.54	91.55	2511.54

LEGEND  
#16, WB1, Inc Surveys VO  
Plan #2B 03-21-14





## **Yates Petroleum Corp.**

**Eddy County, NM (NAD83 NME)**

**Roy AET State Com**

**#10H**

**WB1/Job #1410492**

**Plan: Plan #2B 03-21-14**

## **Standard Planning Report**

**21 March, 2014**





# Phoenix Technology Services Planning Report



Database:	GCR DB	Local Co-ordinate Reference:	Well #10H
Company:	Yates Petroleum Corp.	TVD Reference:	KB @ 3535.00usft (Silver Oak 11)
Project:	Eddy County, NM (NAD83 NME)	MD Reference:	KB @ 3535.00usft (Silver Oak 11)
Site:	Roy AET State Com	North Reference:	Grid
Well:	#10H	Survey Calculation Method:	Minimum Curvature
Wellbore:	WB1/Job #1410492		
Design:	Plan #2B 03-21-14		

Project	Eddy County, NM (NAD83 NME)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Roy AET State Com		
Site Position:		Northing:	607,439.10 usft
From:	Map	Easting:	490,431.50 usft
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "
		Grid Convergence:	-0.09 °

Well	#10H		
Well Position	+N/-S	-2,466.00 usft	Northing: 604,973.10 usft
	+E/-W	120.80 usft	Easting: 490,552.30 usft
Position Uncertainty	0.00 usft	Wellhead Elevation:	Ground Level: 3,517.00 usft

Wellbore	WB1/Job #1410492		
Magnetics	Model Name	Sample Date	Declination
	IGRF2010_14	03/21/14	7.71
			Dip Angle
			60.37
			Field Strength
			48,501

Design	Plan #2B 03-21-14		
Audit Notes:			
Version:	Phase:	PROTOTYPE	Tie On Depth: 0.00
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W
	(usft)	(usft)	(usft)
	0.00	0.00	0.00
			Direction
			266.64

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2,070.25	0.00	0.00	2,070.25	0.00	0.00	0.00	0.00	0.00	0.00	
2,833.17	91.55	253.70	2,547.54	-137.63	-470.67	12.00	12.00	0.00	253.70	
3,336.98	91.55	268.82	2,533.82	-213.94	-967.00	3.00	0.00	3.00	89.78	
7,353.14	91.55	268.82	2,425.00	-296.63	-4,980.84	0.00	0.00	0.00	0.00	PBHL-Roy AET #10H
7,453.14	91.55	268.82	2,422.29	-298.68	-5,080.78	0.00	0.00	0.00	0.00	



# Phoenix Technology Services Planning Report



Database: GCR DB  
Company: Yates Petroleum Corp.  
Project: Eddy County, NM (NAD83 NME)  
Site: Roy AET State Com  
Well: #10H  
Wellbore: WB1/Job #1410492  
Design: Plan #2B 03-21-14

Local Co-ordinate Reference: Well #10H  
TVD Reference: KB @ 3535.00usft (Silver Oak 11)  
MD Reference: KB @ 3535.00usft (Silver Oak 11)  
North Reference: Grid  
Survey Calculation Method: Minimum Curvature

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>San Andres</b>									
2,070.25	0.00	0.00	2,070.25	0.00	0.00	0.00	0.00	0.00	0.00
<b>KOP, 12°/100' Build</b>									
2,100.00	3.57	253.70	2,099.98	-0.26	-0.89	0.90	12.00	12.00	0.00
2,170.46	12.02	253.70	2,169.72	-2.94	-10.06	10.21	12.00	12.00	0.00
<b>Glorieta</b>									
2,200.00	15.57	253.70	2,198.41	-4.92	-16.82	17.08	12.00	12.00	0.00
2,253.55	22.00	253.70	2,249.08	-9.75	-33.36	33.87	12.00	12.00	0.00
<b>Yeso</b>									
2,300.00	27.57	253.70	2,291.24	-15.22	-52.04	52.84	12.00	12.00	0.00
2,400.00	39.57	253.70	2,374.40	-30.71	-105.01	106.64	12.00	12.00	0.00
2,500.00	51.57	253.70	2,444.28	-50.71	-173.43	176.11	12.00	12.00	0.00
2,600.00	63.57	253.70	2,497.81	-74.36	-254.29	258.22	12.00	12.00	0.00
2,700.00	75.57	253.70	2,532.65	-100.61	-344.07	349.38	12.00	12.00	0.00
2,800.00	87.57	253.70	2,547.29	-128.33	-438.84	445.62	12.00	12.00	0.00
2,811.54	88.96	253.70	2,547.64	-131.56	-449.92	456.86	12.00	12.00	0.00
<b>Yeso Target</b>									
2,833.17	91.55	253.70	2,547.54	-137.63	-470.67	477.94	12.00	12.00	0.00
<b>LP, Begin 3°/100' Turn</b>									
2,900.00	91.56	255.71	2,545.73	-155.26	-535.11	543.30	3.00	0.01	3.00
3,000.00	91.56	258.71	2,543.01	-177.39	-632.58	641.90	3.00	0.01	3.00
3,100.00	91.56	261.71	2,540.28	-194.39	-731.07	741.22	3.00	0.00	3.00
3,200.00	91.56	264.71	2,537.55	-206.21	-830.32	840.99	3.00	0.00	3.00
3,300.00	91.56	267.71	2,534.82	-212.82	-930.06	940.94	3.00	-0.01	3.00
3,336.98	91.55	268.82	2,533.82	-213.94	-967.00	977.89	3.00	-0.01	3.00
<b>Hold 91.55° Inc, 268.82° Azm</b>									
3,400.00	91.55	268.82	2,532.11	-215.24	-1,029.99	1,040.84	0.00	0.00	0.00
3,500.00	91.55	268.82	2,529.40	-217.29	-1,129.93	1,140.73	0.00	0.00	0.00
3,600.00	91.55	268.82	2,526.69	-219.35	-1,229.87	1,240.62	0.00	0.00	0.00
3,700.00	91.55	268.82	2,523.98	-221.41	-1,329.81	1,340.52	0.00	0.00	0.00
3,800.00	91.55	268.82	2,521.28	-223.47	-1,429.76	1,440.41	0.00	0.00	0.00
3,900.00	91.55	268.82	2,518.57	-225.53	-1,529.70	1,540.30	0.00	0.00	0.00
4,000.00	91.55	268.82	2,515.86	-227.59	-1,629.64	1,640.19	0.00	0.00	0.00
4,100.00	91.55	268.82	2,513.15	-229.65	-1,729.58	1,740.08	0.00	0.00	0.00
4,200.00	91.55	268.82	2,510.44	-231.71	-1,829.52	1,839.97	0.00	0.00	0.00
4,300.00	91.55	268.82	2,507.73	-233.77	-1,929.47	1,939.86	0.00	0.00	0.00
4,400.00	91.55	268.82	2,505.02	-235.82	-2,029.41	2,039.75	0.00	0.00	0.00
4,500.00	91.55	268.82	2,502.31	-237.88	-2,129.35	2,139.64	0.00	0.00	0.00
4,600.00	91.55	268.82	2,499.60	-239.94	-2,229.29	2,239.53	0.00	0.00	0.00
4,700.00	91.55	268.82	2,496.89	-242.00	-2,329.24	2,339.42	0.00	0.00	0.00
4,800.00	91.55	268.82	2,494.18	-244.06	-2,429.18	2,439.31	0.00	0.00	0.00
4,900.00	91.55	268.82	2,491.47	-246.12	-2,529.12	2,539.20	0.00	0.00	0.00
5,000.00	91.55	268.82	2,488.76	-248.18	-2,629.06	2,639.09	0.00	0.00	0.00
5,100.00	91.55	268.82	2,486.05	-250.24	-2,729.00	2,738.98	0.00	0.00	0.00
5,200.00	91.55	268.82	2,483.34	-252.30	-2,828.95	2,838.88	0.00	0.00	0.00
5,300.00	91.55	268.82	2,480.63	-254.35	-2,928.89	2,938.77	0.00	0.00	0.00
5,400.00	91.55	268.82	2,477.92	-256.41	-3,028.83	3,038.66	0.00	0.00	0.00
5,500.00	91.55	268.82	2,475.21	-258.47	-3,128.77	3,138.55	0.00	0.00	0.00
5,600.00	91.55	268.82	2,472.50	-260.53	-3,228.71	3,238.44	0.00	0.00	0.00
5,700.00	91.55	268.82	2,469.79	-262.59	-3,328.66	3,338.33	0.00	0.00	0.00
5,800.00	91.55	268.82	2,467.08	-264.65	-3,428.60	3,438.22	0.00	0.00	0.00



# Phoenix Technology Services

## Planning Report



Database:	GCR DB	Local Co-ordinate Reference:	Well #10H
Company:	Yates Petroleum Corp.	TVD Reference:	KB @ 3535.00usft (Silver Oak 11)
Project:	Eddy County, NM (NAD83 NME)	MD Reference:	KB @ 3535.00usft (Silver Oak 11)
Site:	Roy AET State Com	North Reference:	Grid
Well:	#10H	Survey Calculation Method:	Minimum Curvature
Wellbore:	WB1/Job #1410492		
Design:	Plan #2B 03-21-14		

### Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,900.00	91.55	268.82	2,464.37	-266.71	-3,528.54	3,538.11	0.00	0.00	0.00
6,000.00	91.55	268.82	2,461.66	-268.77	-3,628.48	3,638.00	0.00	0.00	0.00
6,100.00	91.55	268.82	2,458.95	-270.82	-3,728.42	3,737.89	0.00	0.00	0.00
6,200.00	91.55	268.82	2,456.25	-272.88	-3,828.37	3,837.78	0.00	0.00	0.00
6,300.00	91.55	268.82	2,453.54	-274.94	-3,928.31	3,937.67	0.00	0.00	0.00
6,400.00	91.55	268.82	2,450.83	-277.00	-4,028.25	4,037.56	0.00	0.00	0.00
6,500.00	91.55	268.82	2,448.12	-279.06	-4,128.19	4,137.45	0.00	0.00	0.00
6,600.00	91.55	268.82	2,445.41	-281.12	-4,228.13	4,237.35	0.00	0.00	0.00
6,700.00	91.55	268.82	2,442.70	-283.18	-4,328.08	4,337.24	0.00	0.00	0.00
6,800.00	91.55	268.82	2,439.99	-285.24	-4,428.02	4,437.13	0.00	0.00	0.00
6,900.00	91.55	268.82	2,437.28	-287.30	-4,527.96	4,537.02	0.00	0.00	0.00
7,000.00	91.55	268.82	2,434.57	-289.35	-4,627.90	4,636.91	0.00	0.00	0.00
7,100.00	91.55	268.82	2,431.86	-291.41	-4,727.85	4,736.80	0.00	0.00	0.00
7,200.00	91.55	268.82	2,429.15	-293.47	-4,827.79	4,836.69	0.00	0.00	0.00
7,300.00	91.55	268.82	2,426.44	-295.53	-4,927.73	4,936.58	0.00	0.00	0.00
7,353.14	91.55	268.82	2,425.00	-296.63	-4,980.84	4,989.66	0.00	0.00	0.00
PBHL-Roy AET #10H									
7,400.00	91.55	268.82	2,423.73	-297.59	-5,027.67	5,036.47	0.00	0.00	0.00
7,453.14	91.55	268.82	2,422.29	-298.68	-5,080.78	5,089.55	0.00	0.00	0.00
TD at 7453.14' MD 100' Past Hardline									

### Design Targets

Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
- hit/miss target									
- Shape									
PBHL-Roy AET #10H	0.00	0.07	2,425.00	-296.63	-4,980.84	604,676.48	485,571.46	32° 39' 43.81611 N	104° 30' 52.36201 W
- plan hits target center									
- Point									


### Formations

Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
700.00	700.00	San Andres		-1.55	266.59
2,170.46	2,169.72	Glorieta		-1.55	266.59
2,253.55	2,249.08	Yeso		-1.55	266.59
2,811.54	2,547.64	Yeso Target		-1.55	266.59

### Plan Annotations


Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
2,070.25	2,070.25	0.00	0.00	KOP, 12°/100' Build
2,833.17	2,547.54	-137.63	-470.67	LP, Begin 3°/100' Turn
3,336.98	2,533.82	-213.94	-967.00	Hold 91.55° Inc, 268.82° Azm
7,453.14	2,422.29	-298.68	-5,080.78	TD at 7453.14' MD 100' Past Hardline






# Yates Petroleum Corporation Typical 3,000 psi Pressure System Schematic Annular with Double Ram Preventer Stack

BOP-3




Typical 3,000 psi choke manifold assembly with at least these minimum features




# YATES PETROLEUM CORPORATION

Piping from Choke Manifold  
to the Closed Loop Drilling Mud System



# YATES PETROLEUM CORPORATION

## SILVER OAK RIG #11



## Yates Petroleum Corporation

### Hydrogen Sulfide Drilling Operation Plan

#### I. HYDROGEN SULFIDE TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards and characteristics of hydrogen sulfide (H<sub>2</sub>S).
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H<sub>2</sub>S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H<sub>2</sub>S on metal components. If high tensile tubular are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H<sub>2</sub>S Drilling Operations Plan and H<sub>2</sub>S Contingency Plan.

There will be an initial training session just prior to encountering a known or probable H<sub>2</sub>S zone (within 3 days or 500 feet) and weekly H<sub>2</sub>S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H<sub>2</sub>S Drilling Operation Plan and the H<sub>2</sub>S Contingency Plan. **The location of this well does not require a Public Protection Plan.**

## II. H2S SAFETY EQUIPMENT AND SYSTEMS

NOTE: All H2S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H2S.

### 1. Well Control Equipment:

- A. Flare line
- B. Choke manifold will have a remotely operated adjustable choke system.
- C. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment may include if applicable: annular preventer & rotating head.
- E. Mud/Gas Separator.

### 2. Protective equipment for essential personnel:

- A. Mark II Survive Air (or equivalent) 30-minute units located in the doghouse and at briefing areas, as indicated on well site diagram.

### 3. H2S detection and monitoring equipment:

- A. 3 portable H2S monitors positioned at: Shale Shaker, Bell Nipple, and Rig Floor. These units have warning lights and audible sirens when H2S levels of 10 PPM are reached.

### 4. Visual warning systems:

- A. Wind direction indicators as shown on well site diagram (attached).
- B. Caution/Danger signs (attached) shall be posted on roads providing direct access to location. Signs will be painted with high visibility yellow with black lettering of a sufficient size to be readable at a reasonable distance from the immediate location. Bilingual signs will be used, when appropriate. See example attached.

### 5. Mud program:

- A. The mud program has been designed to minimize the volume of H2S circulated to the surface. Proper mud weight, safe drilling practices and the use of H2S scavengers will minimize hazards when penetrating H2S bearing zones.

### 6. Metallurgy:

- A. All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H2S service.
- B. All elastomers used for packing and seals shall be H2S trim.

**7. Communication:**

- A. Cellular communications in company vehicles.
- B. Land line (telephone) communication at the Office.

**8. Well testing:**

- A. There will be no drill stem testing.


**EXHIBIT**

**DANGER**

**POISONS GAS**


**HYDROGEN SULFIDE**

 **NORMAL OPERATIONS**  
(GREEN)

**CAUTION POTENTIAL DANGER**  
(YELLOW)

 **DANGER POISONS GAS ENCOUNTERED**  
(RED) **AUTHORIZED PERSONAL ONLY.**  
**LOCATION SECURED.**

**1-575-746-1096**

**1-877-879-8899**

EDDY COUNTY EMERGENCY NUMBERS

ARTESIA FIRE DEPT. 575-746-5050  
ARTESIA POLICE DEPT. 575-746-5000  
EDDY CO. SHERIFF DEPT. 575-746-9888

LEA COUNTY EMERGENCY NUMBERS

HOBBS FIRE DEPT. 575-397-9308  
HOBBS POLICE DEPT. 575-397-9285  
LEA CO. SHERIFF DEPT. 575-396-1196

Yates Petroleum Corporation  
105 S. Fourth Street  
Artesia, NM 88210

## Hydrogen Sulfide (H<sub>2</sub>S) Contingency Plan



For

Roy AET Com #10H  
1935' FNL & 15' FEL  
Section 17, T19S-R25E  
Eddy County, NM



## Roy AET State Com #10H

This is an open drilling site. H<sub>2</sub>S monitoring equipment and emergency response equipment will be used within 500' of zones known to contain H<sub>2</sub>S, including warning signs, wind indicators and H<sub>2</sub>S monitor.



Assumed 100 ppm ROE = 3000'

100 ppm H<sub>2</sub>S concentration shall trigger activation of this plan.

## Emergency Procedures

In the case of a release of gas containing H<sub>2</sub>S, the first responder(s) must isolate the area and prevent entry by other persons into the 100 ppm ROE. Additionally the first responder(s) must evacuate any public places encompassed by the 100 ppm ROE. First responder(s) must take care not to injure themselves during this operation. Company and/or local officials must be contacted to aid in this operation. Evacuation of the public should be beyond the 100 ppm ROE.

All responders must have training in the detection of H<sub>2</sub>S, measures for protection against the gas, equipment used for protection and emergency response. Additionally, responders must be equipped with H<sub>2</sub>S monitors and air packs in order to control the release. Use the "buddy system" to ensure no injuries during the response.

## Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO<sub>2</sub>). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas

## Characteristics of H<sub>2</sub>S and SO<sub>2</sub>

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H <sub>2</sub> S	1.189 Air = 1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO <sub>2</sub>	2.21 Air = 1	2 ppm	N/A	1000 ppm

## Contacting Authorities

YPC personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. YPC Company response must be in coordination with the State of New Mexico's 'Hazardous Materials Emergency Response Plan' (HMER)

## ***Yates Petroleum Corporation Phone Numbers***

---

YPC Office .....	(575) 748-1471
Wade Bennett/Prod Superintendent .....	(575) 748-4236
LeeRoy Richards/Assistant Prod Superintendent .....	(575) 748-4228
Mike Larkin/Drilling .....	(575) 748-4222
Paul Hanes/Prod. Foreman/Roswell .....	(575) 624-2805
Tim Bussell/Drilling Superintendent .....	(575) 748-4221
Artesia Answering Service .....	(575) 748-4302
(During non-office hours)	

### **Agency Call List**

#### **Eddy County (575)**

##### **Artesia**

State Police .....	746-2703
City Police.....	746-2703
Sheriff's Office .....	746-9888
Ambulance.....	911
Fire Department.....	746-2701
LEPC (Local Emergency Planning Committee) .....	746-2122
NMOCD.....	748-1283

##### **Carlsbad**

State Police .....	885-3137
City Police.....	885-2111
Sheriff's Office.....	887-7551
Ambulance.....	911
Fire Department.....	885-2111
LEPC (Local Emergency Planning Committee).....	887-3798
US Bureau of Land Management.....	887-6544
New Mexico Emergency Response Commission (Santa Fe) .....	(505) 476-9600
24 HR .....	(505) 827-9126
New Mexico State Emergency Operations Center.....	(505) 476-9635
National Emergency Response Center (Washington, DC) ...	(800) 424-8802

##### **Other**

Boots & Coots IWC .....	1-800-256-9688 or (281) 931-8884
Cudd Pressure Control.....	(915) 699-0139 or (915) 563-3356
Halliburton .....	(575) 746-2757
B. J. Services.....	(575) 746-3569
Flight For Life -4000 24th St, Lubbock, TX .....	(806) 743-9911
Aerocare -Rr 3 Box 49f, Lubbock, TX .....	(806) 747-8923
Med Flight Air Amb 2301 Yale Blvd SE #D3, Albuq, NM .....	(505) 842-4433
S B Air Med Svc 2505 Clark Carr Loop SE, Albuq, NM .....	(505) 842-4949


SILVER OAK RIG #11



# Interim Reclamation Well Pad Layout Example\*

\*dimensions and locations will vary and are not intending to be actual representations. Final plans will be discussed with the Surface Owner, the BLM and Yates at time of interim reclamation.

North



# **MULTI-POINT SURFACE USE AND OPERATIONS PLAN**

## **Yates Petroleum Corporation**

Roy AET Com #10H  
1935' FNL and 15' FEL - Surface Hole Location  
2310' FNL and 330' FWL -Bottom Hole Location  
Section 17, T19S-R25E  
Eddy County, New Mexico

This plan is submitted with Form 3160-3, Application for Permit to Drill, covering the above described well. The purpose of this plan is to describe the location of the proposed well, the proposed construction activities and operations plan, the magnitude of the surface disturbance involved and the procedures to be followed in rehabilitating the surface after completion of the operations, so that a complete appraisal can be made of the environmental effect associated with the operations.

### **1. EXISTING ROADS:**

(See Exhibit) is a portion of the County map showing the well and roads in the vicinity of the proposed location. The proposed well site is located approximately 15 miles south of Artesia, New Mexico and the access route to the location is indicated on Exhibit. Operator will maintain existing roads in condition the same or better than before operations begin. Operator will repair pot holes, clear ditches, repair the crown, etc. All existing structures along the entire access route such as cattle guards, other range improvement projects, culverts, etc. will be properly repaired or replaced if they are damaged or have deteriorated beyond practical use. Operator will reasonably prevent and abate fugitive dust as needed when created by vehicular traffic and equipment caused by the operator. The BLM's written approval will be acquired before application of surfactants, binding agents, or other dust suppression chemicals on public or federal roadways.

#### **DIRECTIONS:**

(See Exhibit) From Artesia, go South on highway 285 for approximately 10.5 miles. Turn right (West) onto CR 21 (Rocking R Red Road). Travel west on CR 21 7 Miles and turn Right (North) onto lease road and continue keeping on lease road for 1 mile, veer right (East) and continue for 0.65 of a mile. Southwest corner of the location.

### **2. PLANNED ACCESS ROAD.**

- A. (See Exhibit) There will be no new road needed.
- B. The road is already there, but repairs will be 14 feet in width (driving surface) and will be adequately drained to control runoff and soil erosion. Ditches will be 3' wide with a 3:1 slopes.
- C. Existing roads will be maintained in the same or better condition.
- D. The route of road is visible.
- E. The proposed lease road is represented in Exhibits.

### **3. LOCATION OF EXISTING WELL**

- A. There is no drilling activity within a one-mile radius of the well site.
- B. Exhibits shows existing wells within a one-mile radius of the proposed well site.

4. LOCATION OF EXISTING AND/OR PROPOSED FACILITIES

- A. There are production facilities on this lease at the present time.
- B. There will flowline from proposed location to the existing Aparejo Battery.

5. LOCATION AND TYPE OF WATER SUPPLY:

- A. It is planned to drill the proposed well with a fresh water system. The water will be obtained from commercial sources and will be hauled to the location by truck over the existing and proposed roads shown in Exhibit or through fast lines provided by said commercial source.

6. SOURCE OF CONSTRUCTION MATERIALS:

Dirt contractor and construction foreman worked out a deal with the surface owner for the building material.

7. METHODS OF HANDLING WASTE DISPOSAL:

- A. This well will be drilled with a closed loop system
- B. The closed loop system will be constructed, maintained, and closed in compliance with the State of New Mexico, Energy and Natural Resources Department, Oil Conservation Division – the "Pit Rule" 19.15.17 NMAC.
- C. Drilling fluids will be removed after drilling and completions are completed.
- D. Water produced during operations will be collected in tanks until hauled to an approved disposal system, or separate disposal application will be submitted.
- E. Oil produced during operations will be stored in tanks until sold.
- F. Current laws and regulations pertaining to the disposal of human waste will be complied with.
- G. All trash, junk, and other waste materials will be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not approved.

8. ANCILLARY FACILITIES: None.

9. WELLSITE LAYOUT:

- A. Attached exhibit shows the relative location and dimensions of the well pad, the closed loop mud system, location of the drilling equipment. All of the location will be constructed within the 400' x 400' staked area.
- B. A 400' x 400' area was staked and flagged.

10. PLANS FOR RESTORATION:

- A. After finishing drilling and/or completion operations, all equipment and other material not needed for further operations will be removed. The location will be cleaned of all trash and junk to leave the well site in as aesthetically pleasing a condition as possible. At this point reclamation was completed in accordance with the Surface Owner Agreement that has been included in this APD. Please note attached Reclamation Plat.
- B. If the proposed well is plugged and abandoned, all equipment and other material will be removed. The location will be cleaned of all trash and junk to leave the well site in as aesthetically pleasing a condition as possible. At this point the surfacing material will be



removed, topsoil will be redistributed. The area will be contoured as closely as possible to its original location and reseeded. These actions will be completed and accomplished as expeditiously as possible.

- C. The reclamation of the pad will be done in sixty days if possible after the well is put in production.

11. SURFACE OWNERSHIP:

Surface Estate: James H. and Betty R. Howell Revocable Trust  
PO Box 75  
Lakewood, NM 88254

Mineral Estate: (40 acres; Unit F)  
Federal Lease NM-12833  
Bureau of Land Management  
620 East Greene Street, Carlsbad, NM 88220  
(Remaining mineral estate are Fee leases)

12. OTHER INFORMATION:

- A. Topography: Refer to the existing archaeological report for a description of the topography, flora, fauna, soil characteristics, dwellings, historical and cultural sites.
- B. The primary surface use is for grazing.
- C. A surface use agreement will be reached with the surface owner prior to the drilling of this well. The agreement will be similar to the agreement on the Roy AET Com #9H.

CERTIFICATION  
YATES PETROLEUM CORPORATION  
Roy AET Com #10H

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; and an someone under employment of Yates Petroleum Corporation has full knowledge of state and federal laws applicable to the operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

Executed this 25 day of June 2015

Signature 

Name Travis Hahn

Position Title Land Regulatory Agent

Address 105 South Fourth Street, Artesia, New Mexico 88210

Telephone (575) 748-4120

Field Representative (if not above signatory) Tim Bussell, Drilling Supervisor

Address (if different from above) Same as above

Telephone (if different from above) (575) 748-4221

# PECOS DISTRICT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Yates Petroleum Corporation
LEASE NO.:	NMNM125008
WELL NAME & NO.:	Roy AET Com 10H
SURFACE HOLE FOOTAGE:	1935'/N & 15'/E
BOTTOM HOLE FOOTAGE:	2310'/N & 330'/W
LOCATION:	Section 17, T.19 S., R.25 E., NMPM
COUNTY:	Eddy County, New Mexico

## TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
  - Aplomado Falcon
  - Communitization Agreement
  - Cave Karst Resources
- ☐ **Construction**
  - Notification
  - Topsoil
  - Closed Loop System
  - Federal Mineral Material Pits
  - Well Pads
  - Roads
- ☐ **Road Section Diagram**
- ☒ **Drilling**
  - Casing/Cement Requirements
  - H2S – Requirements
  - Logging Requirements
  - Medium Cave/Karst
  - Waste Material and Fluids
- ☐ **Production (Post Drilling)**
  - Well Structures & Facilities
- ☐ **Interim Reclamation**
- ☐ **Final Abandonment & Reclamation**

## **I. GENERAL PROVISIONS**

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

## **II. PERMIT EXPIRATION**

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

## **III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES**

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

## **IV. NOXIOUS WEEDS**

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

## V. SPECIAL REQUIREMENT(S)

In order to minimize impacts to aplomado falcon, the following Conditions of Approval will apply:

- No yuccas or trees over 5 feet in height will be damaged, to protect nesting structures.
- All active raptor nests will be avoided by a minimum of 400 meters by all activities or curtail activities until fledging is complete. All inactive raptor nests will be avoided by a minimum of 200 meters by all activities.
- Well pad size will not exceed 300 ft. x 390 ft.
- All roads associated with well development will not exceed 30 ft in width
- Reserve pits for drilling and disposal are not allowed unless the pit can be effectively netted to the satisfaction of the BLM. Steel tank circulation system must be used if the reserve pit is not netted.
- All unused portions of the well pad associated with producing wells will be reclaimed following the abandoned well protocol below
- Final abandonment protocol: Remove all caliche from well pads and roads that are plugged and abandoned. Reclamation will consist of disking, mulching, seeding with a drill (See seed mixture below), and application of water to encourage seed germination.

Buffalograss ( <i>Buchloe dactyloides</i> )	4 lbs/acre
Blue grama ( <i>Bouteloua gracilis</i> )	1 lbs/acre
Cane bluestem ( <i>Bothriochloa barbinodis</i> )	5 lbs/acre
Sideoats grama ( <i>Bouteloua curtipendula</i> )	5 lbs/acre
Plains bristlegrass ( <i>Setaria macrostachya</i> )	6 lbs/acre

### **Communitization Agreement**

- The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

### **Cave/Karst Surface Mitigation**

The following stipulations will be applied to minimize impacts during construction, drilling and production.

#### **Construction:**

In the advent that any underground voids are opened up during construction activities, construction activities will be halted and the BLM will be notified immediately.

#### **No Blasting:**

No blasting will be utilized for pad construction. The pad will be constructed and leveled by adding the necessary fill and caliche.

#### **Pad Berming:**

The entire perimeter of the well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad.

- The compacted berm shall be constructed at a minimum of 12 inches high with impermeable mineral material (e.g. caliche).
- No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad.
- The topsoil stockpile shall be located outside the bermed well pad.
- Topsoil, either from the well pad or surrounding area, shall not be used to construct the berm.
- No storm drains, tubing or openings shall be placed in the berm.
- If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.
- The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed.
- Any access road entering the well pad shall be constructed so that the integrity of the berm height surrounding the well pad is not compromised. (Any access road crossing the berm cannot be lower than the berm height.)

#### **Tank Battery Liners and Berms:**

Tank battery locations and all facilities will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.

#### **Leak Detection System:**

A method of detecting leaks is required. The method could incorporate gauges to measure loss, siting valves and lines so they can be visually inspected, or installing electronic sensors to alarm when a leak is present. Leak detection plan will be submitted to BLM for approval.

#### **Automatic Shut-off Systems:**

Automatic shut off, check valves, or similar systems will be installed for pipelines and tanks to minimize the effects of catastrophic line failures used in production or drilling.

### **Cave/Karst Subsurface Mitigation**

The following stipulations will be applied to protect cave/karst and ground water concerns:

#### **Rotary Drilling with Fresh Water:**

Fresh water will be used as a circulating medium in zones where caves or karst features are expected. SEE ALSO: Drilling COAs for this well.

#### **Directional Drilling:**

Kick off for directional drilling will occur at least 100 feet below the bottom of the cave occurrence zone. SEE ALSO: Drilling COAs for this well.

#### **Lost Circulation:**

ALL lost circulation zones from the surface to the base of the cave occurrence zone will be logged and reported in the drilling report.

Regardless of the type of drilling machinery used, if a void of four feet or more and circulation losses greater than 70 percent occur simultaneously while drilling in any cave-bearing zone, the BLM will be notified immediately by the operator. The BLM will assess the situation and work with the operator on corrective actions to resolve the problem.

#### **Abandonment Cementing:**

Upon well abandonment in high cave karst areas additional plugging conditions of approval may be required. The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

#### **Pressure Testing:**

Annual pressure monitoring will be performed by the operator on all casing annuli and reported in a sundry notice. If the test results indicated a casing failure has occurred, remedial action will be undertaken to correct the problem to the BLM's approval.



## **VI. CONSTRUCTION**

### **A. NOTIFICATION**

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

### **B. TOPSOIL**

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

### **C. CLOSED LOOP SYSTEM**

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

### **D. FEDERAL MINERAL MATERIALS PIT**

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

### **E. WELL PAD SURFACING**

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

## **F. EXCLOSURE FENCING (CELLARS & PITS)**

### **Exclosure Fencing**

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

## **G. ON LEASE ACCESS ROADS**

### **Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

### **Surfacing**

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

### **Crowning**

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

### **Ditching**

Ditching shall be required on both sides of the road.

### **Turnouts**


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

### **Drainage**

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outslowing and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

**Cross Section of a Typical Lead-off Ditch**



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

### **Formula for Spacing Interval of Lead-off Ditches**

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

### **Cattleguards**

An appropriately sized cattleguard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattleguards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguards that are in place and are utilized during lease operations.

### **Fence Requirement**

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

### **Public Access**

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

## Construction Steps

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

## VII. DRILLING

### A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☒ **Eddy County**

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,  
(575) 361-2822

1. **Hydrogen Sulfide has been reported as a hazard in formations deeper than the proposed depth. It is recommended that monitoring equipment be onsite for potential Hydrogen Sulfide. If Hydrogen Sulfide is encountered, report measurements and formations to the BLM; and Hydrogen Sulfide area must meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items.**
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval. **If the drilling rig is removed without approval – an Incident of Non-Compliance will be written and will be a “Major” violation.**
3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works is located, this does not include the dog house or stairway area.
4. **The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies.**

### B. CASING

Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

**Wait on cement (WOC) for Water Basin:**

After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements.

**Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.**

**No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.**

**Medium Cave/Karst**

**Possibility of lost circulation in the San Andres**

1. The 9-5/8 inch surface casing shall be set at approximately 800 feet and cemented to the surface.
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
  - b. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.**
  - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
  - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the 5-1/2 inch production casing is:  
☒ Cement to surface. If cement does not circulate, contact the appropriate BLM office.
3. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

**C. PRESSURE CONTROL**

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **3000 (3M)** psi.
3. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
  - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
  - b. The tests shall be done by an independent service company utilizing a test plug **not a cup or J-packer**. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
  - c. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
  - d. The results of the test shall be reported to the appropriate BLM office.
  - e. All tests are required to be recorded on a calibrated test chart. **A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.**
  - f. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.

#### **D. DRILL STEM TEST**

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

#### **E. WASTE MATERIAL AND FLUIDS**

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

**MHH 10182016**

## **VIII. PRODUCTION (POST DRILLING)**

### **A. WELL STRUCTURES & FACILITIES**

#### **Placement of Production Facilities**

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

#### **Exclosure Netting (Open-top Tanks)**

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

#### **Chemical and Fuel Secondary Containment and Exclosure Screening**

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

#### **Open-Vent Exhaust Stack Exclosures**



The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended enclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

#### **Containment Structures**

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

#### **Painting Requirement**

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

### **IX. INTERIM RECLAMATION**

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

### **X. FINAL ABANDONMENT & RECLAMATION**

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

#### Aplomado Falcon Habitat Seed Mixture

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)\* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law (s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first).. The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed\* per acre:

<u>Species</u>	<u>lb/acre</u>
Buffalograss (Buchloe dactyloides)) -----	4 lbs/acre
Blue grama (Bouteloua gracilis) -----	1 lb/acre
Cane bluestem (Bothriochloa barbinodis) -----	5 lbs/acre
Sideoats grama (Bouteloua curtipendula) -----	5 lbs/acre
Plains bristlegrass (Setaria macrostachya) -----	6 lbs/acre

\*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed

## NMOCD CONDITION OF APPROVAL

The *New!* Gas Capture Plan (GCP) notice is posted on the NMOCD website under Announcements. The Plan became effective May 1, 2016. A copy of the GCP form is included with the NOTICE and is also in our FORMS section under Unnumbered Forms. Please review filing dates for all applicable activities currently approved or pending and submit accordingly. Failure to file a GCP may jeopardize the operator's ability to obtain C-129 approval to flare gas after the initial 60-day completion period.