District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division
1220 South St. Francis Dr. NM OIL CONSERVATION
Santa Fe. NM 87505

ARTESIA DISTRICT

			Santa Fe, N	INT 9 \ 2002	74153186	121 - 111 - 12 - 12 - 12 - 12 - 12 - 12
2 20 17		GAS CA	APTURE PL	_AN	FEE	2 2 20%
Date: 2-20-17					RF	CEIVED
✓ Original		0,,,,,,,	e. ocnin	Na . Massiba		
☑ Original		-	r & OGRID	No.: <u>iviewbo</u>	ume On Con	mpany - 14744
☐ Amended - Reason for	Amendment:_					
This Gas Capture Plan out new completion (new drill,				to reduce we	ell/production	ı facility flaring/venting fo
Note: Form C-129 must be sub	bmitted and app	roved prior to excee	eding 60 days o	allowed by Ru	le (Subsection .	4 of 19.15.18.12 NMAC).
Well(s)/Due desettes Essili		· C:1:4				
Well(s)/Production Facili	ty – Name or	<u>lacinty</u>				
The well(s) that will be loc	ated at the pro	oduction facility	are shown in	the table be	low.	
Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Rockspur 27 W0CN State Com #2H	30-015-44	6-27 24S 28E	250' FNL & 1590'FWL	0		Online after frac
	11 BT 410					
Gathering System and Pi Well(s) will be connected t			lowback one	rations are c	omnlete if	roc transnorter system is
place. The gas produced						
<u>Crestwood</u> low/h	nigh pressure	gathering system	m located in	1 Eddy	County, New	Mexico. It will requi
500 ' of pipeline to o	connect the fa	cility to low/high	h pressure g	athering sys	em. Mewbo	ourne Oil Company provid
(periodically) to Crestwo						
be drilled in the foreseeab		U, 1		-		
conference calls to discuss	s changes to	drilling and con	npletion sche	edules. Gas	from these	wells will be processed
Crestwood	_ Processing P	Plant located in Se	ec. <u>29</u> , Tw	vn. <u>245</u> , Rn	g. 28E, Ed	dy County, New Mexic
The actual flow of the gas w						

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Crestwood system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines