Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Artesia

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

5.	Lease Senal No.
	NMNM18626

SUNDRY NOTICES AND REPORTS ON WELLS

Casing Repair

Change Plans Convert to Injection

abandoned we	6. If Indian, Allottee	6. If Indian, Allottee or Tribe Name			
SUBMIT IN	TRIPLICATE - Other in	structions on page 2	7. If Unit or CA/Agr	reement, Name and/or No.	
Type of Well	ier		8. Well Name and N GINGER FEDE		
2. Name of Operator RKI EXPLORATION & PROD	Contact: LLC E-Mail: caitlin.oh	CAITLIN O'HAIR air@wpxenergy.com	9. API Well No. 30-015-25744	-00-S1	
3a. Address 3500 ONE WILLIAMS CENTE TULSA, OK 74172	ER MD 35	3b. Phone No. (include area code) Ph: 539-573-3527	10. Field and Pool o E ROSS DRA		
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description	on)	11. County or Parisl	h, State	
Sec 24 T26S R30E SWSE 46	OFSL 1880FEL		EDDY COUN	TY, NM	
12. CHECK THE AI	PPROPRIATE BOX(ES) TO INDICATE NATURE O	F NOTICE, REPORT, OR O	THER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of Intent	☐ Acidize	☐ Deepen	☐ Production (Start/Resume)	■ Water Shut-Off	
Nonce of Intent	☐ Alter Casing	☐ Hydraulic Fracturing	☐ Reclamation	■ Well Integrity	
☐ Subsequent Report	Casing Panair	New Construction	□ Recomplete	□ Other	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleted. Final Abandonment Notices must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection. determined that the site is ready for final inspection.

□ Plug Back

■ New Construction

☑ Plug and Abandon

☐ Recomplete

■ Water Disposal

☐ Temporarily Abandon

RKI EXPLORATION & PRODUCTION RESPECTFULLY REQUESTS TO P&A THE ABOVE MENTIONED WELL. THE ATTACHED WBD AND PROCESS ATTACHED.

WIN ON CONSERVATION FLE 28 7017

☐ Final Abandonment Notice

RECEIVED


RECLAMATION PROCEDURE **ATTACHED**


SEE ATTACHED FOR CONDITIONS OF APPROVAL

□ Other

Vecebjed to Lecold 14. I hereby certify that the foregoing is true and correct Electronic Submission #364910 verified by the BLM Well Information System For RKI EXPLORATION & PROD LLC, sent to the Carlsbad Committed to AFMSS for processing by PRISCILLA PEREZ on 01/31/2017 (17PP0123SE) Title PERMIT TECHNICIAN II Name (Printed/Typed) CAITLIN O'HAIR 01/25/2017 Signature (Electronic Submission) Date THIS SPACE FOR FEDERAL OR STATE OFFICE USE 2-15-Date Approved By Title Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Office

Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction







Ginger Federal #1 Plug and Abandon Procedure

East Ross Draw, Delaware Field

Section 24, T-26S, R-30E Eddy Co., New Mexico

API # 30-015-25744 Lease # 18626

Spud Date: 07/28/87

TD Date: : 08/22/87

Producing Formations:

Williamson Sand Perfs: 5,809' - 5,817'

KB Elev: 3124' GL Elev: 3113' **TD:** 7,060' PBTD: 6,980' Marker Joint: N/A

CASING SUMMARY:

Safety Factor = 80% of new applied to burst, collapse and tension parameters in table.

Size	Depth	Weight	Grade	Connection	Capacity	ID	Drift	Burst	Collapse	Tension
	(ft)	(#/ft)	psi	Type	(bbls/ft)	(in)	(in)	(psi)	(psi)	(lbs)
13 3/8"	906'	54.5 #	K-55	n/a	.1571	n/a	n/a	n/a	n/a	n/a
8 5/8"	3,545'	24 #	J-55	n/a	.0637	n/a	n/a	n/a	n/a	n/a
5 1/2"	7,060'	17#	n/a	n/a	.0232	n/a	n/a	n/a	n/a	n/a

Surface:

13 3/8": 0' - 906' - TOC @ surface cmt. w- 850 sxs

Surface:

8 5/8": 0' - 3,545' - TOC @ 1725' cmt. w-1550sxs

Production:

5 1/2": 0'- 7,060' - TOC @ 2100' cmt. w- 1000 sxs

COMPLETION HISTORY TO DATE:

OBJECTIVE: Plug and abandon.

WPX REQUIRES THAT HARD HATS, STEEL TOE BOOTS, FIRE RETARDANT CLOTHING, AND SAFETY GLASSES BE WORN ON LOCATION.

HOLD SAFETY MEETING PRIOR TO COMMENCING PERFORATING, WIRE LINE AND PUMPING **OPERATIONS**

NO IGNITION SOURCES WITHIN 100 FT OF THE WELLHEAD, FLOWBACK TANKS OR MANIFOLD.

PROCEDURE:

- 1) Test safety anchors and replace as necessary. Set 1 clean frac tank and fill with 480 BFW.
- 2) MIRU Service Unit. Deliver, unload and tally 6,000' 2-3/8" 4.7# J-55 EUE work string.
- 3) ND WH, NU 3K# BOP.
- 4) POOH rods & tbg. & Lay Dn.
- 5) MI RU wireline unit. Run 5 1/2" GR/JB to 5,725'.
- 6) RIH w- 5 1/2" tbg. conveyed CIBP & set @ 5,725'. PU 1 jt. & circulate with 135 bbls. mud. Spot 25sx Class C Cement (14.8 ppg, 6.3 gps, 1.32 cfs yield) 5,725' 5,500' & flush with heavy mud. TOOH w- tbg.
- 7) POOH & LD tbg. to 5,350' & spot 25 sxs. to 5,200'.
- 8) POOH & LD tbg. to 3,600' Stand back rest of tbg. in derrick.
- 9) RU WL & Perforate 4 holes @ 3,595'. RD MO wireline.
- 10) RIH w- Pkr & tbg. set Pkr -Establish injection rate & sqz. 50 sxs. Class C Cement (14.8 ppg, 6.3 gps, 1.32 cfs yield). from 3,595' -3,445'. If unable to sqz. Spot 25 sxs.
- 11) WOC & Tag @ 3,445'.
- 12) POOH to 1,530' & spot 25 sxs. 1,530' = 1,430'.
- 13) POOH & LD Tbg.
- 14) RU WL & Perforate 4 holes @ 150'. RD MO wireline.
- 15) Sqz. 50 sxs. cmt. from 150' to surface.
- 16) RDMO Service Unit. RDMO Cementers.
- 17) MIRU Welder. Cut-off casing head. WO cap with well name and number, operator name, and date.
- 18) Pull safety anchors, dress, and reclaim surface location if necessary.

RKI Contact List:

WPX	Title	Office	Cell
Danny Emerson	Production Superintendent	575-885-1313	505-614-4867
Scott Armstrong	Permian Production Engineer	539-573-0162	918-557-9944
Brad Ballinger	Permian Production Engineer	539-573-0135	303-928-0799
Glenn Griffin	Permian Production Engineer	539-573-7547	405-437-9557
Heather Stephens	Permian Production Engineer	539-573-8961	303-898-3918
Josh Walker	Regulatory Specialist	539-573-0108	580-716-0330
Les Peeler	Plugging Consultant	405-454-0008	405-659-5185

Emergency Contacts - New Mexico:

Hospital:

Carlsbad Medical Center

(575) 887-4100

2430 W. Pierce St., Carlsbad, NM 88220

Sheriff's Office:

Lea County Sheriff Dept

(575) 396-3611

Eddy County Sheriff Dept

(575) 887-7551

Emergency Contacts - Texas:

Hospital:

Reeves County Hospital

(432) 447-3551

2323 Texas St, Pecos TX 79772

Sheriff's Office:

Reeves County Sheriff Dept

(432) 445-4901

Loving County Sheriff Dept

(432) 377-2411

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Henryetta Price Environmental Protection Specialist 575-234-5951

Shelly Tucker Environmental Protection Specialist 575-234-5979

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612