Form 3160-5 (April2004)

## UNITEDSTATES OCD-ARTESIA DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

FORMAPPROVED OM B No. 1004-0137 Expires: March 31, 2007

## 5. Lease Serial No.

LC-	068545
-----	--------

6. If Indian, Allottee or Tribe Name

abandoned we	II. Use Form 3160-3 (AP	PD) for su	ch pr	oposals.			
SUBMIT IN TRI	PLICATE - Other instruc	ctions on	reve	rse side.		it or CA/Agreement, Name and/or No.	
1. Type of Well	Gas Well Other			-		Jama and No.	
2. NameofOperator						Lake Unit #163	
Bass Enterprises Product	ion Co.				9. API V		
3a. Address				de area code)	30-015-34183		
P. O. Box 2760 - Midland,		(432)6	83-22	277		10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec		-		-		Draw (Delaware, BS, Avalon)	
SENW 1980' FNL & 2360' FWL Unit F, Sec 6, T24S, R30E Lat 32.248528 deg N, Lon 103.921917 deg W						11. County or Parish, State Eddy County, New Mexico	
12. CHECK AP	PROPRIATE BOX(ES)TO IN	NDICATE 1	NATU	RE OF NOTICE, RE	PORT, (	OR OTHER DATA	
TYPE OF SUBMISSION	· · · · · · · · · · · · · · · · · · ·		TY	PEOF ACTION			
Notice of Intent  Subsequent Report Final Abandonment Notice	Acidize Deepen Production (Standard Reclamation Recomplete Change Plans Plug and Abandon Temporarily A					Water Shut-Off Well Integrity StockerDrilling Operations	
following completion of the involved operations. If the operation results in a multiple completion or recompletion testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclar determined that the site is ready for final inspection.)  Spudded well at 1:30 am on 3/4/06. Drilled 12-1/4" hole to 800'. Ran 17 jts 8-5/8' 32#, K55, STC csg, set at 800'. Cmtd w/ 200 sx Class C + 3% S1 +5 pps D24 + 0.025 pps D29 + 6% D20 lead (12.6 ppg, 1.99 yld) and 325 sx Class C + 2% S1 (14.8 ppg, 1.34 yld). Plug down @ 12:43 AM 3/5/06. Full rels circ 90 sx to pit. W0 24-1/2 hrs. Tested csg to 1000 psi for 30 mins. Drilled 7-7/8" hole to 7535'. Run 137 jts 5-1/2", 15.50# & 34 jts 17#, J-55, LTC csg, set at 7534'. Cmtd w/ 860 sx LiteCrete + 2% D153 + 2% D24 + 0.05 gps D604AM + 0.03 bps MO45 + 0.04 gp D801 lead (10.2 ppg, yld 2.41), & 235 sx LiteCrete + 2% D153 + 2% D24 + 0.05 gps D604AM + 0.03 bps MO45 + 0.04 gps D801 tail (10.5 ppg, yld 2.23). TOC by Temperature Survey 3010'.  Released rig at 8:00 am CST on 3/18/05. Prep for completion.					ation, have		
				,		ALEXIS C. SWOBODA	
14. I hereby certify that the foreg Name (Printed/Typed)	oing is true and correct	1			I		
Annette Childers			Title	Administrative A	ssistan	t	
Signature Omnett	e Childer		Date	03/23/2006			
	THIS SPACE FOR FE	DERAL	OR S	STATE OFFICE U	JSE		
Approved by				Title		Date	
Conditions of approval, if any, are a certify that the applicant holds legal which would entitle the applicant	or equitable title to those rights in to conduct operations thereon.	the subject le	nt or ease	Office			
Title 18 U.S.C. Section 1001 and Titl States any false, fictitious or fraud	le 43 U.S.C. Section 1212, make it a ulent statements or representation	a crime for any as as to any m	person natter w	knowingly and willfully to ithin its jurisdiction.	make to	any department or agency of the United	

		TEMPE	ERATURE SURVEY REPO	⊰Τ	
ompany	BASS ENTERP		POKER LAKE UNIT	Well #	163
eld urvey Date	3/18/2006	County	16:52	State	HECTOR
		Top of Cement	3010		
		Total Depth	7445		
		Zero @	GL		
		Plug Down @	3/17/06 @ 19:00 +/-		
		Casing Size	5 1/2		
		Hole Size	7 7/8		
		Sacks of Cement			
		Ran By	C. HOMER		
		Calculated By	C. KENNEDY		

## TEMPERATURE SURVEY REPORT

