Form 3160-5 ('un@2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

5. Lease Serial No. NMLC031844

SUNDRY Do not use thi abandoned wel	NMLC031844 6. If Indian, Allottee or Tribe Name							
SUBMIT IN 1	7. If Unit or CA/Agreement, Name and/or No. NMNM135871							
Type of Well	8. Well Name and No. HUMMINGBIRD FEDERAL COM 18H							
Name of Operator APACHE CORPORATION	9. API Well No. 30-015-43486-00-X1							
3a. Address 303 VETERANS AIRPARK LA MIDLAND, TX 79705	(include area code) 8.1167		10. Field and Pool or Exploratory Area FREN					
4. Location of Well (Footage, Sec., T.		11. County or Parish, State						
Sec 1 T17S R31E NWNW 330			EDDY COUNTY	ſ, NM				
12. CHECK THE AF	PROPRIATE BOX(ES)	TO INDICA	TE NATURE OI	F NOTICE, 1	REPORT, OR OTH	IER I	DATA	
TYPE OF SUBMISSION	F ACTION							
Notice of Intent ■ Notice of Intent Notice of	☐ Acidize		pen	☐ Production (Start/Resume)		■ Water Shut-Off		
_	☐ Alter Casing	☐ Hyd	raulic Fracturing	☐ Reclama	tion	"	Well Integrity	
☐ Subsequent Report	□ Casing Repair	□ New	Construction	☐ Recomp				
☐ Final Abandonment Notice	☐ Change Plans	□ Plug	and Abandon	□ Tempora	□ Temporarily Abandon		ange to Original A	
	☐ Convert to Injection	Plug	□ Plug Back		□ Water Disposal			
13. Describe Proposed or Completed Ope If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for final	ally or recomplete horizontally, is will be performed or provide operations. If the operation re- pandonment Notices must be file	give subsurface the Bond No. or sults in a multipl	locations and measur in file with BLM/BIA e completion or reco	red and true ver Required sub- empletion in a ne	tical depths of all perting sequent reports must be ew interval, a Form 316	ent ma filed v 0-4 mu	rkers and zones. vithin 30 days ast be filed once	
BLM-CO-1463 NATIONWIDE	NMB-000736							
APACHE REQUEST A VARIA	NCE TO USE A FLEXIB	LE HOSE BE	TWEEN BOP &	CHOKE MAI	NIFOLD			
SEE ATTACHMENT FOR AD					_			
Manufacturer: Continental SN: 69915 ID: 3" WP: 10,000psi TP: 15,000psi Accepted for record - NMOCDCONDITIONS OF APPROVAL ARTESIA DISTR								
WP: 10,000psi TP: 15,000psi TP: 15,000psi Accepted for record - NMOCDCONDITIONS OF AFTICOVIDE								
11 . 10,000psi				SIA DISTRICT				
						APR	1 0 2017	
14. I hereby certify that the foregoing is	Electronic Submission #	E CORPORAT	ON, sent to the C RAH MCKINNEY o	Carlsbad on 04/03/2017	(17DLM1197SE)	RE	CEIVED	
Name (Printed/Typed) SORINA F	LORES		Title SUBMIT	ITING CONT	TACT			
Signature (Electronic S	Submission)		Date 03/27/20	017				
	THIS SPACE FO	R FEDERA	L OR STATE	OFFICE US	SE .			
_Approved By_MUSTAFA_HAQUE			TitlePETROLEUM ENGINEER				Date 04/05/2017	
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Carlsbac	d				
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s				willfully to ma	ke to any department or	agency	y of the United	

ARTESIA DISTRICT

APR 1 0 2017

PECOS DISTRICT CONDITIONS OF APPROVAL

RECEIVED

OPERATOR'S NAME:

Apache Corporation

LEASE NO.:

NMLC-031844

WELL NAME & NO.:

Hummingbird Federal Com 18H

SURFACE HOLE FOOTAGE:

0330' FNL & 0100' FWL

BOTTOM HOLE FOOTAGE

0330' FNL & 0330' FEL

LOCATION:

Section 01, T. 17 S., R 31 E., NMPM

COUNTY:

Eddy County, New Mexico

All previous COAs still apply, except for the following:

1. Variance approved to use flex line from BOP to choke manifold. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor. If the BLM inspector questions the straightness of the hose, a BLM engineer will be contacted and will review in the field or via picture supplied by inspector to determine if changes are required (operator shall expect delays if this occurs).

MHH 04052017

CONTITECH RUBBER No: QC-DB-205 / 2015 Industrial Kft.

Page: 8 / 128

ContiTech

QUALITY CONTROL INSPECTION AND TEST CERTIFICATE							N°:	581				
PURCHASER:	& Marine Corp.			P.O. Nº:		4500511543	·					
CONTITECH RUBBER order N°: 540352			HOSE TYPE: 3" ID				Choke and Kill Hose					
HOSE SERIAL N°: 69915			NOMINAL / ACTUAL LENGTH:				10,67 m / 10,76 m					
W.P. 68,9 MPa 10	0000 psi	T.P.	103,4	MPa	1500	O psi	Duration:	60	min.			
Pressure test with water at ambient temperature See attachment. (1 page)												
COUPLINGS Type			Serial N°			Qu	Quality Hea					
3" coupling with		75	563	7565		AISI	4130	A0996X				
4 1/16" 10K API b.w. Flange end						AISI	4130	036282	036282			
NOT DESIGNED FOR WELL TESTING API Spec 16 C Temperature rate:"B" All metal parts are flawless												
WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER INSPECTED AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT.												
STATEMENT OF CONFORMITY: We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements.												
COUNTRY OF ORIGIN HUNGARY/EU												
Date: Inspector Quality Control Confilted Conf							/ \	2				

Page: 1/1

