

NM OIL CONSERVATION

ARTESIA DISTRICT

Submit 1 Copy To Appropriate District Office

District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

APR 17 2017

State of New Mexico

Energy, Minerals and Natural Resources

RECEIVED

CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-103

Revised July 18, 2013

WELL API NO.

30-015-44052

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Terlingua 23 State

8. Well Number 501H

9. OGRID Number

7377

10. Pool name or Wildcat

Santo Nino; Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
EOG Resources, Inc.

3. Address of Operator
P.O. Box 2267 Midland, TX 79702

4. Well Location
Unit Letter P 200 feet from the South line and 330 feet from the East line
Section 23 Township 18S Range 29E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3449' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/24/17 Spud 17-1/2" hole.

3/25/17 Ran 12 jts 13-3/8", 54.5#, J55 STC casing set at 507'.

Cement lead w/ 640 sx Class C, 13.5 ppg, 1.76 CFS yield;

tail w/ 310 sx Class C, 14.8 ppg, 1.36 CFS yield. Did not circulate.

Top out cement w/ 100 sx Class C, 14.8 ppg, 1.36 CFS yield. Cement circulated to surface.

4/06/17 Tested casing to 1500 psi for 30 minutes. Test good.

Resumed drilling 12-1/4" hole.

Spud Date: 3/24/17

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Stan Wagner
Stan Wagner

TITLE

Regulatory Analyst

DATE

4/07/2017

Type or print name

E-mail address:

PHONE:

432-686-3689

For State Use Only

APPROVED BY:

Stan Wagner

TITLE

4-18-17 STAFF Mgr

DATE

4-18-17

Conditions of Approval (if any):