Submit 1 Copy To Appropriate District  State of New Me	exico Form C-103
Office District I – (575) 393-6161  NM OIL CONSERVATION In Property of the Conservation of the Conservatio	
1625 N. French Dr., Hobbs, NM 88240 ARTESIA DISTRICT	WELL API NO.
District II - (575) 748-1283 811 S. First St., Artesia, NM 88210 JUL <b>20812010</b> NSERVATION	DIVISION 30-015-26300
District III – (505) 334-6178 1220 South St. Fran	3. Indicate Type of Bease
1000 Rio Brazos Rd., Aztec, NM 87410	
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	LG-1525
87505	
SUNDRY NOTICES AND REPORTS ON WELLS	į
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PL DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR	OP SUCH
PROPOSALS.)	8. Well Number
1. Type of Well: Oil Well Gas Well Other P&A	4
2. Name of Operator EOG Y Resources, Inc.	9. OGRID Number 025575
3. Address of Operator	10. Pool name or Wildcat
104 South Fourth Street, Artesia, NM 88210	Cemetary; Morrow
4. Well Location	
Unit Letter F: 1980 feet from the North	line and 1980 feet from the West line
	<del></del>
Section 36 Township 19S Ra  11. Elevation (Show whether DR	nge 24E NMPM Eddy County
11. Elevation (snow whether DR)	
12. Check Appropriate Box to Indicate Na	
12. Check Appropriate Box to indicate Na	ture of Notice, Report of Other Data
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK 🗌 PLUG AND ABANDON 🔲	REMEDIAL WORK ALTERING CASING
TEMPORARILY ABANDON   CHANGE PLANS	COMMENCE DRILLING OPNS.☐ P AND A 🔻
PULL OR ALTER CASING	CASING/CEMENT JOB
DOWNHOLE COMMINGLE	
CLOSED-LOOP SYSTEM  OTHER:	OTHER:
13. Describe proposed or completed operations. (Clearly state all	
date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of	
proposed completion or recompletion.	
6/26/17 – ND wellhead and NU BOP. Pumped 40 bbls fresh water on 4-1/2" casing. Pumped 35 bbls down tubing. Set a 4-1/2" CIBP at	
9058'. Tagged CIBP.	
6/27/17 – Broke circulation with 22 bbls. Displaced hole with 120 bbls mud gel. Spotted 25 sx Class "H" cement on top of CIBP.	
Approximate TOC 8477'. Tagged TOC 8804'. 6/28/17 – RIH with jet cutter and cut casing at 8200'. Speared 4-1/2" casing, did not come free. As per Bob Byrd NMOCD-Artesia, ok to	
cut at 8200'. RIH with jet cutter and cut casing at 8000'. Pumped 25 bbls brine down 7" casing, worked casing and came free.	
6/30/17 – Broke circulation with 50 bbls brine. Spotted 50 sx Class "H" cement from 8250'-7850' calc TOC.	
7/5/17 - Tagged TOC 7895'. Ran gyro survey to 7200'. Ran GR/JB stacked out at 4900'. Ran in hole with bit and scraper to 7632'.	
7/6/17 – Set a 7" CIBP at 7632'. Spotted 25 sx Class "C" cement on top of CIBP to 7478' calc TOC. WOC. Tagged TOC 7480'. Spotted	
70 sx Class "C" cement from 5453'-5018' calc TOC. 7/7/17 – Tagged TOC 5051'. Perforated at 3434'. Spotted 25 sx Class "C" cement at 3480'-3326' calc TOC.	
7/10/17 – Tagged TOC 3330'. Perforated at 2067'. Did not squeeze. Spotted 25 sx Class "C" cement from 2118'-1964' calc TOC. WOC.	
Tagged TOC 1972'. Perforated at 1250'. Tried to squeeze, held pressure.	
7/11/17 – Spotted 90 sx Class "C" cement from 1297'-744' calc TOC.	1701
7/12/17 – Tagged TOC 835'. Perforated at 150'. Squeezed 50 sx Class "C'7/20/17 – Dug up cellar and cut off wellhead. Installed dry hole marker. C ABANDONED.	over cellar and cut off all anchors. WELLAS PLACED AND
ABANDONED.	te:    Aprilia
	Shraging is court of the Page
	rived frider housen at OOD muslocal
Spud Date: Rig Release Da	ite: Arrivitis di subse sound en ne stre
	Coi C 10 traa C W. Trank
	te:    Aprentiation of the control o
I hereby certify that the information above is true and complete to the be	est of my knowledge and belief.
SIGNATURE ( Title Regulatory Specialist DATE July 26, 2017	
SIGNATURE TITLE Regulatory Specialist DATE July 26, 2017	
Type or print name Tina Huerta E-mail address:tina	huerta@eogresources.com PHONE: 575-748-4168
For State Use Only	
// / / / ^ /	100000000000000000000000000000000000000
	I ANDE OFFICER DATE 7/28/2017
Conditions of Approval (if any):	