Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

NMOCD Artesia FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

5. Lease Serial No. NMLC029426A

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals

ININECO	23420/	

abandoned well. Use form 3160-3 (APD) for such proposals.					6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on page 2					7. If Unit or CA/Agreement, Name and/or No.		
Type of Well ☐ Gas Well ☐ Other					8. Well Name and No. CEDAR LAKE FEDERAL CA 302H		
Name of Operator Contact: SORINA FLORES APACHE CORPORATION E-Mail: sorina.flores@apachecorp.com					9. API Well No. 30-015-43560-00-X1		
3a. Address 303 VETERANS AIRPARK LANE SUITE 3000 MIDLAND, TX 79705 3b. Phone No. (include area code) Ph: 432.818.1167					10. Field and Pool or Exploratory Area CEDAR LAKE		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, State			
Sec 3 T17S R31E SWNW 1855FNL 173FWL					EDDY COUNTY, NM		
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICA	TE NATURE O	F NOTICE,	REPORT, OR OTH	IER DATA	
TYPE OF SUBMISSION							
□ Notice of Intent	☐ Acidize	☐ Dee	pen	☐ Product	ion (Start/Resume)	■ Water Shut-Off	
	☐ Alter Casing	☐ Hyd	raulic Fracturing	☐ Reclam	ation	■ Well Integrity	
Subsequent Report	☐ Casing Repair	□ Nev	Construction	☐ Recomp	olete	⊠ Other	
☐ Final Abandonment Notice	☐ Change Plans	Plug	g and Abandon	☐ Tempor	arily Abandon	Drilling Operations	
	☐ Convert to Injection	Plug	g Back	☐ Water [Disposal		
following completion of the involved testing has been completed. Final Al determined that the site is ready for f BLM-CO-1463 NMB-000736 7/24/17: SPUD 7/24/17: Drilling 17-1/2" hole t 7/25/17: RU Lewis csg crew, r J55 LTC, set csg @ 660', FC (14.8ppg, 1.34 yld), circ 196sy 7/26/17: Test csg 1300psi/30r	bandonment Notices must be fil inal inspection. Action 660', run 16jts of 13-3/8" 48# @ 617', emt w/600sx CL ox to surf, WOC min - OK; TIH, drlg 12-1/4	cepted for r	requirements, includ	VM OIL C D ARTES SEP	ONSERVATION 2 6 2017	nd the operator has	
, , ,	#Electronic Submission For APACHI nmitted to AFMSS for proc	E CORPORAT	ON, sent to the C SCILLA PEREZ or	Carlsbad n 08/17/2017	(17PP0902SE)		
Name (1 rimew Typeu) SURINA	LUNES		Title SUBMIT	TING CON	TED FOR REC	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
Signature (Electronic S			Date 08/17/20	1111		7	
	THIS SPACE FO	R FEDERA	L OR STATE	ÞFFI¢⊭ U:	SEP : 1/2017		
Approved By Conditions of approval, if any, are attache certify that the applicant holds legal or equ which would entitle the applicant to conductive the applicant to conductive the states any false, fictitious or fraudulent states and first false fir	d. Approval of this notice does uitable title to those rights in the act operations thereon. U.S.C. Section 1212, make it a statements or representations as	not warrant or subject lease crime for any pe to any matter w	Title Office rson knowingly and ithin its jurisdiction	CAR willfully to ma	OF LAND MANASE L LSBAD NELD OFFICE ake to any department or	agency of the United	
** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **							

Additional data for EC transaction #385035 that would not fit on the form

32. Additional remarks, continued

7/26-7/27/17: Drlg f/2240-3525'.

7/28/17: RU Lewis csg, run 79jts 9-5/8" 36# J55 LTC csg to 3525', FC @ 3477', cmt w/Lead: 1100sx 35/65 PozC Cl C w/5% salt, 6% gel, 0.3pps kolseal, 0.4pps defoamer, 0.125 cellophane (12.9 ppg, 1.92 yld)
Tail: 300sx Cl C w/0.2% retarder(14.8 ppg, 1.32yld)Circ 411sx to surf, WOC, Test csg 1500psi/30min-OK

7/29/17: Drlg 8-1/2" hole f/3525'-4742', TOH f/curve assembly, KOP @ 4742'.

7/30-8/3/17: Drig 8-1/2" curve & lateral f/4742'-9785, POOH, LD dir assembly, PU packers plus reamers.

8/4/17: RU Lewis csg, run 5.5" and 7" tapered prod csg set @ 9785' ' (105 jts 7" 29# L80 LTC & 103 jts 5.5" 20# L80 LTC w/packers plus ssembly - DVT @ 4706', Crossover @ 4732'.)

RU ParFive, cmt w/Lead: 450sx PozC w/5% salt, 6% gel, 0.2% retarder, 0.125#/sk CF, 0.4#/sk defoamer, 3#/sk kolseal (12.6 ppg, 2.06 yld) Tail: 200sx Poz w/1.3% salt, 5% extender, 0.5% fluid loss, 0.1% anti-setting agent, 0.4#/sk defoamer (13 ppg, 1.48 yld), Circ 166sx cmt to surf, ND BOP

8/4/17: RR @ 24:00hrs