Submit 1 Copy To Appropriate District Office	State of New Mex	Form C-103						
<u>District 1</u> – (575) 393-6161	Energy, Minerals and Natura	l Resources			Revised July	18, 2013		
1625 N. French Dr., Hobbs, NM 88240	NM OIL CON	SERVATION	WELL API N					
<u>District II</u> – (575) 748-1283	OIL CONSERVATION I		30-015-2887					
811 S. First St., Artesia, NM 88210 District III - (505) 334-6178			5. Indicate T	ype <u>of</u> Lea				
1000 Rio Brazos Rd., Aztec, NM 87410	1220 South Stoff Eranc		STAT	<u>E []</u>	FEE 🛛			
District IV - (505) 476-3460	Santa Fe, NM 875	05	6. State Oil &	د Gas Leas	e No.			
1220 S. St. Francis Dr., Santa Fe, NM								
87505	RECE							
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name					
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			Ryburn FZ					
PROPOSALS.)			8. Well Number					
1. Type of Well: Oil Well 🔲 Gas Well 🗍 Other P&A			3					
2. Name of Operator			9. OGRID Number					
EOG Y Resources, Inc.			025575					
3. Address of Operator			10. Pool name or Wildcat					
104 South Fourth Street, Artesia, NM 88210			Atoka; San Andres					
4. Well Location				<u> </u>				
	990 feet from the South	line and	990 feet t	from the	West	line		
			<u> </u>			IIIIC		
Section 22	Township 18S Rang			Eddy	County			
	11. Elevation (Show whether DR, RKB, RT, GR, etc.)							
na an a	3340'G	<u>R</u>		i e selara				
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data								
		,	1					
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:								
PERFORM REMEDIAL WORK D PLUG AND ABANDON REMEDIAL WORK ALTERING CASING								
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A								
PULL OR ALTER CASING		CASING/CEMENT]				

CLOSED-LOOP SYSTEM OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: OTHER:

11/29/17 - MIRU. Bled off well. NU BOP. Set a 5-1/2" CIBP at 1565'.

DOWNHOLE COMMINGLE

11/30/17 – Ran gyro survey to surface. Tagged CIBP. Circulated with plugging mud. Pressure tested casing to 500 psi, held good. Spotted 25 sx Class "C" cement on top of CIBP to 1318' calc TOC.

12/3/17 – Tagged TOC at 1336'. Spotted 25 sx Class "C" cement from 963'-716' calc TOC. Dug out cellar. Notified Gilbert with NMOCD that we will not perforate 8-5/8" casing below casing shoe. ND BOP. Spotted 68 sx Class "C" cement from 674' up to surface. Topped off well with cement.

12/8/17 - Cut off wellhead. Installed dry hole marker and cut off anchors. WELL IS PLUGGED AND ABANDONED.

Spud Date:		Rig Rela	ease Date:	
I hereby certify that the signature	• • • •	•	o the best of my knowledge a	
Type or print name	Tina Huerta	E-mail address:	tina_huerta@eogresources	.com PHONE: <u>575-748-4168</u>
APPROVED BY:	val (if any):	TITLE 5-	taff Mg-	DATE 12-15-17