District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

> Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

MM OIL CONSERVATION

ARTESIA DISTRICT

Form C-141 Revised April 3, 2017

JAN 16 2018

Submit I Copy to appropriate District Office in accordance with 19.15.29 NMAC.

RECEIVED

Release Notification and Corrective Action													
NABIS	01 05	OPERATOR				l Report		Final Report					
Name of Co	mpany: M	arathon Oil				Contact: Jas				•			
		lipe St., Hou			Telephone No.: 575-297-0682								
Facility Name: Black River 15 10 State COM X 2H Facility Type: Gas Well													
Surface Owner: State Mineral Owner: S							State API No.: 30-015-42728						
LOCATION OF RELEASE													
Unit Letter P	Section 15	Township 24S	Range 27E	Feet from the 270	l.	South Line FSL	Feet from the 1070	East/West Line FEL		County Eddy			
Latitude <u>32.21064077</u> Longitude <u>-104.17339692</u> NAD83													
Type of Release: HCL & Fresh Water NATURE OF RELEASE Volume of Release: 250 bbls Volume Recovered: 0 bbls													
Source of Release: 500 bbl tank						Date and Hour of Occurrence: Date and				Hour of Discovery: 01/04/2018			
Was Immediate Notice Given? ☐ Yes ☐ No ☐ Not Required							If YES, To Whom? Notification via email to Crystal Weaver, Mike Bratcher						
By Whom? Jason Wardell							Date and Hour: 01/04/2018 1712 HRS 5: (2.0 M)						
Was a Watercourse Reached? ☐ Yes ☑ No							If YES, Volume Impacting the Watercourse. N/A						
If a Watercourse was Impacted, Describe Fully.* N/A													
Describe Cause of Problem and Remedial Action Taken.* Nipple failure on a 500 bbl tank holding a Hydrochloric Acid and fresh water mix caused fluid to exit tank into temporary secondary containment. The secondary containment also failed resulting in the fluid to impact the well pad as well as run off pad. Leak was stopped and tank repaired.													
Describe Area Affected and Cleanup Action Taken.* Caliche pad was affected on the SW portion of the well pad. Fluid ran off of pad to the S of the well pad as well as the SW most corner. Berms were erected to prevent any further fluid from leaving the pad and soda ash was used per the sds sheet to neutralize the acid both on and off the pad. Impacted caliche was scraped up and disposed of properly. Offsite impacted soil will be delineated and samples taken to ensure all impacted soil has been removed.													
I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.													
							OIL CONSERVATION DIVISION						
Signature: Jason Wardell						· · · · · · · · · · · · · · · · · · ·							
Printed Name: Jason Wardell							Approved by Environmental Specialist A to Environmental Specialist						
Title: HES Professional						Approval Da	te: 111118		Expiration 1	Date: N	A		
E-mail Address: jlwardell@marathonoil.com						Conditions of Approval: Attached							
Date: 01/16/2018 Phone: 575-297-06892							See attached 2RP-4569						

* Attach Additional Sheets If Necessary

1110/18 AB

Operator/Responsible Party,

The OCD has received the form C-141 you provided on 1/16/2018 regarding an unauthorized release. The information contained on that form has been entered into our incident database and remediation case number has been assigned. Please refer to this case number in all future correspondence.

It is the Division's obligation under both the Oil & Gas Act and Water Quality Act to provide for the protection of public health and the environment. Our regulations (19.15.29.11 NMAC) state the following,

The responsible person shall complete <u>division-approved corrective action</u> for releases that endanger public health or the environment. The responsible person shall address releases in accordance with a remediation plan submitted to and approved by the division or with an abatement plan submitted in accordance with 19.15.30 NMAC. [emphasis added]

Release characterization is the first phase of corrective action unless the release is ongoing or is of limited volume and all impacts can be immediately addressed. Proper and cost-effective remediation typically cannot occur without adequate characterization of the impacts of any release. Furthermore, the Division has the ability to impose reasonable conditions upon the efforts it oversees. As such, the Division is requiring a workplan for the characterization of impacts associated with this release be submitted to the OCD District $\underline{2}$ office in $\underline{ARTESIA}$ on or before $\underline{2/16/2018}$. If and when the release characterization workplan is approved, there will be an associated deadline for submittal of the resultant investigation report. Modest extensions of time to these deadlines may be granted, but only with acceptable justification.

The goals of a characterization effort are: 1) determination of the lateral and vertical extents along with the magnitude of soil contamination. 2) determine if groundwater or surface waters have been impacted. 3) If groundwater or surface waters have been impacted, what are the extents and magnitude of that impact. 4) The characterization of any other adverse impacts that may have occurred (examples: impacts on vegetation, impacts on wildlife, air quality, loss of use of property, etc.). To meet these goals as quickly as possible, the following items must, at a minimum, be addressed in the release characterization workplan and subsequent reporting:

- Horizontal delineation of soil impacts in each of the four cardinal compass directions. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. This is not an exclusive list of potential contaminants. Analyzed parameters should be modified based on the nature of the released substance(s). Soil sampling must be both within the impacted area and beyond.
- Vertical delineation of soil impacts. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. As above, this is not an exclusive list of potential contaminants and can be modified. Vertical characterization samples should be taken at depth intervals no greater than five feet apart. Lithologic description of encountered soils must also be provided. At least ten vertical feet of soils with contaminant concentrations at or below these values must be demonstrated as existing above the water table.
- Nominal detection limits for field and laboratory analyses must be provided.
- Composite sampling is not generally allowed.
- Field screening and assessment techniques are acceptable (headspace, titration, EC [include algorithm for validation purposes], EM, etc.), but the sampling and assay procedures must be clearly defined. Copies of field notes are highly desirable. A statistically significant set of split samples must be submitted for confirmatory laboratory analysis, including the laterally farthest and vertically deepest sets of soil samples. Make sure there are at least two soil samples submitted

for laboratory analysis from each borehole or test pit (highest observed contamination and deepest depth investigated). Copies of the actual laboratory results must be provided including chain of custody documentation.

- •Probable depth to shallowest protectable groundwater and lateral distance to nearest surface water. If there is an estimate of groundwater depth, the information used to arrive at that estimate must be provided. If there is a reasonable assumption that the depth to protectable water is 50 feet or less, the responsible party should anticipate the need for at least one groundwater monitoring well to be installed in the area of likely maximum contamination.
- If groundwater contamination is encountered, an additional investigation workplan may be required to determine the extents of that contamination. Groundwater and/or surface water samples, if any, must be analyzed by a competent laboratory for volatile organic hydrocarbons (typically Method 8260 full list), total dissolved solids, pH, major anions and cations including chloride and sulfate, dissolved iron, and dissolved manganese. The investigation workplan must provide the groundwater sampling method(s) and sample handling protocols. To the fullest extent possible, aqueous analyses must be undertaken using nominal method detection limits. As with the soil analyses, copies of the actual laboratory results must be provided including chain of custody documentation.
- Accurately scaled and well-drafted site maps must be provided providing the location of borings, test pits, monitoring wells, potentially impacted areas, and significant surface features including roads and site infrastructure that might limit either the release characterization or remedial efforts. Field sketches may be included in subsequent reporting, but should not be considered stand-alone documentation of the site's layout. Digital photographic documentation of the location and fieldwork is recommended, especially if unusual circumstances are encountered.

Nothing herein should be interpreted to preclude emergency response actions or to imply immediate remediation by removal cannot proceed as warranted. Nonetheless, characterization of impacts and confirmation of the effectiveness of remedial efforts must still be provided to the OCD before any release incident will be closed.

Jim Griswold
OCD Environmental Bureau Chief
1220 South St. Francis Drive
Santa Fe, New Mexico 87505
505-476-3465
jim.griswold@state.nm.us