

Submit 1 Copy To Appropriate District Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30-015-44558

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Dee State Com

8. Well Number #1H

9. OGRID Number 7377

10. Pool name or Wildcat N. Seven
Rivers; Glorieta-Yeso

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

EOG RESOURCES INC

3. Address of Operator

104 S. 4TH Street Artesia, NM 88210

4. Well Location

Unit Letter M : 755 feet from the South line and 165 feet from the West line
Section 36 Township 19S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,630' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

DOWNHOLE COMMINGLE ☐

CLOSED-LOOP SYSTEM ☐

OTHER: ☐ Plug Back Pilot ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ P AND A ☐

CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

The following is EOG Resources plan to plug back the pilot hole.

Plug on bottom 4150'-3950'

Cemented whipstock will be set at our approx. 1835' with cement plug from 1650'-2090'.

Thank you.

Spud Date:

1/15/18

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Naomi Farmer

TITLE

Engineering Tech

DATE 1/26/18

Type or print name Naomi Farmer

E-mail address: naomi_farmer@eogresources.com

PHONE: 575-748-4211

For State Use Only

APPROVED BY:

[Signature] TITLE Staff Mgr

DATE 1-26-18

Conditions of Approval (if any):

Com #1H

20" conductor set @ 113' (KB) TOC = 0' →

9 5/8" set @ 1273' TOC = 0' →

KOP = approx. 1,844' @ 9° degrees/100' →

Cemented
Whipstock

752' X-over to
2752'-7305'

Cement 1650'-2090' →

Bottom Plug 3950'-4150' →

Pilot hole = 4,150'

