June 2015)	UNITED STATE DEPARTMENT OF THE BUREAU OF LAND MAN	INTERIOR	OMB Expires	M APPROVED NO. 1004-0137 January 31, 2018	
SUNDRY NOTICES AND REPORTS ON WELLS		ORTS ON WELLS	5. Lease Serial No. NMNM6026		
Do not u abandone	se this form for proposals to d well. Use form 3160-3 (Af	o drill or to re-enter an PD) for such proposals.	6. If Indian, Allotte	e or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2			7. If Unit or CA/Ag SW892	7. If Unit or CA/Agreement, Name and/or No. SW892	
1. Type of Well Oil Well S Gas Well	□ Other			8. Well Name and No. FEDERAL CM 1	
2. Name of Operator Contact: 1		TINA HUERTA ta@eogresources.com	9. API Well No. 30-015-20800	9. API Well No. 30-015-20800-00-S1	
3a. Address 105 S 4TH STREET ARTESIA, NM 88210		3b. Phone No. (include area code) Ph: 575-748-4168 Fx: 575-748-4585	10. Field and Pool of PENASCO Di	10. Field and Pool or Exploratory Area PENASCO DRAW	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description			11. County or Paris	h, State	
Sec 12 T19S R24E SWSW 990FNL 400FEL			EDDY COUNTY, NM		
12. CHECK T	HE APPROPRIATE BOX(ES) TO INDICATE NATURE O	F NOTICE, REPORT, OR O	THER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION			
	🗖 Acidize	Deepen	Production (Start/Resume)	□ Water Shut-Off	
Notice of Intent	□ Alter Casing	Hydraulic Fracturing	□ Reclamation	Well Integrity	
🛛 Subsequent Report	Casing Repair	□ New Construction	Recomplete	Other	
🗖 Final Abandonment No	tice 🔲 Change Plans	🛛 Plug and Abandon	Temporarily Abandon		
	Convert to Injectior	Plug Back	Water Disposal		
If the proposal is to deepen di Attach the Bond under which following completion of the in testing has been completed. F	rectionally or recomplete horizontally the work will be performed or provid wolved operations. If the operation r inal Abandonment Notices must be f	ent details, including estimated startin , give subsurface locations and measu e the Bond No. on file with BLM/BIA esults in a multiple completion or rec iled only after all requirements, including the substant of	red and true vertical depths of all per Required subsequent reports must impletion in a new interval, a Form 3	tinent markers and zones. be filed within 30 days 160-4 must be filed once	
If the proposal is to deepen di Attach the Bond under which following completion of the in testing has been completed. If determined that the site is read 12/27/17 - MIRU. Pump 12/28/17 - Notified Carls Set packer at 838 ft. Pri rate down tubing into op Pumped 70 sx Class C 1024 ft. Top perf 1021 ff surface with 500 psi, hel 12/29/17 - Ran gyro sur circulated well with 20 b good. Spotted 25 sx Cla inch casing at 850 ft. Att	rectionally or recomplete horizontally the work will be performed or provid volved operations. If the operation r inal Abandonment Notices must be f ly for final inspection. ed 60 bbls brine water down v bad BLM that parted tubing (1 essure tested up to surface wi en perfs. Jim Amos ok'd to so cement and displaced to 938 f t. Loaded casing with 6 bbls v d good. Notified Carlsbad BL vey from 980 ft up to surface. ols plugging mud. Pressure te ass C cement at 1025 ft. Reve	r, give subsurface locations and measure the Bond No. on file with BLM/BIA esults in a multiple completion or reco illed only after all requirements, includive vell. NU BOP. 122 ft) is below top set of perfet th 500 psi, held good. Establish ueeze cement below packer in the WOC to tag. Released pack vater to surface. Pressure test M. Tagged TOC at 1025 ft. Load usted casing to surface with 50 rse circulated well clean. Perfor at 850 ft. no rate. Spotted 25	red and true vertical depths of all per Required subsequent reports must impletion in a new interval, a Form 3 ing reclamation, have been complete (1022 ft). led injection to open perfs. ler. Tagged TOC at ed casing to ed and 0 psi, held rated 4-1/2	tinent markers and zones. be filed within 30 days 160-4 must be filed once d and the operator has	
If the proposal is to deepen di Attach the Bond under which following completion of the in testing has been completed. If determined that the site is read 12/27/17 - MIRU. Pump 12/28/17 - Notified Carls Set packer at 838 ft. Pri rate down tubing into op Pumped 70 sx Class C 1024 ft. Top perf 1021 ff surface with 500 psi, hel 12/29/17 - Ran gyro sur circulated well with 20 b good. Spotted 25 sx Cla inch. casing at 850 ft. Att	rectionally or recomplete horizontally the work will be performed or provid ivolved operations. If the operation r imal Abandonment Notices must be f by for final inspection. ed 60 bbls brine water down w bad BLM that parted tubing (1 essure tested up to surface wi en perfs. Jim Amos ok/d to so cement and displaced to 938 f t. Loaded casing with 6 bbls w d good. Notified Carlsbad BL vey from 980 ft up to surface. bls plugging mud. Pressure te empted injection rate into perf 85 ft calc TOC. WOC to tag.	r, give subsurface locations and measure e the Bond No. on file with BLM/BL4 esults in a multiple completion or reco iled only after all requirements, include vell. NU BOP. 122 ft) is below top set of perfs th 500 psi, held good. Establish ueeze cement below packer in t. <u>WOC to tag</u> . Released pack vater to surface. Pressure test M. Tagged TOC at 1025 ft. Load ested casing to surface with 50 rse circulated well clean. Perfor at 850 ft. no rate. Spotted 25 Accepted for #400043 verified by the BLM We RESOURCES [NC, sent to the C	red and true vertical depths of all per Required subsequent reports must impletion in a new interval, a Form 3 ing reclamation, have been complete (1022 ft). ned injection to open perfs. .ter. Tagged TOC at ed casing to ed and 0 psi, held rated 4-1/2 sx Class 	tinent markers and zones. be filed within 30 days 160-4 must be filed once	
If the proposal is to deepen di Attach the Bond under which following completion of the in testing has been completed. If determined that the site is read 12/27/17 - MIRU. Pump 12/28/17 - Notified Carls Set packer at 838 ft. Pri- rate down tubing into op Pumped 70 sx Class C (1024 ft. Top perf 1021 ft surface with 500 psi, he 12/29/17 - Ran gyro sur- circulated well with 20 b good. Spotted 25 sx Cla inch casing at 850 ft. Att C cement from 870 ft. 5	rectionally or recomplete horizontally the work will be performed or provid ivolved operations. If the operation r imal Abandonment Notices must be f by for final inspection. ed 60 bbls brine water down w bad BLM that parted tubing (1 essure tested up to surface wi en perfs. Jim Amos ok/d to so cement and displaced to 938 f t. Loaded casing with 6 bbls w d good. Notified Carlsbad BL vey from 980 ft up to surface. bls plugging mud. Pressure te empted injection rate into perf 85 ft calc TOC. WOC to tag.	r, give subsurface locations and measure e the Bond No. on file with BLM/BL4 esults in a multiple completion or reco iled only after all requirements, include vell. NU BOP. 122 ft) is below top set of perfs th 500 psi, held good. Establish ueeze cement below packer in t. <u>WOC to tag</u> . Released pack vater to surface. Pressure test M. Tagged TOC at 1025 ft. Load ested casing to surface with 50 rse circulated well clean. Perfor at 850 ft. no rate. Spotted 25 Accepted for the surface NC, sent to the C cessing by PRISCILLA PEREZ of	red and true vertical depths of all per Required subsequent reports must impletion in a new interval, a Form 3 ing reclamation, have been complete (1022 ft). ned injection to open perfs. .ter. Tagged TOC at ed casing to ed and 0 psi, held rated 4-1/2 sx Class 	tinent markers and zones. be filed within 30 days 160-4 must be filed once d and the operator has	
If the proposal is to deepen di Attach the Bond under which following completion of the in testing has been completed. I determined that the site is read 12/27/17 - MIRU. Pump 12/28/17 - Notified Carls Set packer at 838 ft. Pri- rate down tubing into op Pumped 70 sx Class C of 1024 ft. Top perf 1021 ft surface with 500 psi, hel 12/29/17 - Ran gyro sur circulated well with 20 b good. Spotted 25 sx Cla inch casing at 850 ft. Att C cement from 870 ft - 5 Name (Printed/Typed) TIN/	rectionally or recomplete horizontally the work will be performed or provid inal Abandonment Notices must be f by for final inspection. The definition of the second second bad BLM that parted tubing (1 essure tested up to surface with en perfs. Jim Arnos ok'd to so cement and displaced to 938 f t. Loaded casing with 6 bbls v d good. Notified Carlsbad BL vey from 980 ft up to surface. bls plugging mud. Pressure te ass C cement at 1025 ft. Reve empted injection rate into perf 85 ft calc TOC. WOC to tag. Tor Electronic Submission For EOG Y Committed to AFMSS for pro-	r, give subsurface locations and measure e the Bond No. on file with BLM/BIA esults in a multiple completion or reco iled only after all requirements, include vell. NU BOP. 122 ft) is below top set of perfs th 500 psi, held good. Establish ueeze cement below packer in t. <u>WOC to tag</u> . Released pack vater to surface. Pressure test M. Tagged TOC at 1025 ft. Load ested casing to surface with 50 rse circulated well clean. Perfor at 850 ft. no rate. Spotted 25 Accepted for the RESOURCES NC, sent to the Constrained to the Constrained by the BLM We RESOURCES NC, sent to the Constrained Title REGUL	red and true vertical depths of all per Required subsequent reports must impletion in a new interval, a Form 3 ing reclamation, have been complete (1022 ft). ned injection to open perfs. ter. Tagged TOC at ed casing to ed and 0 psi, held rated 4-1/2 sx Class Information System carisbad n 01/11/2018 (18JA0058SE) ATORY SPECIALIST	tinent markers and zones. be filed within 30 days 160-4 must be filed once d and the operator has	
If the proposal is to deepen di Attach the Bond under which following completion of the in testing has been completed. If determined that the site is read 12/27/17 - MIRU. Pump 12/28/17 - Notified Carls Set packer at 838 ft. Pri- rate down tubing into op Pumped 70 sx Class C of 1024 ft. Top perf 1021 f surface with 500 psi, hel 12/29/17 - Ran gyro sur- circulated well with 20 b good. Spotted 25 sx Cla inch.casing at 850 ft. Att C cement from 870 ft - 5 14. I hereby certify that the forego Name (Printed/Typed) TIN/ Signature (Elec	rectionally or recomplete horizontally the work will be performed or provid volved operations. If the operation r inal Abandonment Notices must be f by for final inspection. ed 60 bbls brine water down w bad BLM that parted tubing (1 essure tested up to surface wi en perfs. Jim Amos ok'd to so cement and displaced to 938 f t. Loaded casing with 6 bbls w d good. Notified Carlsbad BL vey from 980 ft up to surface. bls plugging mud. Pressure te ass C cement at 1025 ft. Reve empted injection rate into perf 85 ft calc TOC. WOC to tag. for Electronic Submission in For EOG Y Committed to AFMSS for pro- A HUERTA	r, give subsurface locations and measure e the Bond No. on file with BLM/BIA esults in a multiple completion or reco iled only after all requirements, include vell. NU BOP. 122 ft) is below top set of perfs th 500 psi, held good. Establist ueeze cement below packer in t. <u>WOC to tag</u> . Released pack vater to surface. Pressure test M. Tagged TOC at 1025 ft. Load ested casing to surface with 50 rse circulated well clean. Perfor at 850 ft. no rate. Spotted 25 Accepted for the RESOURCES NC, sent to the Co cessing by PRISCILLA PEREZ o Title REGUL	red and true vertical depths of all per Required subsequent reports must impletion in a new interval, a Form 3 ing reclamation, have been complete (1022 ft). red injection to open perfs. ter. Tagged TOC at red casing to ed and 0 psi, held rated 4-1/2 sx Class 1 1 1 1 1 1 1 1	tinent markers and zones. be filed within 30 days 160-4 must be filed once d and the operator has	
If the proposal is to deepen di Attach the Bond under which following completion of the in testing has been completed. If determined that the site is read 12/27/17 - MIRU. Pump 12/28/17 - Notified Carls Set packer at 838 ft. Pri- rate down tubing into op Pumped 70 sx Class C of 1024 ft. Top perf 1021 f surface with 500 psi, hel 12/29/17 - Ran gyro sur- circulated well with 20 b good. Spotted 25 sx Cla inch casing at 850 ft. Att C cement from 870 ft - 5 14. I hereby certify that the forego Name (Printed/Typed) TIN/ Signature (Elec	rectionally or recomplete horizontally the work will be performed or provid volved operations. If the operation r inal Abandonment Notices must be f by for final inspection. ed 60 bbls brine water down v bad BLM that parted tubing (1 essure tested up to surface wi en perfs. Jim Amos ok'd to so cement and displaced to 938 f t. Loaded casing with 6 bbls v d good. Notified Carlsbad BL vey from 980 ft up to surface. bls plugging mud. Pressure te ass C cement at 1025 ft. Reve empted injection rate into perf 85 ft calc TOC. WOC to tag. For EOG Y Committed to AFMSS for pro- A HUERTA	r, give subsurface locations and measu e the Bond No. on file with BLM/BIA soults in a multiple completion or reco iled only after all requirements, includ vell. NU BOP. 122 ft) is below top set of perfs th 500 psi, held good. Establish jueeze cement below packer in t. <u>WOC to tag</u> . Released pack vater to surface. Pressure test M. Tagged TOC at 1025 ft. Load isted casing to surface with 50 rse circulated well clean. Perfor at 850 ft. no rate. Spotted 25 Accepted for the RESOURCES NC, sent to the C cessing by PRISCILLA PEREZ o Title REGUL Date 01/09/2 OR FEDERAL OR STATE	red and true vertical depths of all per Required subsequent reports must impletion in a new interval, a Form 3 ing reclamation, have been complete (1022 ft). led injection to open perfs. er. Tagged TOC at ed casing to ed and 0 psi, held trated 4-1/2 sx Class record - NMOCD Information System arisbad n 01/11/2018 (18JA0058SE) ATORY SPECIALIST 018 OFFICE USE	tinent markers and zones. be filed within 30 days 160-4 must be filed once d and the operator has SECLAMATIC UE <u>7-5-/8</u> UE <u>7-18-18</u>	
If the proposal is to deepen di Attach the Bond under which following completion of the in testing has been completed. If determined that the site is read 12/27/17 - MIRU. Pump 12/28/17 - Notified Carls Set packer at 838 ft. Pri- rate down tubing into op Pumped 70 sx Class C of 1024 ft. Top perf 1021 f surface with 500 psi, hel 12/29/17 - Ran gyro sur- circulated well with 20 b good. Spotted 25 sx Cla inch casing at 850 ft. Att C cement from 870 ft - 5 14. I hereby certify that the foreg Name (Printed/Typed) TIN/ Signature (Elec Approved By Conditions of approval of any, are	rectionally or recomplete horizontally the work will be performed or provid volved operations. If the operation r inal Abandonment Notices must be f by for final inspection. ed 60 bbls brine water down v bad BLM that parted tubing (1 essure tested up to surface wi en perfs. Jim Amos ok'd to so cement and displaced to 938 f t. Loaded casing with 6 bbls v d good. Notified Carlsbad BL vey from 980 ft up to surface ass C cement at 1025 ft. Reve empted injection rate into perf 85 ft calc TOC. WOC to tag. for EOG Y Committed to AFMSS for pro- A HUERTA tronic Submission) Fuel C. THIS SPACE F attached. Approval of this notice doe 1 or equitable title to those rights in th	r, give subsurface locations and measu e the Bond No. on file with BLM/BIA soults in a multiple completion or reco iled only after all requirements, includ vell. NU BOP. 122 ft) is below top set of perfs th 500 psi, held good. Establish jueeze cement below packer in t. <u>WOC to tag</u> . Released pack vater to surface. Pressure test M. Tagged TOC at 1025 ft. Load isted casing to surface with 50 rse circulated well clean. Perfor at 850 ft. no rate. Spotted 25 Accepted for the RESOURCES NC, sent to the C cessing by PRISCILLA PEREZ o Title REGUL Date 01/09/2 OR FEDERAL OR STATE	red and true vertical depths of all per Required subsequent reports must impletion in a new interval, a Form 3 ing reclamation, have been complete (1022 ft). red injection to open perfs. ter. Tagged TOC at red casing to ed and 0 psi, held rated 4-1/2 sx Class 1 1 1 1 1 1 1 1	tinent markers and zones. be filed within 30 days 160-4 must be filed once d and the operator has SECLAMATIC UE <u>7-5-/8</u>	

** BLM REVISED **

Additional data for EC transaction #400043 that would not fit on the form

32. Additional remarks, continued

.

>

٠

12/30/17 - Tagged TOC at 596 ft. Perforated 7 inch casing at 350 ft. Loaded casing and attempted injection rate into perf at 350 ft, ho rate. Spotted 45 sx Class C cement from 434 ft up to surface. Topped off well with cement. 1/5/18 - Cut off wellhead. Installed dry hole marker and cut off anchors. WELL IS PLUGGED AND ABANDONED.

.

.