MM OIL CONSERVATION
ARTESIA DISTRICT

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department EB 1 5 20 Submit Original District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

RECEIVED.

Date: 2-13-18	GAS CAPTURE PLAN
☑ Original☐ Amended - Reason for Amendment:	Operator & OGRID No.: <u>Mewbourne Oil Company - 14744</u>

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
PORTY NINER RIDGE UNIT #107H	30-015-44652	J-16-23S-30E	2323 FSL & 2562 FE	. 0	NA	ONLINE AFTER FRAC
ORTY NINER RIDGE UNIT #108H	30-015-44653	J-J6-23S-30E	2323 PSL & 2637 PE	, 0	NA NA	ONLINE AFTER FRAC
ORTY NINER RIDGE UNIT #109H	30-015-44654	J-16-23S-30E	2398 FSL & 2638 FE	. 0	NA NA	ONLINE AFTER FRAC
109 H	44654					

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to DCP_Midstream and will be connected to DCP_Midstream low/high pressure gathering system located in EDDY County, New Mexico. It will require <a href="Operation-of-Operation-opera

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on DCP Midstream system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines