Form 3160-3 (March 2012)

UNITED STATES

| FORM | APPROVED |
|-----------|---------------|
| OMB N | lo. 1004-0137 |
| Expires C | ctober 31, 20 |

| DEPARTMENT OF THE I BUREAU OF LAND MAN | 5. Lease Serial No. NMNM119275 | NMNM119275 | | | | | | |
|---|---|-----------------------|--|------------------------|--------------|--|--|--|
| APPLICATION FOR PERMIT TO | DRILL OR REENTER | | 6. If Indian, Allotee of | r Tribe Name | | | | |
| la. Type of work: DRILL REENTE | ER | | 7 If Unit or CA Agreer | | - 222 | | | |
| lb. Type of Well: Oil Well as Well Other | Single Zone | Multiple Zone | 8. Lease Name and We CASEY JONES 16 F | JII 1 10. | 079 8 | | | |
| 2. Name of Operator EOG RESOURCES INCORPORATED | | 377 | 9. API Well No. 30-015 | 5-44700 | | | | |
| 3a. Address 1111 Bagby Sky Lobby2 Houston TX 77002 | 3b. Phone No. (include area co (713)651-7000 | de) | 10. Field and Pool, or Ex RED HILLS / WILDS | AT WOLFCAMP OH | | | | |
| 4. Location of Well (Report location clearly and in accordance with an | y State requirements.*) | | 11. Sec., T. R. M. or Blk | and Survey or Area | 78220 | | | |
| At surface SESW / 260 FSL / 2000 FWL / LAT 32.03598 At proposed prod. zone NENW / 230 FNL / 1660 FWL / LA | | 3.8894852 | SEC 16 / T26S / R30 | DE / NMP | | | | |
| 14. Distance in miles and direction from nearest town or post office* 32 miles | | | 12. County or Parish EDDY | 13. State NM | | | | |
| 15. Distance from proposed* location to nearest 230 feet property or lease line, ft. (Also to nearest drig. unit line, if any) | 16. No. of acres in lease 480 | 17. Spacii 640 | ng Unit dedicated to this we | | | | | |
| Distance from proposed location* to nearest well, drilling, completed, 665 feet applied for, on this lease, ft. | 19. Proposed Depth 10613 feet / 20768 feet | 20. BLM/ FED: N | BIA Bond No. on file M2308 | | | | | |
| 21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3034 feet | 22. Approximate date work w | rill start* | 23. Estimated duration 25 days | | | | | |
| | 24. Attachments | | | | | | | |
| The following, completed in accordance with the requirements of Onshor | re Oil and Gas Order No.1, mus | t be attached to th | nis form: | | | | | |
| Well plat certified by a registered surveyor. A Drilling Plan. A Surface Use Plan (if the location is on National Forest System SUPO must be filed with the appropriate Forest Service Office). | Lands, the 5. Operator of | ove). ertification | ons unless covered by an ex- | Č | | | | |
| 25. Signature (Electronic Submission) | Name (Printed/Typed) Stan Wagner / Ph: | (432)686-3689 | 1 | Date 05/05/2017 | : | | | |
| Title Regulatory Specialsit | | | | | | | | |
| Approved by (Signature) (Electronic Submission) | Name (Printed/Typed) Cody Layton / Ph: (| 575)234-5959 | I | Date 02/02/2018 | | | | |
| Title Supervisor Multiple Resources | Office CARLSBAD | | | | | | | |
| Application approval does not warrant or certify that the applicant hold conduct operations thereon. Conditions of approval, if any, are attached. | is legal or equitable title to thos | e rights in the sui | bject lease which would ent | title the applicant to | _ | | | |
| Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a ct States any false, fictitious or fraudulent statements or representations as | | | make to any department or | agency of the United | | | | |
| (Continued on page 2) | | | *(Instru | ictions on page 2) | : | | | |

REST CIL CONSERVATION

FEB 1 5 2018

Approval Date: 02/02/2018

RECEIVED

Application for Permit to Drill

Date Printed: 02/06/2018 11:58 AM

ALCOLCONSERVATION

ARTESIA DISTRICT

FEB 1 5 2018

FCFIVE

APD Package Report

APD ID: 10400013562 Well Status: AAPD

APD Received Date: 05/05/2017 12:48 PM Well Name: CASEY JONES 16 FED COM

Operator: EOG RESOURCES INCORPORATED Well Number: 703H

APD Package Report Contents

- Form 3160-3

- Operator Certification Report

- Application Report

- Application Attachments

-- Well Plat: 1 file(s)

- Drilling Plan Report

- Drilling Plan Attachments

-- Blowout Prevention Choke Diagram Attachment: 3 file(s)

-- Blowout Prevention BOP Diagram Attachment: 1 file(s)

-- Casing Taperd String Specs: 2 file(s)

-- Casing Design Assumptions and Worksheet(s): 3 file(s)

-- Hydrogen sulfide drilling operations plan: 1 file(s)

-- Proposed horizontal/directional/multi-lateral plan submission: 2 file(s)

-- Other Facets: 8 file(s)

- SUPO Report

- SUPO Attachments

-- Existing Road Map: 1 file(s)

-- New Road Map: 3 file(s)

-- Attach Well map: 1 file(s)

-- Production Facilities map: 4 file(s)

-- Water source and transportation map: 1 file(s)

-- Construction Materials source location attachment: 1 file(s)

-- Well Site Layout Diagram: 3 file(s)

-- Recontouring attachment: 1 file(s)

-- Other SUPO Attachment: 3 file(s)

- PWD Report

- PWD Attachments

-- None

PECOS DISTRICT DRILLING OPERATIONS CONDITIONS OF APPROVAL

OPERATOR'S NAME: EOG Resources, Inc.

LEASE NO.: NMNM-119275

WELL NAME & NO.: | Casey Jones 16 Fed Com 703H

SURFACE HOLE FOOTAGE: 0260' FSL & 2000' FWL BOTTOM HOLE FOOTAGE 0230' FNL & 1660' FWL

LOCATION: Section 16, T. 26 S., R 30 E., NMPM

COUNTY: | County, New Mexico

Communitization Agreement

The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.

- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- · In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☐ Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220, (575) 361-2822

A. Hydrogen Sulfide

- 1. Although Hydrogen Sulfide has not been reported in the area, it is always a potential hazard. If Hydrogen Sulfide is encountered, report measured amounts and formations to the BLM.
- 2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval. If the drilling rig is removed without approval an Incident of Non-Compliance will be written and will be a "Major" violation.
- 3. Option Setting surface casing with Surface Rig
 - a. Notify the BLM when removing the Surface Rig.
 - b. Notify the BLM when moving in the H&P Flex Rig. Rig to be moved in within 60 days of notification that Ashton Oilfield Services Rig has left the location. Failure to notify or have rig on location within 60 days will result in an Incident of Non-Compliance.
 - c. Once the H&P Flex Rig is on location, it shall not be removed from over the hole without prior approval unless the production casing has been run and cemented or the well has been properly plugged. If the drilling rig is removed without approval an Incident of Non-Compliance will be written and will be a "Major" violation.
 - d. BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as H&P Flex Rig is rigged up on well. CIT for the surface casing shall be performed and results recorded on subsequent sundry pressure to be 1200 psi.
- 4. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works is located, this does not include the dog house or stairway area.
- 5. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.
- A. CASING

Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) for Water Basin:

After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements.

Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

High Cave/Karst

Possibility of water flows in the Castile and Salado.
Possibility of lost circulation in the Rustler, Red Beds, and Delaware.

A MINIMUM OF TWO CASING STRINGS CEMENTED TO SURFACE IS REQUIRED IN HIGH CAVE/KARST AREAS. THE CEMENT MUST BE IN A SOLID SHEATH. THEREFORE, ONE INCH OPERATIONS ARE NOT SUFFICIENT TO PROTECT CAVE KARST RESOURCES. A CASING DESIGN THAT HAS A ONE INCH JOB PERFORMED DOES NOT COUNT AS A SOLID SHEATH. IF THE PRIMARY CEMENT JOB ON THE SURFACE CASING DOES NOT CIRCULATE, THEN THE NEXT TWO CASING STRINGS MUST BE CEMENTED TO SURFACE.

1. The 10-3/4 inch surface casing shall be set at approximately 900 feet and cemented to the surface.

- a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
- b. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Formation below the 10-3/4" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe and the mud weight for the bottom of the hole. Report results to BLM office.

| 3 |
|---|
| Cement to surface. If cement does not circulate see B.1.a, c-d above. Wait on |
| cement (WOC) time for a primary cement job is to include the lead |
| cement slurry due to cave/karst. |

2. The minimum required fill of cement behind the 7-5/8 inch intermediate casing is:

Formation below the 7-5/8" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight for the bottom of the hole. Report results to BLM office.

- 3. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - Cement should as proposed by operator. Operator shall provide method of verification. Excess calculates to 9% Additional cement may be required.
 - 4. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

B. PRESSURE CONTROL

- 1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API 53.
- 2. Variance approved to use flex line from BOP to choke manifold. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor. If the BLM inspector questions the straightness of the hose, a BLM engineer will be contacted and will review in the field or via picture supplied by inspector to determine if changes are required (operator shall expect delays if this occurs).
- 3. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Operator shall perform the intermediate casing integrity test to 70% of the casing burst. This will test the multi-bowl seals.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.

Variance approved to use a 5M annular. The annular must be tested to full working pressure (5000 psi.)

10M system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.

4. The appropriate BLM office shall be notified a minimum of hours in advance for a representative to witness the tests.

- a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
- a. The tests shall be done by an independent service company utilizing a test plug **not** a **cup** or **J-packer**.
- b. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- c. The results of the test shall be reported to the appropriate BLM office.
- d. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- e. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- f. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the **Wolfcamp** formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the **Wolfcamp** formation, and shall be used until production casing is run and cemented.

D. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

E. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

JAM 011018

Page 7 of 7

Approval Date: 02/02/2018

PECOS DISTRICT SURFACE USE CONDITIONS OF APPROVAL

| OPERATOR'S NAME: | |
|-----------------------|--------------------------------------|
| LEASE NO.: | NM119275 |
| WELL NAME & NO.: | Casey Jones 16 Fed Com – 703H |
| SURFACE HOLE FOOTAGE: | 260'/S & 2000'/W |
| BOTTOM HOLE FOOTAGE | 230'/N & 1660'/W, sec. 9 |
| LOCATION: | Section 16, T. 26 S., R. 30 E., NMPM |
| COUNTY: | Eddy County, New Mexico |

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

| General Provisions |
|---|
| Permit Expiration |
| Archaeology, Paleontology, and Historical Sites |
| Noxious Weeds |
| Special Requirements |
| Cave/Karst |
| Phantom Banks |
| Watershed |
| ☐ Construction |
| Notification |
| Topsoil |
| Closed Loop System |
| Federal Mineral Material Pits |
| Well Pads |
| Roads |
| Road Section Diagram |
| ⊠ Production (Post Drilling) |
| Well Structures & Facilities |
| Pipelines |
| Electric Lines |
| ☐ Interim Reclamation |
| Final Abandonment & Reclamation |

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

Page 2 of 18

Approval Date: 02/02/2018

V. SPECIAL REQUIREMENT(S)

Cave and Karst

** Depending on location, additional Drilling, Casing, and Cementing procedures may be required by engineering to protect critical karst groundwater recharge areas.

Cave/Karst Surface Mitigation

The following stipulations will be applied to minimize impacts during construction, drilling and production.

Construction:

In the advent that any underground voids are opened up during construction activities, construction activities will be halted and the BLM will be notified immediately.

No Blasting:

No blasting will be utilized for pad construction. The pad will be constructed and leveled by adding the necessary fill and caliche.

Pad Berming:

The entire perimeter of the well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad.

- The compacted berm shall be constructed at a minimum of 12 inches high with impermeable mineral material (e.g. caliche).
- No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad.
- The topsoil stockpile shall be located outside the bermed well pad.
- Topsoil, either from the well pad or surrounding area, shall not be used to construct the berm.
- No storm drains, tubing or openings shall be placed in the berm.
- If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.
- The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed.
- Any access road entering the well pad shall be constructed so that the integrity of the berm height surrounding the well pad is not compromised. (Any access road crossing the berm cannot be lower than the berm height.)

Tank Battery Liners and Berms:

Tank battery locations and all facilities will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.

Leak Detection System:

A method of detecting leaks is required. The method could incorporate gauges to measure loss, situating values and lines so they can be visually inspected, or installing electronic sensors to alarm when a leak is present. Leak detection plan will be submitted to BLM for approval.

Automatic Shut-off Systems:

Automatic shut off, check values, or similar systems will be installed for pipelines and tanks to minimize the effects of catastrophic line failures used in production or drilling.

Cave/Karst Subsurface Mitigation

The following stipulations will be applied to protect cave/karst and ground water concerns:

Rotary Drilling with Fresh Water:

Fresh water will be used as a circulating medium in zones where caves or karst features are expected. SEE ALSO: Drilling COAs for this well.

Directional Drilling:

Kick off for directional drilling will occur at least 100 feet below the bottom of the cave occurrence zone. SEE ALSO: Drilling COAs for this well.

Lost Circulation:

ALL lost circulation zones from the surface to the base of the cave occurrence zone will be logged and reported in the drilling report.

Regardless of the type of drilling machinery used, if a void of four feet or more and circulation losses greater than 70 percent occur simultaneously while drilling in any cavebearing zone, the BLM will be notified immediately by the operator. The BLM will assess the situation and work with the operator on corrective actions to resolve the problem.

Abandonment Cementing:

Upon well abandonment in high cave karst areas additional plugging conditions of approval may be required. The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

Pressure Testing:

Annual pressure monitoring will be performed by the operator on all casing annuli and reported in a sundry notice. If the test results indicated a casing failure has occurred, remedial action will be undertaken to correct the problem to the BLM's approval.

Phantom Banks Heronry

Surface disturbance will not be allowed within 660 feet of active heronries or by delaying activity for up to 120 days, or a combination of both. Exhaust noise from engines must be muffled or otherwise controlled so as not to exceed 75 decibels measured at 30 feet from the source of the noise.

Page 4 of 18

Approval Date: 02/02/2018

Watershed

- The entire well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The berm shall be maintained through the life of the well and after interim reclamation has been completed.
- Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion.

Page 5 of 18

Approval Date: 02/02/2018

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Page 6 of 18

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outsloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

400 foot road with 4% road slope:
$$\frac{400'}{4\%} + 100' = 200'$$
 lead-off ditch interval

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

- 1. Salvage topsoil
- 3. Redistribute topsoil
- 2. Construct road
- 4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or F5 local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Page 10 of 18

Approval Date: 02/02/2018

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. PIPELINES

BURIED PIPELINE STIPULATIONS

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

- 1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
- 2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
- 3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C.6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of

Page 11 of 18

the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

- 4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.
- 5. All construction and maintenance activity will be confined to the authorized right-of-way.
- 6. The pipeline will be buried with a minimum cover of 36 inches between the top of the pipe and ground level.
- 7. The maximum allowable disturbance for construction in this right-of-way will be $\underline{30}$ feet:
 - Blading of vegetation within the right-of-way will be allowed: maximum width of blading operations will not exceed **20** feet. The trench is included in this area. (Blading is defined as the complete removal of brush and ground vegetation.)
 - Clearing of brush species within the right-of-way will be allowed: maximum width of clearing operations will not exceed 30 feet. The trench and bladed area are included in this area. (Clearing is defined as the removal of brush while leaving ground vegetation (grasses, weeds, etc.) intact. Clearing is best accomplished by holding the blade 4 to 6 inches above the ground surface.)
 - The remaining area of the right-of-way (if any) shall only be disturbed by compressing the vegetation. (Compressing can be caused by vehicle tires, placement of equipment, etc.)
- 8. The holder shall stockpile an adequate amount of topsoil where blading is allowed. The topsoil to be stripped is approximately ___6__ inches in depth. The topsoil will be segregated from other spoil piles from trench construction. The topsoil will be evenly distributed over the bladed area for the preparation of seeding.

Page 12 of 18

- 9. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
- 10. Vegetation, soil, and rocks left as a result of construction or maintenance activity will be randomly scattered on this right-of-way and will not be left in rows, piles, or berms, unless otherwise approved by the Authorized Officer. The entire right-of-way shall be recontoured to match the surrounding landscape. The backfilled soil shall be compacted and a 6 inch berm will be left over the ditch line to allow for settling back to grade.
- 11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.
- 12. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

| (X) seed mixture 1 | () seed mixture 3 |
|------------------------|-----------------------------|
| () seed mixture 2 | () seed mixture 4 |
| () seed mixture 2/LPC | () Aplomado Falcon Mixture |

- 13. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be color which simulates "Standard Environmental Colors" **Shale Green**, Munsell Soil Color No. 5Y 4/2.
- 14. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. All signs and information thereon will be posted in a permanent, conspicuous manner, and will be maintained in a legible condition for the life of the pipeline.

- 15. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder before maintenance begins. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway. As determined necessary during the life of the pipeline, the Authorized Officer may ask the holder to construct temporary deterrence structures.
- 16. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.
- 17. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes associated roads, pipeline corridor and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.
- 18. <u>Escape Ramps</u> The operator will construct and maintain pipeline/utility trenches [that are not otherwise fenced, screened, or netted] to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:
 - a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
 - b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.

C. ELECTRIC LINES

STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

- 1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
- 2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
- 3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.
- 4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.
- 5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006. The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching

deterrence shall be placed on all vertical poles that extend past the cross arms.

- 6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
- 7. The BLM serial number assigned to this authorization shall be posted in a permanent, conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.
- 8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply with those abandonment procedures as prescribed by the Authorized Officer.
- 9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.
- 10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

11. Special Stipulations:

- For reclamation remove poles, lines, transformer, etc. and dispose of properly.
- Fill in any holes from the poles removed.

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce

the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Page 17 of 18

Approval Date: 02/02/2018

Seed Mixture 1 for Loamy Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed shall be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed shall be planted using a drill equipped with a depth regulator to ensure proper depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture shall be evenly and uniformly planted over the disturbed area (small/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed shall be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre shall be doubled. The seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

| Species | <u>lb/acre</u> |
|--|----------------|
| Plains lovegrass (Eragrostis intermedia) | 0.5 |
| Sand dropseed (Sporobolus cryptandrus) | 1.0 |
| Sideoats grama (Bouteloua curtipendula) | 5.0 |
| Plains bristlegrass (Setaria macrostachya) | 2.0 |

^{*}Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed

PAFMSS

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT



Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Stan Wagner Signed on: 05/05/2017

Title: Regulatory Specialsit

Street Address: 5509 Champions Drive

City: Midland State: TX Zip: 79702

Phone: (432)686-3689

Email address: Stan Wagner@eogresources.com

Field Representative

Representative Name: Michael Yemm

Street Address: 5509 Champions Drive

City: Midland State: TX Zip: 79706

Phone: (432)556-7258

Email address: michael yemm@eogresources.com

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT



APD ID: 10400013562

Submission Date: 05/05/2017

Highlighted data reflects the most

Operator Name: EOG RESOURCES INCORPORATED

recent changes

Well Name: CASEY JONES 16 FED COM

Well Number: 703H

Show Final Text

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - General

APD ID: 10400013562

Tie to previous NOS?

Submission Date: 05/05/2017

BLM Office: CARLSBAD

User: Stan Wagner

Title: Regulatory Specialsit

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM119275

Lease Acres: 480

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? NO

Permitting Agent? NO

APD Operator: EOG RESOURCES INCORPORATED

Operator letter of designation:

Operator Info

Operator Organization Name: EOG RESOURCES INCORPORATED

Operator Address: 1111 Bagby Sky Lobby2

Zip: 77002

Operator PO Box:

Operator City: Houston

State: TX

Operator Phone: (713)651-7000

Operator Internet Address:

Section 2 - Well Information

Well in Master Development Plan? NO

Mater Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: CASEY JONES 16 FED COM

Well Number: 703H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: RED HILLS

Pool Name: WILDCAT

WOLFCAMP OIL

Is the proposed well in an area containing other mineral resources? NATURAL GAS,OIL

Page 1 of 3

Well Name: CASEY JONES 16 FED COM Well Number: 703H

Describe other minerals:

Is the proposed well in a Helium production area? N Use Existing Well Pad? NO New surface disturbance?

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name: Number: 703H/704H

Well Class: HORIZONTAL CASEY JONES 16 FED COM

Number of Legs: 1

Well Work Type: Drill
Well Type: OIL WELL
Describe Well Type:

Well sub-Type: INFILL

Describe sub-type:

Distance to town: 32 Miles Distance to nearest well: 665 FT Distance to lease line: 230 FT

Reservoir well spacing assigned acres Measurement: 640 Acres

Well plat: Casey_Jones_16_FC_703H_signed_C_102_05-05-2017.pdf

Well work start Date: 11/01/2017 Duration: 25 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83 Vertical Datum: NAVD88

Survey number:

| | NS-Foot | NS Indicator | EW-Foot | EW Indicator | Twsp | Range | Section | Aliquot/Lot/Tract | Latitude | Longitude | County | State | Meridian | Lease Type | Lease Number | Elevation | MD | DVT |
|------------------|---------|--------------|----------|--------------|------|-------|---------|-------------------|----------------|----------------------|----------|-------------------|-------------------|------------|--------------|---------------|-----------|-----------|
| SHL Leg #1 | 260 | FSL | 200 0 | FWL | 268 | 30E | 16 | Aliquot SESW | 32.03598 41 | - 103.8884 125 | EDD Y | MEXI | NEW MEXI CO | S | STATE | 303 4 | 0 | 0 |
| KOP Leg #1 | 52 | FSL | 168 3 | FWL | 26S | 30E | 16 | Aliquot SESW | 32.03541 75 | - 103.8894 392 | EDD Y | NEW MEXI CO | | S | STATE | - 708 5 | 101 31 | 101 19 |
| PPP Leg #1 | 330 | FSL | 165 6 | FWL | 268 | 30E | 16 | 1 | 32.03617 38 | - 103.8895 156 | * | NEW MEXI CO | | S | STATE | - 753 4 | 106 89 | 105 68 |



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Drilling Plan Data Report

02/06/2018

APD ID: 10400013562

Submission Date: 05/05/2017

Highlighted data reflects the most

recent changes

Well Name: CASEY JONES 16 FED COM

Well Number: 703H

Show Final Text

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Geologic Formations

Operator Name: EOG RESOURCES INCORPORATED

| Formation ID | Formation Name | Elevation | True Vertical Depth | Measured Depth | Lithologies | Mineral Resources | Producing Formation |
|--------------|------------------|-----------|------------------------|-------------------|-------------|-------------------|------------------------|
| 1 | PERMIAN | 3034 | Ö | Ō | ANHYDRITE | NONE | No |
| 2 | RUSTLER | 2219 | 815 | 815 | ANHYDRITE | NONE | No |
| 3 | TOP SALT | 1885 | 1149 | 1149 | SALT | NONE | No |
| 4 | BASE OF SALT | -61 | 3095 | 3095 | SALT | NONE | No |
| 5 | LAMAR | -407 | 3441 | 3441 | LIMESTONE | NONE | No |
| 6 | BELL CANYON | -436 | 3470 | 3470 | SANDSTONE | NATURAL GAS,OIL | No |
| 7 | 7 CHERRY CANYON | | 4367 | 4367 | SANDSTONE | NATURAL GAS,OIL | No |
| 8 | BRUSHY CANYON | -2666 | 5700 | 5700 | SANDSTONE | NATURAL GAS,OIL | No |
| 9 | BONE SPRING LIME | -4238 | 7272 | 7272 | LIMESTONE | NONE | No |
| 10 | BONE SPRING 1ST | -5171 | 8205 | 8205 | SANDSTONE | NATURAL GAS,OIL | No |
| 11 | BONE SPRING 2ND | -5767 | 8801 | 8801 | SANDSTONE | NATURAL GAS,OIL | No |
| 12 | BONE SPRING 3RD | -7067 | 10101 | 10101 | SANDSTONE | NATURAL GAS,OIL | No |
| 13 | WOLFCAMP | -7445 | 10479 | 10479 | SHALE | NATURAL GAS,OIL | Yes |

Section 2 - Blowout Prevention

Well Name: CASEY JONES 16 FED COM Well Number: 703H

Pressure Rating (PSI): 10M Rating Depth: 10613

Equipment: The minimum blowout preventer equipment (BOPE) shown in Exhibit #1 will consist of a single ram, mud cross and double ram-type (10,000 psi WP) preventer and an annular preventer (10,000-psi WP). Both units will be hydraulically operated and the ram-type will be equipped with blind rams on bottom and drill pipe rams on top. All BOPE will be tested in accordance with Onshore Oil and Gas order No. 2.

Requesting Variance? YES

Variance request: Variance is requested to use a co-flex line between the BOP and choke manifold (instead of using a 4" OD steel line). Variance is requested to wave the centralizer requirements for the 7-5/8" FJ casing in the 8-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 8-3/4" hole interval to maximize cement bond and zonal isolation. Variance is also requested to wave any centralizer requirements for the 5-1/2" FJ casing in the 6-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 6-3/4" hole interval to maximize cement bond and zonal isolation.

Testing Procedure: Before drilling out of the surface casing, the ram-type BOP and accessory equipment will be tested to 5000/ 250 psig and the annular preventer to 5000/ 250 psig. The surface casing will be tested to 1500 psi for 30 minutes. Before drilling out of the intermediate casing, the ram-type BOP and accessory equipment will be tested to 5000/ 250 psig and the annular preventer to 5000/ 250 psig. The intermediate casing will be tested to 2000 psi for 30 minutes. Pipe rams will be operationally checked each 24-hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. A hydraulically operated choke will be installed prior to drilling out of the intermediate casing shoe.

Choke Diagram Attachment:

Casey_Jones_16_FC_703H_Co_Flex_Hose_Cert_05-05-2017.PDF Casey_Jones_16_FC_703H_Co_Flex_Hose_Chart_05-05-2017.pdf 10M_Choke_Manifold_07-14-2017.pdf

BOP Diagram Attachment:

10M BOPE 07-14-2017.pdf

Section 3 - Casing

| Casing ID | String Type | Hole Size | Csg Size | Condition | Standard | Tapered String | Top Set MD | Bottom Set MD | Top Set TVD | Bottom Set TVD | Top Set MSL | Bottom Set MSL | Calculated casing length MD | Grade | Weight | Joint Type | Collapse SF | Burst SF | Joint SF Type | Joint SF | Body SF Type | Body SF |
|-----------|------------------|-----------|----------|-----------|----------|----------------|------------|---------------|-------------|----------------|-------------|----------------|--------------------------------|-------------|--------|---------------------------|-------------|----------|---------------|----------|--------------|---------|
| 1 | SURFACE | 14.7 5 | 10.75 | NEW | API | N | 0 | 840 | 0 | 840 | 3034 | 2194 | 840 | J-55 | 40.5 | STC | 1.12 5 | 1.25 | BUOY | 1.6 | BUOY | 1,6 |
| 2 | INTERMED IATE | 9.87 5 | 7.625 | NEW | API | Υ | 0 | 9600 | 0 | 9600 | 3034 | -6566 | 9600 | HCP -110 | 29.7 | LTC | 1,12 5 | 1.25 | BUOY | 1.6 | BUOY | 1.6 |
| 3 | PRODUCTI ON | 6.75 | 5.5 | NEW | API | Y | 0 | 20768 | 0 | 10613 | 3034 | -7579 | 20768 | P- 110 | | OTHER - DWC/C-IS MS | 1,12 5 | 1.25 | BUOY | 1.6 | BUOY | 1.6 |

Well Name: CASEY JONES 16 FED COM

Well Number: 703H

Casing Attachments String Type: SURFACE Casing ID: 1 **Inspection Document: Spec Document: Tapered String Spec:** Casing Design Assumptions and Worksheet(s): Casey_Jones_16_FC_703H_BLM_Plan_05-05-2017.pdf Casing ID: 2 String Type: INTERMEDIATE **Inspection Document: Spec Document: Tapered String Spec:** See_previously_attached_Drill_Plan_05-05-2017.pdf Casing Design Assumptions and Worksheet(s): See previously attached Drill Plan 05-05-2017.pdf Casing ID: 3 String Type: PRODUCTION **Inspection Document: Spec Document: Tapered String Spec:** See_previously_attached_Drill_Plan_05-05-2017.pdf Casing Design Assumptions and Worksheet(s): See_previously_attached_Drill_Plan_05-05-2017.pdf

Section 4 - Cement

Well Name: CASEY JONES 16 FED COM Well Number: 703H

| String Type | Lead/Tail | Stage Tool Depth | Top MD | Bottom MD | Quantity(sx) | Yield | Density | Cu Ft | Excess% | Cement type | Additives |
|--------------|-----------|---------------------|--------|-----------|--------------|-------|---------|-------|---------|-------------|---|
| SURFACE | Lead | | 0 | 840 | 400 | 1.73 | 13.5 | 692 | 25 | Class C | Class C + 4.0% Bentonite + 0.6% CD- 32 + 0.5% CaCl2 + 0.25 lb/sk Cello-Flake (TOC @ Surface) |
| SURFACE | Tail | | 840 | 840 | 200 | 1.34 | 14.8 | 268 | 25 | Class C | Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate |
| INTERMEDIATE | Lead | | 0 | 9600 | 2250 | 1.38 | 14.8 | 3105 | 25 | Class C | Class C + 5% Gypsum + 3% CaCl2 pumped via Bradenhead. (TOC @ surface) |
| INTERMEDIATE | Tail | | 9600 | 9600 | 550 | 1.2 | 14.4 | 660 | 25 | Class H | 50:50 Class H:Poz + 0.25% CPT20A + 0.40% CPT49 + 0.20% CPT35 + 0.80% CPT16A + 0.25% CPT503P pumped conventionally |
| PRODUCTION | Lead | | 9100 | 2076 8 | 850 | 1.26 | 14.1 | 1071 | 25 | Class H | Class H + 0.1% C-20 + 0.05% CSA-1000 + 0.20% C-49 + 0.40% C-17 (TOC @ 9100') |

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: (A) A Kelly cock will be kept in the drill string at all times. (B) A full opening drill pipe-stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times. (C) H2S monitoring and detection equipment will be utilized from surface casing point to TD. **Describe the mud monitoring system utilized:** An electronic pit volume totalizer (PVT) will be utilized on the circulating system to monitor pit volume, flow rate, pump pressure and stroke rate.

Circulating Medium Table

Well Name: CASEY JONES 16 FED COM Well Number: 703H

| Top Depth | Bottom Depth | Mud Type | Min Weight (lbs/gal) | Max Weight (lbs/gal) | Density (lbs/cu ft) | Gel Strength (lbs/100 sqft) | ЬН | Viscosity (CP) | Salinity (ppm) | Filtration (cc) | Additional Characteristics |
|-----------|--------------|--------------------|----------------------|----------------------|---------------------|-----------------------------|----|----------------|----------------|-----------------|----------------------------|
| 840 | 9600 | SALT SATURATED | 8.8 | 10 | | | | | | | |
| 9600 | 2076 8 | OIL-BASED MUD | 10 | 14 | | | | | | | |
| 0 | 840 | WATER-BASED MUD | 8.6 | 8.8 | | | | | | | |

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

Open-hole logs are not planned for this well.

List of open and cased hole logs run in the well:

DS

Coring operation description for the well:

None

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 6346 Anticipated Surface Pressure: 4011.14

Anticipated Bottom Hole Temperature(F): 168

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geoharzards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

Casey_Jones_16_FC_703H_H2S_Plan_Summary_05-05-2017.pdf

Well Name: CASEY JONES 16 FED COM Well Number: 703H

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Casey_Jones_16_FC_703H_Planning_Report_05-05-2017.pdf Casey_Jones_16_FC_703H_Wall_Plot_05-05-2017.pdf

Other proposed operations facets description:

Other proposed operations facets attachment:

Casey_Jones_16_FC_703H_5.5in_20.00_VST_P110EC_DWC_C_IS_MS_05-05-2017.pdf
Casey_Jones_16_FC_703H_5.5in_20.00_VST_P110EC_VAM_SFC_05-05-2017.pdf
Casey_Jones_16_FC_703H_7.625in_29.7_P110EC_VAM_SLIJ_II_05-05-2017.pdf
Casey_Jones_16_FC_703H_7.625in_29.70_P_110_FlushMax_III_05-05-2017.pdf
Casey_Jones_16_FC_703H_Rig_Layout_05-05-2017.pdf
Casey_Jones_16_FC_703H_Wellhead_Cap_Diagram_05-05-2017.pdf
Casey_Jones_16_FC_703H_Wellbore_05-05-2017.pdf
Casey_Jones_16_FC_703_deficiency_response_07-17-2017.pdf

Other Variance attachment:

Manufacturer: Midwest Hose & Specialty

Serial Number: SN#90067

Length: 35'

Size: OD = 8" ID = 4"

Ends: Flanges Size: 4-1/16"

WP Rating: 10,000 psi Anchors required by manfacturer: No

MIDWEST

HOSE AND SPECIALTY INC.

| INTERNAL HYDROSTATIC TEST REPORT | | | | | | | | | |
|--|--|-------------------|--------------------------|----------------|-----------------|--|--|--|--|
| Customer | · | | | P.O. Numb | er: | | | | |
| CACTUS | | | | RIG #123 | | | | | |
| | | | | Asset # N | 110761 | | | | |
| | | HOSE SPECI | ICATIONS | | | | | | |
| Туре: | CHOKE LIN | Ē | | Length: | 35' | | | | |
| I.D. | 4" | INCHES | O.D. | 8" | INCHES | | | | |
| WORKING P | RESSURE | TEST PRESSUR | E | BURST PRES | SURE | | | | |
| 10,000 | PSI | 15,000 | PSi . | | PS i | | | | |
| | COUPLINGS | | | | | | | | |
| Type of E | nd Fitting 4 1/16 10K F | LANGE | | | | | | | |
| Type of C | oupling: SWEDGED | | MANUFACTU MIDWEST HOS | | LTY | | | | |
| | | PROC | EDURE | | | | | | |
| | Hose seembh | pressure tested w | ith water at ambier | nt temperature | | | | | |
| 3 | | TEST PRESSURE | | URST PRESSU | RE: | | | | |
| | 1 | MIN. | | | O PSI | | | | |
| COMMENTS: SN#90067 M10761 Hose is covered with stainless steel armour cover and wraped with fire resistant vermiculite coated fiberglass | | | | | | | | | |
| Date: | insulation rated for 1500 degrees complete with lifting eyes Tested By: 6/6/2011 BOBBY FINK Approved: MENDI JACKSON | | | | | | | | |




Internal Hydrostatic Test Graph

Customer: CACTUS

SALES ORDER# 90067

| <u> Scation</u> | Coupling Method Swage Final O.D. 6.68" Hose Assembly Serial # | Final O.D. 6.68" Hose Assembly Serial # | /9006 |
|-----------------|---|--|------------------------------------|
| Veri | Type of Fitting 4 1/16 10K <u>Die Size</u> 6.62" Hose Serial # | <u>Die Size</u> 6.62" <u>Hose Serial #</u> | |
| cifications | Length 35' 0.D. 8" Burst Pressure Standard Safery Multiplier Applies | O.D. 8" Burst Pressure | Standard Safety Multiplier Applies |
| Hose Specifical | Hose Type C & K L.D. 4" Working Pressure 10000 PSI | L.D. 4" Working Pressure | 10000 PSI |



Test Pressure 15000 PSI

Time Held at Test Pressure 11 1/4 Minutes

Tested By: Bobby Fink

Approved By: Mendi Jackson

* Mendi Jackson

Comments: Hose assembly pressure tested with water at ambient temperature.





Exhibit 1 EOG Resources



1. GEOLOGIC NAME OF SURFACE FORMATION:

Permian

2. ESTIMATED TOPS OF IMPORTANT GEOLOGICAL MARKERS:

| Rustler | 815' |
|-----------------------------------|---------|
| Top of Salt | 1,149' |
| Base of Salt / Top Anhydrite | 3,095' |
| Base Anhydrite | 3,441' |
| Lamar | 3,441' |
| Bell Canyon | 3,470° |
| Cherry Canyon | 4,367' |
| Brushy Canyon | 5,700' |
| Bone Spring Lime | 7,272' |
| 1 st Bone Spring Sand | 8,205' |
| 2 nd Bone Spring Shale | 8,523' |
| 2 nd Bone Spring Sand | 8,801' |
| 3 rd Bone Spring Carb | 9,477' |
| 3 rd Bone Spring Sand | 10,101' |
| Wolfcamp | 10,479° |
| TD | 10,613 |

3. ESTIMATED DEPTHS OF ANTICIPATED FRESH WATER, OIL OR GAS:

| Upper Permian Sands | 0-4001 | Fresh Water |
|-----------------------------------|---------|-------------|
| Cherry Canyon | 4,367' | Oil |
| Brushy Canyon | 5,700' | Oil |
| 1st Bone Spring Sand | 8,205' | Oil |
| 2 nd Bone Spring Shale | 8,523' | Oil |
| 2 nd Bone Spring Sand | 8,801' | Oil |
| 3 rd Bone Spring Carb | 9,477 | Oil |
| 3 rd Bone Spring Sand | 10,101' | Oil |
| Wolfcamp | 10,479' | Oil |
| | | |

No other Formations are expected to give up oil, gas or fresh water in measurable quantities. Surface fresh water sands will be protected by setting 10.75" casing at 840' and circulating cement back to surface.

4. CASING PROGRAM - NEW

| Hole | | Csg | | | | DF _{min} | DF _{min} | DF _{min} |
|--------|-----------------|--------|--------|---------|--------------|-------------------|-------------------|-------------------|
| Size | Interval | OD | Weight | Grade | Conn | Collapse | Burst | Tension |
| 14.75" | 0 – 840' | 10.75" | 40.5# | J55 | STC | 1.125 | 1.25 | 1.60 |
| 9.875" | 0 - 1,000 | 7.625" | 29.7# | HCP- | LTC | 1.125 | 1.25 | 1.60 |
| | | | ļ | 110 | | 1 | | |
| 9.875" | 1,000' – | 7.625" | 29.7# | P-110EC | SLIJ II | 1.125 | 1.25 | 1.60 |
| | 3,000' | | | | | | | |
| 8.75" | 3,000' – 9,600' | 7.625" | 29.7# | HCP- | FlushMax III | 1.125 | 1.25 | 1.60 |
| | | | | 110 | | 1 | | |
| 6.75" | 0' - 9,100' | 5.5" | 20# | P-110EC | DWC/C-IS | 1.125 | 1.25 | 1.60 |
| | | | | | MS |] | | |
| 6.75" | 9,100'-20,768' | 5.5" | 20# | P-110EC | VAM SFC | 1.125 | 1.25 | 1.60 |

Variance is requested to wave the centralizer requirements for the 7-5/8" FJ casing in the 8-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 8-3/4" hole interval to maximize cement bond and zonal isolation.

Variance is also requested to wave any centralizer requirements for the 5-1/2" FJ casing in the 6-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 6-3/4" hole interval to maximize cement bond and zonal isolation.

Cementing Program:

| | No. | Wt. | Yld | Mix | |
|---------|-------|------|---------------------|--------|---|
| Depth | Sacks | ppg | Ft ³ /ft | Water | Slurry Description |
| [| | | | Gal/sk | |
| 10-3/4" | 400 | 13.5 | 1.73 | 9.13 | Class C + 4.0% Bentonite + 0.6% CD- $32 + 0.5\%$ CaCl ₂ + 0.25 |
| 840' | | | | | lb/sk Cello-Flake (TOC @ Surface) |
| | 200 | 14.8 | 1.34 | 6.34 | Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium |
| | | | | | Metasilicate |
| 7-5/8" | 250 | 14.8 | 1.38 | 6.48 | Class C + 5% Gypsum + 3% CaCl2 pumped via Bradenhead |
| 9,600' | | | | | (TOC @ Surface) |
| | 2000 | 14.8 | 1.38 | 6.48 | Class C + 5% Gypsum + 3% CaCl2 pumped via Bradenhead |
| | 550 | 14.4 | 1.20 | 4.81 | 50:50 Class H:Poz + 0.25% CPT20A + 0.40% CPT49 + 0.20% |
| 1 | | | | | CPT35 + 0.80% CPT16A + 0.25% CPT503P pumped |
| | | | | | Conventionally |
| 5-1/2" | 850 | 14.1 | 1.26 | 5.80 | Class H + 0.1% C-20 + 0.05% CSA-1000 + 0.20% C-49 + |
| 20,768 | | | | | 0.40% C-17 (TOC @ 9,100') |

Note: Cement volumes based on bit size plus at least 25% excess in the open hole plus 10% excess in the cased-hole overlap section.

5. MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL:

Variance is requested to use a co-flex line between the BOP and choke manifold (instead of using a 4" OD steel line).

The minimum blowout preventer equipment (BOPE) shown in Exhibit #1 will consist of a single ram, mud cross and double ram-type (10,000 psi WP) preventer and an annular preventer (5000-psi WP). Both units will be hydraulically operated and the ram-type will be equipped with blind rams on bottom and drill pipe rams on top. All BOPE will be tested in accordance with Onshore Oil & Gas order No. 2.

Before drilling out of the surface casing, the ram-type BOP and accessory equipment will be tested to 5000/250 psig and the annular preventer to 3500/250 psig. The surface casing will be tested to 1500 psi for 30 minutes.

Before drilling out of the intermediate casing, the ram-type BOP and accessory equipment will be tested to 5000/250 psig and the annular preventer to 3500/250 psig. The intermediate casing will be tested to 2000 psi for 30 minutes.

Pipe rams will be operationally checked each 24-hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets.

A hydraulically operated choke will be installed prior to drilling out of the intermediate casing shoe.

6. TYPES AND CHARACTERISTICS OF THE PROPOSED MUD SYSTEM:

During this procedure we plan to use a Closed-Loop System and haul contents to the required disposal.

The applicable depths and properties of the drilling fluid systems are as follows.

| Depth | Туре | Weight (ppg) | Viscosity | Water Loss |
|------------------|-------------|--------------|-----------|------------|
| 0 – 840' | Fresh - Gel | 8.6-8.8 | 28-34 | N/c |
| 840' - 9,600' | Brine | 8.8-10.0 | 28-34 | N/c |
| 9,600' - 20,768' | Oil Base | 10.0-14.0 | 58-68 | 3 - 6 |
| Lateral | | | | |

The highest mud weight needed to balance formation is expected to be 11.5 ppg. In order to maintain hole stability, mud weights up to 14.0 ppg may be utilized.

An electronic pit volume totalizer (PVT) will be utilized on the circulating system, to monitor pit volume, flow rate, pump pressure and stroke rate.

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept at the wellsite at all times.

7. AUXILIARY WELL CONTROL AND MONITORING EQUIPMENT:

- (A) A kelly cock will be kept in the drill string at all times.
- (B) A full opening drill pipe-stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times.
- (C) H₂S monitoring and detection equipment will be utilized from surface casing point to TD.

8. LOGGING, TESTING AND CORING PROGRAM:

Open-hole logs are not planned for this well.

GR-CCL Will be run in cased hole during completions phase of operations.

9. ABNORMAL CONDITIONS, PRESSURES, TEMPERATURES AND POTENTIAL HAZARDS:

The estimated bottom-hole temperature (BHT) at TD is 168 degrees F with an estimated maximum bottom-hole pressure (BHP) at TD of 6346 psig (based on 11.5 ppg MW). No hydrogen sulfide or other hazardous gases or fluids have been encountered, reported or are known to exist at this depth in this area. Severe loss circulation is expected from 7,300' to Intermediate casing point.

10. ANTICIPATED STARTING DATE AND DURATION OF OPERATIONS:

The drilling operation should be finished in approximately one month. If the well is productive, an additional 60-90 days will be required for completion and testing before a decision is made to install permanent facilities.

(A) EOG Resources requests the option to contract a Surface Rig to drill, set surface casing, and cement on the subject well. If the timing between rigs is such that EOG Resources would not be able to preset the surface, the Primary Rig will MIRU and drill the well in its entirety per the APD.

11. WELLHEAD:

A multi-bowl wellhead system will be utilized.

After running the 10-3/4" surface casing, a 13-5/8" BOP/BOPE system with a minimum working pressure of 5000 psi will be installed on the wellhead system and will be pressure tested to 250 psi low followed by a 5000 psi pressure test. This pressure test will be repeated at least every 30 days, as per Onshore Order No. 2

The minimum working pressure of the BOP and related BOPE required for drilling below the surface casing shoe shall be 5000 psi.

The multi-bowl wellhead will be installed by vendor's representative(s). A copy of the installation instructions for the Stream Flo FBD100 Multi-Bowl WH system has been sent to the NM BLM office in Carlsbad, NM.

The wellhead will be installed by a third party welder while being monitored by WH vendor's representative.

All BOP equipment will be tested utilizing a conventional test plug. Not a cup or J-packer type.

A solid steel body pack-off will be utilized after running and cementing the intermediate casing. After installation the pack-off and lower flange will be pressure tested to 5000 psi.

Both the surface and intermediate casing strings will be tested as per Onshore Order No. 2 to at least 0.22 psi/ft or 1500 psi, whichever is greater.

Hydrogen Sulfide Plan Summary

- A. All personnel shall receive proper H2S training in accordance with Onshore Order III.C.3.a.
- B. Briefing Area: two perpendicular areas will be designated by signs and readily accessible.
- C. Required Emergency Equipment:
 - Well control equipment
 - a. Flare line 150' from wellhead to be ignited by flare gun.
 - b. Choke manifold with a remotely operated choke.
 - c. Mud/gas separator
 - Protective equipment for essential personnel.

Breathing apparatus:

- a. Rescue Packs (SCBA) 1 unit shall be placed at each breathing area, 2 shall be stored in the safety trailer.
- b. Work/Escape packs —4 packs shall be stored on the rig floor th sufficient air hose not to restrict work activity.
- c. Emergency Escape Packs —4 packs shall be stored in the doghouse for emergency evacuation.

Auxiliary Rescue Equipment:

- a. Stretcher
- b. Two OSHA full body harness
- c. 100 ft 5/8 inch OSHA approved rope
- d. 1-20# class ABC fire extinguisher
- H2S detection and monitoring equipment:

The stationary detector with three sensors will be placed in the upper dog house if equipped, set to visually alarm @ 10 ppm and audible @ 14 ppm. Calibrate a minimum of every 30 days or as needed. The sensors will be placed in the following places: Rig floor / Bell nipple / End of flow line or where well bore fluid is being discharged.

(Gas sample tubes will be stored in the safety trailer)

- Visual warning systems.
 - a. One color code condition sign will be placed at the entrance to the site reflecting the possible conditions at the site.
 - b. A colored condition flag will be on display, reflecting the current condition at the site at the time.
 - c. Two wind socks will be placed in strategic locations, visible from all angles.

■ Mud program:

The mud program has been designed to minimize the volume of H2S circulated to surface. The operator will have the necessary mud products to minimize hazards while drilling in H2S bearing zones.

■ Metallurgy:

All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H2S service.

■ Communication:

Communication will be via cell phones and land lines where available.

Emergency Assistance Telephone List

| PUBLIC SAFETY: | 911 or |
|--|-----------------------|
| Eddy County Sheriff's Department | (575) 887-7551 |
| Kent Waller | |
| Fire Department: | |
| Carlsbad | (575) 885-3125 |
| Artesia | (575) 746-5050 |
| Hospitals: | |
| Carlsbad | (575) 887-4121 |
| Artesia | (575) 748-3333 |
| Hobbs | (575) 392-1979 |
| Dept. of Public Safety/Carlsbad | (575) 748-9718 |
| Highway Department | (575) 885-3281 |
| New Mexico Oil Conservation | (575) 476-3440 |
| U.S. Dept. of Labor | (575) 887-1174 |
| EOG Resources, Inc. | |
| EOG / Midland | Office (432) 686-3600 |
| Company Duilling Consultants | |
| Company Drilling Consultants: Jett Dueitt | Cell (432) 230-4840 |
| Blake Burney | Cell (432) 230-4840 |
| blake burney | |
| Drilling Engineer | |
| Steve Munsell | Office (432) 686-3609 |
| Stove Municipality | Cell (432) 894-1256 |
| Drilling Manager | Cen (432) 054 1230 |
| Floyd Hernadez | Office (432) 686-3716 |
| 1 loyd Helliadez | Cell (817) 682-4569 |
| Drilling Superintendent | Cen (617) 602 4305 |
| Jason Fitzgerald | Office (432) 848-9029 |
| Jason I itzgerald | Cell (318) 347-3916 |
| H&P Drilling | Cen (318) 347-3710 |
| H&P Drilling | Office (432) 563-5757 |
| H&P 415 Drilling Rig | Rig (432) 230-4840 |
| 11&F 413 Dinning Rig | Rig (432) 230-4640 |
| Tool Pusher: | |
| Johnathan Craig | Cell (817) 760-6374 |
| Brad Garrett | |
| Safety | |
| Brian Chandler (HSE Manager) | Office (432) 686-3695 |
| - | Cell (817) 239-0251 |



EOG Resources - Midland

Eddy County, NM (NAD 83 NME) Casey Jones 16 Fed Com #703H

OH

Plan: Plan #0.1

Standard Planning Report

25 April, 2017

eog resources

EOG Resources, Inc.

Planning Report

TVD Reference:

MD Reference:

Database: Company: EDM 5000.1 Single User Db

Project:

EOG Resources - Midland

Site:

Eddy County, NM (NAD 83 NME) Casey Jones 16 Fed Com

Well:

#703H

Wellbore:

OH

Plan #0.1 Design:

Local Co-ordinate Reference:

KB = 25' @ 3059.00usft KB = 25' @ 3059.00usft

North Reference:

Survey Calculation Method:

Minimum Curvature

Project

Eddy County, NM (NAD 83 NME)

Map System: Geo Datum:

US State Plane 1983 North American Datum 1983 System Datum:

Mean Sea Level

Well #703H

Grid

Map Zone:

New Mexico Eastern Zone

Site

Casey Jones 16 Fed Com

Site Position:

Мар

Northing:

377,123.00 usft

Latitude:

32.03602732

From:

Easting:

677,714.00 usft

Longitude:

-103.89322193

Position Uncertainty:

0.00 usft

Slot Radius:

13-3/16 "

Grid Convergence:

0.23°

Well

#703H +N/-S

+E/-W

ОН

Well Position

-10.00 usft

Northing:

377,113.00 usft

Latitude:

32.03598305

1,490.00 usft 0.00 usft Easting: Wellhead Elevation:

4/25/2017

679,204.00 usft 0.00 usft

7.10

Longitude: Ground Level: -103.88841369 3,034.00 usft

Position Uncertainty

Magnetics

Wellbore

Model Name

IGRF2015

Sample Date

Declination (°)

Dip Angle (°)

Field Strength

59.84

(nT) 47,810

Design

Plan #0.1

Audit Notes:

Version:

Phase:

PLAN

Tie On Depth:

0.00

Vertical Section:

Depth From (TVD) (usft)

0.00

+N/-S (usft)

0.00

+E/-W (usft)

0.00

Direction (°)

357.89

Plan Sections

| Measured Depth (usft) | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) | TFO (°) | Target |
|-----------------------------|--------------------|----------------|-----------------------------|-----------------|-----------------|-------------------------------|------------------------------|-----------------------------|------------|-------------------|
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | |
| 4,000.00 | 0.00 | 0.00 | 4,000.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | |
| 4,364.83 | 3.65 | 236.84 | 4,364.58 | -6.35 | -9.72 | 1.00 | 1.00 | 0.00 | 236.84 | |
| 10,131.63 | 3.65 | 236.84 | 10,119.70 | -207.05 | -316.92 | 0.00 | 0.00 | 0.00 | 0.00 | |
| 10,898.18 | 90.00 | 359.83 | 10,613.00 | 270.04 | -344.72 | 12.00 | 11.27 | 16.04 | 122.94 | |
| 20,768.18 | 90.00 | 359.83 | 10,613.00 | 10,140.00 | -374.00 | 0.00 | 0.00 | 0.00 | 0.00 PB | HL (C J 16 Fed Co |

Seog resources

EOG Resources, Inc.

Planning Report

Database: Company: EDM 5000.1 Single User Db EOG Resources - Midland Eddy County, NM (NAD 83 NME)

Project: Site:

Casey Jones 16 Fed Com

Well: Wellbore: Design: #703H OH Plan #0.1 Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

North Reference: Survey Calculation Method: Well #703H

KB = 25' @ 3059.00usft KB = 25' @ 3059.00usft

Grid

Minimum Curvature

Planned Survey

| Measured Depth (usft) | Inclination (°) | Azimuth (°) | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |
|-----------------------------|--------------------|------------------|-----------------------------|------------------|-----------------|-------------------------------|-------------------------------|------------------------------|-----------------------------|
| 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 100.00 | 0.00 | 0.00 | 100.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 200.00 | 0.00 | 0.00 | 200.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 300.00 | 0.00 | 0.00 | 300.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 400.00 | 0.00 | 0.00 | 400.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 500.00 | 0.00 | 0.00 | 500.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 600.00 | 0.00 | 0.00 | 600.00 | 0.00 | 0.00 | 0.00 0.00 | 0.00 | 0.00 | 0.00 |
| 700.00 | 0.00 | 0.00 | 700.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 800.00 | 0.00 | 0.00 | 800.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 900.00 | 0.00 | 0.00 | 900.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| | • | | | | | | | | |
| 1,000.00 | 0.00 | 0.00 | 1,000.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 1,100.00 1,200.00 | 0.00 0.00 | 0.00 0.00 | 1,100.00 1,200.00 | 0.00 0.00 | 0.00 0.00 | 0.00 0.00 | 0.00 0.00 | 0.00 | 0.00 0.00 |
| 1,300.00 | 0.00 | 0.00 | 1,200.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 0.00 | 0.00 |
| 1,400.00 | 0.00 | 0.00 | 1,400.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| | | | | | | | | | |
| 1,500.00 | 0.00 | 0.00 | 1,500.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 1,600.00 | 0.00 | 0.00 | 1,600.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 1,700.00 | 0.00 | 0.00 | 1,700.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 1,800.00 | 0.00 0.00 | 00.0 00.0 | 1,800.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 1,900.00 | | | 1,900.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0,00 | 0.00 |
| 2,000.00 | 0.00 | 0.00 | 2,000.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 2,100.00 | 0.00 | 0.00 | 2,100.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 2,200.00 | 0.00 | 0.00 | 2,200.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0,00 | 0.00 |
| 2,300.00 | 0.00 | 0.00 | 2,300.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 2,400.00 | 0.00 | 0.00 | 2,400.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 2,500.00 | 0.00 | 0.00 | 2,500.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 2,600.00 | 0.00 | 00,0 | 2,600.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 2,700.00 | 0.00 | 0.00 | 2,700.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 2,800.00 | 0.00 | 0.00 | 2,800.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 2,900.00 | 0.00 | 0.00 | 2,900.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,000.00 | 0.00 | 0.00 | 3,000.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,100.00 | 0.00 | 0.00 | 3,100.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,200.00 | 0.00 | 0.00 | 3,200.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,300.00 | 0.00 | 0.00 | 3,300.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,400.00 | 0.00 | 0.00 | 3,400.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,500.00 | 0.00 | 0.00 | 3,500.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,600.00 | 0.00 | 0.00 | 3,600.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,700.00 | 0.00 | 0.00 | 3,700.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,800.00 | 0.00 | 0.00 | 3,800.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 3,900.00 | 0.00 | 0.00 | 3,900.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 4,000.00 | 0.00 | 0.00 | 4,000.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| 4,100.00 | 1.00 | 236.84 | 4,100.00 | -0.48 | -0.73 | -0.45 | 1.00 | 1.00 | 0.00 |
| 4,200.00 | 2.00 | 236.84 | 4,199.96 | -1.91 | -2.92 | -1.80 | 1.00 | 1.00 | 0.00 |
| 4,300.00 | 3.00 | 236.84 | 4,299.86 | -4 .29 | -6.57 | -4.05 | 1.00 | 1.00 | 0.00 |
| 4,364.83 | 3.65 | 236.84 | 4,364.58 | -6.35 | -9.72 | -5.99 | 1.00 | 1.00 | 0.00 |
| 4,400.00 | 3.65 | 236.84 | 4,399.68 | -7.57 | -11.59 | -7.14 | 0.00 | 0.00 | 0.00 |
| 4,500.00 | 3.65 | 236.84 | 4,499.48 | -11.06 | -16.92 | -10.42 | 0.00 | 0.00 | 0.00 |
| 4,600.00 | 3.65 | 236.84 | 4,599.28 | -14.54 | -22.25 | -10.42 | 0.00 | 0.00 | 0.00 |
| 4,700.00 | 3.65 | 236.84 | 4,699,07 | -18.02 | -27.58 | -16.99 | 0.00 | 0.00 | 0.00 |
| 4,800.00 | 3.65 | 236.84 | 4,798.87 | -21.50 | -32.90 | -20.27 | 0.00 | 0.00 | 0.00 |
| | | | | | | | | | |
| 4,900.00 | 3.65 3.65 | 236.84 236.84 | 4,898,67 | -24,98 29,46 | -38.23 | -23.55 | 0.00 | 0.00 | 0.00 |
| 5,000.00 | | 236.84 236.84 | 4,998.47 | -28.46 | -43,56 | -26.83 20.41 | 0.00 | 0.00 | 0.00 |
| 5,100.00 5,200.00 | 3.65 3.65 | 236.84 236.84 | 5,098.26 5,198.06 | -31.94 -35.42 | -48.88 54.21 | -30.11 | 0.00 | 0.00 | 0.00 |
| 3,200,00 | . ა.სა | 2,00.04 | J, 130.00 | -30.42 | -54.21 | -33.40 | 0.00 | 0.00 | 0.00 |

eog resources

EOG Resources, Inc.

Planning Report

Database: Company: EDM 5000.1 Single User Db EOG Resources - Midland Eddy County, NM (NAD 83 NME)

Project: Site:

Casey Jones 16 Fed Com

Well: Wellbore: #703H OH

Wellbore Design:

Plan #0.1

Local Co-ordinate Reference:

TVD Reference:

North Reference:

Survey Calculation Method:

Well #703H

KB = 25' @ 3059.00usft KB = 25' @ 3059.00usft

Grid

Minimum Curvature

Planned Survey

| Measured | | | Vertical | | | Vertical | Dogleg | Build | Turn |
|-----------|-------------|---------|-----------|----------------|---------|--------------------|-------------|-------------|-------------|
| Depth | Inclination | Azimuth | Depth | +N/-S | +E/-W | Section | Rate | Rate | Rate |
| (usft) | (°) | (°) | (usft) | (usft) | (usft) | (usft) | (°/100usft) | (°/100usft) | (°/100usft) |
| 5,300.00 | 3,65 | 236.84 | 5,297.86 | -38.90 | -59.54 | -36.68 | 0.00 | 0.00 | 0.00 |
| 5,400.00 | 3.65 | 236.84 | 5,397.66 | -42.38 | -64.86 | -39.96 | 0.00 | 0.00 | 0.00 |
| 5,500.00 | 3.65 | 236.84 | 5,497.45 | - 45.86 | -70.19 | -43.24 | 0.00 | 0.00 | 0.00 |
| 5,600.00 | 3.65 | 236.84 | 5,597.25 | -49.34 | -75.52 | -46.52 | 0.00 | 0.00 | 0.00 |
| 5,700.00 | 3.65 | 236.84 | 5,697.05 | -52.82 | -80.84 | -4 9.80 | 0.00 | 0.00 | 0.00 |
| 5,800.00 | 3.65 | 236.84 | 5,796.85 | -5 6.30 | -86.17 | - 53.09 | 0.00 | 0.00 | 0.00 |
| 5,900.00 | 3.65 | 236.84 | 5,896.64 | -59.78 | -91.50 | -56.37 | 0.00 | 0.00 | 0.00 |
| 6,000.00 | 3.65 | 236.84 | 5,996.44 | -63.26 | -96.83 | -59.65 | 0.00 | 0.00 | 0.00 |
| 6,100.00 | 3.65 | 236.84 | 6,096.24 | -66.74 | -102.15 | -62,93 | 0.00 | 0.00 | 0.00 |
| 6,200.00 | 3.65 | 236.84 | 6,196.03 | -70.22 | -107.48 | -66.21 | 0.00 | 0.00 | 0.00 |
| 6,300.00 | 3.65 | 236.84 | 6,295.83 | -73.70 | -112.81 | -69.49 | 0.00 | 0.00 | 0.00 |
| 6,400.00 | 3.65 | 236.84 | 6,395.63 | -77.18 | -118.13 | -72.77 | 0.00 | 0.00 | 0.00 |
| 6,500.00 | 3.65 | 236.84 | 6,495.43 | -80.66 | -123.46 | -76.06 | 0.00 | 0.00 | 0.00 |
| 6,600.00 | 3.65 | 236,84 | 6,595.22 | -84.14 | -128,79 | -79.34 | 0.00 | 0.00 | 0.00 |
| 6,700.00 | 3.65 | 236.84 | 6,695.02 | -87.62 | -134,11 | -82.62 | 0.00 | 0.00 | 0.00 |
| 6,800.00 | 3.65 | 236.84 | 6,794.82 | -91.10 | -139,44 | -85.90 | 0.00 | 0.00 | 0.00 |
| 6,900.00 | 3.65 | 236.84 | 6,894.62 | <i>-</i> 94.58 | -144.77 | - 89.18 | 0.00 | 0.00 | 0.00 |
| 7,000.00 | 3.65 | 236.84 | 6,994.41 | -98.06 | -150.10 | -92.46 | 0.00 | 0.00 | 0.00 |
| 7,100.00 | 3.65 | 236.84 | 7,094.21 | -101.54 | -155.42 | -95.75 | 0.00 | 0.00 | 0.00 |
| 7,200.00 | 3.65 | 236.84 | 7,194.01 | -105.02 | -160.75 | -99.03 | 0.00 | 0.00 | 0.00 |
| 7,300.00 | 3.65 | 236.84 | 7,293.81 | -108.50 | -166.08 | -102.31 | 0.00 | 0.00 | 0.00 |
| 7,400.00 | 3.65 | 236.84 | 7,393.60 | -111.98 | -171.40 | -105.59 | 0.00 | 0.00 | 0.00 |
| 7,500.00 | 3.65 | 236.84 | 7,493.40 | -115.47 | -176.73 | -108.87 | 0.00 | 0.00 | 0.00 |
| 7,600.00 | 3,65 | 236.84 | 7,593.20 | -118.95 | -182.06 | -112.15 | 0.00 | 0.00 | 0.00 |
| 7,700.00 | 3,65 | 236.84 | 7,692.99 | -122.43 | -187.38 | -115.44 | 0.00 | 0.00 | 0.00 |
| 7,800.00 | 3.65 | 236.84 | 7,792.79 | -125.91 | -192.71 | -118.72 | 0.00 | 0.00 | 0.00 |
| 7,900.00 | 3,65 | 236.84 | 7,892.59 | -129.39 | -198.04 | -122.00 | 0.00 | 0.00 | 0.00 |
| 8,000.00 | 3.65 | 236.84 | 7,992.39 | -132.87 | -203.37 | -125.28 | 0.00 | 0.00 | 0.00 |
| 8,100.00 | 3.65 | 236.84 | 8,092.18 | -136.35 | -208.69 | -128.56 | 0.00 | 0.00 | 0.00 |
| 8,200.00 | 3.65 | 236.84 | 8,191.98 | -139.83 | -214.02 | -131.84 | 0.00 | 0.00 | 0.00 |
| 8,300.00 | 3.65 | 236.84 | 8,291.78 | -143.31 | -219.35 | -135.13 | 0.00 | 0.00 | 0.00 |
| 8,400.00 | 3.65 | 236.84 | 8,391.58 | -146.79 | -224.67 | -138.41 | 0.00 | 0.00 | 0.00 |
| 8,500.00 | 3.65 | 236.84 | 8,491.37 | -150.27 | -230.00 | -141.69 | 0.00 | 0.00 | 0.00 |
| 8,600.00 | 3.65 | 236.84 | 8,591.17 | -153.75 | -235.33 | -144.97 | 0.00 | 0.00 | 0.00 |
| 8,700.00 | 3.65 | 236.84 | 8,690.97 | -157.23 | -240.65 | -148.25 | 0.00 | 0.00 | 0.00 |
| 8,800.00 | 3.65 | 236,84 | 8,790.77 | -160.71 | -245,98 | -151.53 | 0.00 | 0.00 | 0.00 |
| 8,900.00 | 3.65 | 236,84 | 8,890.56 | -164.19 | -251.31 | -154.82 | 0,00 | 0.00 | 0.00 |
| 9,000.00 | 3.65 | 236.84 | 8,990.36 | -167.67 | -256.64 | -158.10 | 0.00 | 0.00 | 0.00 |
| 9,100.00 | 3.65 | 236.84 | 9,090.16 | -171.15 | -261.96 | -161.38 | 0.00 | 0.00 | 0.00 |
| 9,200.00 | 3.65 | 236.84 | 9,189.96 | -174.63 | -267.29 | -164.66 | 0.00 | 0.00 | 0.00 |
| 9,300.00 | 3.65 | 236.84 | 9,289.75 | -178.11 | -272.62 | -167.94 | 0.00 | 0.00 | 0.00 |
| 9,400.00 | 3.65 | 236.84 | 9,389.55 | -181.59 | -277.94 | -171.22 | 0.00 | 0.00 | 0.00 |
| 9,500.00 | 3.65 | 236.84 | 9,489.35 | -185.07 | -283.27 | -174.50 | 0.00 | 0.00 | 0.00 |
| 9,600.00 | 3.65 | 236.84 | 9,589.14 | -188.55 | -288.60 | -177.79 | 0.00 | 0.00 | 0.00 |
| 9,700.00 | 3.65 | 236.84 | 9,688.94 | -192.03 | -293.92 | -181.07 | 0.00 | 0.00 | 0.00 |
| 9,800.00 | 3.65 | 236.84 | 9,788.74 | -195.51 | -299.25 | -184.35 | 0.00 | 0.00 | 0.00 |
| 9,900.00 | 3.65 | 236.84 | 9,888.54 | -198.99 | -304,58 | -187.63 | 0.00 | 0.00 | 0.00 |
| 10,000.00 | 3.65 | 236.84 | 9,988.33 | -202.47 | -309.91 | -190.91 | 0.00 | 0.00 | 0.00 |
| 10,100.00 | 3.65 | 236.84 | 10,088.13 | -205.95 | -315.23 | -194,19 | 0.00 | 0.00 | 0.00 |
| 10,131,63 | 3.65 | 236.84 | 10,119.70 | -207.05 | -316.92 | -195.23 | 0.00 | 0.00 | 0.00 |
| 10,150.00 | 3.07 | 273.92 | 10,138.04 | -207.34 | -317.90 | -195.48 | 12.00 | -3.15 | 201.86 |
| 10,175.00 | 4.44 | 316.31 | 10,162.99 | -206.59 | -319.23 | -194.69 | 12.00 | 5.49 | 169.56 |
| 10,200.00 | 6.93 | 333.72 | 10,187.86 | -204.54 | -320.57 | -192.59 | 12.00 | 9.95 | 69.64 |
| 10,225.00 | 9.71 | 341.62 | 10,212.60 | -201.19 | -321.90 | -189.19 | 12.00 | 11.12 | 31.58 |



EOG Resources, Inc.

Planning Report

Database: EDM 5000.1 Single User Db EOG Resources - Midland Company: Eddy County, NM (NAD 83 NME) Project:

Casey Jones 16 Fed Com

Well: #703H Wellbore: ОН Plan #0.1

Design:

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well #703H

KB = 25' @ 3059,00usft KB = 25' @ 3059,00usft

Grid

Minimum Curvature

Planned Survey

Site:

| 10,275.00 12.59 345.98 10,237.13 1-196.54 3-23.23 148.50 12.00 11.50 17.44 10,275.00 15.22 345.73 12.00 11.70 10.99 10.300.00 18.47 350.61 10,285.29 1-183.43 3-25.84 1-717.30 12.00 11.80 7.56 10.300.00 18.47 350.61 10,285.29 1-183.43 3-25.84 1-717.30 12.00 11.80 7.56 10.300.00 24.40 353.08 10,033.80 1-705.05 3-27.28 1-62.53 12.00 11.80 7.56 10.350.00 24.40 353.08 10,033.80 1-705.05 3-27.28 1-62.53 12.00 11.80 7.56 10.350.00 24.40 353.08 10,033.80 1-705.05 3-27.28 1-62.53 12.00 11.90 3.37 10.400.00 30.35 354.59 10,076.18 1-142.50 1-309.80 1-42.50 12.00 11.91 3.37 10.400.00 30.35 354.59 10,076.18 1-142.50 1-309.80 1-42.50 12.00 11.91 1.91 3.37 10.400.00 30.35 355.66 10,037.80 19.80 1-300.80 1-10.27 12.00 11.93 2.76 10.450.00 38.32 355.66 10,037.80 19.80 1-300.80 1-10.27 12.00 11.94 1.34 2.31 10.450.00 38.32 355.66 10,037.80 19.80 1-300.80 1-10.27 12.00 11.95 1.30 1.00 10.350.00 42.31 356.80 10,456.80 1-83.53 1.30 1-10.27 12.00 11.95 1.50 10.350.00 45.30 356.80 10,476.84 1-63.28 1.350.00 1-71.12 12.00 11.95 1.50 10.350.00 45.30 356.80 10,476.84 1-63.28 1.350.00 1-338.20 1-350.00 11.97 1.10 10.600.00 51.28 357.37 10,476.80 1-63.28 1.350.00 1-338.20 1-16.50 11.97 1.10 10.600.00 51.28 357.37 10.507.80 1-200 13.38 1.00 11.97 1.10 10.600.00 51.28 357.37 10.507.80 1-200 13.38 10.52 1.65 11.00 11.97 1.10 10.600.00 57.27 356.80 10.523.01 1-911 1.398.07 1.399 12.00 11.97 1.10 10.600.00 57.27 356.80 10.523.01 1-911 1.398.07 1.399 12.00 11.97 1.01 10.600.00 57.27 358.88 10.505.03 32.00 338.20 1.46.51 12.00 11.99 1.00 11.90 1.00 11.90 1.00 11.90 1.00 11.90 1.00 11.90 1.00 11.90 1.00 11.90 1.00 11.90 1.00 11.90 1.00 11.90 1.00 11.90 1.00 1.0 | Measured Depth (usft) | Inclination (°) | Azimuth | Vertical Depth (usft) | +N/-S (usft) | +E/-W (usft) | Vertical Section (usft) | Dogleg Rate (°/100usft) | Build Rate (°/100usft) | Turn Rate (°/100usft) |
|--|-----------------------------|--------------------|---------|-----------------------------|-----------------|-----------------|-------------------------------|-------------------------------|------------------------------|-----------------------------|
| 10.375 0.0 | 10.250 00 | 12.59 | 345.98 | 10.237.13 | -196 54 | -323 23 | -184 50 | 12 00 | 11.52 | 17 44 |
| 10.330.00 | · | | | | | | | | | |
| 10,325,00 | | | | | | | | | | |
| 10/350 00 | | | | | | | | | | |
| 10,375.00 | · | | | | | | | | | |
| 10,400.00 30,36 344.59 10,376.18 -142.50 -330.83 -130.21 12.00 11.93 2.76 | | | | | | | | | | |
| 10.425.00 | | | | | | | | | | |
| 10.450.00 36.33 355.66 10.417.93 -115.13 33.14 -102.77 12.00 11.95 1.97 10.475.00 39.2 356.09 10.437.68 -99.84 -334.24 -874.5 12.00 -11.95 1.77 10.500.00 42.31 356.68 10.456.60 -83.53 -335.30 -71.12 12.00 11.96 1.50 10.525.00 45.30 356.86 10.456.60 -83.53 -336.32 -53.82 12.00 11.96 1.50 10.525.00 45.30 356.86 10.476.64 -66.26 -337.29 -35.60 12.00 11.97 1.21 10.550.00 48.29 357.10 10.491.75 -48.06 -337.29 -35.60 12.00 11.97 1.01 10.500.00 51.28 357.37 10.507.89 -29.00 -338.21 -16.51 12.00 11.97 1.01 10.600.00 54.28 357.63 10.537.07 11.54 339.07 3.39 12.00 11.97 1.01 10.650.00 57.27 357.86 10.537.07 11.54 339.07 3.39 12.00 11.97 1.01 10.650.00 60.27 358.08 10.537.07 11.54 339.07 3.39 12.00 11.97 3.04 10.650.00 60.27 358.08 10.557.07 11.54 339.07 3.09 12.00 11.97 3.09 10.650.00 60.27 358.08 10.557.07 11.54 339.07 3.09 12.00 11.97 3.09 10.650.00 60.27 358.08 10.557.07 11.54 339.07 3.09 10.00 11.97 3.09 10.650.00 60.27 358.08 10.557.07 11.54 339.07 3.09 10.750.00 66.25 358.67 10.581.98 10.672.52 77.52 -341.98 90.07 12.00 11.98 0.83 10.700.00 66.25 358.67 10.581.98 10.054 342.55 113.20 12.00 11.98 0.75 10.750.00 75.24 359.00 10.597.22 114.22 -343.06 113.68 012.00 11.98 0.75 10.750.00 75.24 359.00 10.597.22 114.22 -343.06 113.68 012.00 11.98 0.75 10.800.00 78.24 359.19 10.500.96 172.56 -343.89 16.512 12.00 11.98 0.75 10.800.00 78.24 359.19 10.500.96 172.56 -343.89 16.512 12.00 11.98 0.66 10.850.00 84.23 359.35 10.610.00 270.04 344.72 225.57 12.00 11.98 0.66 10.850.00 84.23 359.35 10.610.00 270.04 344.72 225.57 12.00 11.98 0.66 10.850.00 89.00 359.83 10.613.00 270.04 344.72 225.57 12.00 11.98 0.66 10.850.00 90.00 359.83 10.613.00 771.86 346.20 288.40 12.00 0.00 0.00 0.00 11.000 0.00 359.83 10.613.00 771.86 346.20 288.40 0.00 0.00 0.00 0.00 11.000 0.00 359.83 10.613.00 771.86 346.20 784.10 0.00 0.00 0.00 0.00 11.000 0.00 359.83 10.613.00 771.86 346.20 784.10 0.00 0.00 0.00 0.00 11.000 0.00 359.83 10.613.00 771.86 346.20 784.10 0.00 0.00 0.00 0.00 0.00 12.000 0.00 359.83 10.613.00 771.86 346.20 784.10 0.00 0.00 0.00 0.00 | 10,400.00 | 30.36 | 354.59 | 10,376.18 | -142.50 | -330.83 | -130.21 | 12.00 | 11.93 | 2.76 |
| 10,675.00 | | | | | | | | 12.00 | 11.94 | 2.31 |
| 10,550,000 | | | | • | | -333.14 | -102.77 | 12.00 | 11.95 | 1.97 |
| 10,525,00 | | | | | | | | | 11.95 | 1.71 |
| 10.550.00 | 10,500.00 | | 356.46 | 10,456.60 | - 83.53 | -335.30 | <i>-</i> 71.12 | 12.00 | 11.96 | 1.50 |
| 10,757.00 | 10,525.00 | 45.30 | 356.80 | 10,474.64 | - 66.26 | -336.32 | -53.82 | 12.00 | 11.96 | 1.34 |
| 10,757.00 | 10,550,00 | 48.29 | 357.10 | 10,491,75 | -48.06 | -337.29 | -35.60 | 12.00 | 11.97 | 1.21 |
| 10,600,00 | | | | | | | | | | |
| 10,625.00 | | | | | | | | | | |
| 10,650,00 60,27 358,08 10,550,03 32,90 -340,64 45,44 12,00 11,98 0,88 10,675,00 63,26 358,29 10,561,86 54,91 -341,34 67,46 12,00 11,98 0,83 10,700,00 66,25 358,48 10,572,52 77,52 341,98 90,07 12,00 11,98 0,78 10,750,00 72,25 358,67 10,581,98 100,64 -342,55 113,20 12,00 11,98 0,75 10,750,00 72,25 358,68 10,580,02 116,24 -343,06 136,80 12,00 11,98 0,70 11,080,00 75,24 359,02 10,597,22 148,23 -343,51 160,79 12,00 11,98 0,70 11,080,00 76,24 359,02 10,597,22 148,23 -343,51 160,79 12,00 11,98 0,70 11,080,00 78,24 359,02 10,597,22 148,23 -343,51 160,79 12,00 11,98 0,66 10,825,00 81,23 359,36 10,607,41 197,15 344,20 209,71 12,00 11,98 0,66 10,850,00 81,23 359,36 10,607,41 197,15 344,20 209,71 12,00 11,98 0,66 10,850,00 81,23 359,52 10,610,58 221,95 -344,44 234,49 12,00 11,98 0,66 10,850,00 81,23 359,52 10,610,58 221,95 -344,44 224,49 12,00 11,98 0,66 10,850,00 81,23 359,53 10,613,00 270,04 -344,72 282,57 12,00 11,98 0,66 10,850,00 87,22 359,68 10,613,00 270,04 -344,72 282,57 12,00 11,98 0,64 10,900,00 359,83 10,613,00 270,04 -344,72 282,57 12,00 11,98 0,64 10,900,00 90,00 359,83 10,613,00 271,87 345,72 282,57 12,00 11,98 0,64 11,000,00 90,00 359,83 10,613,00 271,87 345,72 284,39 0,00 0,00 0,00 11,200,00 90,00 359,83 10,613,00 371,87 345,52 384,33 0,00 0,00 0,00 11,200,00 90,00 359,83 10,613,00 371,87 345,52 384,33 0,00 0,00 0,00 0,00 11,200,00 90,00 359,83 10,613,00 371,87 345,91 884,15 0,00 0,00 0,00 11,200,00 90,00 359,83 10,613,00 671,87 345,91 884,15 0,00 0,00 0,00 0,00 11,300,00 90,00 359,83 10,613,00 671,87 345,91 884,15 0,00 0,00 0,00 0,00 11,300,00 90,00 359,83 10,613,00 671,87 345,91 884,15 0,00 0,00 0,00 0,00 11,200,00 90,00 359,83 10,613,00 671,87 345,91 884,15 0,00 0,00 0,00 0,00 11,200,00 90,00 359,83 10,613,00 671,87 345,91 884,17 0,00 0,00 0,00 0,00 11,200,00 90,00 359,83 10,613,00 671,87 345,91 884,17 0,00 0,00 0,00 0,00 11,200,00 90,00 359,83 10,613,00 17,86 346,20 983,99 0,00 0,00 0,00 0,00 12,200,00 90,00 359,83 10,613,00 17,86 346,20 983,99 0,00 0,00 0,00 0,00 12,200,00 90,00 359,83 10,613,00 17,871 | | | | | | | | | | |
| 10,700.00 | | | | | | | | | | |
| 10,700.00 | 10 675 00 | 62.26 | 358 30 | 10 561 96 | 64.01 | 241 24 | 67.46 | 12.00 | 11 00 | 0.02 |
| 10,725,00 | | | | | | | | | | |
| 10,750,00 72,25 358,85 10,590,22 124,24 -343,06 136,80 12,00 11,98 0,72 10,775,00 75,24 359,02 10,597,22 148,23 -343,51 160,79 12,00 11,98 0,70 10,800,00 76,24 359,36 10,807,41 197,15 -344,20 209,71 12,00 11,98 0,66 10,850,00 84,23 359,52 10,610,58 221,95 -344,44 234,49 12,00 11,98 0,66 10,875,00 87,22 359,68 10,612,44 248,88 -344,62 259,41 12,00 11,98 0,64 10,898,18 90,00 359,83 10,613,00 270,04 -344,72 282,57 12,00 11,98 0,64 10,900,00 90,00 359,83 10,613,00 271,87 -344,72 284,39 0,00 0,00 0,00 11,000,00 90,00 359,83 10,613,00 371,87 -345,91 864,12 0,00 0, | | | | | | | | | | |
| 10,775.00 | | | | | | | | | | |
| 10,800.00 | | | | | | | | | | |
| 10,825,00 81,23 359,36 10,807,41 197,15 -344,20 209,71 12,00 11,98 0.66 10,850,00 84,23 359,52 10,610,58 221,95 -344,44 234,49 12,00 11,98 0.64 10,875,00 87,22 359,68 10,613,00 270,04 -344,72 282,57 12,00 11,98 0.64 10,980,00 90.00 359,83 10,613,00 270,04 -344,72 282,57 12,00 11,98 0.64 10,900,00 90.00 359,83 10,613,00 271,87 -344,72 284,39 0.00 0.00 0.00 11,000,00 90.00 359,83 10,613,00 371,87 -345,31 484,27 0.00 0.00 0.00 11,200,00 90.00 359,83 10,613,00 571,87 -345,61 584,22 0.00 0.00 0.00 11,400,00 90.00 359,83 10,613,00 771,86 -346,20 784,10 0.00 0.00 </td <td></td> <td></td> <td></td> <td></td> <td></td> <td>-343.51</td> <td>160.79</td> <td>12.00</td> <td>11.90</td> <td>0.70</td> | | | | | | -343.51 | 160.79 | 12.00 | 11.90 | 0.70 |
| 10,850.00 | , | | | | | | | | | 0.68 |
| 10,875,00 87,22 359,68 10,612,44 246,88 -344,62 259,41 12,00 11,98 0,64 10,898,18 90,00 359,83 10,613,00 270,04 -344,72 282,57 12,00 11,98 0,64 10,900,00 90,00 359,83 10,613,00 271,87 -344,72 284,39 0,00 0,00 0,00 0,00 11,000,00 90,00 359,83 10,613,00 471,87 -345,02 384,33 0,00 0,00 0,00 11,200,00 90,00 359,83 10,613,00 471,87 -345,61 484,27 0,00 0,00 0,00 11,200,00 90,00 359,83 10,613,00 671,87 -345,91 684,16 0,00 0,00 0,00 11,400,00 90,00 359,83 10,613,00 71,86 -346,20 784,10 0,00 0,00 0,00 11,500,00 90,00 359,83 10,613,00 771,86 -346,50 84,04 0,00 | 10,825.00 | 81.23 | 359.36 | 10,607.41 | 197.15 | -344.20 | 209.71 | 12.00 | 11.98 | 0.66 |
| 10,898.18 90.00 359.83 10,613.00 270.04 -344.72 282.57 12.00 11.98 0.64 | · | | | 10,610.58 | 221.95 | -344.44 | 234.49 | 12.00 | 11.98 | 0.65 |
| 10,900 00 90.00 359.83 10,613.00 271.87 -344.72 284.39 0.00 0.00 0.00 11,000.00 90.00 359.83 10,613.00 371.87 -345.02 384.33 0.00 0.00 0.00 11,100.00 90.00 359.83 10,613.00 571.87 -345.61 584.22 0.00 0.00 0.00 11,200.00 90.00 359.83 10,613.00 671.87 -345.61 584.22 0.00 0.00 0.00 0.00 11,300.00 90.00 359.83 10,613.00 671.87 -345.61 584.22 0.00 0.00 0.00 0.00 11,300.00 90.00 359.83 10,613.00 771.86 -346.20 784.10 0.00 0.00 0.00 0.00 11,500.00 90.00 359.83 10,613.00 871.86 -346.60 884.04 0.00 0.00 0.00 11,600.00 90.00 359.83 10,613.00 971.86 -346.80 983.99 0.00 0.00 0.00 0.00 11,700.00 90.00 359.83 10,613.00 1,071.86 -347.09 1,083.93 0.00 0.00 0.00 11,700.00 90.00 359.83 10,613.00 1,071.86 -347.09 1,083.93 0.00 0.00 0.00 11,900.00 90.00 359.83 10,613.00 1,071.86 -347.99 1,083.93 0.00 0.00 0.00 11,900.00 90.00 359.83 10,613.00 1,771.86 -347.99 1,283.81 0.00 0.00 0.00 12,000.00 90.00 359.83 10,613.00 1,771.86 -347.99 1,283.81 0.00 0.00 0.00 12,000.00 90.00 359.83 10,613.00 1,771.86 -347.99 1,283.81 0.00 0.00 0.00 12,000.00 90.00 359.83 10,613.00 1,771.86 -347.98 1,383.76 0.00 0.00 0.00 12,000.00 90.00 359.83 10,613.00 1,771.86 -347.98 1,383.76 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,771.86 -347.98 1,383.76 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,771.86 -348.28 1,483.70 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,771.86 -348.28 1,483.70 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,771.86 -348.28 1,483.70 0.00 0.00 0.00 12,300.00 90.00 359.83 10,613.00 1,771.86 -348.28 1,483.70 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,771.86 -348.28 1,483.70 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,771.86 -348.28 1,483.70 0.00 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,771.86 -348.28 1,483.70 0.00 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,771.86 -348.28 1,483.70 0.00 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 2,771.86 -350.56 2,883.41 0.00 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 2,771.86 -350.56 2,883.24 0.00 0.00 0.00 0.00 13,200.00 90.00 359.83 10,613.00 2, | | | | | | -344.62 | 259.41 | 12.00 | 11.98 | 0.64 |
| 11,000.00 90.00 359.83 10,613.00 371.87 -345.02 384.33 0.00 0.00 0.00 11,100.00 90.00 359.83 10,613.00 471.87 -345.31 484.27 0.00 0.00 0.00 11,200.00 90.00 359.83 10,613.00 671.87 -345.61 584.22 0.00 0.00 0.00 11,300.00 90.00 359.83 10,613.00 671.87 -345.91 684.16 0.00 0.00 0.00 11,400.00 90.00 359.83 10,613.00 771.86 -346.20 784.10 0.00 0.00 0.00 11,500.00 90.00 359.83 10,613.00 971.86 -346.50 884.04 0.00 0.00 0.00 11,700.00 90.00 359.83 10,613.00 1,071.86 -347.99 1,083.93 0.00 0.00 0.00 11,900.00 90.00 359.83 10,613.00 1,271.86 -347.99 1,183.87 0.00 0.00 </td <td>10,898.18</td> <td>90.00</td> <td>359.83</td> <td>10,613.00</td> <td>270.04</td> <td>-344.72</td> <td>282.57</td> <td>12,00</td> <td>11.98</td> <td>0.64</td> | 10,898.18 | 90.00 | 359.83 | 10,613.00 | 270.04 | -344.72 | 282.57 | 12,00 | 11.98 | 0.64 |
| 11,000.00 90.00 359.83 10,613.00 371.87 -345.02 384.33 0.00 0.00 0.00 11,100.00 90.00 359.83 10,613.00 471.87 -345.31 484.27 0.00 0.00 0.00 11,200.00 90.00 359.83 10,613.00 671.87 -345.61 584.22 0.00 0.00 0.00 11,300.00 90.00 359.83 10,613.00 671.87 -345.91 684.16 0.00 0.00 0.00 11,400.00 90.00 359.83 10,613.00 771.86 -346.20 784.10 0.00 0.00 0.00 11,500.00 90.00 359.83 10,613.00 971.86 -346.50 884.04 0.00 0.00 0.00 11,700.00 90.00 359.83 10,613.00 1,071.86 -347.99 1,083.93 0.00 0.00 0.00 11,900.00 90.00 359.83 10,613.00 1,271.86 -347.99 1,183.87 0.00 0.00 </td <td>10,900.00</td> <td>90.00</td> <td>359.83</td> <td>10.613.00</td> <td>271.87</td> <td>-344.72</td> <td>284.39</td> <td>0.00</td> <td>0.00</td> <td>0.00</td> | 10,900.00 | 90.00 | 359.83 | 10.613.00 | 271.87 | -344.72 | 284.39 | 0.00 | 0.00 | 0.00 |
| 11,100.00 90.00 359.83 10,613.00 471.87 -345.31 484.27 0.00 0.00 0.00 11,200.00 90.00 359.83 10,613.00 671.87 -345.91 684.12 0.00 0.00 0.00 11,300.00 90.00 359.83 10,613.00 771.86 -346.20 784.10 0.00 0.00 0.00 11,500.00 90.00 359.83 10,613.00 871.86 -346.50 884.04 0.00 0.00 0.00 11,600.00 90.00 359.83 10,613.00 171.86 -346.50 884.04 0.00 0.00 0.00 11,600.00 90.00 359.83 10,613.00 1,071.86 -347.09 1,083.93 0.00 0.00 0.00 11,900.00 90.00 359.83 10,613.00 1,171.86 -347.09 1,083.93 0.00 0.00 0.00 11,900.00 90.00 359.83 10,613.00 1,271.86 -347.69 1,283.81 0.00 0. | | | | | | | | | | |
| 11,200.00 90.00 359.83 10,613.00 571.87 -345.61 584.22 0.00 0.00 0.00 11,300.00 90.00 359.83 10,613.00 671.87 -345.91 684.16 0.00 0.00 0.00 11,400.00 90.00 359.83 10,613.00 871.86 -346.50 884.04 0.00 0.00 0.00 11,600.00 90.00 359.83 10,613.00 971.86 -346.50 884.04 0.00 0.00 0.00 11,700.00 90.00 359.83 10,613.00 1,071.86 -347.99 1,083.93 0.00 0.00 0.00 11,800.00 90.00 359.83 10,613.00 1,71.86 -347.99 1,283.81 0.00 0.00 0.00 11,900.00 90.00 359.83 10,613.00 1,271.86 -347.99 1,283.81 0.00 0.00 0.00 12,000.00 90.00 359.83 10,613.00 1,471.86 -347.99 1,283.81 0.00 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<> | | | | | | | | | | |
| 11,300.00 90.00 359.83 10,613.00 671.87 -345.91 684.16 0.00 0.00 0.00 11,400.00 90.00 359.83 10,613.00 771.86 -346.20 784.10 0.00 0.00 0.00 11,500.00 90.00 359.83 10,613.00 871.86 -346.50 884.04 0.00 0.00 0.00 11,600.00 90.00 359.83 10,613.00 171.86 -346.80 983.99 0.00 0.00 0.00 11,700.00 90.00 359.83 10,613.00 1,7186 -347.09 1,083.93 0.00 0.00 0.00 11,800.00 90.00 359.83 10,613.00 1,171.86 -347.39 1,183.87 0.00 0.00 0.00 11,900.00 90.00 359.83 10,613.00 1,271.86 -347.69 1,283.81 0.00 0.00 0.00 12,000.00 90.00 359.83 10,613.00 1,471.86 -347.69 1,283.81 0.00 | | | | | | | | | | |
| 11,400.00 90.00 359.83 10,613.00 771.86 -346.20 784.10 0.00 0.00 0.00 11,500.00 90.00 359.83 10,613.00 871.86 -346.50 884.04 0.00 0.00 0.00 11,600.00 90.00 359.83 10,613.00 971.86 -346.80 983.99 0.00 0.00 0.00 11,700.00 90.00 359.83 10,613.00 1,071.86 -347.09 1,083.93 0.00 0.00 0.00 11,800.00 90.00 359.83 10,613.00 1,71.86 -347.69 1,283.81 0.00 0.00 0.00 11,900.00 90.00 359.83 10,613.00 1,371.86 -347.69 1,283.81 0.00 0.00 0.00 12,000.00 90.00 359.83 10,613.00 1,371.86 -347.98 1,383.76 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,571.86 -348.58 1,683.64 0.00 | | | 359.83 | | | | | | | |
| 11,500.00 90.00 359.83 10,613.00 871.86 -346.50 884.04 0.00 0.00 0.00 11,600.00 90.00 359.83 10,613.00 971.86 -346.80 983.99 0.00 0.00 0.00 11,700.00 90.00 359.83 10,613.00 1,71.86 -347.09 1,083.93 0.00 0.00 0.00 11,800.00 90.00 359.83 10,613.00 1,718.6 -347.99 1,183.87 0.00 0.00 0.00 11,900.00 90.00 359.83 10,613.00 1,271.86 -347.69 1,283.81 0.00 0.00 0.00 12,000.00 90.00 359.83 10,613.00 1,371.86 -347.69 1,283.81 0.00 0.00 0.00 12,100.00 90.00 359.83 10,613.00 1,471.86 -348.28 1,483.70 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,571.86 -348.28 1,583.64 0.00 | 11 400 00 | 90.00 | 350.83 | 10 613 00 | 771.86 | 346.20 | 78/ 10 | 0.00 | 0.00 | 0.00 |
| 11,600.00 90.00 359.83 10,613.00 971.86 -346.80 983.99 0.00 0.00 0.00 11,700.00 90.00 359.83 10.613.00 1,071.86 -347.09 1,083.93 0.00 0.00 0.00 11,800.00 90.00 359.83 10,613.00 1,171.86 -347.39 1,183.87 0.00 0.00 0.00 11,900.00 90.00 359.83 10,613.00 1,271.86 -347.69 1,283.81 0.00 0.00 0.00 12,000.00 90.00 359.83 10,613.00 1,371.86 -347.98 1,383.76 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,571.86 -348.28 1,483.70 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,571.86 -348.87 1,683.58 0.00 0.00 0.00 12,400.00 90.00 359.83 10,613.00 1,771.86 -349.17 1,783.53 0.00 <td></td> | | | | | | | | | | |
| 11,700,00 90,00 359,83 10,613,00 1,071,86 -347,09 1,083,93 0.00 0.00 0.00 11,800,00 90,00 359,83 10,613,00 1,171,86 -347,39 1,183,87 0.00 0.00 0.00 11,900,00 90,00 359,83 10,613,00 1,271,86 -347,98 1,283,81 0.00 0.00 0.00 12,000,00 90,00 359,83 10,613,00 1,371,86 -347,98 1,383,76 0.00 0.00 0.00 12,100,00 90,00 359,83 10,613,00 1,471,86 -348,28 1,483,70 0.00 0.00 0.00 12,200,00 90,00 359,83 10,613,00 1,571,86 -348,58 1,583,64 0.00 0.00 0.00 12,300,00 90,00 359,83 10,613,00 1,771,86 -348,57 1,683,58 0.00 0.00 0.00 12,400,00 90,00 359,83 10,613,00 1,771,86 -349,17 1,783,53 0.00 | | | | | | | | | | |
| 11,800.00 90.00 359.83 10,613.00 1,171.86 -347.39 1,183.87 0.00 0,00 0,00 11,900.00 90.00 359.83 10,613.00 1,271.86 -347.69 1,283.81 0.00 0.00 0.00 12,000.00 90.00 359.83 10,613.00 1,371.86 -347.98 1,383.76 0.00 0.00 0.00 12,100.00 90.00 359.83 10,613.00 1,471.86 -348.28 1,483.70 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,571.86 -348.58 1,583.64 0.00 0.00 0.00 12,300.00 90.00 359.83 10,613.00 1,771.86 -348.87 1,683.58 0.00 0.00 0.00 12,400.00 90.00 359.83 10,613.00 1,771.86 -349.17 1,783.53 0.00 0.00 0.00 12,600.00 90.00 359.83 10,613.00 1,871.86 -349.17 1,783.53 0.00 | | | | | | | | | | |
| 11,900,00 90,00 359,83 10,613,00 1,271,86 -347,69 1,283,81 0.00 0.00 0.00 12,000,00 90,00 359,83 10,613,00 1,371,86 -347,98 1,383,76 0.00 0.00 0.00 12,100,00 90,00 359,83 10,613,00 1,471,86 -348,28 1,483,70 0.00 0.00 0.00 12,200,00 90,00 359,83 10,613,00 1,571,86 -348,58 1,583,64 0.00 0.00 0.00 12,300,00 90.00 359,83 10,613,00 1,671,86 -348,87 1,683,58 0.00 0.00 0.00 12,400,00 90.00 359,83 10,613,00 1,771,86 -349,17 1,783,53 0.00 0.00 0.00 12,500,00 90.00 359,83 10,613,00 1,871,86 -349,17 1,783,53 0.00 0.00 0.00 12,600,00 90.00 359,83 10,613,00 1,971,86 -349,17 1,883,47 0.00 0.00 0.00 12,700,00 90.00 359,83 10, | | | | | | | | | | |
| 12,000.00 90.00 359.83 10,613.00 1,371.86 -347.98 1,383.76 0.00 0.00 0.00 12,100.00 90.00 359.83 10,613.00 1,471.86 -348.28 1,483.70 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,571.86 -348.58 1,583.64 0.00 0.00 0.00 12,300.00 90.00 359.83 10,613.00 1,671.86 -348.87 1,683.58 0.00 0.00 0.00 12,400.00 90.00 359.83 10,613.00 1,771.86 -349.17 1,783.53 0.00 0.00 0.00 12,500.00 90.00 359.83 10,613.00 1,871.86 -349.17 1,783.53 0.00 0.00 0.00 12,600.00 90.00 359.83 10,613.00 1,971.86 -349.47 1,883.47 0.00 0.00 0.00 12,700.00 90.00 359.83 10,613.00 2,071.86 -350.06 2,083.35 0.00 0.00 0.00 12,800.00 90.00 359.83 10, | | | | | | | | | | |
| 12,100.00 90.00 359.83 10,613.00 1,471.86 -348.28 1,483.70 0.00 0.00 0.00 12,200.00 90.00 359.83 10,613.00 1,571.86 -348.58 1,583.64 0.00 0.00 0.00 12,300.00 90.00 359.83 10,613.00 1,671.86 -348.87 1,683.58 0.00 0.00 0.00 12,400.00 90.00 359.83 10,613.00 1,771.86 -349.17 1,783.53 0.00 0.00 0.00 12,500.00 90.00 359.83 10,613.00 1,871.86 -349.47 1,883.47 0.00 0.00 0.00 12,600.00 90.00 359.83 10,613.00 1,971.86 -349.76 1,983.41 0.00 0.00 0.00 12,700.00 90.00 359.83 10,613.00 2,071.86 -350.06 2,083.35 0.00 0.00 0.00 12,800.00 90.00 359.83 10,613.00 2,171.86 -350.65 2,283.24 0.00 0.00 0.00 12,900.00 90.00 359.83 10, | | | | | | | | | | |
| 12,200.00 90.00 359.83 10,613.00 1,571.86 -348.58 1,583.64 0.00 0.00 0.00 12,300.00 90.00 359.83 10,613.00 1,671.86 -348.87 1,683.58 0.00 0.00 0.00 12,400.00 90.00 359.83 10,613.00 1,771.86 -349.17 1,783.53 0.00 0.00 0.00 12,500.00 90.00 359.83 10,613.00 1,871.86 -349.47 1,883.47 0.00 0.00 0.00 12,600.00 90.00 359.83 10,613.00 1,971.86 -349.76 1,983.41 0.00 0.00 0.00 12,700.00 90.00 359.83 10,613.00 2,071.86 -350.06 2,083.35 0.00 0.00 0.00 12,800.00 90.00 359.83 10,613.00 2,171.86 -350.36 2,183.30 0.00 0.00 0.00 12,900.00 90.00 359.83 10,613.00 2,271.86 -350.65 2,283.24 0.00 0.00 0.00 13,000.00 90.00 359.83 10, | | | | | | | | | | |
| 12,300.00 90.00 359.83 10,613.00 1,671.86 -348.87 1,683.58 0.00 0.00 0.00 12,400.00 90.00 359.83 10,613.00 1,771.86 -349.17 1,783.53 0.00 0.00 0.00 12,500.00 90.00 359.83 10,613.00 1,871.86 -349.47 1,883.47 0.00 0.00 0.00 12,600.00 90.00 359.83 10,613.00 1,971.86 -349.76 1,983.41 0.00 0.00 0.00 12,700.00 90.00 359.83 10,613.00 2,071.86 -350.06 2,083.35 0.00 0.00 0.00 12,800.00 90.00 359.83 10,613.00 2,171.86 -350.36 2,183.30 0.00 0.00 0.00 12,900.00 90.00 359.83 10,613.00 2,271.86 -350.65 2,283.24 0.00 0.00 0.00 13,000.00 90.00 359.83 10,613.00 2,371.86 -350.95 2,383.18 0.00 0.00 0.00 13,200.00 90.00 359.83 10, | • | | | | | | | | | |
| 12,400.00 90.00 359.83 10,613.00 1,771.86 -349.17 1,783.53 0.00 0.00 0.00 12,500.00 90.00 359.83 10,613.00 1,871.86 -349.47 1,883.47 0.00 0.00 0.00 12,600.00 90.00 359.83 10,613.00 1,971.86 -349.76 1,983.41 0.00 0.00 0.00 12,700.00 90.00 359.83 10,613.00 2,071.86 -350.06 2,083.35 0.00 0.00 0.00 12,800.00 90.00 359.83 10,613.00 2,171.86 -350.36 2,183.30 0.00 0.00 0.00 12,900.00 90.00 359.83 10,613.00 2,271.86 -350.65 2,283.24 0.00 0.00 0.00 13,000.00 90.00 359.83 10,613.00 2,371.86 -350.95 2,383.18 0.00 0.00 0.00 13,100.00 90.00 359.83 10,613.00 2,471.86 -351.25 2,483.12 0.00 0.00 0.00 13,200.00 90.00 359.83 10, | , | | | | | | | | | |
| 12,500.00 90.00 359.83 10,613.00 1,871.86 -349.47 1,883.47 0.00 0.00 0.00 12,600.00 90.00 359.83 10,613.00 1,971.86 -349.76 1,983.41 0.00 0.00 0.00 12,700.00 90.00 359.83 10,613.00 2,071.86 -350.06 2,083.35 0.00 0.00 0.00 12,800.00 90.00 359.83 10,613.00 2,271.86 -350.36 2,183.30 0.00 0.00 0.00 12,900.00 90.00 359.83 10,613.00 2,271.86 -350.65 2,283.24 0.00 0.00 0.00 13,000.00 90.00 359.83 10,613.00 2,371.86 -350.95 2,383.18 0.00 0.00 0.00 13,100.00 90.00 359.83 10,613.00 2,471.86 -351.25 2,483.12 0.00 0.00 0.00 13,200.00 90.00 359.83 10,613.00 2,571.86 -351.54 2,583.07 0.00 0.00 0.00 13,300.00 90.00 359.83 10, | 12,300.00 | 90.00 | 359.83 | 10,613.00 | 1,671.86 | -348.87 | 1,683.58 | 0.00 | 0.00 | 0.00 |
| 12,500.00 90.00 359.83 10,613.00 1,871.86 -349.47 1,883.47 0.00 0.00 0.00 12,600.00 90.00 359.83 10,613.00 1,971.86 -349.76 1,983.41 0.00 0.00 0.00 12,700.00 90.00 359.83 10,613.00 2,071.86 -350.06 2,083.35 0.00 0.00 0.00 12,800.00 90.00 359.83 10,613.00 2,271.86 -350.36 2,183.30 0.00 0.00 0.00 12,900.00 90.00 359.83 10,613.00 2,271.86 -350.65 2,283.24 0.00 0.00 0.00 13,000.00 90.00 359.83 10,613.00 2,371.86 -350.95 2,383.18 0.00 0.00 0.00 13,100.00 90.00 359.83 10,613.00 2,471.86 -351.25 2,483.12 0.00 0.00 0.00 13,200.00 90.00 359.83 10,613.00 2,571.86 -351.54 2,583.07 0.00 0.00 0.00 13,300.00 90.00 359.83 10, | 12,400.00 | 90.00 | 359.83 | 10,613.00 | 1,771.86 | -349.17 | 1.783.53 | 0.00 | 0.00 | 0.00 |
| 12,600.00 90.00 359.83 10,613.00 1,971.86 -349.76 1,983.41 0.00 0.00 0.00 12,700.00 90.00 359.83 10,613.00 2,071.86 -350.06 2,083.35 0.00 0.00 0.00 12,800.00 90.00 359.83 10,613.00 2,171.86 -350.36 2,183.30 0.00 0.00 0.00 12,900.00 90.00 359.83 10,613.00 2,271.86 -350.65 2,283.24 0.00 0.00 0.00 13,000.00 90.00 359.83 10,613.00 2,371.86 -350.95 2,383.18 0.00 0.00 0.00 13,100.00 90.00 359.83 10,613.00 2,471.86 -351.25 2,483.12 0.00 0.00 0.00 13,200.00 90.00 359.83 10,613.00 2,571.86 -351.54 2,583.07 0.00 0.00 0.00 13,300.00 90.00 359.83 10,613.00 2,671.86 -351.84 2,683.01 0.00 0.00 0.00 13,400.00 90.00 359.83 10, | 12,500.00 | | | | | | | | | |
| 12,700.00 90.00 359.83 10,613.00 2,071.86 -350.06 2,083.35 0,00 0.00 0.00 12,800.00 90.00 359.83 10,613.00 2,171.86 -350.36 2,183.30 0,00 0.00 0.00 12,900.00 90.00 359.83 10,613.00 2,271.86 -350.65 2,283.24 0.00 0.00 0.00 13,000.00 90.00 359.83 10,613.00 2,371.86 -350.95 2,383.18 0.00 0.00 0.00 13,100.00 90.00 359.83 10,613.00 2,471.86 -351.25 2,483.12 0.00 0.00 0.00 13,200.00 90.00 359.83 10,613.00 2,571.86 -351.54 2,583.07 0.00 0.00 0.00 13,300.00 90.00 359.83 10,613.00 2,671.86 -351.84 2,683.01 0.00 0.00 0.00 13,400.00 90.00 359.83 10,613.00 2,771.86 -352.14 2,782.95 0.00 0.00 0.00 | 12,600.00 | 90.00 | 359.83 | | | | | | | |
| 12,800.00 90.00 359.83 10,613.00 2,171.86 -350.36 2,183.30 0.00 0.00 0.00 12,900.00 90.00 359.83 10,613.00 2,271.86 -350.65 2,283.24 0.00 0.00 0.00 13,000.00 90.00 359.83 10,613.00 2,371.86 -350.95 2,383.18 0.00 0.00 0.00 13,100.00 90.00 359.83 10,613.00 2,471.86 -351.25 2,483.12 0.00 0.00 0.00 13,200.00 90.00 359.83 10,613.00 2,571.86 -351.54 2,583.07 0.00 0.00 0.00 13,300.00 90.00 359.83 10,613.00 2,671.86 -351.84 2,683.01 0.00 0.00 0.00 13,400.00 90.00 359.83 10,613.00 2,771.86 -352.14 2,782.95 0.00 0.00 0.00 | 12,700.00 | 90.00 | 359.83 | | | | | | | |
| 12,900.00 90.00 359.83 10,613.00 2,271.86 -350.65 2,283.24 0.00 0.00 0.00 13,000.00 90.00 359.83 10,613.00 2,371.86 -350.95 2,383.18 0.00 0.00 0.00 13,100.00 90.00 359.83 10,613.00 2,471.86 -351.25 2,483.12 0.00 0.00 0.00 13,200.00 90.00 359.83 10,613.00 2,571.86 -351.54 2,583.07 0.00 0.00 0.00 13,300.00 90.00 359.83 10,613.00 2,671.86 -351.84 2,683.01 0.00 0.00 0.00 13,400.00 90.00 359.83 10,613.00 2,771.86 -352.14 2,782.95 0.00 0.00 0.00 | | | | | | | | | | |
| 13,000.00 90.00 359.83 10,613.00 2,371.86 -350.95 2,383.18 0.00 0.00 0.00 13,100.00 90.00 359.83 10,613.00 2,471.86 -351.25 2,483.12 0.00 0.00 0.00 13,200.00 90.00 359.83 10,613.00 2,571.86 -351.54 2,583.07 0.00 0.00 0.00 13,300.00 90.00 359.83 10,613.00 2,671.86 -351.84 2,683.01 0.00 0.00 0.00 13,400.00 90.00 359.83 10,613.00 2,771.86 -352.14 2,782.95 0.00 0.00 0.00 | | | | | | | | | | |
| 13,100.00 90.00 359.83 10,613.00 2,471.86 -351.25 2,483.12 0.00 0.00 0.00 13,200.00 90.00 359.83 10,613.00 2,571.86 -351.54 2,583.07 0.00 0.00 0.00 13,300.00 90.00 359.83 10,613.00 2,671.86 -351.84 2,683.01 0.00 0.00 0.00 13,400.00 90.00 359.83 10,613.00 2,771.86 -352.14 2,782.95 0.00 0.00 0.00 | | | | | | | | | | |
| 13,200.00 90.00 359.83 10,613.00 2,571.86 -351.54 2,583.07 0.00 0.00 0.00 13,300.00 90.00 359.83 10,613.00 2,671.86 -351.84 2,683.01 0.00 0.00 0.00 13,400.00 90.00 359.83 10,613.00 2,771.86 -352.14 2,782.95 0.00 0.00 0.00 | | | | | | | | | | |
| 13,300.00 90.00 359.83 10,613.00 2,671.86 -351.84 2,683.01 0.00 0.00 0.00 13,400.00 90.00 359.83 10,613.00 2,771.86 -352.14 2,782.95 0.00 0.00 0.00 | | | | | | | | | | |
| 13,400.00 90.00 359.83 10,613.00 2,771.86 -352.14 2,782.95 0.00 0.00 0.00 | • | | | | | | | | | |
| | 13,300.00 | 90.00 | 359.83 | 10,513,00 | ∠,071.86 | -357.84 | ∠,683.01 | 00.0 | 0.00 | 0.00 |
| | 13,400.00 | 90.00 | 359.83 | 10,613.00 | 2,771.86 | -352.14 | 2,782.95 | 0.00 | 0.00 | 0.00 |
| | 13,500.00 | 90.00 | 359.83 | 10,613.00 | 2,871.86 | | | | | |

eog resources

EOG Resources, Inc.

Planning Report

Database: Company: EDM 5000.1 Single User Db EOG Resources - Midland Eddy County, NM (NAD 83 NME)

Project: Site:

Casey Jones 16 Fed Com #703H

Well: Wellbore:

ОН

Plan #0.1 Design:

Local Co-ordinate Reference:

TVD Reference: MD Reference:

North Reference:

Survey Calculation Method:

Well #703H

KB = 25' @ 3059.00usft KB = 25' @ 3059.00usft

Grid

Minimum Curvature

Planned Survey

| Measured | | | Vertical | | | Vertical | Dogleg | Build | Turn |
|-----------|-------------|---------|-----------|----------|---------|----------|-------------|-------------|-------------|
| Depth | Inclination | Azimuth | Depth | +N/-S | +E/-W | Section | Rate | Rate | Rate |
| (usft) | (°) | (°) | (usft) | (usft) | (usft) | (usft) | (°/100usft) | (°/100usft) | (°/100usft) |
| 13,600.00 | 90.00 | 359.83 | 10,613.00 | 2,971,86 | -352,73 | 2,982.84 | 0.00 | 0.00 | 0.00 |
| 13,700.00 | 90,00 | 359.83 | 10,613.00 | 3,071,85 | -353,03 | 3,082.78 | 0.00 | 0,00 | 0.00 |
| 13,800.00 | 90.00 | 359.83 | 10,613.00 | 3,171.85 | -353,33 | 3,182.72 | 0.00 | 0.00 | 0.00 |
| 13,900.00 | 90.00 | 359.83 | 10,613.00 | 3,271.85 | -353.62 | 3,282.66 | 0.00 | 0.00 | 0.00 |
| 14,000.00 | 90.00 | 359.83 | 10,613.00 | 3,371.85 | -353.92 | 3,382.61 | 0.00 | 0.00 | 0.00 |
| 14,100.00 | 90.00 | 359.83 | 10,613.00 | 3,471.85 | -354.22 | 3,482.55 | 0.00 | 0.00 | 0.00 |
| 14,200.00 | 90.00 | 359.83 | 10,613.00 | 3,571.85 | -354.51 | 3,582.49 | 0.00 | 0.00 | 0.00 |
| 14,300.00 | 90.00 | 359.83 | 10,613.00 | 3,671.85 | -354.81 | 3,682.43 | 0.00 | 0.00 | 0.00 |
| 14,400.00 | 90.00 | 359.83 | 10,613.00 | 3,771.85 | -355.11 | 3,782.38 | 0.00 | 0.00 | 0.00 |
| 14,500.00 | 90.00 | 359.83 | 10,613.00 | 3,871.85 | -355.40 | 3,882.32 | 0.00 | 0.00 | 0.00 |
| 14,600.00 | 90.00 | 359.83 | 10,613.00 | 3,971.85 | -355.70 | 3,982.26 | 0.00 | 0.00 | 0.00 |
| 14,700.00 | 90.00 | 359.83 | 10,613.00 | 4,071.85 | -356.00 | 4,082.20 | 0.00 | 0.00 | 0.00 |
| 14,800.00 | 90.00 | 359.83 | 10,613.00 | 4,171.85 | -356.29 | 4,182.15 | 0.00 | 0.00 | 0.00 |
| 14,900.00 | 90.00 | 359,83 | 10,613.00 | 4,271.85 | -356.59 | 4,282.09 | 0.00 | 0.00 | 0.00 |
| 15,000.00 | 90.00 | 359.83 | 10,613.00 | 4,371.85 | -356.89 | 4,382.03 | 0.00 | 0.00 | 0.00 |
| 15,100.00 | 90.00 | 359.83 | 10,613.00 | 4,471.85 | -357.18 | 4,481.98 | 0.00 | 0.00 | 0.00 |
| 15,200.00 | 90.00 | 359,83 | 10,613,00 | 4,571.85 | -357.48 | 4,581.92 | 0.00 | 0.00 | 0.00 |
| 15,300.00 | 90.00 | 359.83 | 10,613.00 | 4,671.85 | -357.78 | 4,681.86 | 0.00 | 0.00 | 0.00 |
| 15,400.00 | 90.00 | 359.83 | 10,613.00 | 4,771.85 | -358.07 | 4,781.80 | 0.00 | 0.00 | 0.00 |
| 15,500.00 | 90.00 | 359.83 | 10,613.00 | 4,871.85 | -358.37 | 4,881.75 | 0.00 | 0.00 | 0.00 |
| 15,600.00 | 90.00 | 359.83 | 10,613.00 | 4,971.85 | -358.67 | 4,981.69 | 0.00 | 0.00 | 0.00 |
| 15,700.00 | 90.00 | 359.83 | 10,613.00 | 5,071.85 | -358.96 | 5,081.63 | 0.00 | 0.00 | 0.00 |
| 15,800.00 | 90.00 | 359.83 | 10,613.00 | 5,171.85 | -359.26 | 5,181.57 | 0.00 | 0.00 | 0.00 |
| 15,900.00 | 90.00 | 359.83 | 10,613.00 | 5,271.84 | -359.56 | 5,281.52 | 0.00 | 0.00 | 0.00 |
| 16,000.00 | 90.00 | 359.83 | 10,613.00 | 5,371.84 | -359.85 | 5,381.46 | 0.00 | 0.00 | 0.00 |
| 16,100.00 | 90.00 | 359.83 | 10,613.00 | 5,471.84 | -360,15 | 5,481.40 | 0.00 | 0.00 | 0.00 |
| 16,200.00 | 90.00 | 359.83 | 10,613.00 | 5,571.84 | -360.45 | 5,581.34 | 0.00 | 0.00 | 0.00 |
| 16,300.00 | 90.00 | 359.83 | 10,613.00 | 5,671.84 | -360.74 | 5,681.29 | 0.00 | 0.00 | 0.00 |
| 16,400.00 | 90.00 | 359.83 | 10,613.00 | 5,771.84 | -361.04 | 5,781.23 | 0.00 | 0.00 | 0.00 |
| 16,500.00 | 90.00 | 359.83 | 10,613.00 | 5,871.84 | -361.34 | 5,881.17 | 0.00 | 0.00 | 0.00 |
| 16,600.00 | 90.00 | 359.83 | 10,613.00 | 5,971.84 | -361.63 | 5,981.11 | 0.00 | 0.00 | 0.00 |
| 16,700.00 | 90.00 | 359.83 | 10,613.00 | 6,071.84 | -361.93 | 6,081.06 | 0.00 | 0.00 | 0.00 |
| 16,800.00 | 90.00 | 359.83 | 10,613.00 | 6,171.84 | -362.23 | 6,181.00 | 0.00 | 0.00 | 0.00 |
| 16,900.00 | 90.00 | 359.83 | 10,613.00 | 6,271.84 | -362.52 | 6,280.94 | 0.00 | 0.00 | 0.00 |
| 17,000.00 | 90.00 | 359.83 | 10,613.00 | 6,371.84 | -362.82 | 6,380.88 | 0.00 | 0.00 | 0.00 |
| 17,100.00 | 90.00 | 359.83 | 10,613.00 | 6,471.84 | -363.12 | 6,480.83 | 0.00 | 0.00 | 0.00 |
| 17,200.00 | 90.00 | 359.83 | 10,613.00 | 6,571.84 | -363.41 | 6,580.77 | 0.00 | 0.00 | 0.00 |
| 17,300.00 | 90.00 | 359.83 | 10,613.00 | 6,671.84 | -363.71 | 6,680.71 | 0.00 | 0.00 | 0.00 |
| 17,400.00 | 90.00 | 359.83 | 10,613.00 | 6,771.84 | -364.01 | 6,780.65 | 0.00 | 0.00 | 0.00 |
| 17,500.00 | 90.00 | 359.83 | 10,613.00 | 6,871.84 | -364.30 | 6,880.60 | 0.00 | 0.00 | 0.00 |
| 17,600.00 | 90.00 | 359.83 | 10,613.00 | 6,971.84 | -364.60 | 6,980.54 | 0.00 | 0.00 | 0.00 |
| 17,700.00 | 90.00 | 359.83 | 10,613.00 | 7,071.84 | -364.90 | 7,080.48 | 0.00 | 0.00 | 0.00 |
| 17,800.00 | 90.00 | 359.83 | 10,613.00 | 7,171.84 | -365.19 | 7,180.42 | 0.00 | 0.00 | 0.00 |
| 17,900.00 | 90.00 | 359.83 | 10,613.00 | 7,271.84 | -365.49 | 7,280.37 | 0.00 | 0.00 | 0.00 |
| 18,000.00 | 90.00 | 359.83 | 10,613.00 | 7,371.84 | -365.79 | 7,380.31 | 0.00 | 0.00 | 0.00 |
| 18,100.00 | 90.00 | 359.83 | 10,613.00 | 7,471.84 | -366.08 | 7,480.25 | 0.00 | 0.00 | 0.00 |
| 18,200.00 | 90.00 | 359.83 | 10,613.00 | 7,571.83 | -366.38 | 7,580.19 | 0.00 | 0.00 | 0.00 |
| 18,300.00 | 90.00 | 359.83 | 10,613.00 | 7,671.83 | -366.68 | 7,680.14 | 0.00 | 0.00 | 0.00 |
| 18,400.00 | 90.00 | 359.83 | 10,613.00 | 7,771.83 | -366.97 | 7,780.08 | 0.00 | 0.00 | 0.00 |
| 18,500.00 | 90.00 | 359.83 | 10,613.00 | 7,871.83 | -367.27 | 7,880.02 | 0.00 | 0.00 | 0.00 |
| 18,600.00 | 90.00 | 359.83 | 10,613.00 | 7,971.83 | -367.57 | 7,979.96 | 0.00 | 0.00 | 0.00 |
| 18,700.00 | 90.00 | 359.83 | 10,613.00 | 8,071.83 | -367.86 | 8,079.91 | 0.00 | 0.00 | 0.00 |
| 18,800.00 | 90.00 | 359.83 | 10,613.00 | 8,171.83 | -368.16 | 8,179.85 | 0.00 | 0.00 | 0.00 |
| | | | | 8,271.83 | -368.46 | 8,279.79 | 0.00 | 0.00 | 0.00 |
| 18,900.00 | 90.00 | 359.83 | 10,613.00 | 0,2/1.83 | -300.40 | 0,219.19 | 0.00 | 0.00 | 0.00 |



EOG Resources, Inc.

Planning Report

Database: Company:

EDM 5000.1 Single User Db EOG Resources - Midland

Project:

Eddy County, NM (NAD 83 NME) Casey Jones 16 Fed Com

Site: Well:

#703H

Wellbore: Design:

OH Plan #0.1 Local Co-ordinate Reference:

TVD Reference: MD Reference:

North Reference: **Survey Calculation Method:** Well #703H

KB = 25' @ 3059.00usft KB = 25' @ 3059,00usft

Grid

Minimum Curvature

Planned Survey


| Measured Depth | Inclination | Azimuth | Vertical Depth | +N/-S | +E/-W | Vertical Section | Dogleg Rate | Build Rate | Turn Rate |
|-------------------|-------------|---------|-------------------|-----------|---------|---------------------|----------------|---------------|--------------|
| (usft) | (°) | (°) | (usft) | (usft) | (usft) | (usft) | (°/100usft) | (°/100usft) | (°/100usft) |
| 19,000.00 | 90.00 | 359.83 | 10,613.00 | 8,371.83 | -368.75 | 8,379.73 | 0.00 | 0.00 | 0.00 |
| 19,100.00 | 90.00 | 359.83 | 10,613.00 | 8,471.83 | -369.05 | 8,479.68 | 0.00 | 0.00 | 0.00 |
| 19,200.00 | 90.00 | 359.83 | 10,613.00 | 8,571.83 | -369.35 | 8,579.62 | 0.00 | 0.00 | 0.00 |
| 19,300.00 | 90.00 | 359.83 | 10,613.00 | 8,671.83 | -369.64 | 8,679.56 | 0.00 | 0.00 | 0.00 |
| 19,400.00 | 90.00 | 359.83 | 10,613.00 | 8,771.83 | -369.94 | 8,779.50 | 0.00 | 0.00 | 0.00 |
| 19,500.00 | 90.00 | 359.83 | 10,613.00 | 8,871.83 | -370.24 | 8,879.45 | 0.00 | 0.00 | 0.00 |
| 19,600.00 | 90.00 | 359.83 | 10,613.00 | 8,971.83 | -370.53 | 8,979.39 | 0.00 | 0.00 | 0.00 |
| 19,700.00 | 90.00 | 359.83 | 10,613.00 | 9,071.83 | -370.83 | 9,079.33 | 0.00 | 0.00 | 0.00 |
| 19,800.00 | 90.00 | 359.83 | 10,613.00 | 9,171.83 | -371.13 | 9,179.27 | 0.00 | 0.00 | 0.00 |
| 19,900.00 | 90.00 | 359.83 | 10,613.00 | 9,271.83 | -371.42 | 9,279.22 | 0.00 | 0.00 | 0.00 |
| 20,000.00 | 90.00 | 359.83 | 10,613.00 | 9,371.83 | -371.72 | 9,379.16 | 0,00 | 0.00 | 0.00 |
| 20,100.00 | 90.00 | 359.83 | 10,613.00 | 9,471.83 | -372.02 | 9,479.10 | 0.00 | 0.00 | 0.00 |
| 20,200.00 | 90.00 | 359.83 | 10,613.00 | 9,571.83 | -372.31 | 9,579.04 | 0.00 | 0.00 | 0.00 |
| 20,300.00 | 90.00 | 359.83 | 10,613.00 | 9,671.83 | -372.61 | 9,678.99 | 0.00 | 0.00 | 0.00 |
| 20,400.00 | 90.00 | 359.83 | 10,613.00 | 9,771.83 | -372.91 | 9,778.93 | 0.00 | 0.00 | 0.00 |
| 20,500.00 | 90.00 | 359.83 | 10,613.00 | 9,871.82 | -373.20 | 9,878.87 | 0.00 | 0.00 | 0.00 |
| 20,600.00 | 90.00 | 359.83 | 10,613.00 | 9,971.82 | -373.50 | 9,978.82 | 0.00 | 0.00 | 0.00 |
| 20,700.00 | 90.00 | 359.83 | 10,613.00 | 10,071.82 | -373.80 | 10,078.76 | 0.00 | 0.00 | 0.00 |
| 20,768.18 | 90.00 | 359.83 | 10,613.00 | 10,140.00 | -374.00 | 10,146.90 | 0.00 | 0.00 | 0.00 |

Design Targets

| Target | Name |
|--------|------|

| - hit/miss target - Shape | Dip Angle (°) | Dip Dir. (°) | TVD (usft) | +N/-S (usft) | +E/-W (usft) | Northing (usft) | Easting (usft) | Latitude | Longitude |
|---|------------------|-----------------|---------------|-----------------|-----------------|--------------------|-------------------|-------------|---------------|
| PBHL (C J 16 Fed Com - plan hits target cen - Point | 0.00 ter | 0.00 | 10,613.00 | 10,140.00 | -374.00 | 387,253.00 | 678,830.00 | 32.06386113 | -103.88948611 |
| FTP (C J 16 Fed Com# | 0.00 | 0.00 | 10,613.00 | 68.00 | -344.00 | 377,181.00 | 678,860.00 | 32.03617387 | -103.88952291 |

⁻ plan misses target center by 40.99usft at 10706.57usft MD (10575.12 TVD, 83.55 N, -342.14 E) - Point





| OD | Weight | Wall Th. | Grade | API Drift | Connection |
|-----------|-------------|-----------|-----------|-----------|--------------|
| 7 5/8 in. | 29.70 lb/ft | 0.375 in. | VM 110 HC | 6.750 in. | VAM® SLIJ-II |

| PIPE PROPER | ries . |
|--------------------------------|---------------|
| Nominal OD | 7.625 in. |
| Nominal ID | 6.875 in. |
| Nominal Cross Section Area | 8.541 sqin. |
| Grade Type | High Collapse |
| Min. Yield Strength | 110 ksi |
| Max. Yield Strength | 140 ksi |
| Min. Ultimate Tensile Strength | 125 ksi |
| | |


| CONNECTION PROPERTIES | | | | | | | |
|------------------------------|-----------------------------|--|--|--|--|--|--|
| Connection Type | Premium integral semi-flush | | | | | | |
| Connection OD (nom) | 7.711 in. | | | | | | |
| Connection ID (nom) | 6.820 in. | | | | | | |
| Make-up Loss | 4.822 in. | | | | | | |
| Critical Cross Section | 5.912 sqin. | | | | | | |
| Tension Efficiency | 69.2 % of pipe | | | | | | |
| Compression Efficiency | 48.5 % of pipe | | | | | | |
| Internal Pressure Efficiency | 100 % of pipe | | | | | | |
| External Pressure Efficiency | 100 % of pipe | | | | | | |

| CONNECTION PERFORMANCES | | | | | | | |
|------------------------------|-------------|--|--|--|--|--|--|
| Tensile Yield Strength | 651 klb | | | | | | |
| Compression Resistance | 455 klb | | | | | | |
| Internal Yield Pressure | 9470 psi | | | | | | |
| Uniaxial Collapse Pressure | 7890 psi | | | | | | |
| Max. Bending Capacity | TDB | | | | | | |
| Max Bending with Sealability | 20 1/100 ft | | | | | | |

| FIELD TORQUE VALUES | | | | | | |
|----------------------|-------------|--|--|--|--|--|
| Min. Make-up torque | 11300 ft.lb | | | | | |
| Opti. Make-up torque | 12600 ft.lb | | | | | |
| Max. Make-up torque | 13900 ft.lb | | | | | |

VAM® SLIJ-II is a semi-flush integral premium connection for all casing applications. It combines a near flush design with high performances in tension, compression and gas sealability.

VAM® SLIJ-II has been validated according to the most stringent tests protocols, and has an excellent performance history in the world's most prolific HPHT wells.




Do you need help on this product? - Remember no one knows $\mathsf{VAM}^{\$}$ like VAM


canada@vamfieldservice.com usa@vamfieldservice.com mexico@vamfieldservice.com brazil@vamfieldservice.com uk@vamfieldservice.com dubai@vamfieldservice.com nigeria@vamfieldservice.com angola@vamfieldservice.com china@vamfieldservice.com baku@vamfieldservice.com singapore@vamfieldservice.com australia@vamfieldservice.com


Over 140 VAM® Specialists available worldwide 24/7 for Rig Site Assistance

Other Connection Data Sheets are available at www.vamservices.com










260' FSL 2000' FWL Section 16 T-26-S, R-30-E

Eddy County, New Mexico Proposed Wellbore

API: 30-015-****

KB: 3,059' GL: 3,034'



Lateral: 20,768' MD, 10,613' TVD
Upper Most Perf:
330' FSL & 1656' FWL Sec. 16
Lower Most Perf:
330' FNL & 1660' FWL Sec. 9
BH Location: 230' FNL & 1660' FWL

Section 9 T-26-S, R-30-E

United States Department of the Interior

BUREAU OF LAND MANAGEMENT CARLSBAD FIELD OFFICE 620 E. GREENE ST.

CARLSBAD, NM 88220 BLM_NM_CFO_APD@BLM GOV

06/28/2017



In Reply To: 3160 (Office Code) [NMNM119275]

Attn: STAN WAGNER EOG RESOURCES INC 1111 BAGBY SKY LOBBY2 HOUSTON, TX 77002

Re: Receipt and Acceptability of Application for Permit to Drill (APD)

FEDERAL - NMNM119275

Well Name / Number:

CASEY JONES 16 FED COM / 703H

Legal Description:

T26S, R30E, SEC 16. SESW

County, State:

EDDY, NM

Date APD Received:

05/05/2017

Dear Operator:

The BLM received your Application for Permit to Drill (APD), for the referenced well, on 05/05/2017. The BLM reviewed the APD package pursuant to part III.D of Onshore Oil and Gas Order No.1 and it is:

| 1. | | e/Deficient (The BLM cannot process the APD until you submi- calendar days of the date of this notice or the BLM will return | |
|----|--------------|---|------|
| | | | |
| | | Well Plat | |
| | | Drilling Plan | |
| | \checkmark | Surface Use Plan of Operations (SUPO) | |
| | | Certification of Private Surface Owner Access Agreen | ient |
| | | Bonding | |
| | | Onsite (The BLM has scheduled the onsite to be on |) |
| | | This requirement is exempt of the 45-day timeframe to deficiencies. This requirement will be satisfied on the | |
| | | Other | |

[Please See Addendum for further clarification of deficiencies]

| 2. Missing Necessary Information (The BLM can start, but cannot complete the analysis until you submit the identified items. This is an early notice and the BLM will restate this in a 30-day deferral letter, if you have not submitted the information at that time. You will have two (2) years from the date of the deferral to submit this information or the BLM will deny your APD.) |
|--|
| |

[Please See Addendum for further clarification of deficiencies]

NOTE: The BLM will return your APD package to you, unless you correct all deficiencies identified above (item 1) within 45 calendar days.

• The BLM will not refund an APD processing fee or apply it to another APD for any returned APD.

Extension Requests:

- If you know you will not be able to meet the 45-day timeframe for reasons beyond your control, you must submit a written request through email/standard mail for extension prior to the 45th calendar day from this notice. 08/12/2017.
- The BLM will consider the extension request if you can demonstrate your diligence (providing reasons and examples of why the delay is occurring beyond your control) in attempting to correct the deficiencies and can provide a date by which you will correct the deficiencies. If the BLM determines that the request does not warrant an extension, the BLM will return the APD as incomplete after the 45 calendar days have elapsed.

The BLM will determine whether to grant an extension beyond the required 45 calendar days and will document this request in the well file. If you fail to submit deficiencies by the date defined in the extension request, the BLM will return the APD.

APDs remaining Incomplete:

• If the APD is still not complete, the BLM will notify you and allow 10 additional business days to submit a written request to the BLM for an extension. The request must describe how you will address all outstanding deficiencies and the timeframe you request to complete the deficiencies.

The BLM will consider the extension request if you can prove your diligence (providing reasons and examples of why the delay is occurring) in attempting to correct the deficiencies and you can provide a date by which you will correct the deficiencies. If the BLM determines that the request does not warrant an additional extension, the BLM will return the APD as incomplete.

If you have any questions, please contact Deborah McKinney at (575) 234-5931.

Sincerely.

Cody Layton Assistant Field Manager

cc: Official File

ADDENDUM - Deficient

Surface Comments


- Location and Type of Water Supply Deficiency:
 Please provide a second source of water.
- ++, 44
- Construction Materials Deficiency:
 Please provide a second location for caliche.

Engineering Comments

- BOP requirements are not met
 - 1. BOP Schematic must have a 10M Annular. Please resubmit with correction.
 - 2. 10M BOP Choke manifold is required. Please resubmit with correction.

taked

- Engineering Review: Other identified drilling plan deficiencies Not a deficiency but cannot approve APD without a waste minimization plan. Please attach state submitted gas capture plan (this will be a sufficient substitute for waste minimization plan).



Deogresources

MIDLAND DIVISION

Author:

4/12/2017

Date:

Projection: WGS_1984_Web_Mercator_Auxiliary_Sphere

1 65.000

THIS MAP IS NOT TO BE USED FOR NAVIGATION

| <u></u> | | | | | | | | | <u> </u> |
|---------|--------------|------------------|--------------------------------|----------------------|--------------|---|-------|---------------------------------|---|
| , di | | ב ה ה ה | | | | | | Seog resources MIDLAND DIVISION | Author: |
| | 4. | F | = | 5 | 2 | CA L | | | ng site and may not be se reliable. VIGATION 7/14/2017 |
| 42 | Pits | ta ta | en T | 5 2 | 22 | 2 K 2 8 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | | <u> </u> | Internet mappi s map may or ent, or otherwi JSED FOR NA Date: |
| 12 | Water | ŗ. | | 2 | 26 | では、 | | | arated static outbut from an Internet mapping site and are layers that appear on this map may or may not be accurate, current, or otherwise reliable. THIS MAP IS NOT TO BE USED FOR NAVIGATION Date: 7/14/2017 |
| * | • | £ | <u> 5</u> | Q1 F4 | 27. | #:0 | | | rgenerated stat |
| \$E | | Jits. | 16 2.5 3.5 3.5 9.5 | 79 | | 77 | = - | | This map is a user generated static output from an Internet mapping site and is for reference only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable. THIS MAP IS NOT TO BE USED FOR NAVIGATION Date: 7/14/2017 |
| 2_ | - ' | Water Pits. | | 85 | 9.7 | | | 7 1 2 2 | tes. |
| E | <u>.</u> | in. | F- | - In T | - | 5 | | | 16.666.7 Feet |
| IL. | . | ζ. Τ | | े . - ख स्व | ţ. | ત્રે | | | 8,333.33 |
| | ; ; ; | 5 | ± | ę., | ! 4 | 3 | - | | D Landiary_Sphere |
| 7.0 | | Ę | Ę | z | | A | ; | | 16,666.7 0 1: 100,000 Projection: WGS_1984_Web_Mercator_Auxiliary_Sphere |
| 75 | - | ± | Caliche zus | | *** | 3 | · = 1 | ~ | 00 : WGS_1984_V |
| | | 1 | C | 1 (s) | | | . i | | 16,666.7 1: 100,000 Projection: |

Well Name: CASEY JONES 16 FED COM Well Number: 703H

New road access plan attachment:

Access road engineering design? NO

Access road engineering design attachment:

Access surfacing type: OTHER

Access topsoil source: ONSITE

Access surfacing type description: 6" of Compacted Caliche

Access onsite topsoil source depth: 6

Offsite topsoil source description:

Onsite topsoil removal process: An adequate amount of topsoil/root zone will be stripped by dozer from the proposed well location and stockpiled along the side of the well location as depicted on the well site diagram / survey plat.

Access other construction information:

Access miscellaneous information:

Number of access turnouts:

Access turnout map:

Drainage Control

New road drainage crossing: OTHER

Drainage Control comments: No drainage crossings

Road Drainage Control Structures (DCS) description: N/A

Road Drainage Control Structures (DCS) attachment:

Access Additional Attachments

Additional Attachment(s):

Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

CASEYJONES16FC703H_radius_05-05-2017.pdf

Existing Wells description:

Section 4 - Location of Existing and/or Proposed Production Facilities

Submit or defer a Proposed Production Facilities plan? SUBMIT

Production Facilities description: Central Tank Battery located SW/4 of section 16

Production Facilities map:

Well Name: CASEY JONES 16 FED COM Well Number: 703H

Casey_Jones_16_Fed_Com_Electric_line_05-05-2017.pdf
Casey_Jones_16_Fed_Com_GGS_Trunk_Line_05-05-2017.pdf
Casey_Jones_16_Fed_Com_infrastructure_05-05-2017.pdf
Casey_Jones_16_Fed_Com_WGS_Main_Line_05-05-2017.pdf

Section 5 - Location and Types of Water Supply

Water Source Table

| Water source use type: OTHER | Water source type: RECYCLED |
|------------------------------|-----------------------------|
| | |

Describe type:

Source latitude: Source longitude:

Source datum:

Water source permit type: WATER RIGHT

Source land ownership: FEDERAL

Water source transport method: PIPELINE, TRUCKING

Source transportation land ownership: FEDERAL

Water source volume (barrels): 0 Source volume (acre-feet): 0

Source volume (gal): 0

Water source and transportation map:

CaseyJones16_FC_Caliche_Water_Map_05-05-2017.pdf

Water source comments:

New water well? NO

New Water Well Info

Well latitude: Well Longitude: Well datum:

Well target aquifer:

Est. depth to top of aquifer(ft): Est thickness of aquifer:

Aquifer comments:

Aquifer documentation:

Well depth (ft): Well casing type:

Well casing outside diameter (in.): Well casing inside diameter (in.):

New water well casing?

Used casing source:

Drilling method: Drill material:

Grout material: Grout depth:

Casing length (ft.): Casing top depth (ft.):

Well Name: CASEY JONES 16 FED COM Well Number: 703H

Well Production type:

Completion Method:

Water well additional information:

State appropriation permit:

Additional information attachment:

Section 6 - Construction Materials

Construction Materials description: Caliche will be supplied from pits shown on the attached caliche source map. Caliche utilized for the drilling pad will be obtained either from an existing approved mineral pit, or by benching into a hill, which will allow the pad to be level with existing caliche from the cut, or extracted by "Flipping" the well location. A mineral material permit will be obtained from BLM prior to excavating any caliche on Federal Lands. Amount will vary for each pad. The procedure for "Flipping" a well location is as follows: * -An adequate amount of topsoil/root zone (usually top 6 inches of soil) will be stripped from the proposed well location and stockpiled along the side of the well location as depicted on the well site diagram/survey plat. -An area will be used within the proposed well site dimensions to excavate caliche. Subsoil will be removed and stockpiled within the surveyed well pad dimensions. -Once caliche/surfacing mineral is found, the mineral material will be excavated and stock piled within the approved drilling pad dimensions. -Then, subsoil will be pushed back in the excavated hole and caliche will be spread accordingly across the entire well pad and road (if available). -Neither caliche, nor subsoil will be stock piled outside of the well pad dimensions. Topsoil will be stockpiled along the edge of the pad as depicted in the Well Site Layout or survey plat. * In the event that no caliche is found onsite, caliche will be hauled in from a BLM approved caliche pit or other established mineral pit. A BLM mineral material permit will be acquired prior to obtaining any mineral material from BLM pits or federal land.

Construction Materials source location attachment:

CaseyJones16_FC_Caliche_Water_Map_05-05-2017.pdf

Section 7 - Methods for Handling Waste

Waste type: DRILLING

Waste content description: Drill fluids and produced oil and water from the well during drilling and completion operations will be stored safely and disposed of properly in an NMOCD approved disposal facility. Garbage and trash produced during drilling and completion operations will be collected in a trash container and disposed of properly. Human waste and grey water will be properly contained of and disposed of properly. After drilling and completion operations; trash, chemicals, salts, frac sand, and other waste material will be removed and disposed of properly at a state approved disposal facility.

Amount of waste: 0 barrels

Waste disposal frequency : Daily

Safe containment description: Steel Tanks

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: Trucked to NMOCD approved disposal facility

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit?

Well Name: CASEY JONES 16 FED COM Well Number: 703H

Reserve pit length (ft.)

Reserve pit width (ft.)

Reserve pit depth (ft.)

Reserve pit volume (cu. yd.)

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? YES

Description of cuttings location Closed Loop System. Drill cuttings will be disposed of into steel tanks and taken to an NMOCD approved disposal facility.

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary Facilities

Are you requesting any Ancillary Facilities?: NO

Ancillary Facilities attachment:

Comments:

Section 9 - Well Site Layout

Well Site Layout Diagram:

Casey_Jones_16_FC_703H_Rig_Layout_05-05-2017.pdf CASEYJONES16FC703H_padsite_05-05-2017.pdf

CASEYJONES16FC703H_wellsite_05-05-2017.pdf

Comments: Exhibit 2A-Wellsite & Exhibit 2B-Padsite Rig Layout Exhibit 4

Operator Name: EOG RESOURCES INCORPORATED

Well Name: CASEY JONES 16 FED COM Well Number: 703H

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance Multiple Well Pad Name: CASEY JONES 16 FED COM

Multiple Well Pad Number: 703H/704H

Recontouring attachment:

CASEYJONES16FC703H_reclamation_05-05-2017.pdf

Drainage/Erosion control construction: Proper erosion control methods will be used on the area to control erosion, runoff, and siltation of the surrounding area.

Drainage/Erosion control reclamation: The interim reclamation will be monitored periodically to ensure that vegetation has reestablished and that erosion is controlled.

Wellpad long term disturbance (acres): 2.852388 Wellpad short term disturbance (acres): 4.178145

Pipeline long term disturbance (acres): 0.34710744 Pipeline short term disturbance (acres): 0.5785124

Other long term disturbance (acres): 0

Other short term disturbance (acres): 0

Total long term disturbance: 3.3983934

Total short term disturbance: 4.9555554

Reconstruction method: In areas planned for interim reclamation, all the surfacing material will be removed and returned to the original mineral pit or recycled to repair or build roads and well pads. Areas planned for interim reclamation will be recontoured to the original contour if feasible, or if not feasible, to an interim contour that blends with the surrounding topography as much as possible. Where applicable, the fill material of the well pad will be backfilled into the cut to bring the area back to the original contour. The interim cut and fill slopes prior to re-seeding will not be steeper than a 3:1 ratio, unless the adjacent native topography is steeper. Note: Constructed slopes may be much steeper during drilling, but will be recontoured to the above ratios during interim reclamation.

Topsoil redistribution: Topsoil will be evenly respread and aggressively revegetated over the entire disturbed area not needed for all-weather operations including cuts and fills. To seed the area, the proper BLM seed mixture, free of noxious weeds, will be used. Final seedbed preparation will consist of contour cultivating to a depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting in order to break the soil crust and create seed germination micro-sites. **Soil treatment:** Re-seed according to BLM standards. All reclaimed areas will be monitored periodically to ensure that revegetation occurs, that the area is not redisturbed, and that erosion is controlled.

Existing Vegetation at the well pad: Grass, forbs, and small woody vegetation, such as mesquite will be excavated as the topsoil is removed. Large woody vegetation will be stripped and stored separately and respreads evenly on the site following topsoil respreading. Topsoil depth is defined as the top layer of soil that contains 80% of the roots. In areas to be heavily disturbed, the top 6 inches of soil material, will be stripped and stockpiled on the perimeter of the well location and along the perimeter of the access road to control run-on and run-off, to keep topsoil viable, and to make redistribution of topsoil more efficient during interim reclamation. Stockpiled topsoil should include vegetative material. Topsoil will be clearly segregated and stored separately from subsoils.

Existing Vegetation at the well pad attachment:

Existing Vegetation Community at the road: All disturbed areas, including roads, pipelines, pads, will be recontoured to the contour existing prior to the initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to recontouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation.

Existing Vegetation Community at the road attachment:

Operator Name: EOG RESOURCES INCORPORATED

Well Name: CASEY JONES 16 FED COM Well Number: 703H

Existing Vegetation Community at the pipeline: All disturbed areas, including roads, pipelines, pads, will be recontoured to the contour existing prior to the initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to recontouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation.

Existing Vegetation Community at the pipeline attachment:

Existing Vegetation Community at other disturbances: All disturbed areas, including roads, pipelines, pads, will be recontoured to the contour existing prior to the initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to recontouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation. **Existing Vegetation Community at other disturbances attachment:**

| Seed Type | Pounds/Acre | |
|---------------------------------|---------------------------|--------------------------|
| Seed Sur | mmary | Total pounds/Acre: |
| PLS pounds per acre: | | Proposed seeding season: |
| Seed use location: | | |
| Seed cultivar: | | |
| Source phone: | | |
| Source name: | • | Source address: |
| Seed name: | | |
| Seed type: | | Seed source: |
| Seed Table | | |
| Seed Management | | |
| Seed harvest description attac | chment: | |
| Seed harvest description: | | |
| Will seed be harvested for use | e in site reclamation? NO |) |
| Seedling transplant description | on attachment: | |
| Will seedlings be transplanted | I for this project? NO | |
| Seedling transplant description | on: | |
| Non native seed description: | | |
| Non native seed used? NO | | |

Seed reclamation attachment:

 $\textbf{Operator Name:} \underbrace{\texttt{EOG}\ \texttt{RESOURCES}\ \texttt{INCORPORATED}}_{\bullet}$

USFS Region:

Well Name: CASEY JONES 16 FED COM Well Number: 703H

| Operator Contact/Responsible Official Contact Info | | | |
|--|---|--|--|
| First Name: Stan | Last Name: Wagner | | |
| Phone: (432)686-3689 | Email: stan_wagner@eogresources.com | | |
| Seedbed prep: | | | |
| Seed BMP: | | | |
| Seed method: | | | |
| Existing invasive species? NO | | | |
| Existing invasive species treatment de | scription: | | |
| Existing invasive species treatment att | achment: | | |
| | claimed areas will be monitored periodically to ensure that revegetation occurs, controlled, and free of noxious weeds. Weeds will be treated if found. | | |
| - · · · · · · · · · · · · · · · · · · · | on will be completed within 6 months of well plugging. All reclaimed areas will be getation occurs, that the area is not redisturbed, erosion is controlled, and free o | | |
| Success standards: N/A | | | |
| Pit closure description: NA | | | |
| Pit closure attachment: | | | |
| | | | |
| Section 11 - Surface Owner | ship | | |
| Disturbance type: WELL PAD | | | |
| Describe: | | | |
| Surface Owner: BUREAU OF LAND MAI | NAGEMENT,STATE GOVERNMENT | | |
| Other surface owner description: | | | |
| BIA Local Office: | | | |
| BOR Local Office: | | | |
| COE Local Office: | | | |
| DOD Local Office: | | | |
| NPS Local Office: | | | |
| State Local Office: STATE OF NEW ME | XICO | | |
| Military Local Office: | | | |
| USFWS Local Office: | | | |
| Other Local Office: | | | |

Operator Name: EOG RESOURCES INCORPORATED

Well Name: CASEY JONES 16 FED COM Well Number: 703H

USFS Forest/Grassland:

USFS Ranger District:

Fee Owner: Oliver Kiehne Fee Owner Address: P.O. Box 135 Orla, TX 79770

Phone: (575)399-9281 Email:

Surface use plan certification: NO

Surface use plan certification document:

Surface access agreement or bond: Agreement

Surface Access Agreement Need description: surface use agreement

Surface Access Bond BLM or Forest Service:

BLM Surface Access Bond number:

USFS Surface access bond number:

Section 12 - Other Information

Right of Way needed? YES

Use APD as ROW? YES

ROW Type(s): 281001 ROW - ROADS

ROW Applications


SUPO Additional Information: An onsite meeting was conducted 3/28/17. Poly lines are planned to transport water for operations. Will truck if necessary. See attached SUPO Plan. **Use a previously conducted onsite?** NO

Previous Onsite information:

Other SUPO Attachment

SUPO_Casey_Jones_16_Fed_Com_703H_05-05-2017.pdf CASEYJONES16FC703H_elevation_05-05-2017.pdf CaseyJones16_FC_703_deficiency_response_07-17-2017.pdf

EXHIBIT 2 VICINITY MAP



Seog resources, inc.

LEASE NAME & WELL NO.: CASEY JONES 16 FED COM #703H

 SECTION
 16
 TWP
 26-S
 RGE
 30-E
 SURVEY
 N.M.P.M.

 COUNTY
 EDDY
 STATE
 NM

 DESCRIPTION
 260' FSL & 2000' FWL

DISTANCE & DIRECTION

FROM INT. OF US-285 & CR. 720, GO SOUTH ON US-285 ±12.6 MILES. THENCE NORTHEAST (LEFT) ON WHITEHORN RD. ±4.1 MILES, THENCE EAST (LEFT) ON PIPELINE RD. ±2.8 MILES, THENCE SOUTH (RIGHT) ON TARBRUSH RD. ±4.2 MILES, THENCE SOUTH (RIGHT) ON LEASE RD. ±1.4 MILES, THENCE CONTINUING ON A PROPOSED ACCESS ROAD ±360 FEET, TO A POINT ±290 FEET SOUTHEAST OF THE LOCATION.


THIS EASEMENT/SERVITUDE LOCATION SHOWN HEREON HAS BEEN SURVEYED ON THE GROUND UNDER MY SUPERVISION AND PREPARED ACCORDING TO THE EVIDENCE FOUND AT THE TIME OF SURVEY. AND DATA PROVIDED BY EGO RESOURCES, INC. THIS CERTIFICATION IS MADE AND LIMITED TO THOSE PERSONS OR ENTITIES SHOWN ON THE FACE OF THIS PLAT AND IS NON-TRANSFERABLE. THIS SURVEY IS CERTIFIED FOR THIS TRANSACTION ONLY.

ALL BEARINGS, DISTANCES, AND COORDINATE VALUES CONTAINED HEREON ARE GRID BASED UPON THE NEW MEXICO STATE PLANE COORDINATE SYSTEM, EAST ZONE OF THE NORTH AMERICAN DATUM 1983, U.S. SURVEY FEET.






1400 EVERMAN PARKWAY, Ste. 197 - FT. WORTH, TEXAS 76140 TELEPHONE: (817) 744-7512 - FAX (817) 744-7548 2993 NORTH BIG SPRING - MIDLAND, TEXAS 78705 TELEPHONE: (432) 682-1653 OR (800) 767-1653 - FAX (432) 682-1743 WWW.70POGRAPHIC.COM





SECTION 16, TOWNSHIP 26-S, RANGE 30-E, N.M.P.M. EDDY COUNTY, NEW MEXICO

DETAIL VIEW SCALE: 1" = 100'



ALL BEARINGS, DISTANCES, AND COORDINATE VALUES CONTAINED HEREON ARE GRID BASED UPON THE NEW MEXICO STATE PLANE COORDINATE SYSTEM, EAST ZONE OF THE NORTH AMERICAN DATUM 1983, U.S. SURVEY FEET

THIS PROPOSED PAD SITE LOCATION SHOWN HEREON HAS BEEN SURVEYED ON THE GROUND UNDER MY SUPERVISION AND PREPARED ACCORDING TO THE EVIDENCE FOUND AT THE TIME OF SURVEY, AND DATA PROVIDED BY EGG RESOURCES, INC. THIS CERTIFICATION IS MADE AND LIMITED TO THOSE PERSONS OR ENTITIES SHOWN ON THE FACE OF THIS PLAT AND IS NON-TRANSFERABLE. THIS SURVEY IS CERTIFICED FOR THIS TRANSACTION ONLY.



1400 EVERMAN PARKWAY, SIe. 197 • FT. WORTH, TEXAS 76140

TELEPHONE: (817) 744-7512 • FAX (817) 744-7548

2903 NORTH BIG SPRING • MIDLAND, TEXAS 79705

TELEPHONE: (432) 682-1653 OR (800) 767-1653 • FAX (432) 682-1743

WWW.TOPOGRAPHIC.COM

= = = = EXISTING ROAD

SECTION LINE PROPOSED ROAD





EXHIBIT 3

eog resources, inc.

SECTION 16, TOWNSHIP 26-S, RANGE 30-E, N.M.P.M. EDDY COUNTY, NEW MEXICO



ALL BEARINGS, DISTANCES, AND COORDINATE VALUES CONTAINED HEREON ARE GRID BASED UPON THE NEW MEXICO STATE PLANE COORDINATE SYSTEM, EAST ZONE OF THE NORTH AMERICAN DATUM 1983, U.S. SURVEY FEET

SCALE: NTS

THIS EASEMENT/SERVITUDE LOCATION SHOWN HEREON HAS BEEN SURVEYED ON THE GROUND UNDER MY SUPERVISION AND PREPARED ACCORDING TO THE EVIDENCE FOUND AT THE TIME OF SURVEY, AND DATA PROVIDED BY EOG RESOURCES, INC. THIS CERTIFICATION IS MADE AND LIMITED TO THOSE PERSONS OR ENTITIES SHOWN ON THE FACE OF THIS PLAT AND IS NON-TRANSFERABLE. THIS SURVEY IS CERTIFIED FOR THIS TRANSACTION ONLY.


#703H LATITUDE


N 32.0359841





1400 EVERMAN PARKWAY, Ste. 197 • FT. WORTH, TEXAS 76140 TELEPHONE: (817) 744-7512 • FAX (817) 744-7548 2903 NORTH BIG SPRING • MIDLAND, TEXAS 79705 TELEPHONE: (432) 682-1653 OR (800) 767-1653 • FAX (432) 682-1743 WWW.TOPOGRAPHIC.COM


#703H LONGITUDE














Surface Use Plan of Operations

Introduction

The following surface use plan of operations will be followed and carried out once the APD is approved. No other disturbance will be created other than what was submitted in this surface use plan. If any other surface disturbance is needed after the APD is approved, a BLM approved sundry notice or right of way application will be acquired prior to any new surface disturbance.

Before any surface disturbance is created, stakes or flagging will be installed to mark boundaries of permitted areas of disturbance, including soils storage areas. As necessary, slope, grade, and other construction control stakes will be placed to ensure construction in accordance with the surface use plan. All boundary markers will be maintained in place until final construction cleanup is completed. If disturbance boundary markers are disturbed or knocked down, they will be replaced before construction proceeds.


If terms and conditions are attached to the approved APD and amend any of the proposed actions in this surface use plan, we will adhere to the terms and conditions.

1. Existing Roads

- a. The existing access road route to the proposed project is depicted on Casey Jones 16 Fed Com 703H vicinity map. Improvements to the driving surface will be done where necessary. No new surface disturbance will be done, unless otherwise noted in the New or Reconstructed Access Roads section of this surface use plan.
- b. The existing access road route to the proposed project does cross lease boundaries and a BLM road right-of-way will be acquired from the BLM prior to construction activities.
- c. The operator will improve or maintain existing roads in a condition the same as or better than before operations begin. The operator will repair pot holes, clear ditches, repair the crown, etc. All existing structures on the entire access route such as cattleguards, other range improvement projects, culverts, etc. will be properly repaired or replaced if they are damaged or have deteriorated beyond practical use.
- d. We will prevent and abate fugitive dust as needed, whether created by vehicular traffic, equipment operations, or wind events. BLM written approval will be acquired before application of surfactants, binding agents, or other dust suppression chemicals on roadways.

2. New or Reconstructed Access Roads

- a. An access road will be needed for this proposed project. See the survey plat for the location of the access road.
- b. The length of access road needed to be constructed for this proposed project is about 361 feet.
- c. The maximum driving width of the access road will be 24 feet. The maximum width of surface disturbance when constructing the access road will not exceed 25 feet. All areas outside of the driving surface will be revegetated.
- d. The access road will be constructed with 6 inches of compacted caliche.
- e. When the road travels on fairly level ground, the road will be crowned and ditched with a 2% slope from the tip of the road crown to the edge of the driving surface. The ditches will be 3 feet wide with 3:1 slopes. See Road Cross Section diagram below.



- f. The access road will be constructed with a ditch on each side of the road.
- g. The maximum grade for the access road will be 2 percent.
- h. No turnouts will be constructed on the proposed access road.
- i. No cattleguards will be installed for this proposed access road.
- j. No BLM right-of-way grant is needed for the construction of this access road.
- k. No culverts will be constructed for this proposed access road.
- 1. No low water crossings will be constructed for the access road.
- m. Since the access road is on level ground, no lead-off ditches will be constructed for the proposed access road.
- n. Newly constructed or reconstructed roads, on surface under the jurisdiction of the Bureau of Land Management, will be constructed as outlined in the BLM "Gold Book" and to meet the standards of the anticipated traffic flow and all anticipated weather requirements as needed. Construction will include ditching, draining, crowning and capping or sloping and dipping the roadbed as necessary to provide a well-constructed and safe road.

3. Location of Existing Wells

- a. Casey Jones 16 Fed Com 703H radius map of the APD depicts all known wells within a one mile radius of the proposed well.
- b. There is no other information regarding wells within a one mile radius.

4. Location of Existing and/or Proposed Production Facilities

- a. All permanent, lasting more than 6 months, above ground structures including but not limited to pumpjacks, storage tanks, barrels, pipeline risers, meter housing, etc. that are not subject to safety requirements will be painted a non-reflective paint color, Shale Green, from the BLM Standard Environmental Colors chart, unless another color is required in the APD Conditions of Approval.
- b. If any type of production facilities are located on the well pad, they will be strategically placed to allow for maximum interim reclamation, recontouring, and revegetation of the well location.
- c. A production facility is proposed to be installed off the proposed well location. Production from the well will be processed at this production facility. Casey Jones 16 Fed Com infrastructure depicts the location of the production facilities.
- d. The proposed production facility will have a secondary containment structure that is constructed to hold the capacity of 1-1/2 times the largest tank, plus freeboard to account for percipitation, unless more stringent protective requirements are deemed necessary.

- e. There is no other diagram that depicts production facilities.
- f. A pipeline to transport production from the proposed well to the production facility will be installed.
 - i. We plan to install a 4 inch buried flex steel pipeline from the proposed well to the offsite production facility. The proposed length of the pipeline will be 504 feet. The working pressure of the pipeline will be about 125 psi. A 50 feet wide work area will be needed to install the buried pipeline. In areas where blading is allowed, topsoil will be stockpiled and separated from the excavated trench mineral material. Final reclamation procedures will match the procedures in Plans for Surface Reclamation. When the excavated soil is backfilled, it will be compacted to prevent subsidence. No berm over the pipeline will be evident.
 - ii. Casey Jones 16 Fed Com infrastructure depicts the proposed production pipeline route from the well to the existing production facility.
 - iii. The proposed pipeline does not cross lease boundaries, so a right of way grant will not need to be acquired from the BLM.

If any plans change regarding the production facility or other infrastructure (pipeline, electric line, etc.), we will submit a sundry notice or right of way (if applicable) prior to installation or construction.

Additional Pipeline(s)

We propose to install 3 additional pipeline(s):

- 1. Buried gas lift pipeline:
 - a. We plan to install a 4 inch buried flex steel pipeline from the proposed well to the central battery. The proposed length of the pipeline will be 504 feet. The working pressure of the pipeline will be about 125 psi. A 50 feet wide work area will be needed to install the buried pipeline. We will need an extra 10 foot wide area near corners to safely install the pipeline. In areas where blading is allowed, topsoil will be stockpiled and separated from the excavated trench mineral material. Final reclamation procedures will match the procedures in Plans for Surface Reclamation. When the excavated soil is backfilled, it will be compacted to prevent subsidence. No berm over the pipeline will be evident.
 - b. Casey Jones 16 Fed Com infrastructure depicts the proposed gas lift pipeline route.
 - c. The proposed pipeline does not cross lease boundaries, so a right of way grant will not need to be acquired from the BLM.
- 2. Buried produced water pipeline:
 - a. We plan to install a 24 inch buried poly pipeline from the central battery to the water disposal tie-in. The proposed length of the pipeline will be 13363 feet. The working pressure of the pipeline will be about 125 psi. A 50 feet wide work area will be needed to install the buried pipeline. We will need an extra 10 foot wide area near corners to safely install the pipeline. In areas where blading is allowed, topsoil will be stockpiled and separated from the excavated trench mineral material. Final reclamation procedures will match the procedures in Plans for Surface Reclamation. When the excavated soil is backfilled, it will be compacted to prevent subsidence. No berm over the pipeline will be evident.
 - b. Casey Jones 16 Fed Com WGS main line depicts the proposed produced water pipeline route.
 - c. Since the proposed pipeline crossess lease boundaries, a right of way grant will be acquired prior to installation of the proposed pipeline.

SHL: 260 FSL & 2000 FWL, Section: 16, T.26S., R.30E.

BHL: 230 FNL & 1660 FWL, Section: 9, T.26S., R.30E.

3. Buried gas sales pipeline:

a. We plan to install a 20 inch buried steel pipeline from the central battery to the gas sales tiein. The proposed length of the pipeline will be 10686 feet. The working pressure of the pipeline
will be about 125 psi. A 50 feet wide work area will be needed to install the buried pipeline. We
will need an extra 10 foot wide area near corners to safely install the pipeline. In areas where
blading is allowed, topsoil will be stockpiled and separated from the excavated trench mineral
material. Final reclamation procedures will match the procedures in Plans for Surface
Reclamation. When the excavated soil is backfilled, it will be compacted to prevent subsidence.
No berm over the pipeline will be evident.

- b. Casey Jones 16 Fed Com GGS trunk line depicts the proposed gas sales pipeline route.
- c. Since the proposed pipeline crossess lease boundaries, a right of way grant will be acquired prior to installation of the proposed pipeline.

Electric Line(s)

- a. We plan to install an overhead electric line for the proposed well. The proposed length of the electric line will be 102 feet. Casey Jones 16 Fed Com electric line depicts the location of the proposed electric line route. The electric line will be construction to provide protection from raptor electrocution.
- b. The proposed electric line does not cross lease boundaries, so a right of way grant will not need to be acquired from the BLM.

5. Location and Types of Water

- a. The source and location of the water supply are as follows: Water will be supplied from the frac pond as shown on the attached water source map This location will be drilled using a combination of water mud systems (outlined in the drilling program) The water will be obtained from commercial water stations in the area or recycled treated water and hauled to location by trucks or poly pipelines using existing and proposed roads depicted on the proposed existing access road maps In these cases where a poly pipeline is used to transport fresh water for drilling purposes_ proper authorizations will be secured by the contractor.
- b. Casey Jones 16 Fed Com water source and caliche map depicts the proposed route for a 12 inch poly temporary (<90 days) water pipeline supplying water for drilling operations.

6. Construction Material

a. Caliche will be supplied from pits shown on the attached caliche source map.

Caliche utilized for the drilling pad will be obtained either from an existing approved mineral pit, or by benching into a hill, which will allow the pad to be level with existing caliche from the cut, or extracted by "Flipping" the well location. A mineral material permit will be obtained from BLM prior to excavating any caliche on Federal Lands. Amount will vary for each pad. The procedure for "Flipping" a well location is as follows:

- -An adequate amount of topsoil/root zone (usually top 6 inches of soil) will be stripped from the proposed well location and stockpiled along the side of the well location as depicted on the well site diagram/survey plat.
- -An area will be used within the proposed well site dimensions to excavate caliche.
- Subsoil will be removed and stockpiled within the surveyed well pad dimensions.
- -Once caliche/surfacing mineral is found, the mineral material will be excavated and stock piled within the approved drilling pad dimensions.
- -Then, subsoil will be pushed back in the excavated hole and caliche will be spread accordingly across the entire well pad and road (if available).
- -Neither caliche, nor subsoil will be stock piled outside of the well pad dimensions. Topsoil will be stockpiled

SHL: 260 FSL & 2000 FWL, Section: 16, T.26S., R.30E.

BHL: 230 FNL & 1660 FWL, Section: 9, T.26S., R.30E.

along the edge of the pad as depicted in the Well Site Layout or survey plat.

In the event that no caliche is found onsite, caliche will be hauled in from a BLM approved caliche pit or other established mineral pit. A BLM mineral material permit will be acquired prior to obtaining any mineral material from BLM pits or federal land.

7. Methods for Handling Waste

- a. Drilling fluids and produced oil and water from the well during drilling and completion operations will be stored safely and disposed of properly in an NMOCD approved disposal facility.
- b. Garbage and trash produced during drilling and completion operations will be collected in a trash container and disposed of properly at a state approved disposal facility. All trash on and around the well site will be collected for disposal.
- c. Human waste and grey water will be properly contained and disposed of properly at a state approved disposal facility.
- d. After drilling and completion operations, trash, chemicals, salts, frac sand and other waste material will be removed and disposed of properly at a state approved disposal facility.
- e. The well will be drilled utilizing a closed loop system. Drill cutting will be properly disposed of into steel tanks and taken to an NMOCD approved disposal facility.

8. Ancillary Facilities

a. No ancillary facilities will be needed for this proposed project.

9. Well Site Layout

- a. The following information is presented in the well site survey plat or diagram:
 - i. reasonable scale (near 1":50')
 - ii. well pad dimensions
 - iii. well pad orientation
 - iv. drilling rig components
 - v. proposed access road
 - vi. elevations of all points
 - vii. topsoil stockpile
 - viii. reserve pit location/dimensions if applicable
 - ix. other disturbances needed (flare pit, stinger, frac farm pad, etc.)
 - x. existing structures within the 600' x 600' archaeoligical surveyed area (pipelines, electric lines, well pads, etc
- b. The proposed drilling pad was staked and surveyed by a professional surveyor. The attached survey plat of the well site depicts the drilling pad layout as staked.
- c. A title of a well site diagram is Casey Jones 16 Fed Com 703H rig layout. This diagram depicts the rig layout.
- d. Topsoil Salvaging
 - i. Grass, forbs, and small woody vegetation, such as mesquite will be excavated as the topsoil is removed.

Large woody vegetation will be stripped and stored separately and respread evenly on the site following topsoil respreading. Topsoil depth is defined as the top layer of soil that contains 80% of the roots. In areas to be heavily disturbed, the top 6 inches of soil material, will be stripped and stockpiled on the perimeter of the well location and along the perimeter of the access road to control run-on and run-off, to keep topsoil viable, and to make redistribution of topsoil more efficient during interim reclamation. Stockpiled topsoil should include vegetative material. Topsoil will be clearly segregated and stored separately from subsoils. Contaminated soil will not be stockpiled, but properly treated and handled prior to topsoil salvaging.

10. Plans for Surface Reclamation

Reclamation Objectives

- i. The objective of interim reclamation is to restore vegetative cover and a portion of the landform sufficient to maintain healthy, biologically active topsoil; control erosion; and minimize habitat and forage loss, visual impact, and weed infestation, during the life of the well or facilities.
- ii. The long-term objective of final reclamation is to return the land to a condition similar to what existed prior to disturbance. This includes restoration of the landform and natural vegetative community, hydrologic systems, visual resources, and wildlife habitats. To ensure that the long-term objective will be reached through human and natural processes, actions will be taken to ensure standards are met for site stability, visual quality, hydrological functioning, and vegetative productivity.
- iii. The BLM will be notified at least 3 days prior to commencement of any reclamation procedures.
- iv. If circumstances allow, interim reclamation and/or final reclamation actions will be completed no later than 6 months from when the final well on the location has been completed or plugged. We will gain written permission from the BLM if more time is needed.
- v. Interim reclamation will be performed on the well site after the well is drilled and completed. Casey Jones 16 Fed Com 703H interim reclamation depicts the location and dimensions of the planned interim reclamation for the well site.

Interim Reclamation Procedures (If performed)

- 1. Within 30 days of well completion, the well location and surrounding areas will be cleared of, and maintained free of, all materials, trash, and equipment not required for production.
- 2. In areas planned for interim reclamation, all the surfacing material will be removed and returned to the original mineral pit or recycled to repair or build roads and well pads.
- 3. The areas planned for interim reclamation will then be recontoured to the original contour if feasible, or if not feasible, to an interim contour that blends with the surrounding topography as much as possible. Where applicable, the fill material of the well pad will be backfilled into the cut to bring the area back to the original contour. The interim cut and fill slopes prior to re-seeding will not be steeper than a 3:1 ratio, unless the adjacent native topography is steeper. Note: Constructed slopes may be much steeper during drilling, but will be recontoured to the above ratios during interim reclamation.
- 4. Topsoil will be evenly respread and aggressively revegetated over the entire disturbed area not needed for all-weather operations including cuts & fills. To seed the area, the proper BLM seed mixture, free of noxious weeds, will be used. Final seedbed preparation will consist of contour cultivating to a depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting in order to break the soil crust and create seed germination micro-sites.
- 5. Proper erosion control methods will be used on the area to control erosion, runoff and siltation of the

SHL: 260 FSL & 2000 FWL, Section: 16, T.26S., R.30E.

BHL: 230 FNL & 1660 FWL, Section: 9, T.26S., R.30E.

surrounding area.

6. The interim reclamation will be monitored periodically to ensure that vegetation has reestablished and that erosion is controlled.

Final Reclamation (well pad, buried pipelines, etc.)

- 1. Prior to final reclamation procedures, the well pad, road, and surrounding area will be cleared of material, trash, and equipment.
- 2. All surfacing material will be removed and returned to the original mineral pit or recycled to repair or build roads and well pads.
- 3. All disturbed areas, including roads, pipelines, pads, production facilities, and interim reclaimed areas will be recontoured to the contour existing prior to initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to recontouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation.
- 4. After all the disturbed areas have been properly prepared, the areas will be seeded with the proper BLM seed mixture, free of noxious weeds. Final seedbed preparation will consist of contour cultivating to a depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting in order to break the soil crust and create seed germination micro-sites.
- 5. Proper erosion control methods will be used on the entire area to control erosion, runoff and siltation of the surrounding area.
- 6. All unused equipment and structures including pipelines, electric line poles, tanks, etc. that serviced the well will be removed.
- 7. All reclaimed areas will be monitored periodically to ensure that revegetation occurs, that the area is not redisturbed, and that erosion is controlled.

11. Surface Ownership

a. The surface ownership of the proposed project is State of New Mexico.

12. Other Information

a. An onsite meeting was conducted 03/28/17.

We plan to use 2, 12-inch lay flat hoses to transport water with an option to use 7, 4-inch poly lines for drilling and frac operations.

We are asking for 4 associated pipelines all depicted on the attached Casey Jones 16 Fed Com infrastructure sketch:

One 4-inch flex steel gas lift line per well

One 4-inch flex steel production flowline per well

One 24-inch produced water disposal from the CTB to the existing disposal line.

One 20-inch gas sales line from the CTB to the gas sales tie-in.

The well is planned to be produced using gas lift as the artificial lift method.

Produced water will be transported via pipeline to the EOG produced water gathering system.

13. Maps and Diagrams

Casey Jones 16 Fed Com 703H vicinity map - Existing Road

EOG Resources, Inc. Casey Jones 16 Fed Com 703H SHL: 260 FSL & 2000 FWL, Section: 16, T.26S., R.30E. BHL: 230 FNL & 1660 FWL, Section: 9, T.26S., R.30E.

Casey Jones 16 Fed Com 703H radius map - Wells Within One Mile

Casey Jones 16 Fed Com infrastructure - Production Facilities Diagram

Casey Jones 16 Fed Com infrastructure - Production Pipeline

Casey Jones 16 Fed Com infrastructure - gas lift Pipeline

Casey Jones 16 Fed Com WGS main line - produced water Pipeline

Casey Jones 16 Fed Com GGS trunk line - gas sales Pipeline


Casey Jones 16 Fed Com electric line - Electric Line

Casey Jones 16 Fed Com water source and caliche map - Drilling Water Pipeline

Casey Jones 16 Fed Com 703H rig layout - Well Site Diagram

Casey Jones 16 Fed Com 703H interim reclamation - Interim Reclamation

LOCATION & ELEVATION VERIFICATION MAP



eog resources, inc.


LEASE NAME & WELL NO.: CASEY JONES 16 FED COM #703H

 SECTION
 16
 TWP
 26-S
 RGE
 30-E
 SURVEY
 N.M.P.M.

 COUNTY
 EDDY
 STATE
 NM
 ELEVATION
 3034'

 DESCRIPTION
 260' FSL & 2000' FWL

LATITUDE N 32.0359841 LONGITUDE W 103.8884125



THIS EASEMENT/SERVITUDE LOCATION SHOWN HEREON HAS BEEN SURVEYED ON THE GROUND UNDER MY SUPERVISION AND PREPARED ACCORDING TO THE EVIDENCE FOUND AT THE TIME OF SURVEY, AND DATA PROVIDED BY EOG RESOURCES, INC. THIS CERTIFICATION IS MADE AND LIMITED TO THOSE PERSONS OR ENTITIES SHOWN ON THE FACE OF THIS PLAT AND IS NON-TRANSFERABLE. THIS SURVEY IS CERTIFIED FOR THIS TRANSACTION ONLY,

ALL BEARINGS, DISTANCES, AND COORDINATE VALUES CONTAINED HEREON ARE GRID BASED UPON THE NEW MEXICO STATE PLANE COORDINATE SYSTEM, EAST ZONE OF THE NORTH AMERICAN DATUM 1983, U.S. SURVEY FEET.



1400 EVERMAN PARKWAY, Ste. 197 • FT. WORTH, TEXAS 76140 TELEPHONE: (817) 744-7512 • FAX. (817) 744-7548 2903 NORTH BIG SPRING • MIDLAND, TEXAS 79705 TELEPHONE: (432) 682-1653 OR (800) 767-1653 • FAX. (432) 682-1743 WWW.TOPOGRAPHIC.COM



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT



Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits Would you like to utilize Lined Pit PWD options? NO Produced Water Disposal (PWD) Location: PWD surface owner: PWD disturbance (acres): Lined pit PWD on or off channel: Lined pit PWD discharge volume (bbl/day): Lined pit specifications: Pit liner description: Pit liner manufacturers information: Precipitated solids disposal: Decribe precipitated solids disposal: Precipitated solids disposal permit: Lined pit precipitated solids disposal schedule: Lined pit precipitated solids disposal schedule attachment: Lined pit reclamation description:

Linea pit reciantation description

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment:

Section 3 - Unlined Pits Would you like to utilize Unlined Pit PWD options? NO Produced Water Disposal (PWD) Location: PWD surface owner: PWD disturbance (acres): Unlined pit PWD on or off channel: Unlined pit PWD discharge volume (bbl/day): Unlined pit specifications: Precipitated solids disposal: Decribe precipitated solids disposal: Precipitated solids disposal permit: Unlined pit precipitated solids disposal schedule: Unlined pit precipitated solids disposal schedule attachment: Unlined pit reclamation description: Unlined pit reclamation attachment: Unlined pit Monitor description: Unlined pit Monitor attachment: Do you propose to put the produced water to beneficial use? Beneficial use user confirmation: Estimated depth of the shallowest aquifer (feet): Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected? TDS lab results: Geologic and hydrologic evidence: State authorization: Unlined Produced Water Pit Estimated percolation: Unlined pit: do you have a reclamation bond for the pit? Is the reclamation bond a rider under the BLM bond? Unlined pit bond number: Unlined pit bond amount: Additional bond information attachment: Section 4 - Injection Would you like to utilize Injection PWD options? NO **Produced Water Disposal (PWD) Location:**

PWD disturbance (acres):

Injection PWD discharge volume (bbl/day):

PWD surface owner:

Injection well mineral owner:

| Injection well type: | |
|---|-------------------------|
| Injection well number: | Injection well name: |
| Assigned injection well API number? | Injection well API numb |
| Injection well new surface disturbance (acres): | |
| Minerals protection information: | |
| Mineral protection attachment: | |
| Underground Injection Control (UIC) Permit? | |
| UIC Permit attachment: | |
| Section 5 - Surface Discharge | |
| Would you like to utilize Surface Discharge PWD options? NO | |
| Produced Water Disposal (PWD) Location: | |
| PWD surface owner: | PWD disturbance (acre |
| Surface discharge PWD discharge volume (bbl/day): | |
| Surface Discharge NPDES Permit? | |
| Surface Discharge NPDES Permit attachment: | |
| Surface Discharge site facilities information: | |
| Surface discharge site facilities map: | |
| Section 6 - Other | |
| Would you like to utilize Other PWD options? NO | |
| Produced Water Disposal (PWD) Location: | |
| PWD surface owner: | PWD disturbance (acre |
| Other PWD discharge volume (bbl/day): | |
| Other PWD type description: | |
| Other PWD type attachment: | |
| Have other regulatory requirements been met? | |
| Other regulatory requirements attachment: | |

TAFMSS

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Bond Info Data Report 02/06/2018

Bond Information

Federal/Indian APD: FED

BLM Bond number: NM2308

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment: