# DISTRICT I 1625 N. French Dr., Hobbs, NM 88240 NM O!L CONSERVATIONS of New Mexico

District II 811 S. First St., Artesia, NM 89210

District I

ARTESIMENSTANDTherals and Natural Resources Department

Submit Original to Appropriate District Office

District III 1000 Rio Brazos Road, Aztec, NM 874 1 0 1220 S. St. Francis Dr., Santa Fe, NM 87505

FEB 07 2018 Oil Conservation Division 1220 South St. Francis Dr.

GAS (	CAPTURE BLAN	NM OIL CONSERVATION		
	CAPTURE PLAN	ARTESIA DISTRICT		
		FEB 07 2018		
Operator & OGRID No.: Mack Energy Corporation - 013837				
•		RECEIVED		
	-	II/production facility flaring/venting for		
	taken by the			

## Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Prince George Fed Com #111	30-005	Sec. 29 T15S R29E	200 FSL 2285 FEL	50		
	64310					

Note: James C. Demostic Suburgia Unit growing a reservation (III line all models and Subsection 1939) INDER MARC

#### Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to DCP Midstream and will be connected to DCP Midstream low/high pressure gathering system located in Chaves County, New Mexico. It will require 0 (existing) of pipeline to connect the facility to low/high pressure gathering system. Mack Energy Corporaiton provides (periodically) to DCP Midstream a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Mack Energy Corporaton and DCP Midstream have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at DCP Midstream Linam Ranch Processing Plant located in Sec. 6 Twn. 19S , Rng. 37E Lea County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

#### Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on DCP Midstream system at that time. Based on current information, it is Mack Energy Corporation belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the Use Of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

### Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

• Power Generation - On lease

Only a portion of gas is consumed operating the generator, remainder of gas will be flared Compressed Natural Gas - On lease

Gas flared would be minimal, but might be uneconomical to operate when gas volume declines

Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines