Office	To Appropriate Distri		State of New Mexico			Form C-103 Revised July 18, 2013	
	n Dr., Hobbs, NM 882	•••	Energy, Minerals and Natural Resources		WELL API NO.		
	, Artesia, NM 88210		OIL CONSERVATION DIVISION		30-015-44558 5. Indicate Type of		
1000 Rio Brazo	District III - (505) 334-6178 1220 South St. Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505				STATE 🔯 6. State Oil & Gas I		
1220 S. St. Francis Dr., Santa Fe, NM 87505					LG-1525		
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH					7. Lease Name or Unit Agreement Name Dee State Com		
PROPOSALS.)  1. Type of Well: Oil Well  Gas Well  Other					8. Well Number 1H	ļ	
2. Name of Operator					9. OGRID Number		
EOG Resources, Inc.  3. Address of Operator					7377 10. Pool name or W	Vildcat	
104 South Fourth Street, Artesia, NM 88210					N. Seven Rivers; Gl		
4. Well Location							
Unit Letter M : 755 feet from the South line and 165 feet from the West line Unit Letter P 350 feet from the South line and 230 feet from the East line							
Section 36 Township 19S Range 24E NMPM Eddy County							
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3630' GR							
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data							
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:							
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING							
	TEMPORARILY ABANDON						
PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEMENT JOB   DOWNHOLE COMMINGLE							
CLOSED-LOOP SYSTEM							
OTHER:				OTHER: Production			
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of							
proposed completion or recompletion.							
1/24/18 – TD 8-3/4" vertical hole to 4150'.							
1/27/18-1/29/18 - Pulled up hole to 4130' and pumped a 75 sx Class "C" Neat cement plug (yld 1.32, wt 14.8). Pumped 5.2 bbls FW and							
50.1 bbls mud to displace cement and balance the plug. RIH with baker whipstock assembly. Top of slide at 1835'. Bottom of slide at							
1846'. Cemented whipstock with 200 sx Class "H" cement (yld 0.94, wt 17.5). Pump FW and mud to displace cement and balance the plug. WOC for 24 hrs prior to kick off. Tagged hard cement at 1712'. Drilled cement from 1712'- 1735' KOP. RIH with 8-1/2" bit and							
continued drilling directional.							
2/5/18 – Reached TD 8-1/2" hole to 7273' at 3:00 AM.							
2/7/18 – Ran tapered string 7" x 5-1/2" casing and set at 7203'. Cemented with 150 sx lead cement (yld 2.47, wt 11.9) and tailed in with 900 sx (yld 1.48, wt 13). Displaced cement with fresh water. Pressured up to 1530 psi, held good for 5 min. Full circulation during							
cement job. Verified density with pressurized mud balance on both lead and tail. Circulated 11 sx cement to surface. ND BOP							
2/8/18 – Rig released at 3:00 PM.  NM OIL CONSERVATION  ARTES/A DISTRICT							
Spud Date:	1/	9/18	Rig Release Date	a.	2/8/18	FEB <b>2 0</b> 2618	
Spud Date.			Rig Release Dan				
**************************************							
I hereby certify that the information above is true and complete to the best of my knowledge and belief.							
SIGNATURE (Vine) Lucria TITLE Regulatory Specialist DATE February 15, 2018							
Type or print name Tina Huerta E-mail address: tina huerta@eogresources.com PHONE: 575-748-4168							
For State Use		<u>—</u> .	_				
APPROVED BY: DATE 2-2)-18 Conditions of Approval (if any):							
Conditions of	ryphronai (ii aiià)	•					