Submit 3 Copies To Appropriate District Office	State of New Mexico Energy, Minerals and Natural Resources		Form C-103 Revised March 25, 1999	
District I 1625 N. French Dr., Hobbs, NM 88240			WELL API NO.	
<u>District II</u> 811 South First, Artesia, NM 88210	OIL CONSERVATION DIVISION		30-015-34589	CI
District III	1220 South St. Francis Dr.		5. Indicate Type of Lease STATE X FEE	
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u>	Santa Fe, NM 87505		6. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM 87505				
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well X Other			7. Lease Name or Unit Agreement Name: Wisetail State Com	
2. Name of Operator	RECE	NEC	8. Well No.	
Yates Drilling Company	, , , _ .		1	
3. Address of Operator	APR 1 9 2006		9. Pool name or Wildcat	
105 South 4 th St., Artesia,	NM 88210 UUU-AMIEOM		Wildcat Chester	
4. Well Location				
Unit Letter A: 660' feet from the North line and 990' feet from the East line				
Section 24	Township 18S Range		мрм Eddy	County
10. Elevation (Show whether DR, RKB, RT, GR, etc.)				
3595' GL				
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
				ALTERING
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WOR	к	CASING
TEMPORARILY ABANDON	CHANGE PLANS MULTIPLE			PLUG AND ABANDONMENT
PULL OR ALTER CASING	COMPLETION	CEMENT JOB	X	
OTHER:		OTHER:		
Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.				
TD 2,520', 12 ¼" hole at 2:15 PM, 4/7/2006. Ran 59 jts., 9 5/8", 36# J-55 ST&C casing, set at 2520'. Float shoe set at 2520' and float collar set at 2478.55'. Cemented with 700 sxs. BJ Lite 65:35:6 + ¼# Celloflake + 2% CaCl2 (yld 1.88, wt 12.8). Tailed in with 225 sxs Class "C" + 2% CaCl2 (yld 1.34, wt 14.8). PD at 12:00 AM, 4/8/2006. Bumped plug to 1800 psi, held OK. Circulated 114 sxs to pit. Centralizers on jts. 1,2, 5,8,11 and 14. WOC 31 hrs. Reduced hole to 8 ¾" and resumed drilling at 7:00 AM, 4/9/2006. NMOCD notified of running and cementing casing, did not witness.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Lessman TITLE Operations Tech DATE 4/17/2006				
Type or print name Karen J. I	eishman	Telephone No. 50)5-748-8463	
(This space for State use) APPPROVED BY Conditions of approval, if any:	R RECORDS ONLY			APR 1 9 2006 DATE