District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

# State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division OIL CONSERVATION
1220 South St. Francis Dr.

Santa Fe, NM 87505

JUN 2 5 2018

#### GAS CAPTURE PLAN

		0.10 0.11 10		•
	Operator: Apache Corporation	OGRID No:	873	Date:6/15/2018
☐ Amended				Date:
Reasor	for Amendment:			
	ure Plan outlines actions to be ta n (new drill, recomplete to new zo			educe well/production facility flaring/venting for

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

### Well(s)/Production Facility - Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Palmillo 26 State Com  (213H)	30-015-45040	Sec 26 T19S R28E	1580' FNL & 230' FEL	500	Flared	Flared only in emergency
Palmillo 26 State Com 214H	30-015-45041	Sec 26 T19S R28E	740' FNL & 230' FEL	500	Flared	Flared only in emergency

# **Gathering System and Pipeline Notification**

#### Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on **DCP MIDSTREAM LP** system at that time. Based on current information, it is Apache Corporation's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

## **Alternatives to Reduce Flaring**

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines