	State of New Mexico	Form C-103
Office <u>District I</u> – (575) 393-6161	Energy, Minerals and Natural Resources	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
<u>District II</u> – (575) 748-1283 811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-015-44261
<u>District III</u> – (505) 334-6178	1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460	Santa Fe, NM 87505	STATE FEE
1220 S. St. Francis Dr., Santa Fe, NM	5unta 1 0, 14141 07505	6. State Oil & Gas Lease No.
87505		
	CES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR LISE "APPLIC	SALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A CATION FOR PERMIT" (FORM C-101) FOR SUCH	Chicago 9/8 W0IL Fee Com
PROPOSALS.)	ATION TORTERWIT (FORM C-101) FOR SUCH	8. Well Number
1. Type of Well: Oil Well	Gas Well 🛛 Other	1H
2. Name of Operator		9. OGRID Number
Mewbourne Oil Company		14744
3. Address of Operator		10. Pool name or Wildcat
PO Box 5270, Hobbs NM 88240		Purple Sage; Wolfcamp (Gas) 98220
4. Well Location		
Unit Letter H : 23	00feet from the _North line and33	feet from the East line
Section 9	Township 24S Range 28E NMP	
	11. Elevation (Show whether DR, RKB, RT, GR, of	
	3010' GL	
12 Check A	ppropriate Box to Indicate Nature of Notice	a Panert or Other Data
12. Check A	appropriate box to indicate Nature of Notice	e, Report of Other Data
NOTICE OF IN	TENTION TO: SI	JBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON   REMEDIAL W	
TEMPORARILY ABANDON		DRILLING OPNS. □ P AND A □
PULL OR ALTER CASING	MULTIPLE COMPL CASING/CEMI	<del>-</del>
DOWNHOLE COMMINGLE	MOETH EE SOME GAOING/SEM	- M 100
CLOSED-LOOP SYSTEM		
OTHER:	□ OTHER:	П
	eted operations. (Clearly state all pertinent details,	and give pertinent dates, including estimated date
of starting any proposed wo	rk). SEE RULE 19.15.7.14 NMAC. For Multiple	Completions: Attach wellbore diagram of
of starting any proposed wo	rk). SEE RULE 19.15.7.14 NMAC. For Multiple	Completions: Attach wellbore diagram of
of starting any proposed wo	rk). SEE RULE 19.15.7.14 NMAC. For Multiple	Completions: Attach wellbore diagram of
of starting any proposed wo proposed completion or reco	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer	Completions: Attach wellbore diagram of atted w/300 sks Class C w/additives. Mixed @
of starting any proposed wo proposed completion or reco 06/16/18TD'ed 8 3/4" hole @ 9717' 10.0#/g w/3.17 yd. Followed w/100 s	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemerals Lite Class C (60:40:0) w/additives. Mixed @ 11	Completions: Attach wellbore diagram of uted w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2)
of starting any proposed wo proposed completion or reconcept (10.01/18TD'ed 8 3/4" hole @ 9717' 10.01/19 w/3.17 yd. Followed w/100 sw/additives. Mixed @ 14.21/19 w/1.20	rk). SEE RULE 19.15.7.14 NMAC. For Multiple of Completion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemerals Lite Class C (60:40:0) w/additives. Mixed @ 11 of yd. Displaced w/358 bbls OBM. Plug down @ 1:4	Completions: Attach wellbore diagram of atted w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) to AM 06/17/18. Did not circ cmt. Est TOC @
of starting any proposed wo proposed completion or reconstruction of the completion of reconstruction of the complete of the c	rk). SEE RULE 19.15.7.14 NMAC. For Multiple of Completion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer iks Lite Class C (60:40:0) w/additives. Mixed @ 11:6 yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k	Completions: Attach wellbore diagram of atted w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) to AM 06/17/18. Did not circ cmt. Est TOC @
of starting any proposed wo proposed completion or reconcept (10.01/18TD'ed 8 3/4" hole @ 9717' 10.01/19 w/3.17 yd. Followed w/100 sw/additives. Mixed @ 14.21/19 w/1.20	rk). SEE RULE 19.15.7.14 NMAC. For Multiple of Completion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer iks Lite Class C (60:40:0) w/additives. Mixed @ 11:6 yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k	Completions: Attach wellbore diagram of atted w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) to AM 06/17/18. Did not circ cmt. Est TOC @
of starting any proposed wo proposed completion or reco 06/16/18TD'ed 8 3/4" hole @ 9717' 10.0#/g w/3.17 yd. Followed w/100 s w/additives. Mixed @ 14.2#/g w/1.20 2150'. Lift pressure 300# @ 3 BPM. mins, held OK. FIT test to 12.5 PPG	rk). SEE RULE 19.15.7.14 NMAC. For Multiple of Completion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer cks Lite Class C (60:40:0) w/additives. Mixed @ 116 yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.	Completions: Attach wellbore diagram of atted w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) 15 AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion of recompletion of recompletion of recompletion of the start of t	rk). SEE RULE 19.15.7.14 NMAC. For Multiple of completion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer iks Lite Class C (60:40:0) w/additives. Mixed @ 116 yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD	Completions: Attach wellbore diagram of the w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) s AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion of recompletion of the start of t	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer iks Lite Class C (60:40:0) w/additives. Mixed @ 116 yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD 24/g w/2.86 yd. Released dart. Displaced w/245 bbl	Completions: Attach wellbore diagram of ted w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) 5 AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C s BW. Plug down @ 4:00 A.M. 07/02/18. Bump
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion of recompletion of the start of t	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemeriks Lite Class C (60:40:0) w/additives. Mixed @ 116 yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD 2#/g w/2.86 yd. Released dart. Displaced w/245 bbls release from liner. Displaced 7" csg w/220 bbls B	Completions: Attach wellbore diagram of ted w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) 5 AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C s BW. Plug down @ 4:00 A.M. 07/02/18. Bump W. Circ 78 sks of cmt off of liner top to the pit.
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion of recompletion of the start of t	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer iks Lite Class C (60:40:0) w/additives. Mixed @ 116 yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD 24/g w/2.86 yd. Released dart. Displaced w/245 bbl	Completions: Attach wellbore diagram of ted w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) 5 AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C s BW. Plug down @ 4:00 A.M. 07/02/18. Bump W. Circ 78 sks of cmt off of liner top to the pit.
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion of recompletion of recompletion of recompletion of the start o	rk). SEE RULE 19.15.7.14 NMAC. For Multiple of Completion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemeroks Lite Class C (60:40:0) w/additives. Mixed @ 116 yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD 2#/g w/2.86 yd. Released dart. Displaced w/245 bbl crelease from liner. Displaced 7" csg w/220 bbls But to 1500# for 30 mins, held OK. Top of liner @ 89	Completions: Attach wellbore diagram of the wide wide wide wide wide wide wide wid
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion of recompletion of the start of t	rk). SEE RULE 19.15.7.14 NMAC. For Multiple of Completion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemeroks Lite Class C (60:40:0) w/additives. Mixed @ 116 yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD 2#/g w/2.86 yd. Released dart. Displaced w/245 bbl crelease from liner. Displaced 7" csg w/220 bbls But to 1500# for 30 mins, held OK. Top of liner @ 89	Completions: Attach wellbore diagram of ted w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) 5 AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C s BW. Plug down @ 4:00 A.M. 07/02/18. Bump W. Circ 78 sks of cmt off of liner top to the pit.
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion of recompletion of recompletion of the start o	rk). SEE RULE 19.15.7.14 NMAC. For Multiple of completion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer lks Lite Class C (60:40:0) w/additives. Mixed @ 11 for the complete of	Completions: Attach wellbore diagram of the wide wide wide wide wide wide wide wid
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion of recompletion of recompletion of recompletion of the start o	rk). SEE RULE 19.15.7.14 NMAC. For Multiple of Completion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemeroks Lite Class C (60:40:0) w/additives. Mixed @ 116 yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD 2#/g w/2.86 yd. Released dart. Displaced w/245 bbl crelease from liner. Displaced 7" csg w/220 bbls But to 1500# for 30 mins, held OK. Top of liner @ 89	Completions: Attach wellbore diagram of the wide wide wide wide wide wide wide wid
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion of recompletion of recompletion of the start o	rk). SEE RULE 19.15.7.14 NMAC. For Multiple of completion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer lks Lite Class C (60:40:0) w/additives. Mixed @ 11 for the complete of	Completions: Attach wellbore diagram of the wide wide wide wide wide wide wide wid
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion of recompletion or recompletion of the complete of the complet	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer iks Lite Class C (60:40:0) w/additives. Mixed @ 11 is yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD is release from liner. Displaced w/245 bbl is release from liner. Displaced 7" csg w/220 bbls Boto 1500# for 30 mins, held OK. Top of liner @ 89 is Rig Release Date: 07/03/201	Completions: Attach wellbore diagram of the wide wide wide wide wide wide wide wid
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion of recompletion or recompletion of the complete of the complet	rk). SEE RULE 19.15.7.14 NMAC. For Multiple of completion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer lks Lite Class C (60:40:0) w/additives. Mixed @ 11 for the complete of	Completions: Attach wellbore diagram of the wide wide wide wide wide wide wide wid
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion of recompletion or recompletion of the complete of the complet	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer iks Lite Class C (60:40:0) w/additives. Mixed @ 11 is yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD is w/2.86 yd. Released dart. Displaced w/245 bbl is release from liner. Displaced 7" csg w/220 bbls Boto 1500# for 30 mins, held OK. Top of liner @ 89 is it is release Date: 07/03/2010 is release Date: 07/03/2010 is release Date: 07/03/2010 is release Date: 07/03/2010 is true and complete to the best of my knowledge.	Completions: Attach wellbore diagram of the dw/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) is AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C is BW. Plug down @ 4:00 A.M. 07/02/18. Bump W. Circ 78 sks of cmt off of liner top to the pit. 85'
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion of recompletion or recompletion of the complete of the complet	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer iks Lite Class C (60:40:0) w/additives. Mixed @ 11 is yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD is w/2.86 yd. Released dart. Displaced w/245 bbl is release from liner. Displaced 7" csg w/220 bbls Boto 1500# for 30 mins, held OK. Top of liner @ 89 is it is release Date: 07/03/2010 is release Date: 07/03/2010 is release Date: 07/03/2010 is release Date: 07/03/2010 is true and complete to the best of my knowledge.	Completions: Attach wellbore diagram of the dw/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) is AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C is BW. Plug down @ 4:00 A.M. 07/02/18. Bump W. Circ 78 sks of cmt off of liner top to the pit. 85'
of starting any proposed wo proposed completion or recompletion or recompletion or recompletion or recompletion or recompletion of recompletion or recompletion of the complete of the complet	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer iks Lite Class C (60:40:0) w/additives. Mixed @ 11 is yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD is release from liner. Displaced w/245 bbl is release from liner. Displaced 7" csg w/220 bbls Boto 1500# for 30 mins, held OK. Top of liner @ 89 is Rig Release Date: 07/03/201	Completions: Attach wellbore diagram of the dw/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) is AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C is BW. Plug down @ 4:00 A.M. 07/02/18. Bump W. Circ 78 sks of cmt off of liner top to the pit. 85'
of starting any proposed wo proposed completion or recompletion of the following with the foll	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer lks Lite Class C (60:40:0) w/additives. Mixed @ 11 for yellow ye	Completions: Attach wellbore diagram of the w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) is AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C is BW. Plug down @ 4:00 A.M. 07/02/18. Bump W. Circ 78 sks of cmt off of liner top to the pit. 85'  RECEIVED  8  JUL 1 9 2018  DISTRICT II-ARTESIA O.C.D.  DATE _07/10/18
of starting any proposed wo proposed completion or recompletion of the completion of	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer iks Lite Class C (60:40:0) w/additives. Mixed @ 11 is yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD is w/2.86 yd. Released dart. Displaced w/245 bbl is release from liner. Displaced 7" csg w/220 bbls Boto 1500# for 30 mins, held OK. Top of liner @ 89 is it is release Date: 07/03/2010 is release Date: 07/03/2010 is release Date: 07/03/2010 is release Date: 07/03/2010 is true and complete to the best of my knowledge.	Completions: Attach wellbore diagram of the w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) is AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C is BW. Plug down @ 4:00 A.M. 07/02/18. Bump W. Circ 78 sks of cmt off of liner top to the pit. 85'  RECEIVED  8  JUL 1 9 2018  DISTRICT II-ARTESIA O.C.D.  DATE _07/10/18
of starting any proposed wo proposed completion or recompletion of the completion of t	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer iks Lite Class C (60:40:0) w/additives. Mixed @ 11 is yd. Displaced w/358 bbls OBM. Plug down @ 1:4 Set Cameron mandrel hanger through BOP w/225k EMW. Drilled out with 6 1/8" bit.  225' MD. Ran 19185' of 4 1/2" 13.5# HCP110 CD 2#/g w/2.86 yd. Released dart. Displaced w/245 bbls is release from liner. Displaced 7" csg w/220 bbls Bot to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK. Top of liner @ 89 is to 1500# for 30 mins, held OK.	Completions: Attach wellbore diagram of the w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) is AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C is BW. Plug down @ 4:00 A.M. 07/02/18. Bump W. Circ 78 sks of cmt off of liner top to the pit. 85'  RECEIVED  8  JUL 1 9 2018  DISTRICT II-ARTESIA O.C.D.  DATE _07/10/18
of starting any proposed wo proposed completion or recompletion of the completion of t	rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.  Ran 9702' of 7" 29# HCP110 LT&C Csg. Cemer lks Lite Class C (60:40:0) w/additives. Mixed @ 11 for yellow ye	Completions: Attach wellbore diagram of the w/300 sks Class C w/additives. Mixed @ .5#/g w/2.54 yd. Tail w/400 sks Class C (50:50:2) is AM 06/17/18. Did not circ cmt. Est TOC @ #. At 2:30 AM 06/18/18, tested csg to 1500# 30 C HTQ csg. Cmt w/500 sks Lite Class C is BW. Plug down @ 4:00 A.M. 07/02/18. Bump W. Circ 78 sks of cmt off of liner top to the pit. 85'  RECEIVED  8  JUL 1 9 2018  DISTRICT II-ARTESIA O.C.D.  DATE _07/10/18