Form 3160-5 (June 2015)

1. Type of We

3a. Address

4. Location of

DEPARTMENT OF THE INTERIOR RECEIVED CD Artesia

BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 201

SUNDRY Do not use th abandoned we	5. Lease Serial No. NMNM2748 6. If Indian, Allotted					
SUBMIT IN		reement, Name and/or No.				
Type of Well ☑ Oil Well ☐ Gas Well ☐ Ott	GISSLER B 41					
Name of Operator BURNETT OIL COMPANY IN	9. API Well No. 30-015-36271	9. API Well No. 30-015-36271-00-S1				
Address 801 CHERRY STREET UNIT FORT WORTH, TX 76102-68		3b. Phone No. (include area code) Ph: 817.583.8730		10. Field and Pool or Exploratory Area LOCO HILLS-QU-GB-SA		
Location of Well (Footage, Sec., 7	11. County or Paris	11. County or Parish, State				
Sec 8 T17S R30E SWSE 330	EDDY COUN	EDDY COUNTY, NM				
12. CHECK THE A	PPROPRIATE BOX(ES)	TO INDICATE NATURE O	F NOTICE, REPORT, OR O	THER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION					
☑ Notice of Intent ☐ Subsequent Report	☐ Acidize	☐ Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off		
	☐ Alter Casing	☐ Hydraulic Fracturing	□ Reclamation	■ Well Integrity		
	□ Casing Repair	■ New Construction	□ Recomplete	Other		
☐ Final Abandonment Notice	☐ Change Plans	☐ Plug and Abandon ☐ Temporarily Abandon		Venting and/or Plari		
	☐ Convert to Injection	□ Plug Back	☐ Water Disposal	" Site tacilit		

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed once. following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

Attached is an update site security diagram for the Gissler B 5 Battery.

C C 6-14-18 Accepted for record - NMOCD

The Gissler B 5 battery is located at: T17S, R 30 E, SECTION 8, UNIT O, SWSE Approx: 233' FSL, 1674' FEL

which would entitle the applicant to conduct operations thereon.

LEASE: NMNM-2748

updated 4//18 om

ACCEPTED FOR RECORD JUN - **≰**I∂018 BUREAU OF LANDIMANAGEMENT CARLSBAD FIELD OFFICE

14. Thereby certify	For BURNETT	397552 verified by the BLM Well Information System OIL COMPANY INC, sent to the Carlsbad essing by PRISCILLA PEREZ on 12/15/2017 (18PP0537SE)				
Name (Printed/T	yped) LESLIE GARVIS	Title REGULATORY MANAGER				
Signature	(Electronic Submission)	Date 12/11/2017				
THIS SPACE FOR FEDERAL OR STATE OFFICE USE						

Approved By Date Title Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FLARE GAS METER

UPDATED: 12/6/2017

EDDY (COUNTY, NM						
GISSLE	R B S BATTERY				•	GISSLER B5 BATTERY	
T 175,	T 175, R 30E, SEC 8, UNIT O ,SWSE						
330' FS	330' FSL,1650' FEL						
Federa	Federal Lease: NMNM-2748						
						GISSLER B 42	
						GISSLER 8 45	
ATTAC	HMENT TO SITE FACILITY DIAGRA	MA				GISSLER B 46	
Genera	General sealing of valves, sales by tank guage						
Produc	Production Phase:						
Load Li	Load Line Valves sealed closed. Fill valve to tank that is in production will be open.						
Equaliz	ter valve to tank that is in product	ion will be open. Circulation valves will	be opened as necessary,	then resealed.		GISSLER B 63	
BS&W	BS&W Load Line valve will be sealed at all times, unless cleaning tanks, then resealed once tank maintenance is complete.						
Sales P	Sales Phase:						
The tar	The tank from which sales are being made will be isolated by sealing closed the fill line valve, circulating valve, and the						
equaliz	ter valve during sales and opening	the sales valve. Upon completion of ti	he sale, the sales valve wi	II be resealed.		GISSLER B 78	
Sales b	y truck will be by tank gauge. Sale	es by LACT will be by LACT meter.				GISSLER B 79	
						GISSLER B 80	
	<u>VALVE</u>	PRODUCTION PHASE	SALES PHASE	CIRCULATING	NOTE	GISSLER B 81	
	LOAD LINE VALVE	CLOSED ·	OPEN	CLOSED		GISSLER B 92	
						GISSLER B 94	
	PRODUCTION	OPEN OR CLOSED	CLOSED	CLOSED OR OPEN		GISSLER B 98	
	FILL LINE VALVE						
	EQUALIZER LINE VALVE	OPEN	CLOSED	CLOSED OR OPEN			
	CIRCULATING LINE VALVE	OPEN OR CLOSED	CLOSED	OPEN	RE-SEALED ONCE CIRCULATING IS COMPLETE OPEN FOR TANK MAINTENANCE, RESEALED ONCE MAINTENANCE IS COMPLETE		
	BS&W LOAD LINE VALVE	CLOSED	CLOSED	CLOSED			
•	WATER LINE VALVE	OPEN	NA	NA	WATER TANKS ARE ISOLATED FROM OIL PRODUCTION TANKS		

BURNETT OIL CO., INC.