District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV

## State of New Mexico Energy, Minerals and Natural Resources Department

partment to Appropriate
District Office
NM OIL CONSERVATION

Submit Original

Oil Conservation Division 1220 South St. Francis Dr. **ARTESIA DISTRICT** 

1220 S. St. Francis Dr., Santa Fe, NM 87505		Santa Fe, NM 87505				CED 21 2018		
Date: 12-6-2017		GAS CA	PTURE PLA	AN	1	RECEIVED		
☑ Original		Operator	& OGRID N	io.: <u>Mewbou</u>	ırne Oil Com	pany - 14744		
☐ Amended - Reason for A	mendment:_							
This Gas Capture Plan outlinew completion (new drill, r	ecomplete to	o new zone, re-fra	c) activity.					
Note: Form C-129 must be subn	y – Name of	<u>facility</u>				l of 19.13.18.12 NMAC).		
The well(s) that will be loca Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments		
DELAWARE RANCH II WING FEE III	0.414	N-11-26S-28E	83 FSL & 1600 FWL	0	NA	ONLINE AFTER FRAC		
	015-44	584						

Gathering System and Pipeline Notification
Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in
place. The was produced from production facility is dedicated to BROWN Transfer and will be connected to
Bridge Transfer low/high pressure gathering system located in County, New Mexico. It will require
' of pipeline to connect the facility to low/high pressure gathering system. Mewbourne Oil Company provides
(periodically) to groupy transfer a drilling, completion and estimated first production date for wells that are scheduled to
be drilled in the foreseeable future. In addition, Mewbourne Oil Company and BROWN Transfer have periodic
conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at
Processing Plant located in Sec. 33, Twn. 248, Rng. 37E, Lea County, New Mexico.
The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on \_\_\_\_\_\_ system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

## Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines