

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.
30-015-23793

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Sharp QS

7. Well No.

1

8. Pool name or Wildcat
POW Strawn

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter P : 660 feet from the South line and 660 feet from the East line

Section 4 Township 17S Range 26E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3356' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: Shut-In Mechanical Integrity Test ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Temporary Abandoned Status approved
until 5-28-05

4/28/03 - Set retainer at 4096' (hole in casing at 4148'-4180'). Squeeze with 300 sx "C" with 2% CC.

4/29/03 - Set retainer at 3055'. Squeeze with 300 sx "C" with 2% CC.

4/30/03 - Cemented from surface down 4-1/2" with 300 sx "C" with 2% CC. Squeezed holes from 1440' and 1546' to 1577'.

5/4/03 - Spotted 23 sx Class "C" cement from 1250'-1584'. Attempted to squeeze cement into hole at 1562'. Est. cement pumped into hole at 1562', less than 1 sack.

5/8/03 - Tagged retainer at 3055'. Drilled retainer from 3055'-3057'.

5/13/03 - Squeeze hole in 4-1/2" at 4150' with 411' of tail pipe with bottom tail pipe at 4184'. Spotted 25 sx Micro Matrix cement from 4184'-3910'. WOC 72 hrs.

CONTINUED ON NEXT PAGE:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE June 9, 2003

Type or print name Tina L. Huerta

Telephone No. 505-748-1471

(This space for State use)

APPROVED BY [Signature]

TITLE Wild Rep II


DATE JUN 11 2003

Conditions of approval, if any

Yates Petroleum Corporation
Sharp QS #1
Section 4-T17S-R26E
Eddy County, New Mexico

Form C-103 Continued:

Yates Petroleum Corporation is performing this Mechanical Integrity Test pursuant to rule 203 and in full compliance with the testing and reporting provisions of Supplemental Stipulation and agreement effective October 24, 2002, as to Shut-In Wells.


Tina Huerta
Regulatory Compliance Supervisor
June 9, 2003