<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
<u>District II</u>
811 S. First St., Artesia, NM 89210
<u>District III</u>
1000 Rio Brazos Road, Aztec, NM 874 1 0
<u>District IV</u>
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy, Minerals and Natural Resources Department

Submit Originat to Appropriate District Office

Oil Conservation Division NM OIL CONSERVATION 1220 South St. Francis Dr. Santa Fe, NM 87505

MAR 1 4 2019

ъ.	1/3/19		GAS CAPTURE PLAN				
Date:	1/3/19					RE	CEIVED
🛛 0	riginal	Operator	Operator & OGRID No.: Mack Energy Corporation - 013837				
	mended - Reason for A	.mendment:	•				
new (Gas Capture Plan outling completion (new drill, Form C-129 must be submit (s)/Production Facility	recomplete to	o new zone, re-fra	c) activity.			
The	well(s) that will be locate	ted at the pro-	duction facility are	e shown in th	e table belov	v	
	Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
[Meadow Lake Federal 1H		Sec. 28 T15S R29E	565 FNL & 990 FEL	50		
	3	0.005-6	4330				

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to DCP Midstream and will be connected to DCP Midstream low/high pressure gathering system located in Chaves— County, New Mexico. It will require (existing) of pipeline to connect the facility to low/high pressure gathering system. Mack Energy Corporation provides (periodically) to DCP Midstream a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Mack Energy Corporaton and DCP Midstream have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at DCP Midstream Linam Ranch Processing Plant located in Sec. 6——, Twn. 19S—, Rng. 37E—— County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on DCP Midstream system at that time. Based on current information, it is Mack Energy Corporation belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the Use Of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

· Power Generation - On lease

Only a portion of gas is consumed operating the generator, remainder of gas will be flared Compressed Natural Gas - On lease

Gas flared would be minimal, but might be uneconomical to operate when gas volume declines NGL Removal - On lease

Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines