	SUNDRY	NOTICES AND REPO	RTS ON WELCO D	Antesia NMNM274	48	
	abandoned wel	is form for proposals to II. Use form 3160-3 (API		6. If Indian, Al	lottee or Tribe Name	
=	SUBMIT IN 1	TRIPLICATE - Other inst	tructions on page 2	7. If Unit or C	A/Agreement, Name and/or N	
-	1. Type of Well Gas Well Other			8. Well Name a KIRK FEDE	nd No. ERAL COM 3H	
-	2. Name of Operator EOG RESOURCES INC	Contact:	TINA HUERTA a@eogresources.com	9. API Well No 30-015-45	o. 5662-00-X1	
-	3a. Address 1111 BAGBY SKY LOBBY2 HOUSTON, TX 77002		3b. Phone No. (include area code) Ph: 575-748-4168) 10. Field and P LOCO HIL	Pool or Exploratory Area LS-GLORIETA-YESO	
-	4. Location of Well (Footage, Sec., T.	., R., M., or Survey Description	· · · · · · · · · · · · · · · · · · ·	11. County or 1	Parish, State	
	Sec 12 T17S R30E NWNW 12 32.852722 N Lat, 103.931938			EDDY CC	DUNTY, NM	
-	12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA					
-	TYPE OF SUBMISSION		TYPE O	TYPE OF ACTION		
-			Deepen	Production (Start/Result	me) 🔲 Water Shut-C	
	Notice of Intent	Alter Casing	Hydraulic Fracturing	Reclamation	🗖 Well Integrity	
	Subsequent Report	Casing Repair	□ New Construction	Recomplete	Other	
	Final Abandonment Notice	Change Plans	Plug and Abandon	Temporarily Abandon	Drilling Operati	
		Convert to Injection	Plug Back	Water Disposal		
-	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi	ally or recomplete horizontally, rk will be performed or provide operations. If the operation re bandonment Notices must be fil inal inspection.	the Bond No. on file with BLM/BI/ sults in a multiple completion or rec- ed only after all requirements, include	ured and true vertical depths of a A. Required subsequent reports r completion in a new interval a Fo	Il pertinent markers and zone must be filed within 30 days	
_	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling witl J-55 ST&C casing at 428 ft. C	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re bandonment Notices must be fil inal inspection. nductor hole. Set 118 ft c h rotary tools. TD 17-1/2 emented with 160 sx Clas	give subsurface locations and measu the Bond No. on file with BLM/BL/ sults in a multiple completion or rec- ed only after all requirements, inclu- of 20 inch conductor and cemu- inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar	ured and true vertical depths of a A. Required subsequent reports r completion in a new interval a Fo	Il pertinent markers and zone must be filed within 30 days	
	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling with J-55 ST&C casing at 428 ft. C 470 sx Class C cement with a 4/6/19 - Moved in big rig and c 4/9/19 - TD 12-1/4 inch hole to	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re bandonment Notices must be fil inal inspection. Inductor hole. Set 118 ft of h rotary tools. TD 17-1/2 emented with 160 sx Clas dditives. Cement circulate continue drilling. Tested c b 3404 ft. Set 9-5/8 inch 4	give subsurface locations and measu the Bond No. on file with BLM/BI/ sults in a multiple completion or rec- ed only after all requirements, inclu- of 20 inch conductor and cem- inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar ed to surface. asing to 1500 psi for 30 min, 0Lb J-55 LT&C casing at 338	ared and true vertical depths of a A. Required subsequent reports r completion in a new interval, a Fo ding reclamation, have been com ented to surface binch 48Lb and tailed in with held good. By ft. Cemented	Il pertinent markers and zone must be filed within 30 days	
	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling witi J-55 ST&C casing at 428 ft. C 470 sx Class C cement with at 4/6/19 - Moved in big rig and c 4/9/19 - TD 12-1/4 inch hole to with 1130 sx Class C cement T ested casing to 1590 psi for 3 4/13/19 - Reached TD 8-3/4 in L-80 BTC casing at 9102 ft. C	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re andonment Notices must be fil inal inspection. Inductor hole. Set 118 ft of h rotary tools. TD 17-1/2 emented with 160 sx Clas dditives. Cement circulate continue drilling. Tested c o 3404 ft. Set 9-5/8 inch 4 with additives and tailed i 30 min, held good. Ceme hch hole to 9118 ft. Set 7 emented with 145 sx Clas	give subsurface locations and measu the Bond No. on file with BLM/BL/ sults in a multiple completion or rec- ed only after all requirements, includ- of 20 inch conductor and cemu- inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar ed to surface. asing to 1500 psi for 30 min, 0Lb J-55 LT&C casing at 338 n with 250 sx Class C cemen nt circulated to surface. inch 29Lb L-80 BTC x 5-1/2 in	ared and true vertical depths of a A. Required subsequent reports r ompletion in a new interval, a Fo ding reclamation, have been com ented to surface B inch 48Lb and tailed in with held good. B9 ft. Cemented t with additives. nch 17Lb P110	Il pertinent markers and zone must be filed within 30 days orm 3160-4 must be filed onc pleted and the operator has 3 0 119 . NMOCD for record . NMOCD	
	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling witi J-55 ST&C casing at 428 ft. C 470 sx Class C cement with at 4/6/19 - Moved in big rig and c 4/9/19 - TD 12-1/4 inch hole to with 1130 sx Class C cement to Tested casing to 1590 psi for 3 4/13/19 - Reached TD 8-3/4 in	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re andonment Notices must be fil inal inspection. Inductor hole. Set 118 ft of h rotary tools. TD 17-1/2 emented with 160 sx Clas dditives. Cement circulate continue drilling. Tested c o 3404 ft. Set 9-5/8 inch 4 with additives and tailed i 30 min, held good. Ceme hch hole to 9118 ft. Set 7 emented with 145 sx Clas	give subsurface locations and measu the Bond No. on file with BLM/BL/ sults in a multiple completion or rec- ed only after all requirements, includ- of 20 inch conductor and cemu- inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar ed to surface. asing to 1500 psi for 30 min, 0Lb J-55 LT&C casing at 338 n with 250 sx Class C cemen nt circulated to surface. inch 29Lb L-80 BTC x 5-1/2 in	ared and true vertical depths of a A. Required subsequent reports r ompletion in a new interval, a Fo ding reclamation, have been com ented to surface binch 48Lb and tailed in with held good. 39 ft. Cemented t with additives. nch 17Lb P110 nd tailed in with	Il pertinent markers and zone must be filed within 30 days orm 3160-4 must be filed onc pleted and the operator has 3 o / 19 or NAMOCD for record - NAMOCD RECEIVED	
-	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling witi J-55 ST&C casing at 428 ft. C 470 sx Class C cement with at 4/6/19 - Moved in big rig and c 4/9/19 - TD 12-1/4 inch hole to with 1130 sx Class C cement T ested casing to 1590 psi for 3 4/13/19 - Reached TD 8-3/4 in L-80 BTC casing at 9102 ft. C	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re andonment Notices must be fil inal inspection. Inductor hole. Set 118 ft of h rotary tools. TD 17-1/2 emented with 160 sx Clas dditives. Cement circulate continue drilling. Tested c b 3404 ft. Set 9-5/8 inch 4 with additives and tailed i 30 min, held good. Ceme hch hole to 9118 ft. Set 7 emented with 145 sx Clas dditives.	give subsurface locations and measu the Bond No. on file with BLM/BL/ sults in a multiple completion or rec- ed only after all requirements, inclu- of 20 inch conductor and cemu- inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar ed to surface. asing to 1500 psi for 30 min, 0Lb J-55 LT&C casing at 338 n with 250 sx Class C cemen nt circulated to surface. inch 29Lb L-80 BTC x 5-1/2 in ss C cement with additives ar	and true vertical depths of a A. Required subsequent reports r ompletion in a new interval, a Fo ding reclamation, have been com ented to surface B inch 48Lb and tailed in with held good. 39 ft. Cemented t with additives. nch 17Lb P110 and tailed in with DIS	Il pertinent markers and zone must be filed within 30 days orm 3160-4 must be filed onc pleted and the operator has 3 •)19 • NMOCD Frecord • NMOCD RECEIVED APR 2 5 2019	
	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling with J-55 ST&C casing at 428 ft. C 470 sx Class C cement with a 4/6/19 - Moved in big rig and c 4/9/19 - TD 12-1/4 inch hole to with 1130 sx Class C cement i Tested casing to 1590 psi for 4/13/19 - Reached TD 8-3/4 ir L-80 BTC casing at 9102 ft. C 865 sx Class C cement with a	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re bandonment Notices must be fil inal inspection. Inductor hole. Set 118 ft of h rotary tools. TD 17-1/2 emented with 160 sx Clar dditives. Cement circulate continue drilling. Tested c b 3404 ft. Set 9-5/8 inch 4 with additives and tailed i 30 min, held good. Ceme hoch hole to 9118 ft. Set 7 emented with 145 sx Clar dditives.	give subsurface locations and measu the Bond No. on file with BLM/BL/ sults in a multiple completion or rece ed only after all requirements, include of 20 inch conductor and cernel inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar ed to surface. asing to 1500 psi for 30 min, t0Lb J-55 LT&C casing at 338 n with 250 sx Class C cemen nt circulated to surface. inch 29Lb L-80 BTC x 5-1/2 in ss C cement with additives ar	ared and true vertical depths of a A. Required subsequent reports r ompletion in a new interval, a Fo ding reclamation, have been com ented to surface B inch 48Lb Accepted a tailed in with held good. B ft. Cemented t with additives. nch 17Lb P110 a tailed in with DIS ell Information System carlsbad	Il pertinent markers and zone must be filed within 30 days orm 3160-4 must be filed onc pleted and the operator has 3 b) 19 cm cm cm cm 3 cm cm cm cm cm cm cm 3 cm cm cm cm cm cm cm cm 3 cm cm cm cm cm cm cm cm cm cm 3 cm cm 3 cm	
-	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling with J-55 ST&C casing at 428 ft. C 470 sx Class C cement with a 4/6/19 - Moved in big rig and c 4/9/19 - TD 12-1/4 inch hole to with 1130 sx Class C cement i Tested casing to 1590 psi for 4/13/19 - Reached TD 8-3/4 ir L-80 BTC casing at 9102 ft. C 865 sx Class C cement with a	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re andonment Notices must be fil inal inspection. Inductor hole. Set 118 ft of h rotary tools. TD 17-1/2 emented with 160 sx Clar dditives. Cement circulate continue drilling. Tested c b 3404 ft. Set 9-5/8 inch 4 with additives and tailed i 30 min, held good. Ceme hole to 9118 ft. Set 7 emented with 145 sx Clar dditives.	give subsurface locations and measu the Bond No. on file with BLM/BL/ sults in a multiple completion or rece ed only after all requirements, include of 20 inch conductor and cernel inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar ed to surface. asing to 1500 psi for 30 min, 0Lb J-55 LT&C casing at 336 n with 250 sx Class C cemen nt circulated to surface. inch 29Lb L-80 BTC x 5-1/2 in ss C cement with additives ar ess C cement with additives ar	ared and true vertical depths of a A. Required subsequent reports r ompletion in a new interval, a Fo ding reclamation, have been com ented to surface B inch 48Lb Accepted a tailed in with held good. B ft. Cemented t with additives. nch 17Lb P110 a tailed in with DIS ell Information System carlsbad	Il pertinent markers and zone must be filed within 30 days orm 3160-4 must be filed onc pleted and the operator has 3 o) 19 of the	
-	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling with J-55 ST&C casing at 428 ft. C 470 sx Class C cement with at 4/6/19 - Moved in big rig and c 4/9/19 - TD 12-1/4 inch hole to with 1130 sx Class C cement vith Tested casing to 1590 psi for 3 4/13/19 - Reached TD 8-3/4 in L-80 BTC casing at 9102 ft. C 865 sx Class C cement with at 14. I hereby certify that the foregoing is Name (<i>Printed/Typed</i>) TINA HUE	ally or recomplete horizontally, rk will be performed or provide loperations. If the operation re bandonment Notices must be fil inal inspection. Inductor hole. Set 118 ft of h rotary tools. TD 17-1/2 emented with 160 sx Clas dditives. Cement circulate continue drilling. Tested c b 3404 ft. Set 9-5/8 inch 4 with additives and tailed i 30 min, held good. Ceme nch hole to 9118 ft. Set 7 emented with 145 sx Clas dditives.	give subsurface locations and measu the Bond No. on file with BLM/BL/ sults in a multiple completion or rece ed only after all requirements, include of 20 inch conductor and cernel inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar ed to surface. asing to 1500 psi for 30 min, 0Lb J-55 LT&C casing at 338 n with 250 sx Class C cemen nt circulated to surface. inch 29Lb L-80 BTC x 5-1/2 in ss C cement with additives ar 461541 verified by the BLM We ESOURCES INC, sent to the C essing by PRISCILLA PEREZ o Title REGUL	ared and true vertical depths of a A. Required subsequent reports r ompletion in a new interval, a Fo ding reclamation, have been com ented to surface B inch 48Lb ad tailed in with held good. 39 ft. Cemented t with additives. nch 17Lb P110 ad tailed in with DK ell Information System carlsbad on 04/17/2019 (19PP1688SE) LATORY SPECIALIST	Il pertinent markers and zone must be filed within 30 days orm 3160-4 must be filed onc pleted and the operator has 3 o) 19 RECEIVED APR 2 5 2019 STRICT II-ARTESIA O.	
-	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling with J-55 ST&C casing at 428 ft. C 470 sx Class C cement with at 4/6/19 - Moved in big rig and c 4/9/19 - TD 12-1/4 inch hole to with 1130 sx Class C cement vith Tested casing to 1590 psi for 3 4/13/19 - Reached TD 8-3/4 in L-80 BTC casing at 9102 ft. C 865 sx Class C cement with at 14. I hereby certify that the foregoing is Corr	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re sandonment Notices must be fil inal inspection. Inductor hole. Set 118 ft of h rotary tools. TD 17-1/2 emented with 160 sx Clas dditives. Cement circulate continue drilling. Tested of 0 3404 ft. Set 9-5/8 inch 4 with additives and tailed i 30 min, held good. Ceme hoch hole to 9118 ft. Set 7 emented with 145 sx Clas dditives.	give subsurface locations and measu the Bond No. on file with BLM/BL// sults in a multiple completion or rec- ed only after all requirements, include of 20 inch conductor and cerner inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar ed to surface. asing to 1500 psi for 30 min, 0Lb J-55 LT&C casing at 33& n with 250 sx Class C cemen nt circulated to surface. inch 29Lb L-80 BTC x 5-1/2 in ss C cement with additives ar essing by PRISCILLA PEREZ of Title REGUL Date 04/15/2	ared and true vertical depths of a A. Required subsequent reports r ompletion in a new interval, a Fo ding reclamation, have been com ented to surface B inch 48Lb ad tailed in with held good. B9 ft. Cemented t with additives. nch 17Lb P110 ad tailed in with DIS ell Information System carlsbad on 04/17/2019 (19PP1688SE) LATORY SPECIALIST 2019	Il pertinent markers and zone must be filed within 30 days orm 3160-4 must be filed onc pleted and the operator has 3 o) 19 of the	
-	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling with J-55 ST&C casing at 428 ft. C 470 sx Class C cement with at 4/6/19 - Moved in big rig and c 4/9/19 - TD 12-1/4 inch hole to with 1130 sx Class C cement vith Tested casing to 1590 psi for 3 4/13/19 - Reached TD 8-3/4 in L-80 BTC casing at 9102 ft. C 865 sx Class C cement with at 14. I hereby certify that the foregoing is Name (<i>Printed/Typed</i>) TINA HUE	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re sandonment Notices must be fil inal inspection. Inductor hole. Set 118 ft of h rotary tools. TD 17-1/2 emented with 160 sx Clas dditives. Cement circulate continue drilling. Tested of 0 3404 ft. Set 9-5/8 inch 4 with additives and tailed i 30 min, held good. Ceme hoch hole to 9118 ft. Set 7 emented with 145 sx Clas dditives.	give subsurface locations and measu the Bond No. on file with BLM/BL// sults in a multiple completion or rece ed only after all requirements, inclue of 20 inch conductor and cerne inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar ed to surface. asing to 1500 psi for 30 min, 0Lb J-55 LT&C casing at 338 n with 250 sx Class C cemen nt circulated to surface. inch 29Lb L-80 BTC x 5-1/2 in ss C cement with additives ar 461541 verified by the BLM We ESOURCES INC, sent to the C essing by PRISCILLA PEREZ o Title REGUL Date 04/15/2 DR FEDERAL OR STATE	ared and true vertical depths of a A. Required subsequent reports r ompletion in a new interval, a Fo ding reclamation, have been com ented to surface B inch 48Lb ad tailed in with held good. 39 ft. Cemented t with additives. nch 17Lb P110 ad tailed in with DIS ell Information System arlsbad on 04/17/2019 (19PP1688SE) _ATORY SPECIALIST 2019 OFFICE USE	Il pertinent markers and zone must be filed within 30 days orm 3160-4 must be filed onc pleted and the operator has 3 ° / 19 ~ NMOCD RECEIVED APR 2 5 2019 STRICT II-ARTESIA O.	
:	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling with J-55 ST&C casing at 428 ft. C 470 sx Class C cement with at 4/6/19 - Moved in big rig and c 4/9/19 - TD 12-1/4 inch hole to with 1130 sx Class C cement vith Tested casing to 1590 psi for 3 4/13/19 - Reached TD 8-3/4 in L-80 BTC casing at 9102 ft. C 865 sx Class C cement with at 14. I hereby certify that the foregoing is Corr Name (<i>Printed/Typed</i>) TINA HUE Signature (Electronic S Approved By	ally or recomplete horizontally, rk will be performed or provide loperations. If the operation re andonment Notices must be fil inal inspection. Inductor hole. Set 118 ft of h rotary tools. TD 17-1/2 emented with 160 sx Clar dditives. Cement circulate continue drilling. Tested c b 3404 ft. Set 9-5/8 inch 4 with additives and tailed i 30 min, held good. Ceme nch hole to 9118 ft. Set 7 emented with 145 sx Clar dditives. true and correct. Electronic Submission # For EOG R nmitted to AFMSS for proc ERTA Submission)	give subsurface locations and measu the Bond No. on file with BLM/BL// sults in a multiple completion or rec- ed only after all requirements, include of 20 inch conductor and cerner inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar ed to surface. asing to 1500 psi for 30 min, 0Lb J-55 LT&C casing at 338 n with 250 sx Class C cemen nt circulated to surface. inch 29Lb L-80 BTC x 5-1/2 in ss C cement with additives ar essing by PRISCILLA PEREZ of Title REGUL Date 04/15/2 DR FEDERAL OR STATE	A. Required subsequent reports r ompletion in a new interval, a Fo ding reclamation, have been com ented to surface B inch 48Lb and tailed in with held good. 39 ft. Cemented t with additives. nch 17Lb P110 and tailed in with DIS Construction System arisbad on 04/17/2019 (19PP1688SE) ATORY SPECIALIST 2019 OFFICE USE	Il pertinent markers and zone must be filed within 30 days orm 3160-4 must be filed onc pleted and the operator has 3 ° / 19 ~ NMOCD RECEIVED APR 2 5 2019 STRICT II-ARTESIA O.	
-	If the proposal is to deepen directiona Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi 2/14/19 - Spudded 30 inch cor with 14 yards of redi-mix. 2/20/19 - Resumed drilling witi J-55 ST&C casing at 428 ft. C 470 sx Class C cement with at 4/6/19 - Moved in big rig and c 4/6/19 - TD 12-1/4 inch hole to with 1130 sx Class C cement to Tested casing to 1590 psi for 3/13/19 - Reached TD 8-3/4 ir L-80 BTC casing at 9102 ft. C 865 sx Class C cement with at 14. I hereby certify that the foregoing is Corr Name (<i>Printed/Typed</i>) TINA HUE Signature (Electronic S	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re andonment Notices must be fil- inal inspection. Inductor hole. Set 118 ft c h rotary tools. TD 17-1/2 emented with 160 sx Class dditives. Cement circulate continue drilling. Tested c to 3404 ft. Set 9-5/8 inch 4 with additives and tailed i 30 min, held good. Cement inch hole to 9118 ft. Set 7 emented with 145 sx Class dditives. true and correct. Electronic Submission # For EOG R mitted to AFMSS for proc ERTA Submission) THIS SPACE FC	give subsurface locations and measu the Bond No. on file with BLM/BL//Bl/ sults in a multiple completion or rec- ed only after all requirements, include of 20 inch conductor and cerner inch hole to 428 ft. Set 13-3/8 ss C cement with additives ar ed to surface. asing to 1500 psi for 30 min, 0Lb J-55 LT&C casing at 338 n with 250 sx Class C cemen nt circulated to surface. inch 29Lb L-80 BTC x 5-1/2 in ss C cement with additives ar essing by PRISCILLA PEREZ of Title REGUL Date 04/15/2 DR FEDERAL OR STATE	ared and true vertical depths of a A. Required subsequent reports r ompletion in a new interval, a Fo ding reclamation, have been com ented to surface B inch 48Lb ad tailed in with held good. 39 ft. Cemented t with additives. nch 17Lb P110 ad tailed in with DIS ell Information System arlsbad on 04/17/2019 (19PP1688SE) _ATORY SPECIALIST 2019 OFFICE USE	Il pertinent markers and zone must be filed within 30 days orm 3160-4 must be filed onc pleted and the operator has 3 ° / 19 • NIMOCO RECEIVED APR 2 5 2019 STRICT II-ARTESIA O.	

Additional data for EC transaction #461541 that would not fit on the form

32. Additional remarks, continued

5

ł

4/15/19 - Rig released 6:00 PM.