Form 3160-5 (June 2015)

UNITED STATES

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT ISDAO

SUNDRY NOTICES AND REPORTS ON WELL

Do not use this form for proposals to drill or to relever and the proposals to the proposals to the proposals to the proposals to the proposals to

abandoned we	II. Use form 3160-3 (APD) for	such proposals. " ""	o. II Ilidiali, Ali	ottee of Tribe Name
SUBMIT IN TRIPLICATE - Other instructions on page 2			7. If Unit or CA	/Agreement, Name and/or No.
Type of Well	· · · · · · · · · · · · · · · · · · ·	8. Well Name at BUBBLES 2	nd No. 22 15 FEDERAL 1H	
2. Name of Operator Contact: CHERYL ROWE XTO ENERGY INCORPORATED E-Mail: Cheryl_rowell@xtoenergy.com			9. API Well No 30-015-45	
3a. Address 6401 HOLIDAY HILL ROAD E MIDLAND, TX 79707	hone No. (include area code) 432-571-8205	10. Field and Po DELAWAF	10. Field and Pool or Exploratory Area DELAWARE	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			11. County or P	arish, State
Sec 22 T19S R30E NESW 1900FSL 1800FEL 32.643833 N Lat, 103.957085 W Lon			EDDY CO	UNTY, NM
12. CHECK THE AI	PPROPRIATE BOX(ES) TO IN	IDICATE NATURE OI	F NOTICE, REPORT, OR	OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION			
☐ Notice of Intent	☐ Acidize	☐ Deepen	☐ Production (Start/Resun	ne) 🗖 Water Shut-Off
_	☐ Alter Casing	☐ Hydraulic Fracturing	□ Reclamation	■ Well Integrity
Subsequent Report Subsequent Re	☐ Casing Repair	■ New Construction	☐ Recomplete	Other
☐ Final Abandonment Notice	☐ Change Plans	☐ Plug and Abandon	☐ Temporarily Abandon	Drilling Operations
	☐ Convert to Injection	☐ Plug Back	■ Water Disposal	
well. 01/03/19 to 01/06/2019 Spud well 01/03/2019. Drill 24	sundry notice to report the drilling inch hole to 466 ft. Run 18-5/8	?, 87.5#, J-55 casing se	t at 461 ft.	Frecord NMOCD
Cement casing with 1268 sxs Class C cmt. Bump plug. No cement to surface. WOC. Run Temp Log. TOC @ 167?. Top out w/ 379 sxs Class C. WOC. Test csg 1500 psi, 30 mins (good).				
01/07/2019 to 01/11/2019 Drill 17 1/2 inch hole to 1606 f 1900 Class C lead and 615 50 casing 1500 psi, 30 mins (goo	t. Run 13-3/8, 68#, J-55 casing 0/50 POZ tail. Did not bump plug d).	set at 1601 ft. Cement og. Circulate cement to su	ırface. WOC. Test	JUN 2.5 2019
14. I hereby certify that the foregoing is	true and correct	· · · · · · · · · · · · · · · · · · ·		CTILARTESIAO.C.D.
	Electronic Submission #466080	ORPORATED, sent to th	e Carlsbad	•
Name (Printed/Typed) CHERYL	· 1	ATORY COORDINATOR		
Signature (Electronic Submission) Date 05/20			019	
	THIS SPACE FOR FE	DERAL OR STATE (OFFICE USE	
Approved By		Title Acce	pted for Record	MAY Z 9 ZU19 Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			nathon Shepard Irlsbad Field Office	·
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s			willfully to make to any departm	nent or agency of the United

Additional data for EC transaction #466080 that would not fit on the form

32. Additional remarks, continued

01/12/2019 to 01/17/2019
Drill 12 1/4 inch hole to 4075 ft, Run 9-5/8 inch 40#, J-55 casing set @ 4071 ft. Cement casing with 384 sxs Class H lead, 435 Class H tail. Bump Plug, Open DV tool. Cement casing with 430 sxs Class C lead and 142 sxs Class C. Bump plug. Circulate cement to surface. WOC. Skid Rig. Install TA cap.

04/18/2019 to 05/12/2019 Test 9-5/8 inch to 1500 psi, 30 mins (good). Drill 8-3/4 inch hole to 16928 ft. Run 5-1/2 inch, 20#, P-110 casing set @ 16815 ft.. Cement casing with 880 sxs Class C lead, 1700 sxs Class C tail. Bump plug. Circulate cement to surface. WOC.

Rig Release 05/12/19