

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-46009
5. Indicate Type of Lease STATE [ ] FEE [x]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name LEAVITT 13
8. Well Number #2H
9. OGRID Number 277558
10. Pool name or Wildcat Red Lake, Glorieta-Yeso (51120)
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3288' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [x] Gas Well [ ] Other [ ]
2. Name of Operator LIME ROCK RESOURCES II-A, L.P.
3. Address of Operator c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401
4. Well Location Unit Letter D : 495 feet from the NORTH line and 498 feet from the WEST line
Section 18 Township 18-S Range 27-E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [ ] PLUG AND ABANDON [ ]
TEMPORARILY ABANDON [ ] CHANGE PLANS [ ]
PULL OR ALTER CASING [ ] MULTIPLE COMPL [ ]
DOWNHOLE COMMINGLE [ ]
CLOSED-LOOP SYSTEM [x]
OTHER: [ ]
SUBSEQUENT REPORT OF:
REMEDIAL WORK [ ] ALTERING CASING [ ]
COMMENCE DRILLING OPNS. [ ] P AND A [ ]
CASING/CEMENT JOB [x]
OTHER: Production Casing [x]

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Drilled 8-3/4" hole from surface csg shoe to MD8345' on 7/26/19. On 7/27/19, landed 118 jts 5-1/2" 20# L-80 csg @ 8345' w/cross over @ 3273' to 72 jts 7" 29# L-80 csg to surface.

Cmtd lead w/180sx (536 cf) 50/50 poz "C" cmt w/1.5% Cacl2, 0.2% anti-foam, 0.25 ppsx LCM, 5% salt, 10% gel, & 0.6% extender. Tailed w/1345 sx (1749 cf) 35/65 Poz "H" cmt w/4% gel, 0.2% anti-foam, 0.3% fluid loss. Circ 47 sx cmt to pit. Released drilling rig on 7/28/19. Plan to pressure test the 5-1/2" csg before completion operations.

Bottom Hole: 524' FNL & 129' FWL, Sec. 13 T18S R27E
Spud Date: 7/11/19 Drilling Rig Release Date: 7/28/19

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Petroleum Engineer - Agent DATE 8/2/19

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573
For State Use Only

APPROVED BY: [Signature] TITLE Geologist DATE 8-6-2019
Conditions of Approval (if any):

RECEIVED

AUG 05 2019

DISTRICT II-ARTESIA O.C.D.

Ref 8-6-19