Submit 1 Copy To Appropriate District	State of New Mexico	Form C-103
Office <u>District I</u> – (575) 393-6161 Energy	, Minerals and Natural Resources	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240		WELL API NO. 30-005-64334
	CONSERVATION DIVISION	5. Indicate Type of Lease
	220 South St. Francis Dr.	STATE FEE X
000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> – (505) 476-3755777777777777777777777777777777777	DSanta Fe, NM 87505	6. State Oil & Gas Lease No.
220 S. St. Francis Dr., Saina Pe, NNI		
SUNDRY NOTICES AND RE		7. Lease Name or Unit Agreement Name
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL DIFFERENT RESERVOIR. USE "APPLICATION FOR PE		Hellcat
PROPOSALS.)		
. Type of Well: Oil Well 🕅 Gas Well	Other	8. Well Number 2H
2. Name of Operator Tamaroa Operating, LI	LC	9. OGRID Number 328666
3. Address of Operator PO Box 866937, Plano Tx, 75086-6937		10. Pool name or Wildcat
PO Box 866937, Plan	10 1x, /5086-693/	Twin Lake; San Andres
4. Well Location	· · · · · · · · · · · · · · · · · · ·	-
Unit Letter_H = 2310 fe	et from the <u>N</u> line and <u>9</u>	90feet from theline
	ownship 8S Range 28E	NMPM Chaves County
	on (Show whether DR, RKB, RT, GR, etc.	
3938 (
12 Check Announists	Dan to Ladiante Nature of Matine	Demost on Other Data
12. Check Appropriate	Box to Indicate Nature of Notice,	Report of Other Data
NOTICE OF INTENTION	TO: SUE	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK 🔲 🛛 PLUG AND	ABANDON	
PULL OR ALTER CASING MULTIPLE	COMPL CASING/CEMEN	IT JOB
		П
DTHER:	D OTHER:	d give pertinent dates, including estimated date
OTHER:		d give pertinent dates, including estimated date
OTHER: 13. Describe proposed or completed operatio	ns. (Clearly state all pertinent details, an	
A 7 7/8" hole was drilled to MD 7149' (TVD 2	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f	from surface to TD. The casing was
OTHER: 13. Describe proposed or completed operatio	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f	from surface to TD. The casing was
OTHER: 13. Describe proposed or completed operation A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3	from surface to TD. The casing was 328'.
A 7 7/8" hole was drilled to MD 7149' (TVD 2 equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (from surface to TD. The casing was 328'.
OTHER: 13. Describe proposed or completed operation A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (from surface to TD. The casing was 328'.
DTHER: 13. Describe proposed or completed operation A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (from surface to TD. The casing was 328'.
DTHER: 13. Describe proposed or completed operation A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (from surface to TD. The casing was 328'.
A 7 7/8" hole was drilled to MD 7149' (TVD 2 equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (from surface to TD. The casing was 328'.
A 7 7/8" hole was drilled to MD 7149' (TVD 2 equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (from surface to TD. The casing was 328'.
OTHER: 13. Describe proposed or completed operatio A 7 7/8" hole was drilled to MD 7149' (TVD 2 equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (from surface to TD. The casing was 328'.
OTHER: 13. Describe proposed or completed operatio A 7 7/8" hole was drilled to MD 7149' (TVD 2 equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (from surface to TD. The casing was 328'.
DTHER: 13. Describe proposed or completed operation A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class cement circulated to surface. Plug down @ 2.5	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (58 am 7/16/19.	From surface to TD. The casing was 328'. C lite mixed at 14.2 lb/gal with 10 bbls
DTHER: 13. Describe proposed or completed operation A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class cement circulated to surface. Plug down @ 2.5	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (58 am 7/16/19.	From surface to TD. The casing was 328'. C lite mixed at 14.2 lb/gal with 10 bbls
DTHER: 13. Describe proposed or completed operation A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class cement circulated to surface. Plug down @ 2.5	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (58 am 7/16/19.	From surface to TD. The casing was 328'. C lite mixed at 14.2 lb/gal with 10 bbls
OTHER: 13. Describe proposed or completed operatio A 7 7/8" hole was drilled to MD 7149' (TVD 2 equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class cement circulated to surface. Plug down @ 2.5 pud Date: June 13, 2019	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (58 am 7/16/19. Rig Release Date: July 16, 201	From surface to TD. The casing was 328'. C lite mixed at 14.2 lb/gal with 10 bbls
OTHER: 13. Describe proposed or completed operatio A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class cement circulated to surface. Plug down @ 2:5	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (58 am 7/16/19. Rig Release Date: July 16, 201	From surface to TD. The casing was 328'. C lite mixed at 14.2 lb/gal with 10 bbls
OTHER: 13. Describe proposed or completed operatio A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class cement circulated to surface. Plug down @ 2:5 pud Date: June 13, 2019 hereby certify that the information above is true	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (58 am 7/16/19. Rig Release Date: July 16, 201 and complete to the best of my knowledg	From surface to TD. The casing was 328'. C lite mixed at 14.2 lb/gal with 10 bbls 9 ge and belief.
OTHER: 13. Describe proposed or completed operatio A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class cement circulated to surface. Plug down @ 2.5 pud Date: June 13, 2019	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (58 am 7/16/19. Rig Release Date: July 16, 201 and complete to the best of my knowledg 	From surface to TD. The casing was 328'. C lite mixed at 14.2 lb/gal with 10 bbls 9 ge and belief.
DTHER: 13. Describe proposed or completed operatio A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class cement circulated to surface. Plug down @ 2:5 pud Date: June 13, 2019 hereby certify that the information above is true IGNATURE	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (58 am 7/16/19. Rig Release Date: July 16, 201 and complete to the best of my knowledg 	From surface to TD. The casing was 328'. C lite mixed at 14.2 lb/gal with 10 bbls 9 ge and belief.
DTHER: 13. Describe proposed or completed operatio A 7 7/8" hole was drilled to MD 7149' (TVD 2/ equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class cement circulated to surface. Plug down @ 2.5 pud Date: June 13, 2019 hereby certify that the information above is true IGNATURE ype or print name Phelps White	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (58 am 7/16/19. Rig Release Date: July 16, 201 and complete to the best of my knowledg	From surface to TD. The casing was 328'. C lite mixed at 14.2 lb/gal with 10 bbls 9 ge and belief.
DTHER: 13. Describe proposed or completed operatio A 7 7/8" hole was drilled to MD 7149' (TVD 2/ equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class cement circulated to surface. Plug down @ 2.5 pud Date: June 13, 2019 hereby certify that the information above is true IGNATURE ype or print name Phelps White	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (58 am 7/16/19. Rig Release Date: July 16, 201 and complete to the best of my knowledg 	From surface to TD. The casing was 328'. C lite mixed at 14.2 lb/gal with 10 bbls 9 ge and belief.
DTHER: 13. Describe proposed or completed operation A 7 7/8" hole was drilled to MD 7149' (TVD 2) equipped with a float shoe, float collar, turboliz The 5 1/2" casing was cemented w/240 sx class cement circulated to surface. Plug down @ 2:5 pud Date: June 13, 2019 hereby certify that the information above is true IGNATURE	ns. (Clearly state all pertinent details, an 6L00'). 5 1/2" 17# L-80 casing was run f zers every other joint and a float sub @ 3 s C Lite mixed at 13.5 lb/gal and 860 sx (58 am 7/16/19. Rig Release Date: July 16, 201 and complete to the best of my knowledg 	From surface to TD. The casing was 328'. C lite mixed at 14.2 lb/gal with 10 bbls 9 ge and belief.