Form 3160-5 (June 2015)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMEN AILS DAD FIELD

FORM APPROVED OMB NO. 1004-0137 Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS

Office Serial No.

abandoned we	II. Use form 3160-3 (APD) for su	ch proposals.	I (CS) 6. If Indian, Allottee or	Tribe Name	
SUBMIT IN	7. If Unit or CA/Agrees 891000326X	7. If Unit or CA/Agreement, Name and/or No. 891000326X			
Type of Well Gas Well			8. Well Name and No.	8. Well Name and No. BIG EDDY UNIT 29 FEDERAL SWD 1	
Oil Well Gas Well Oth Name of Operator	9. API Well No.	91 EDETAL SWD 1			
XTO PERMIAN OPERATING	. ROWELL nergy.com	30-015-43253-00-X1			
3a. Address 6401 HOLIDAY HILL ROAD E MIDLAND, TX 79707		ne No. (include area code) 2-571-8205	10. Field and Pool or E WILDCAT	Field and Pool or Exploratory Area WILDCAT	
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description)	`	11. County or Parish, S	11. County or Parish, State	
Sec 29 T21S R29E SWSW 98	80FSL 450FWL		EDDY COUNTY, NM		
12. CHECK THE AI	PPROPRIATE BOX(ES) TO IND	ICATE NATURE OF	F NOTICE, REPORT, OR OTH	ER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION				
- □ Notice of Intent	☐ Acidize \ □	Deepen	☐ Production (Start/Resume)	■ Water Shut-Off	
•	☐ Alter Casing ☐	Hydraulic Fracturing	☐ Reclamation	■ Well Integrity	
Subsequent Report	☐ Casing Repair ☐	New Construction	☐ Recomplete	☑ Other Drilling Operations	
☐ Final Abandonment Notice		Plug and Abandon	☐ Temporarily Abandon	Diffing Operations	
	Convert to Injection	Plug Back	☐ Water Disposal		
following completion of the involved testing has been completed. Final Al determined that the site is ready for f XTO respectfully submits this	rk will be performed or provide the Bond No operations. If the operation results in a moandonment Notices must be filed only afternal inspection. Sundry notice to report the drilling	ultiple completion or recorder all requirements, including	mpletion in a new interval, a Form 3160 ing reclamation, have been completed an	-4 must be filed once	
well.		,			
02/16/2019 to 02/19/2019 Spud well 02/16/2019. Drill 24 ft. Cement casing with 100 sx: 30 mins (good).	inch hole, TD at 375 ft. Run 18 5/s s Class C cmt. Bump plug. Cemen	8?, 87.5#, J-55 casin t to surface. WOC. T	g set at 375 est csg 1500 psi,	EGEWED .	
02/20/2019 to 02/24/2019 Drill 17 1/2 inch hole to 2870 ft. Run 13-3/8, 68#, HCL-80 casing set at 2870 ft. Cement casing with 2625 sxs Class POZC/C cement. Bump Plug. Circulate cement to surface. WOC. Test casing 1500					
psi, 30 mins (good).	cement. Bump Flug: Circulate cem	ient to surface. WOC		ARTESIAO.	
		<u> </u>			
14. I hereby certify that the foregoing is	: true and correct. Electronic Submission #462280 ve For XTO PERMIAN OPER nmitted to AFMSS for processing by	ATING LLC, sent to th	he Carlsbad		
Name (Printed/Typed) CHERYL		1	LATORY COORDINATOR		
	*				
Signature (Electronic Submission)		Date 04/22/20	019		
	THIS SPACE FOR FEDI	ERAL OR STATE	OFFICE USE		
				APR 2 5 2019	
Approved By		Title ACC	epted for Record	Date	
	d. Approval of this notice does not warran aitable title to those rights in the subject lead act operations thereon.	at or lase Office	onathon Shepard arlsbad Field Office		
	H C C C 1212 1		716 11 4 1 4	C41 11 4 1	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2) ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

Additional data for EC transaction #462280 that would not fit on the form

32. Additional remarks, continued

02/25/2019 to 03/13/2019
Drill 12 1/4 inch hole to 10245 ft, Run 9-5/8 inch, 53.5#, HCP-110 casing set @ 10240?. Cement casing with 2950 POZC/Class C Blend. Bump plug. Circulate cement to surface. WOC. Test casing 2260 psi, 30 mins (good).

03/14/2019 to 30/30/2019 Drill 8-1/2 inch hole to 14,020 ft. Run 7 inch, 32 #, P-110 casing set @ 14020?. Cement casing with 835 sxs Class H cement. Bump plug. Circulate cement to surface.

3/31/2019 to 4/13/19
Drill 6 inch hole to 14900 ft. Set packer at 13,950?. Run 5-1/2 tbg to 9286 and 4-1/2? tbg set at 13,950?. Test annulus to 500 psi for 30 mins (good).

Rig Release 04/13/19