NM OIL CONSERVATION

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy, Minerals and Natural Resources Department 1 1 2019

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr.

RECEIVED

Santa Fe, NM 87505

Date: 4-22-19		GAS CA	APTURE PI	AN			
☑ Original							
new completion (new d	lrill, recomplete t	o new zone, re-fr	ac) activity.			n facility flaring/venting fo	
Note: Form C-129 must be Well(s)/Production Fa  The well(s) that will be	cility – Name of	facility				A of 19.15.18.12 NMAC).	
Well Name	API		Footages	Expected MCF/D	Flared or Vented	Comments	
Sundown 31/32 W0DA Fee #1H	(30=015=45904)	1- 31- 22S - 27E	1030' FNL & 250' FV	0	NA	ONLINE AFTER FRAC	
western love in the forese conference calls to discontinuous product of pipeline to the forese conference calls to discontinuous product in the forest calls are the forest calls	ed to a production bed from production whigh pressure to connect the far a connect future. In course changes toProcessing P	n facility after floor facility is de gathering system cility to low/high drilling, completio addition, Mewbo drilling and comlant located in Sec	edicated to _n located in pressure gan and estima nume Oil Coupletion sche	thering systed first produmpany and dules. Gas	County, New em. Mewbo uction date for western from these	gas transporter system is in and will be connected to Mexico. It will require urne Oil Company provides or wells that are scheduled to have periodic wells will be processed at unty, Texas. The actual flow	
Flowback Strategy After the fracture treatm flared or vented. During	nent/completion of flowback, the flo	operations, well(s)	) will be prootent will be r	duced to tem	porary produ	action tanks and gas will be luced fluids contain minimal lls start flowing through the	

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

production facilities, unless there are operational issues on \_\_\_\_westerp \_\_\_\_ system at that time. Based on current information, it

## Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

is Operator's belief the system can take this gas upon completion of the well(s).

- Power Generation On lease
  - o Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
  - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines