

District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources

Form C-101
May 27, 2004

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit to appropriate District Office

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address LCX ENERGY, LLC. 110 NORTH MATIENFELD SUITE 200 MIDLAND, TEXAS 79701		2 OGRID Number 218885 API Number 30 - 015-34856
Property Code 33040	Property Name 1724 STATE	Well No. 312
Proposed Pool 1 Gopher -WOLFCAMP		Proposed Pool 2 77660

7 Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
	31	17S	24E		660'	NORTH	760'	EAST	EDDY

8 Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
	31	17S	24E		660'	SOUTH	760'	EAST	EDDY

Additional Well Information

Work Type Code N	Well Type Code G	Cable/Rotary ROTARY	Lease Type Code S	Ground Level Elevation
Multiple NO	Proposed Depth MD-8721 TVD-4960'	Formation WOLFCAMP	Contractor BIG DOG DRILLING	Spud Date WHEN APPROVED
Depth to Groundwater 100' +		Distance from nearest fresh water well		Distance from nearest surface water CATCLAW DRAW 1/2 MI. NORTH
Pit: Liner: Synthetic ☒ 12 mils thick Clay ☐ Pit Volume: 18M bbls		Drilling Method: Fresh Water ☒ Brine ☒ Diesel/Oil-based ☐ Gas/Air ☐		
Closed-Loop System ☐				

21 Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
26"	20"	Conductor	40'	Redi-mix	Surface
17 1/2"	13 3/8"	48#	350'	400 Sx.	Surface
12 1/2"	9 5/8"	36#	1200'	475 Sx.	Surface
8 3/4"-7 7/8"	5 1/2"	15.5#	MD-8721 TVD 4960'	600 Sx.	1000' F surface

** Describe the proposed program. If this application is to DEEPEN or PLUG BACK, give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

* Verify by Temp Survey or CBL

RECEIVED

MAY 11 2006

ODD-ANTEOM

SEE ATTACHED SHEET FOR DETAIL

NOTIFY OCD OF SPUD &
TIME TO WITNESS
CEMENTING OF SURFACE &
INTERMEDIATE CASING

I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify that the drilling pit will be constructed according to NMOCD guidelines ☒ a general permit ☐ or an (attached) alternative OCD-approved plan ☐ .		OIL CONSERVATION DIVISION	
Printed name: Joe T. Janica		Approved by: BRYAN G. ARANT	
Title: Agent		DISTRICT II GEOLOGIST	
E-mail Address: joejanica@valornet.com		Approval Date: MAY 12 2006 Expiration Date: MAY 12 2007	
Date: 05/10/06	Phone: 505-391-8503	Conditions of Approval Attached ☐	

DISTRICT I
1625 N. French Dr., Hobbs, NM 88240

DISTRICT II
1301 W. Grand Avenue, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
1220 South St. Frances Dr.
Santa Fe, NM 87505

Form C-102
Revised October 12, 2005
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number	Pool Code 7766c	Pool Name C. Gopher - WOLFCAMP
Property Code	Property Name 1724 STATE	Well Number 312
OGRID No. 218885	Operator Name LCX ENERGY, LLC	Elevation 3883'

Surface Location

UL or lot No. A	Section 31	Township 17 S	Range 24 E	Lot Idn	Feet from the 660	North/South line NORTH	Feet from the 760	East/West line EAST	County EDDY
--------------------	---------------	------------------	---------------	---------	----------------------	---------------------------	----------------------	------------------------	----------------

Bottom Hole Location If Different From Surface

UL or lot No. P	Section 31	Township 17 S	Range 24 E	Lot Idn	Feet from the 660	North/South line SOUTH	Feet from the 760	East/West line EAST	County EDDY
Dedicated Acres 320	Joint or Infill	Consolidation Code	Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

Plane Coordinate X = 452,575.0 Y = 653,885.2 VA-2586 NOTE: 1) Plane Coordinates shown hereon are Transverse Mercator Grid and Conform to the "New Mexico Coordinate System", New Mexico East Zone, North American Datum of 1983. Distances shown hereon are mean horizontal surface values.	3879.9' 3877.0' 3886.3' 3882.3' 660' 760' 3966' BHL 760' 660'	OPERATOR CERTIFICATION I hereby certify the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unless mineral interests in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or is a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Joe T. Janica</i> Signature Date Joe T. Janica 05/10/06 Printed Name Agent SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision and that the same is true and correct to the best of my belief. April 22, 2006 Date of Survey LVA Signature & Seal of Professional Surveyor W.O. Num. 2006-0393 Certificate No. MACON McDONALD 12185
--	--	--

LCX ENERGY, LLC.
1724 STATE # 312
SL- 660' FNL & 760' FEL
BHL-660' FSL & 760' FEL
SECTION 31 T17S-R24E
EDDY CO. NEW MEXICO

**Horizontal Drilling Procedure
Abo Wildcat Horizontals
(Eddy Co., NM)**

1. Drill 26" hole to 40'. Set 40' of 20" conductor pipe and cement to surface with Redi-mix.
2. Drill 17-1/2" hole to 350'.
3. Drill 12-1/4" hole to 1200'. Run and set 1200' of 9-5/8" 36# J-55 ST&C casing. Cement with 375 sx of 35/65 Poz/C + 5% NaCl + 6% Bentonite, tail in with 100 sx. of Class "C" cement + 2% CaCl, circulate cement to surface.
4. Drill 7-7/8" or 8-3/4" hole to approx. 5000'. Set cement kick-off plug from TD to approx. 4400 ft with 150 sx H + 0.5% dispersant.
5. Dress cement top to desired kick-off point. Drill 7-7/8" curve and land lateral in pay zone (approx. 4900 ft TVD). Pickup lateral drilling assembly with an 8-3/4" or 7-7/8" bit and drill a +/-4000' lateral to 660' from lease line (approx. 4000 ft vertical section).
6. Run and set 5-1/2" 17# N80 or stronger production casing. Cement 5-1/2" with acid soluble cement through the lateral and 400 sx 50/50 Poz/C + 10% gel and tail in with 200 sx C + 200% CaCO₃ (acid soluble cement) + fluid loss additive + retarder (as required), attempting to bring top of cement to 1,000'.

Contingency Strings:

If lost circulation occurs in the surface hole:

- 2a. Run and set 350' of 13-3/8" 48# H-40 ST&C casing. Cement with 200 sx 35/65 Poz/C + 6% gel and tail in with 200 sx of Class "C" cement + 2% CaCl, circulate cement to surface.

If hole conditions dictate running a 7" contingency string in the 8-3/4" hole :

- 4a. Run approx. 5100 ft 7" 26# J55 or stronger casing to TD. Cement with 700 sx class 'C' cement + add's attempting bringing TOC to approx. 1,000 ft. This may be done in the vertical pilot hole or at the end of the 8-3/4" curve section.
- 4b. Run whipstock and cut a window in the 7" casing (or drill out with 6-1/8" BHA if 7" set at end of curve). Drill to TD.
- 5a. Step 5 will be omitted.
- 6a. Run and set approximately 4400 ft 4-1/2" 11.6# N/L80 liner from TD to approximately 200' above the window/7" casing shoe. Cement with approx. 110 sx C + 200% CaCO₃ (acid soluble cement) + add's attempting to bring TOC above liner top.

FRESH WATER WILL BE USED TO DRILL THE 350' HOLE AND THE 1200' HOLE.


THERE IS NO KNOWN PRESENCE OF ANY H₂S IN THIS AREA. OTHER WELLS DRILLED HAVE NOT ENCOUNTERED ANY HYDROGEN SULFIDE WHILE DRILLING.

BLOWOUT PREVENTER SYSTEM

3000 PSI


Fill Line

Flow Line



900 SERIES
3000 PSI WP

Choke Manifold Assembly for 5M WP System




SECTION 31, TOWNSHIP 17 SOUTH, RANGE 24 EAST, N.M.P.M.

EDDY COUNTY

NEW MEXICO

L-2006-0393



LCX ENERGY, LLC

1724 STATE #312


Located 660' FNL & 760' FEL, Section 31
Township 17 S, Range 24 E, N.M.P.M.
Eddy County, New Mexico

Drawn By: JSR	Date: April 28, 2006
Scale: 1"=100'	Field Book: 326 /
Revision Date:	Quadrangle: Hope SE
W.O. No: 2006-0393	Dwg. No.: L-2006-0393

WEST
COMPANY
of Midland, Inc.

110 W. LOUISIANA, STE. 110
MIDLAND TEXAS, 79701
(432) 687-0865 - (432) 687-0868 FAX

LOCATION VERIFICATION MAP



SCALE: 1" = 2000'

CONTOUR INTERVAL:
HOPE SE - 10'

SEC. 31 TWP. 17-S RGE. 24-E

SURVEY N.M.P.M.

COUNTY EDDY

DESCRIPTION 760' FEL & 660' FNL

ELEVATION 3883'

OPERATOR LCX ENERGY, LLC

LEASE 1724 STATE #312


U.S.G.S. TOPOGRAPHIC MAP
HOPE SE, N.M.



**WEST
COMPANY**
of Midland, Inc.

110 W. LOUISIANA, STE. 110
MIDLAND TEXAS, 79701
(432) 687-0865 - (432) 687-0868 FAX

VICINITY MAP



SCALE: 1" = 2 MILES

SEC. 31 TWP. 17-S RGE. 24-E
SURVEY N.M.P.M.
COUNTY EDDY
DESCRIPTION 760' FEL & 660' FNL
ELEVATION 3883'
OPERATOR LCX ENERGY, LLC
LEASE 1724 STATE #312



WEST
COMPANY
of Midland, Inc.

110 W. LOUISIANA, STE. 110
MIDLAND TEXAS, 79701
(432) 687-0865 - (432) 687-0868 FAX

Proposal



Report Date: May 9, 2006	Survey / DLS Computation Method: Minimum Curvature / Lubinski
Client: LCX Energy	Vertical Section Azimuth: 179.310°
Field: Eddy County, NM Nad 83	Vertical Section Origin: N 0.000 ft, E 0.000 ft
Structure / Slot: 1724 State 312 / 1724 State 312	TVD Reference Datum: RKB
Well: 1724 State 312	TVD Reference Elevation: 0.0 ft relative to
Borehole: 1724 State #312	Sea Bed / Ground Level Elevation: 0.000 ft relative to
UWI/API#:	Magnetic Declination: 8.703°
Survey Name / Date: 1724 State #312_r1 / May 9, 2006	Total Field Strength: 49391.441 nT
Tort / AHD / DDI / ERD ratio: 90.000° / 3966.12 ft / 5.798 / 0.800	Magnetic Dip: 60.656°
Grid Coordinate System: NAD83 New Mexico State Planes, Eastern Zone, US Feet	Declination Date: May 09, 2006
Location Lat/Long: N 32 47 50.021, W 104 37 19.927	Magnetic Declination Model: IGRF 2005
Location Grid N/E Y/X: N 653885.200 ftUS, E 452575.000 ftUS	North Reference: Grid North
Grid Convergence Angle: -0.15647167°	Total Corr Mag North -> Grid North: +8.859°
Grid Scale Factor: 0.99991811	Local Coordinates Referenced To: Well Head

Comments	Measured Depth (ft)	Inclination (deg)	Azimuth (deg)	TVD (ft)	Vertical Section (ft)	NS (ft)	EW (ft)	Closure (ft)	Closure Azimuth (deg)	DLS (deg/100 ft)	Tool Face (deg)
Tie-In	0.00	0.00	179.31	0.00	0.00	0.00	0.00	0.00	0.00	0.00	179.31M
KOP	4482.54	0.00	179.31	4482.54	0.00	0.00	0.00	0.00	0.00	0.00	179.31M
	4500.00	2.10	179.31	4500.00	0.32	-0.32	0.00	0.32	179.31	12.00	179.31M
	4600.00	14.10	179.31	4598.82	14.38	-14.38	0.17	14.38	179.31	12.00	0.00G
	4700.00	26.10	179.31	4692.56	48.67	-48.67	0.58	48.67	179.31	12.00	0.00G
	4800.00	38.10	179.31	4777.12	101.71	-101.70	1.22	101.71	179.31	12.00	0.00G
	4900.00	50.10	179.31	4848.81	171.17	-171.16	2.05	171.17	179.31	12.00	0.00G
	5000.00	62.10	179.31	4904.49	254.01	-254.00	3.04	254.01	179.31	12.00	0.00G
	5100.00	74.10	179.31	4941.72	346.63	-346.60	4.15	346.63	179.31	12.00	0.00G
	5200.00	86.10	179.31	4958.89	444.95	-444.92	5.33	444.95	179.31	12.00	0.00G
EOC	5232.54	90.00	179.31	4960.00	477.46	-477.43	5.72	477.46	179.31	12.00	0.00G
	5300.00	90.00	179.31	4960.00	544.93	-544.89	6.53	544.93	179.31	0.00	0.00G
	5400.00	90.00	179.31	4960.00	644.93	-644.88	7.72	644.93	179.31	0.00	0.00G
	5500.00	90.00	179.31	4960.00	744.93	-744.88	8.92	744.93	179.31	0.00	0.00G
	5600.00	90.00	179.31	4960.00	844.93	-844.87	10.12	844.93	179.31	0.00	0.00G
	5700.00	90.00	179.31	4960.00	944.93	-944.86	11.32	944.93	179.31	0.00	0.00G
	5800.00	90.00	179.31	4960.00	1044.93	-1044.85	12.52	1044.93	179.31	0.00	0.00G
	5900.00	90.00	179.31	4960.00	1144.93	-1144.85	13.71	1144.93	179.31	0.00	0.00G
	6000.00	90.00	179.31	4960.00	1244.93	-1244.84	14.91	1244.93	179.31	0.00	0.00G
	6100.00	90.00	179.31	4960.00	1344.93	-1344.83	16.11	1344.93	179.31	0.00	0.00G
	6200.00	90.00	179.31	4960.00	1444.93	-1444.83	17.31	1444.93	179.31	0.00	0.00G
	6300.00	90.00	179.31	4960.00	1544.93	-1544.82	18.50	1544.93	179.31	0.00	0.00G
	6400.00	90.00	179.31	4960.00	1644.93	-1644.81	19.70	1644.93	179.31	0.00	0.00G
	6500.00	90.00	179.31	4960.00	1744.93	-1744.80	20.90	1744.93	179.31	0.00	0.00G
	6600.00	90.00	179.31	4960.00	1844.93	-1844.80	22.10	1844.93	179.31	0.00	0.00G
	6700.00	90.00	179.31	4960.00	1944.93	-1944.79	23.30	1944.93	179.31	0.00	0.00G
	6800.00	90.00	179.31	4960.00	2044.93	-2044.78	24.49	2044.93	179.31	0.00	0.00G
	6900.00	90.00	179.31	4960.00	2144.93	-2144.78	25.69	2144.93	179.31	0.00	0.00G
	7000.00	90.00	179.31	4960.00	2244.93	-2244.77	26.89	2244.93	179.31	0.00	0.00G
	7100.00	90.00	179.31	4960.00	2344.93	-2344.76	28.09	2344.93	179.31	0.00	0.00G
	7200.00	90.00	179.31	4960.00	2444.93	-2444.75	29.28	2444.93	179.31	0.00	0.00G
	7300.00	90.00	179.31	4960.00	2544.93	-2544.75	30.48	2544.93	179.31	0.00	0.00G
	7400.00	90.00	179.31	4960.00	2644.93	-2644.74	31.68	2644.93	179.31	0.00	0.00G
	7500.00	90.00	179.31	4960.00	2744.93	-2744.73	32.88	2744.93	179.31	0.00	0.00G
	7600.00	90.00	179.31	4960.00	2844.93	-2844.73	34.08	2844.93	179.31	0.00	0.00G
	7700.00	90.00	179.31	4960.00	2944.93	-2944.72	35.27	2944.93	179.31	0.00	0.00G
	7800.00	90.00	179.31	4960.00	3044.93	-3044.71	36.47	3044.93	179.31	0.00	0.00G
	7900.00	90.00	179.31	4960.00	3144.93	-3144.70	37.67	3144.93	179.31	0.00	0.00G

Comments	Measured Depth (ft)	Inclination (deg)	Azimuth (deg)	TVD (ft)	Vertical Section (ft)	NS (ft)	EW (ft)	Closure (ft)	Closure Azimuth (deg)	DLS (deg/100 ft)	Tool Face (deg)
	8000.00	90.00	179.31	4960.00	3244.93	-3244.70	38.87	3244.93	179.31	0.00	0.00G
	8100.00	90.00	179.31	4960.00	3344.93	-3344.69	40.06	3344.93	179.31	0.00	0.00G
	8200.00	90.00	179.31	4960.00	3444.93	-3444.68	41.26	3444.93	179.31	0.00	0.00G
	8300.00	90.00	179.31	4960.00	3544.93	-3544.68	42.46	3544.93	179.31	0.00	0.00G
	8400.00	90.00	179.31	4960.00	3644.93	-3644.67	43.66	3644.93	179.31	0.00	0.00G
	8500.00	90.00	179.31	4960.00	3744.93	-3744.66	44.85	3744.93	179.31	0.00	0.00G
	8600.00	90.00	179.31	4960.00	3844.93	-3844.65	46.05	3844.93	179.31	0.00	0.00G
	8700.00	90.00	179.31	4960.00	3944.93	-3944.65	47.25	3944.93	179.31	0.00	0.00G
PBHL	8721.19	90.00	179.31	4960.00	3966.12	-3965.83	47.50	3966.12	179.31	0.00	0.00G

LCX Energy

WELL	1724 State 312	FIELD	Eddy County, NM	STRUCTURE	1724 State 312
Magnetic Parameters Model: IGRF 2005 Dip: 60.656° Date: May 09, 2006 Mag Dec: +8.703° PB: 49391.4 nT Surface Location Lat: N32 47 50.021 Lon: W104 37 19.827 NAD83 New Mexico State Planes, Eastern Zone, US Feet Northing: 653895.20 ftUS Easting: 452575.00 ftUS Scale Fact: 0.9999181133 Miscellaneous Slot: 1724 State 312 Plan: 1724 State 312.r1 TVD Ref: RK6 (0.00 ft above) Srvy Date: Tue 10:47 AM May 09, 2006					



Critical Points								
Critical Point	MD	INCL	AZIM	TVD	YSEC	N(+) / S(-)	E(+) / W(-)	DLS
Tie-In	0.00	0.00	179.31	0.00	0.00	0.00	0.00	0.00
KOP	4482.54	0.00	179.31	4482.54	0.00	0.00	0.00	0.00
EOC	5232.54	90.00	179.31	4960.00	477.46	-477.43	5.72	12.00
PBHL	8721.19	90.00	179.31	4960.00	3966.12	-3965.83	47.50	0.00

INTREPID
Directional Drilling Specialists

