300001	NOTICES AND REPO	GEMENT RTS OWED Arte	NMLC063079A	т. Х. Ч	
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.		ee or Tribe Name			
SUBMIT IN TRIPLICATE - Other instructions on page 2         1. Type of Well         Oil Well         Gas Well         Other			7. If Unit or CA/Agree 891000303X	<ul> <li>7. If Unit or CA/Agreement, Name and/or No. 891000303X</li> <li>8. Well Name and No. POKER LAKE UNIT 25 BD 102H</li> </ul>	
2. Name of Operator XTO PERMIAN OPERATING	Contact: LLC E-Mail: kelly_kard	KELLY KARDOS os@xtoenergy.com	9. API Well No. 30-015-45846-	9. API Well No. 30-015-45846-00-X1	
3a. Address 6401 HOLIDAY HILL ROAD I MIDLAND, TX 79707	BLDG 5	3b. Phone No. (include area code) Ph: 432-620-4374		0. Field and Pool or Exploratory Area PURPLE SAGE-WOLFCAMP (GAS	
4. Location of Well (Footage, Sec., )	T., R., M., or Survey Description	1)	11. County or Parish,	, State	
Sec 25 T25S R30E SWNW 2 32.101479 N Lat, 103.84079			EDDY COUNT	EDDY COUNTY, NM	
12. CHECK THE A	PPROPRIATE BOX(ES)	TO INDICATE NATURE O	NOTICE, REPORT, OR OT	HER DATA	
TYPE OF SUBMISSION		TYPE OF	ACTION		
Notice of Intent	Acidize	Deepen	Production (Start/Resume)	U Water Shut-Off	
	□ Alter Casing	Hydraulic Fracturing	Reclamation	U Well Integrity	
Subsequent Report	Casing Repair	□ New Construction	Recomplete	Other Drilling Operation	
Final Abandonment Notice	Change Plans	Plug and Abandon Plug Back	Temporarily Abandon Water Disposal		
following completion of the involve testing has been completed. Final A determined that the site is ready for XTO Permian Operating, LLC	d operations. If the operation r bandonment Notices must be fi final inspection. C received verbal approva the 9-5/8" casing. The v	I on 8/6/19 from Jonathon She vellhead is manufactured to AP	ng reclamation, have been completed pard (BLM) to weld I standards.	60-4 must be filed once and the operator has	
following completion of the involve testing has been completed. Final A determined that the site is ready for XTO Permian Operating, LLC an 11" x 10k x 9-5/8" SOW to The field welding procedure i Cut 9-5/8" casing to a depth v will allow us to hang the 7" ca ground level. Welding on the Test the weld to 80% of 9-5/8	d operations. If the operation r bandonment Notices must be fi final inspection. C received verbal approva the 9-5/8" casing. The v s as follows: where the 11" x 10k flang asing on a mandrel hange casing head will be per C	esults in a multiple completion or reco led only after all requirements, includ	mpletion in a new interval, a Form 31 ng reclamation, have been completed pard (BLM) to weld I standards. This height A cap below procedure.	60-4 must be filed once	
following completion of the involve testing has been completed. Final A determined that the site is ready for XTO Permian Operating, LLC an 11" x 10k x 9-5/8" SOW to The field welding procedure i Cut 9-5/8" casing to a depth v will allow us to hang the 7" ca ground level. Welding on the	d operations. If the operation r bandonment Notices must be fi final inspection. C received verbal approva the 9-5/8" casing. The v s as follows: where the 11" x 10k flang asing on a mandrel hange casing head will be per G Casing collapse. P.	esults in a multiple completion or reco led only after all requirements, includ I on 8/6/19 from Jonathon She vellhead is manufactured to AP e sits 14" below ground level. T or, set a packoff, and install a T	mpletion in a new interval, a Form 31 ing reclamation, have been completed I standards. This height A cap below procedure. AUG	60-4 must be filed once and the operator has <b>NSERVATION</b> IA DISTRICT 2 1 2019	
following completion of the involve testing has been completed. Final A determined that the site is ready for XTO Permian Operating, LLC an 11" x 10k x 9-5/8" SOW to The field welding procedure i Cut 9-5/8" casing to a depth v will allow us to hang the 7" ca ground level. Welding on the Test the weld to 80% of 9-5/8 Install the BOP. Set 11" test plug and test BO Remove existing packer inside 14. Thereby certify that the foregoing	d operations. If the operation r bandonment Notices must be fi final inspection. C received verbal approva the 9-5/8" casing. The v s as follows: where the 11" x 10k flang asing on a mandrel hange casing head will be per G s" casing collapse. P. le the 9-5/8" casing. Electronic Submission a For XTO PERM	esults in a multiple completion or reco led only after all requirements, includ I on 8/6/19 from Jonathon She vellhead is manufactured to AP e sits 14" below ground level. T or, set a packoff, and install a T	Information System high Carlsbad	60-4 must be filed once and the operator has <b>NSERVATION</b> LA DISTRICT 2 1 2019	
following completion of the involve testing has been completed. Final A determined that the site is ready for XTO Permian Operating, LLC an 11" x 10k x 9-5/8" SOW to The field welding procedure i Cut 9-5/8" casing to a depth v will allow us to hang the 7" ca ground level. Welding on the Test the weld to 80% of 9-5/8 Install the BOP. Set 11" test plug and test BO Remove existing packer inside 14. Thereby certify that the foregoing	d operations. If the operation r bandonment Notices must be fi final inspection. C received verbal approva the 9-5/8" casing. The v s as follows: where the 11" x 10k flang asing on a mandrel hange casing head will be per G s" casing collapse. P. le the 9-5/8" casing. P. le the 9-5/8" casing. is true and correct. Electronic Submission a For XTO PERM mmitted to AFMSS for prov	sults in a multiple completion or reco led only after all requirements, includ I on 8/6/19 from Jonathon She vellhead is manufactured to AP e sits 14" below ground level. T r, set a packoff, and install a T. E recommended field wedding #476968 verified by the BLM Wel IAN OPERATING LLC, sent to ti cessing by PRISCILLA PEREZ of	Information System high Carlsbad	60-4 must be filed once and the operator has <b>NSERVATION</b> LA DISTRICT 2 1 2019	
following completion of the involve testing has been completed. Final A determined that the site is ready for XTO Permian Operating, LLC an 11" x 10k x 9-5/8" SOW to The field welding procedure i Cut 9-5/8" casing to a depth v will allow us to hang the 7" ca ground level. Welding on the Test the weld to 80% of 9-5/8 Install the BOP. Set 11" test plug and test BO Remove existing packer inside 14. 1 hereby certify that the foregoing Name ( <i>Printed/Typed</i> ) KELLY K	d operations. If the operation r bandonment Notices must be fi final inspection. C received verbal approva the 9-5/8" casing. The v s as follows: where the 11" x 10k flang asing on a mandrel hange casing head will be per G s" casing collapse. P. le the 9-5/8" casing. P. le the 9-5/8" casing. is true and correct. Electronic Submission a For XTO PERM mmitted to AFMSS for prov	sults in a multiple completion or reco led only after all requirements, includ I on 8/6/19 from Jonathon She vellhead is manufactured to AP e sits 14" below ground level. T r, set a packoff, and install a T. E recommended field wedding #476968 verified by the BLM Wel IAN OPERATING LLC, sent to ti cessing by PRISCILLA PEREZ of	Information System the Carlsbad 1 08/07/2019 (19PP2932SE) ATORY COORDINATOR	60-4 must be filed once and the operator has <b>NSERVATION</b> LA DISTRICT 2 1 2019	
following completion of the involve testing has been completed. Final A determined that the site is ready for XTO Permian Operating, LLC an 11" x 10k x 9-5/8" SOW to The field welding procedure i Cut 9-5/8" casing to a depth v will allow us to hang the 7" ca ground level. Welding on the Test the weld to 80% of 9-5/8 Install the BOP. Set 11" test plug and test BO Remove existing packer inside 14. 1 hereby certify that the foregoing Name ( <i>Printed/Typed</i> ) KELLY K	d operations. If the operation n bandonment Notices must be fi final inspection. C received verbal approva the 9-5/8" casing. The v s as follows: where the 11" x 10k flang asing on a mandrel hange casing head will be per C s" casing collapse. P. le the 9-5/8" casing. Electronic Submission a For XTO PERN mmitted to AFMSS for prov ARDOS	sults in a multiple completion or reco led only after all requirements, includ I on 8/6/19 from Jonathon She vellhead is manufactured to AP e sits 14" below ground level. T r, set a packoff, and install a T. E recommended field wedding #476968 verified by the BLM Wel IIAN OPERATING LLC, sent to t cessing by PRISCILLA PEREZ of Title REGUL	Information System he Carlsbad 1 08/07/2019 (19PP2932SE) ATORY COORDINATOR D19	60-4 must be filed once and the operator has <b>NSERVATION</b> LA DISTRICT 2 1 2019	
following completion of the involve testing has been completed. Final A determined that the site is ready for XTO Permian Operating, LLC an 11" x 10k x 9-5/8" SOW to The field welding procedure i Cut 9-5/8" casing to a depth v will allow us to hang the 7" ca ground level. Welding on the Test the weld to 80% of 9-5/8 Install the BOP. Set 11" test plug and test BO Remove existing packer inside 14. Thereby certify that the foregoing Co Name ( <i>Printed/Typed</i> ) KELLY K Signature (Electronic	d operations. If the operation n bandonment Notices must be fi final inspection. C received verbal approva the 9-5/8" casing. The v s as follows: where the 11" x 10k flang asing on a mandrel hange casing head will be per C s" casing collapse. P. le the 9-5/8" casing. Electronic Submission a For XTO PERN mmitted to AFMSS for prov ARDOS	sults in a multiple completion or reco led only after all requirements, includ I on 8/6/19 from Jonathon She vellhead is manufactured to AP e sits 14" below ground level. 1 r, set a packoff, and install a T. E recommended field wedding #476968 verified by the BLM Wel IAN OPERATING LLC, sent to t cessing by PRISCILLA PEREZ of Title REGUL Date 08/07/2 OR FEDERAL OR STATE	Information System he Carlsbad 1 08/07/2019 (19PP2932SE) ATORY COORDINATOR D19	60-4 must be filed once and the operator has NSERVATION IA DISTRICT 2 1 2019 ECEIVED	
following completion of the involve testing has been completed. Final A determined that the site is ready for XTO Permian Operating, LLC an 11" x 10k x 9-5/8" SOW to The field welding procedure i Cut 9-5/8" casing to a depth v will allow us to hang the 7" ca ground level. Welding on the Test the weld to 80% of 9-5/8 Install the BOP. Set 11" test plug and test BO Remove existing packer inside 14. Thereby certify that the foregoing Co Name ( <i>Printed/Typed</i> ) KELLY K Signature (Electronic	d operations. If the operation r bandonment Notices must be fi final inspection. C received verbal approva the 9-5/8" casing. The v s as follows: where the 11" x 10k flang asing on a mandrel hange casing head will be per G s" casing collapse. P. de the 9-5/8" casing. Electronic Submission a For XTO PERM mmitted to AFMSS for prov ARDOS Submission) THIS SPACE F	sults in a multiple completion or reco led only after all requirements, includ I on 8/6/19 from Jonathon She vellhead is manufactured to AP e sits 14" below ground level. T r, set a packoff, and install a T. E recommended field wedding the sits of the set of the s	Information System the Carlsbad to 08/07/2019 (19PP2932SE) ATORY COORDINATOR	60-4 must be filed once and the operator has NSERVATION A DISTRICT 2 1 2019 ECEIVED	
following completion of the involve testing has been completed. Final A determined that the site is ready for XTO Permian Operating, LLC an 11" x 10k x 9-5/8" SOW to The field welding procedure i Cut 9-5/8" casing to a depth v will allow us to hang the 7" ca ground level. Welding on the Test the weld to 80% of 9-5/8 Install the BOP. Set 11" test plug and test BO Remove existing packer inside 14. 1 hereby certify that the foregoing Co Name ( <i>Printed/Typed</i> ) KELLY K Signature (Electronic Approved By /S/JOnatho onditions of approval, if any, are attacher tify that the applicant holds legal or ex	d operations. If the operation r bandonment Notices must be fi final inspection. C received verbal approva the 9-5/8" casing. The v s as follows: where the 11" x 10k flang asing on a mandrel hange casing head will be per G s" casing collapse. P. le the 9-5/8" casing. Submission a for XTO PERN mmitted to AFMSS for prov ARDOS Submission) THIS SPACE F	esults in a multiple completion or reco led only after all requirements, includ I on 8/6/19 from Jonathon She vellhead is manufactured to AP e sits 14" below ground level. T r, set a packoff, and install a T is recommended field wedding #476968 verified by the BLM Wel IAN OPERATING LLC, sent to t cessing by PRISCILLA PEREZ of Title REGUL Date 08/07/2 OR FEDERAL OR STATE e subject lease a crime for any person knowingly and	Information System he Carlsbad 08/07/2019 (19PP2932SE) ATORY COORDINATOR 019 0FFICE USE Field Office	60-4 must be filed once and the operator has <b>DNSERVATION</b> IA DISTRICT 2 1 2019 ECEIVED AUG 0 8 20	


## Additional data for EC transaction #476968 that would not fit on the form

## 32. Additional remarks, continued

Â

مسلزة

Install wear bushing & resume drilling operations.



	Pressure Control				
	9-5/8" x 7" 15M RSH-1 Wellhead Assembly, With T-EBS-F-HP Tubing Head				
COPYWRIGHT & PROPRIETARY NOTICE	DRAWN BY: VJK	DRAWING NO.	10014725		
Copywright 2017 Baker Hughes, a GE company, LLC (unpublished work). All rights reserved. The information contained in this document i company confidential and proprietary property of Baker Hughes and its affiliates. It is to be used only for the benefit of Baker Hughes and	REVIEWED BY:	Rev. A	Sht. of		
may not be distributed, transmitted, reproduced, altered or used for any purpose without the express written consent of Baker Hughes, ALL DIMENSIONS ARE APPROXIMATE, NOT FOR MANUFACTURING USE.	APPROVED BY:	DATE: 26MAR18			

XTO ENERGY, INC.