District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

GAS	CAP	TU	RE	PL	AN
-----	-----	----	----	----	----

Date: 06/17/19		
x Original Amended - Reason for Amendment:	Devon & OGRID No.: D	evon Energy Prod Co., LP (6137)
This Gas Capture Plan outlines actions to be tal completion (new drill, recomplete to new zone,	•	well/production facility flaring/venting for new
Note: Form C-129 must be submitted and approved pr	ior to exceeding 60 days allowe	ed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages		Expected MCF/D	Flared/ Vented	Comments
Papa Fritas 27-22 Fed Com 331H		Sec. 11, T24S, R29E	102 FNL, 943 F	WL			Papa Fritas 27 CTB 1
Papa Fritas 27-22 Fed Com 332H		Sec. 11, T24S, R29E	152 FSL, 1822F	EL			Papa Fritas 27 CTB
Papa Fritas 27-22 Fed Com 621H		Sec. 11, T24S, R29E	102 FNL, 993 F	WL			Papa Fritas 27 CTB
Papa Fritas 27-22 Fed Com 622H		Sec. 11, T24S, R29E	152 FSL, 1762 F	EL			Papa Fritas 27 CTB
Papa Fritas 27-22 Fed Com 711H		Sec. 11, T24S, R29E	102 FNL, 968 F	WL			Papa Fritas 27 CTB
Papa Fritas 27-22 Fed Com 712H		Sec. 11, T24S, R29E	152 FNL, 1792 I	FEL			Papa Fritas 27 CTB

Gathering System and Pipeline Notification

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>DCP</u> system at that time. Based on current information, it is <u>Devon's</u> belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - o Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - o Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines