

Submit 3 Copies To Appropriate District
Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico

Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-015-32813

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

B-8617-1

7. Lease Name or Unit Agreement Name:

Spurck 16 State Com

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Yates Drilling Company

3. Address of Operator

105 South 4th St. Artesia, NM 88210

8. Well No.

2

9. Pool name or Wildcat

Morrow

4. Well Location

Unit Letter K : 1980 feet from the S line and 1980 feet from the W line

Section 16 Township 17S Range 28E County Eddy NMPM

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3559' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

6-20-2003 TD 2020'. Ran 48 jts. 8 5/8", 32# J-55 ST&C (2024.70') casing. Regular guide shoe set at 2020'. Float collar set at 1980.38'. Cemented with 500 sxs. 35-65-6 "C" + 1% CaCl2 + 25# Celloflake (yld 1.95, wt 12.5). Tailed in with 200 sxs "C" + 2% CaCl2 (yld 1.34, wt 14.8). PD at 12:03 AM, 6-21-2003. Bumped plug to 1105 psi. Float held okay. Circulated 120 sxs. WOC 22 hrs.
NOTE: Ran centralizers on joints 1,4,6,8,10,12,14,16. Notified Phil Hawkins, NMOCD of TD time and cement.

6-22-2003 Resumed drilling 7 7/8" hole.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Karen J. Leishman TITLE Engineering Tech DATE 7-18-2003

Type or print name Karen J. Leishman Telephone No. 505-748-8463

(This space for State use)

APPROVED BY Simon W. Green TITLE SUPERVISOR, DISTRICT II DATE JUL 24 2003

Conditions of approval, if any: