30 015 46707 RECEIVED

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy, Minerals and Natural Resources Depart FEB 1 0 2020

Submit Original to Appropriate District Office

Oil Conservation Division 1220 South St. Francis DEMNRD-OCD ARTESIA Santa Fe, NM 87505

GAS CAPTURE PLAN

Date: 04/26/2019

⊠ Original

Operator & OGRID No.: XTO Energy, Inc [005380]

□ Amended - Reason for Amendment:

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility - Name of facility: Chain-Blue CTBS

The well(s) that will be located at the production facility are shown in the table below.

Well NameAPIWell Location (ULSTR)FootagesExpected MCF/DFlared or VentedComments CommentsChain-Blue Lightning 26 Fed 108HP-23-25S-29E331'FSL & 273'FEL2500MCF/DFlared/SoldChain-Blue Lightning 26 Fed 703HN-23-25S-29E296'FSL & 2025'FWL2500MCF/DFlared/SoldChain-Blue Lightning 26 Fed 162HM-23-25S-29E366'FSL & 955'FWL2500MCF/DFlared/SoldChain-Blue Lightning 26 Fed 162HM-23-25S-29E366'FSL & 955'FWL2500MCF/DFlared/SoldChain-Blue Lightning 26 Fed 162HM-23-25S-29E366'FSL & 955'FWL2500MCF/DFlared/Sold	
Fed 108H273'FELChain-Blue Lightning 26N-23-25S-29E296'FSL & 2500MCF/DFlared/SoldFed 703H2025'FWL1Chain-Blue Lightning 26M-23-25S-29E366'FSL & 2500MCF/DFlared/SoldFed 162H955'FWL11Chain-Blue Lightning 26M-23-25S-29E366'FSL & 2500MCF/DFlared/Sold	· .
Chain-Blue Lightning 26N-23-25S-29E296'FSL & 2500MCF/DFlared/SoldFed 703H2025'FWL2025'FWL1Chain-Blue Lightning 26M-23-25S-29E366'FSL & 2500MCF/DFlared/SoldFed 162H955'FWL11Chain-Blue Lightning 26M-23-25S-29E366'FSL & 2500MCF/DFlared/Sold	· · · · · · · · · · · · · · · · · · ·
Fed 703H2025'FWLChain-Blue Lightning 26M-23-25S-29E366'FSL & 2500MCF/DFlared/SoldFed 162H955'FWLIChain-Blue Lightning 26M-23-25S-29E366'FSL & 2500MCF/DFlared/Sold	
Chain-Blue Lightning 26M-23-25S-29E366'FSL & 2500MCF/DFlared/SoldFed 162H955'FWL1Chain-Blue Lightning 26M-23-25S-29E366'FSL & 2500MCF/DFlared/Sold	
Fed 162H 955'FWL Chain-Blue Lightning 26 M-23-25S-29E 366'FSL & 2500MCF/D Flared/Sold	
Chain-Blue Lightning 26 M-23-25S-29E 366'FSL & 2500MCF/D Flared/Sold	
Fed 161H 705'FWL	
Chain-Blue Lightning 26 M-23-25S-29E 331'FSL & 2500MCF/D Flared/Sold	
Fed 121H 705'FWL	
Chain-Blue Lightning 26 M-23-25S-29E 331'FSL & 2500MCF/D Flared/Sold	
Fed 122H 955'FWL	
Chain-Blue Lightning 26 M-23-258-29E 296'FSL & 2500MCF/D Flared/Sold Fed 701H 705'FWL 705'FWL	
Chain-Blue Lightning 26 M-23-25S-29E 296'FSL & 2500MCF/D Flared/Sold	
Fed 102H 955'FWL	
Chain-Blue Lightning 26 N-23-25S-29E 366'FSL & 2500MCF/D Flared/Sold	
Fed 164H 2275'FWL	
Chain-Blue Lightning 26 N-23-25S-29E 366'FSL & 2500MCF/D Flared/Sold	
Fed 163H 2025'FWL Chair Direct Linkwise 20 N 22 255 20F 22 250 20F	
Chain-Blue Lightning 26N-23-25S-29E331'FSL & 2500MCF/DFlared/SoldFed 103H2025'FWLI	
Chain-Blue Lightning 26 N-23-25S-29E 331'FSL & 2500MCF/D Flared/Sold	
Fed 104H	
Chain-Blue Lightning 26 N-23-25S-29E 296'FSL & 2500MCF/D Flared/Sold	
Fed 124H 2275'FWL	
Chain-Blue Lightning 26 O-23-25S-29E 365'FSL & 2500MCF/D Flared/Sold	
Federal 166H 2230'FEL	
Chain-Blue Lightning 26 O-23-25-S29E 365'FSL & 2500MCF/D Flared/Sold	
Fed 165H 2480'FEL	
Chain-Blue Lightning 26 O-23-25S-29E 330'FSL & 2500MCF/D Flared/Sold	
Fed 125H 2480'FEL	
Chain-Blue Lightning 26 O-23-25S-29E 330'FSL & 2500MCF/D Flared/Sold	
Fed 126H 2230'FEL Chain Dhan Linhamma 20 0.22.255.20E 200/JESL # 2500MOE/D	
Chain-Blue Lightning 26O-23-25S-29E295'FSL &2500MCF/DFlared/SoldFed 105H2480'FEL105H105H105H105H	
Ped 105H 2480 FEL Chain-Blue Lightning 26 O-23-25S-29E 295'FSL & 2500MCF/D Flared/Sold	
Fed 705H 2230'FEL 2300WCF/D Plated/30d	
Chain-Blue Lightning 26 P-23-25S-29E 366'FSL & 2500MCF/D Flared/Sold	
Fed 168H 273'FEL 200 101 00 100 000000000000000000000000	

	•				
Chain-Blue Lightning 26	P-23-258-29E		2500MCF/D	Flared/Sold	
Fed 167H		523'FEL			
Chain-Blue Lightning 26	P-23-25S-29E	330'FSL &	2500MCF/D	Flared/Sold	
Fed 107H	•	523'FEL	1		
Chain-Blue Lightning 26	P-23-25S-29E	295'FSL &	2500MCF/D	Flared/Sold	· · · · · · · · · · · · · · · · · · ·
Fed 127H		523'FEL	j.		
Chain-Blue Lightning 26	P-23-25S-29E	296'FSL &	2500MCF/D	Flared/Sold	
Fed 708H		273'FEL			4

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Enlink and will be connected to Enlink low/high pressure gathering system located in Loving County, Texas. It will require 0' of pipeline to connect the facility to low/high pressure gathering system. XTO Energy, Inc. provides (periodically) to Enlink a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, XTO Energy, Inc. and Enlink have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Enlink Processing Plant located in Block 27, Section 4, Loving County, Texas. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on <u>Enlink</u> system at that time. Based on current information, it is <u>XTO</u> <u>Energy</u>, Inc.'s belief the system can take this gas upon completion of the well(s).

-Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines