

RECEIVED

FEB 12 2020

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
EMERALD ARTESIA

APPLICATION FOR PERMIT TO DRILL OR REENTER

FORM APPROVED
OMB No. 1004-0137
Expires: January 31, 2018

- 1a. Type of work: ☒ DRILL ☐ REENTER
1b. Type of Well: ☐ Oil Well ☒ Gas Well ☐ Other
1c. Type of Completion: ☐ Hydraulic Fracturing ☒ Single Zone ☐ Multiple Zone

2. Name of Operator
MEWBORNE OIL COMPANY

3a. Address
PO Box 5270 Hobbs NM 88240

3b. Phone No. (include area code)
(575)393-5905

4. Location of Well (Report location clearly and in accordance with any State requirements. *)
At surface SWSW / 810 FSL / 215 FWL / LAT 32.1103593 / LONG -104.065809
At proposed prod. zone SESE / 330 FSL / 330 FEL / LAT 32.1091074 / LONG -104.0332197

5. Lease Serial No.
NMNM013413A

6. If Indian, Allottee or Tribe Name

327155

7. If Unit or CA Agreement, Name and No.

8. Lease Name and Well No.

OXBOW 23/24 WOMP FED COM
1H

9. API Well No.

30015 46738

10. Field and Pool, or Exploratory

WILDCAT; WOLFCAMP / WOLFCAMP G

11. Sec., T, R, M, or Blk. and Survey or Area
SEC 23 / T25S / R28E / NMP

14. Distance in miles and direction from nearest town or post office*
8.5 miles

12. County or Parish
EDDY

13. State
NM

15. Distance from proposed*
location to nearest
property or lease line, ft.
(Also to nearest drig. unit line, if any)
330 feet

16. No. of acres in lease
1280

17. Spacing Unit dedicated to this well
640

18. Distance from proposed location*
to nearest well, drilling, completed,
applied for, on this lease, ft.
50 feet

19. Proposed Depth
9753 feet / 19692 feet

20. BLM/BIA Bond No. in file
FED: NM1693

21. Elevations (Show whether DF, KDB, RT, GL, etc.)
2936 feet

22. Approximate date work will start*
03/21/2019

23. Estimated duration
60 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office)

4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification.
6. Such other site specific information and/or plans as may be requested by the BLM.

25. Signature
(Electronic Submission)

Name (Printed/Typed)
Bradley Bishop / Ph: (575)393-5905

Date
02/12/2019

Title
Regulatory

Approved by (Signature)
(Electronic Submission)

Name (Printed/Typed)
Cody Layton / Ph: (575)234-5959

Date
01/27/2020

Title
Assistant Field Manager Lands & Minerals

Office
CARLSBAD

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

APPROVED WITH CONDITIONS
Approval Date: 01/27/2020

CS 2-12-20

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

ITEM 24: If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM connects this information to an evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Connection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Mewbourne Oil Company
LEASE NO.:	NMNM013413A
WELL NAME & NO.:	Oxbow 23/24 W0MP Fed Com 1H
SURFACE HOLE FOOTAGE:	810'/S & 215'/W
BOTTOM HOLE FOOTAGE:	330'/S & 330'/E
LOCATION:	Section 23, T.25 S., R.28 E., NMPM
COUNTY:	Eddy County, New Mexico

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input checked="" type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit

A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

B. CASING

Casing Design:

1. The 13-3/8 inch surface casing shall be set at approximately **500 feet** (a minimum of **70 feet (Eddy County)** into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after

- completing the cement job.
- b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The **9-5/8** inch intermediate casing shall be set at approximately **2685** feet. The minimum required fill of cement behind the **9-5/8** inch intermediate casing is:
- Cement to surface. If cement does not circulate see B.1.a, c-d above.
Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.
Excess cement calculates to 21%, additional cement might be required.
- ❖ In Medium Cave/Karst Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
3. The minimum required fill of cement behind the **7** inch production casing is:

Option 1 (Single Stage):

- Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.
- **Excess cement calculates to 4%, additional cement might be required.**

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- b. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- c. Second stage above DV tool:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

d. The minimum required fill of cement behind the 4-1/2 inch production liner is:

- Cement should tie-back **100 feet** into the previous casing. Operator shall provide method of verification.

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

D. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.

- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☒ Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

☒ Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as

well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the

plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

OTA12302019

**PECOS DISTRICT
SURFACE USE
CONDITIONS OF APPROVAL**

OPERATOR'S NAME:	Mewbourne Oil Company
WELL NAME & NO.:	Oxbow 23/24 W0MP Fed Com 1H
SURFACE HOLE FOOTAGE:	810'/S & 215'/W
BOTTOM HOLE FOOTAGE	330'/S & 330'/E
LOCATION:	Section 23, T.25 S., R.28 E., NMPM
COUNTY:	Eddy County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
 - Cave/Karst
 - Hydrology
 - Special Status Plant Species Habitat
 - Texas Hornshell
- ☐ **Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- ☐ **Road Section Diagram**
- ☐ **Production (Post Drilling)**
 - Well Structures & Facilities
- ☐ **Interim Reclamation**
- ☐ **Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

Cave/Karst Surface Mitigation

The following stipulations will be applied to minimize impacts during construction, drilling and production:

Construction:

General Construction:

- No blasting
- The BLM, Carlsbad Field Office, will be informed immediately if any subsurface drainage channels, cave passages, or voids are penetrated during construction, and no additional construction shall occur until clearance has been issued by the Authorized Officer.
- All linear surface disturbance activities will avoid sinkholes and other karst features to lessen the possibility of encountering near surface voids during construction, minimize changes to runoff, and prevent untimely leaks and spills from entering the karst drainage system.
- All spills or leaks will be reported to the BLM immediately for their immediate and proper treatment.

Pad Construction:

- The pad will be constructed and leveled by adding the necessary fill and caliche – no blasting.
- The entire perimeter of the well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad.
- The compacted berm shall be constructed at a minimum of 12 inches high with impermeable mineral material (e.g., caliche).
- No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad.
- The topsoil stockpile shall be located outside the bermed well pad.
- Topsoil, either from the well pad or surrounding area, shall not be used to construct the berm.
- No storm drains, tubing or openings shall be placed in the berm.
- If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.
- The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed.
- Any access road entering the well pad shall be constructed so that the integrity of the berm height surrounding the well pad is not compromised (i.e. an access road crossing the berm cannot be lower than the berm height).
- Following a rain event, all fluids will be vacuumed off of the pad and hauled off-site and disposed at a proper disposal facility.

Tank Battery Construction:

- The pad will be constructed and leveled by adding the necessary fill and caliche – no blasting.
- All tank battery locations and facilities will be lined and bermed.
- The liner should be at least 20 mil in thickness and installed with a 4 oz. felt backing, or equivalent, to prevent tears or punctures.
- Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.

Road Construction:

- Turnout ditches and drainage leadoffs will not be constructed in such a manner as to alter the natural flow of water into or out of cave or karst features.
- Special restoration stipulations or realignment may be required if subsurface features are discovered during construction.

Buried Pipeline/Cable Construction:

- Rerouting of the buried line(s) may be required if a subsurface void is encountered during construction to minimize the potential subsidence/collapse of the feature(s) as well as the possibility of leaks/spills entering the karst drainage system.

Powerline Construction:

- Smaller powerlines will be routed around sinkholes and other karst features to avoid or lessen the possibility of encountering near surface voids and to minimize changes to runoff or possible leaks and spills from entering karst systems.
- Larger powerlines will adjust their pole spacing to avoid cave and karst features.
- Special restoration stipulations or realignment may be required if subsurface voids are encountered.

Surface Flowlines Installation:

- Flowlines will be routed around sinkholes and other karst features to minimize the possibility of leaks/spills from entering the karst drainage system.

Leak Detection System:

- A method of detecting leaks is required. The method could incorporate gauges to measure loss, siting valves and lines so they can be visually inspected, or installing electronic sensors to alarm when a leak is present.
- A leak detection plan will be submitted to BLM that incorporates an automatic shut off system (see below) to minimize the effects of an undesirable event that could negatively sensitive cave/karst resources.
- Well heads, pipelines (surface and buried), storage tanks, and all supporting equipment should be monitored regularly after installation to promptly identify and fix leaks.

Automatic Shut-off Systems:

- Automatic shut off, check valves, or similar systems will be installed for pipelines and tanks to minimize the effects of catastrophic line failures used in production or drilling.

Cave/Karst Subsurface Mitigation

The following stipulations will be applied to protect cave/karst and groundwater concerns:

Closed Loop System:

- A closed loop system using steel tanks will be utilized during drilling – no pits
- All fluids and cuttings will be hauled off-site and disposed of properly at an authorized site

Rotary Drilling with Fresh Water:

- Fresh water will be used as a circulating medium in zones where caves or karst features are expected. SEE ALSO: Drilling COAs for this well.

Directional Drilling:

- The kick off point for directional drilling will occur at least 100 feet below the bottom of the cave occurrence zone. SEE ALSO: Drilling COAs for this well.

Lost Circulation:

- ALL lost circulation zones between surface and the base of the cave occurrence zone will be logged and reported in the drilling report.
- If a void of four feet or more and circulation losses greater than 70 percent occur simultaneously while drilling in any cave-bearing zone, regardless of the type of drilling machinery used, the BLM will be notified immediately by the operator. The BLM will assess the situation and work with the operator on corrective actions to resolve the problem.

Abandonment Cementing:

- Additional plugging conditions of approval may be required upon well abandonment in high and medium karst potential occurrence zones.
- The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

Pressure Testing:

- The operator will perform annual pressure monitoring on all casing annuli and reported in a sundry notice.
- If the test results indicated a casing failure has occurred, remedial action will be undertaken to correct the problem to the BLM's approval.

Hydrology

The entire well pad(s) will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. The compacted berm shall be constructed at a minimum of 12 inches with impermeable mineral material (e.g. caliche). Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed. Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion. Stockpiling of topsoil is required. The top soil shall be stockpiled in an appropriate location to prevent loss of soil due to water or wind erosion and not used for berming or erosion control. If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.

Tank battery locations will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank or 24 hour production, whichever is greater. Automatic shut off, check valves, or similar systems will be installed for tanks to minimize the effects of catastrophic line failures used in production or drilling.

When crossing ephemeral drainages the pipeline(s) will be buried to a minimum depth of 48 inches from the top of pipe to ground level. Erosion control methods such as gabions and/or rock aprons should be placed on both up and downstream sides of the pipeline crossing. In addition, curled (weed free) wood/straw fiber wattles/logs and/or silt fences should be placed on the downstream side for sediment control during construction and maintained until soils and vegetation have stabilized. Water bars should be placed within the ROW to divert and dissipate surface runoff. A pipeline access road is not permitted to cross these ephemeral drainages. Traffic should be diverted to a preexisting route. Additional seeding may be required in floodplains and drainages to restore energy dissipating vegetation.

Prior to pipeline installation a leak detection plan should be developed. The method could incorporate gauges to detect pressure drops, situating valves and lines so they can be visually inspected periodically or installing electronic sensors to alarm when a leak is present. The leak detection plan will incorporate an automatic shut off system that will be installed for proposed pipelines to minimize the effects of an undesirable event.

Any water erosion that may occur due to the construction of overhead electric line and during the life of the power line will be quickly corrected and proper measures will be taken to prevent future erosion. A power pole should not be placed in drainages, playas, wetlands, riparian areas, or floodplains and must span across the features at a distance away that would not promote further erosion.

Special Status Plant Species (SSPS) Habitat Stipulations:

Vehicles and equipment will be kept on existing roads and approved surfaces only, and will avoid travel across undisturbed surfaces; workers will be instructed not to park off the roads or ROW in undisturbed areas. Alterations to project design and additions of project components will require SSPS surveys and re-analysis of impacts if those project elements intersect SSPS suitable habitat.

Texas Hornshell

Oil and Gas and Associated Infrastructure Mitigation Measures for Zone D – CCA
Boundary Requirements:

- Provide CEHMM with the permit, lease grant, or other authorization form BLM, if applicable.
- Provide CEHMM with plats or other electronic media describing the new surface disturbance for the project.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS**Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.


Turnouts

Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill out sloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Seed Mixture 1 for Loamy Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed shall be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed shall be planted using a drill equipped with a depth regulator to ensure proper depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture shall be evenly and uniformly planted over the disturbed area (small/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed shall be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre shall be doubled. The seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains lovegrass (<i>Eragrostis intermedia</i>)	0.5
Sand dropseed (<i>Sporobolus cryptandrus</i>)	1.0
Sideoats grama (<i>Bouteloua curtipendula</i>)	5.0
Plains bristlegrass (<i>Setaria macrostachya</i>)	2.0

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Operator Certification Data Report

02/05/2020

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Bradley Bishop

Signed on: 02/12/2019

Title: Regulatory

Street Address: PO Box 5270

City: Hobbs

State: NM

Zip: 88260

Phone: (575)393-5905

Email address: bbishop@mewbourne.com

Field Representative

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Application Data Report

02/05/2020

APD ID: 10400037522

Submission Date: 02/12/2019

Highlighted data
reflects the most
recent changes

Operator Name: MEWBOURNE OIL COMPANY

Well Name: OXBOW 23/24 W0MP FED COM

Well Number: 1H

[Show Final Text](#)

Well Type: CONVENTIONAL GAS WELL

Well Work Type: Drill

Section 1 - General

APD ID: 10400037522

Tie to previous NOS?

Submission Date: 02/12/2019

BLM Office: CARLSBAD

User: Bradley Bishop

Title: Regulatory

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM013413A

Lease Acres: 1280

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? YES

Permitting Agent? NO

APD Operator: MEWBOURNE OIL COMPANY

Operator letter of designation:

Operator Info

Operator Organization Name: MEWBOURNE OIL COMPANY

Operator Address: PO Box 5270

Zip: 88240

Operator PO Box:

Operator City: Hobbs

State: NM

Operator Phone: (575)393-5905

Operator Internet Address:

Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: OXBOW 23/24 W0MP FED COM

Well Number: 1H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: WILDCAT;
WOLFCAMP

Pool Name: WOLFCAMP GAS

Is the proposed well in an area containing other mineral resources? NONE

Operator Name: MEWBOURNE OIL COMPANY

Well Name: OXBOW 23/24 W0MP FED COM

Well Number: 1H

Is the proposed well in an area containing other mineral resources? NONE

Is the proposed well in a Helium production area? N Use Existing Well Pad? NO New surface disturbance?

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name:
OXBOW 23/24 LI & MP WELLS
Number of Legs: 1

Number: 4

Well Class: HORIZONTAL

Well Work Type: Drill

Well Type: CONVENTIONAL GAS WELL

Describe Well Type:

Well sub-Type: EXPLORATORY (WILDCAT)

Describe sub-type:

Distance to town: 8.5 Miles

Distance to nearest well: 50 FT

Distance to lease line: 330 FT

Reservoir well spacing assigned acres Measurement: 640 Acres

Well plat: Oxbow23_24W0MPFedCom1H_wellplat_20190121094547.pdf

Well work start Date: 03/21/2019

Duration: 60 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83

Vertical Datum: NAVD88

Survey number:

Reference Datum:

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
SHL Leg #1	810	FSL	215	FW L	25S	28E	23	Aliquot SWS W	32.11035 93	- 104.0658 09	EDD Y	NEW MEXI CO	NEW MEXI CO	F	NMNM 013413 A	293 6	0	0	
KOP Leg #1	330	FSL	10	FW L	25S	28E	23	Aliquot SWS W	32.10903 61	- 104.0664 701	EDD Y	NEW MEXI CO	NEW MEXI CO	F	NMNM 013413 A	- 616 5	912 3	910 1	
PPP Leg #1-1	330	FSL	132 6	FEL	25S	28E	24	Aliquot SESE	32.10910 09	- 104.0364 365	EDD Y	NEW MEXI CO	NEW MEXI CO	F	NMNM 016104	- 679 9	186 96	973 5	



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Drilling Plan Data Report

02/05/2020

APD ID: 10400037522

Submission Date: 02/12/2019

Highlighted data
reflects the most
recent changes

Operator Name: MEWBOURNE OIL COMPANY

Well Name: OXBOW 23/24 W0MP FED COM

Well Number: 1H

[Show Final Text](#)

Well Type: CONVENTIONAL GAS WELL

Well Work Type: Drill

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
366491	UNKNOWN	2936	27	27		NONE	N
366482	CASTILE	1854	1145	1145	SALT	NONE	N
366483	BASE OF SALT	519	2480	2480	SALT	NONE	N
366484	LAMAR	339	2660	2660	LIMESTONE	NATURAL GAS, OIL	N
366485	BELL CANYON	309	2690	2690	SANDSTONE	NATURAL GAS, OIL	N
366492	CHERRY CANYON	-566	3565	3565	SANDSTONE	NATURAL GAS, OIL	N
366493	MANZANITA	-711	3710	3710	LIMESTONE	NATURAL GAS, OIL	N
366494	BRUSHY CANYON	-2211	5210	5210	SANDSTONE	NATURAL GAS, OIL	N
366486	BONE SPRING LIME	-3441	6440	6440	LIMESTONE, SHALE	NATURAL GAS, OIL	N
366487	BONE SPRING 1ST	-4301	7300	7300	SANDSTONE	NATURAL GAS, OIL	N
366488	BONE SPRING 2ND	-5096	8095	8095	SANDSTONE	NATURAL GAS, OIL	N
366489	BONE SPRING 3RD	-6216	9215	9215	SANDSTONE	NATURAL GAS, OIL	N
366490	WOLFCAMP	-6586	9585	9585	LIMESTONE, SANDSTONE, SHALE	NATURAL GAS, OIL	Y

Section 2 - Blowout Prevention

Operator Name: MEWBOURNE OIL COMPANY

Well Name: OXBOW 23/24 W0MP FED COM

Well Number: 1H

Pressure Rating (PSI): 5M

Rating Depth: 19692

Equipment: Annular, Blind Ram, Pipe Ram

Requesting Variance? YES

Variance request: A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. Anchors are not required by manufacturer. A multi-bowl wellhead is being used. See attached schematic.

Testing Procedure: BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested. Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

Choke Diagram Attachment:

Armstrong_26_23_W1HA_Fed_Com_1H_5M_BOPE_Choke_Diagram_20190116151050.pdf

Armstrong_26_23_W1HA_Fed_Com_1H_Flex_Line_Specs_20190116151051.pdf

Oxbow_23_24_W0MP_Fed_Com_1H_Flex_Line_Specs_API_16C_20191213153850.pdf

BOP Diagram Attachment:

Armstrong_26_23_W1HA_Fed_Com_1H_5M_BOPE_Schematic_20190116151101.pdf

Armstrong_26_23_W1HA_Fed_Com_1H_Multi_Bowl_WH_20190116151102.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	500	0	500			500	H-40	48	ST&C	3.37	7.56	DRY	13.42	DRY	22.54
2	INTERMEDIATE	12.25	9.625	NEW	API	N	0	2685	0	2685			2685	J-55	36	LT&C	1.45	2.52	DRY	4.69	DRY	5.83
3	PRODUCTION	8.75	7.0	NEW	API	N	0	9711	0	9551			9711	P-110	26	LT&C	1.32	2.11	DRY	2.53	DRY	3.29
4	LINER	6.125	4.5	NEW	API	N	9123	19692	9101	9753			10569	P-110	13.5	LT&C	1.75	2.04	DRY	2.37	DRY	2.96

Casing Attachments

Operator Name: MEWBOURNE OIL COMPANY

Well Name: OXBOW 23/24 W0MP FED COM

Well Number: 1H

Casing Attachments

Casing ID: 1 **String Type:** SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Oxbow_23_24_W0MP_Fed_Com_1H_Csg_Assumptions_20190116151307.docx

Casing ID: 2 **String Type:** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Oxbow_23_24_W0MP_Fed_Com_1H_Csg_Assumptions_20190116151346.docx

Casing ID: 3 **String Type:** PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Oxbow_23_24_W0MP_Fed_Com_1H_Csg_Assumptions_20190116151444.docx

Operator Name: MEWBOURNE OIL COMPANY

Well Name: OXBOW 23/24 W0MP FED COM

Well Number: 1H

Casing Attachments

Casing ID: 4 String Type: LINER

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Oxbow_23_24_W0MP_Fed_Com_1H_Csg_Assumptions_20190116151551.docx

Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	312	210	2.12	12.5	445	100	Class C	Salt, Gel, Extender, LCM
SURFACE	Tail		312	500	200	1.34	14.8	268	100	Class C	Retarder
INTERMEDIATE	Lead		0	2001	370	2.12	12.5	784	25	Class C	Salt, Gel, Extender, LCM
INTERMEDIATE	Tail		2001	2685	200	1.34	14.8	268	25	Class C	Retarder
PRODUCTION	Lead	3710	2485	3026	50	2.12	12.5	106	25	Class C	Salt, Gel, Extender, LCM
PRODUCTION	Tail		3026	3710	100	1.34	14.8	134	25	Class C	Retarder
PRODUCTION	Lead	3710	3710	7203	310	2.12	12.5	657	25	Class C	Gel, Retarder, Defoamer, Extender
PRODUCTION	Tail		7203	9711	400	1.18	15.6	472	25	Class H	Retarder, Fluid Loss, Defoamer
LINER	Lead		9123	19692	420	2.97	11.2	1247	25	Class H	Salt, Gel, Fluid Loss, Retarder, Dispersant, Defoamer, Anti-Settling Agent

Operator Name: MEWBOURNE OIL COMPANY

Well Name: OXBOW 23/24 W0MP FED COM

Well Number: 1H

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Sufficient mud materials to maintain mud properties & meet minimum lost circulation and weight increase requirements will be kept on location at all times.

Describe the mud monitoring system utilized: Pason/PVT/Visual Monitoring

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	500	SPUD MUD	8.6	8.8							
500	2685	SALT SATURATED	10	10							
2685	9551	WATER-BASED MUD	8.6	9.5							
9551	9753	OIL-BASED MUD	10	12							MW up to 13.0 ppg may be required for shale control. The highest MW needed to balance formation pressure is expected to be 12.0 ppg.

Operator Name: MEWBOURNE OIL COMPANY

Well Name: OXBOW 23/24 W0MP FED COM

Well Number: 1H

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

Will run GR/CNL from KOP (9123') to surface

Will run MWD GR from KOP (9123') to TD

List of open and cased hole logs run in the well:

CNL,GR,MWD,MUDLOG

Coring operation description for the well:

None

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 6085

Anticipated Surface Pressure: 3939.34

Anticipated Bottom Hole Temperature(F): 165

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geohazards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

Oxbow_23_24_W0MP_Fed_Com_1H_H2S_Plan_20190116152618.pdf

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

OXBOW_23_24_W0MP_FED_COM_1H_DIR_PLAN_20190116152638.pdf

OXBOW_23_24_W0MP_FED_COM_1H_DIR_PLOT_20190116152639.pdf

Other proposed operations facets description:

Other proposed operations facets attachment:

Oxbow_23_24_W0MP_Fed_Com_1H_Additional_Points_20190116152718.pdf

Oxbow_23_24_W0MP_Fed_Com_1H_Drig_Program_20190116152720.docx

Other Variance attachment:

Hydrogen Sulfide Drilling Operations Plan
Mewbourne Oil Company

1. General Requirements

Rule 118 does not apply to this well because MOC has researched this area and no high concentrations of H₂S were found. MOC will have on location and working all H₂S safety equipment before the Delaware formation for purposes of safety and insurance requirements.

2. Hydrogen Sulfide Training

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will have received training from a qualified instructor in the following areas prior to entering the drilling pad area of the well:

1. The hazards and characteristics of hydrogen sulfide gas.
2. The proper use of personal protective equipment and life support systems.
3. The proper use of hydrogen sulfide detectors, alarms, warning systems, briefing areas, evacuation procedures.
4. The proper techniques for first aid and rescue operations.

Additionally, supervisory personnel will be trained in the following areas:

- 1 The effects of hydrogen sulfide on metal components. If high tensile tubular systems are utilized, supervisory personnel will be trained in their special maintenance requirements.
- 2 Corrective action and shut in procedures, blowout prevention, and well control procedures while drilling a well.
- 3 The contents of the Hydrogen Sulfide Drilling Operations Plan.

There will be an initial training session prior to encountering a known hydrogen sulfide source. The initial training session shall include a review of the site specific Hydrogen Sulfide Drilling Operations Plan.

3. Hydrogen Sulfide Safety Equipment and Systems

All hydrogen sulfide safety equipment and systems will be installed, tested, and operational prior to drilling below the 9 5/8" intermediate casing.

1. Well Control Equipment
 - A. Choke manifold with minimum of one adjustable choke/remote choke.
 - B. Blowout preventers equipped with blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
 - C. Auxiliary equipment including annular type blowout preventer.
2. Protective Equipment for Essential Personnel

Thirty minute self contained work unit located in the dog house and at briefing areas.

Additionally: If H₂S is encountered in concentrations less than 10 ppm, fans will be placed in work areas to prevent the accumulation of hazardous amounts of poisonous gas. If higher concentrations of H₂S are detected the well will be shut in and a rotating head, mud/gas separator, remote choke and flare line with igniter will be installed.

3. Hydrogen Sulfide Protection and Monitoring Equipment
Two portable hydrogen sulfide monitors positioned on location for optimum coverage and detection. The units shall have audible sirens to notify personnel when hydrogen sulfide levels exceed 20 PPM.
4. Visual Warning Systems
 - A. Wind direction indicators as indicated on the wellsite diagram.
 - B. Caution signs shall be posted on roads providing access to location. Signs shall be painted a high visibility color with lettering of sufficient size to be readable at reasonable distances from potentially contaminated areas.

4. **Mud Program**

The mud program has been designed to minimize the amount of hydrogen sulfide entrained in the mud system. Proper mud weight, safe drilling practices, and the use of hydrogen sulfide scavengers will minimize hazards while drilling the well.

5. **Metallurgy**

All tubular systems, wellheads, blowout preventers, drilling spools, kill lines, choke manifolds, and valves shall be suitable for service in a hydrogen sulfide environment when chemically treated.

6. **Communications**

State & County Officials phone numbers are posted on rig floor and supervisors trailer. Communications in company vehicles and toolpushers are either two way radios or cellular phones.

7. **Well Testing**

Drill stem testing is not an anticipated requirement for evaluation of this well. If a drill stem test is required, it will be conducted with a minimum number of personnel in the immediate vicinity. The test will be conducted during daylight hours only.

8. **Emergency Phone Numbers**

Eddy County Sheriff's Office	911 or 575-887-7551
Ambulance Service	911 or 575-885-2111
Carlsbad Fire Dept	911 or 575-885-2111
Loco Hills Volunteer Fire Dept.	911 or 575-677-3266
Closest Medical Facility - Columbia Medical Center of Carlsbad	575-492-5000

Mewbourne Oil Company	Hobbs District Office	575-393-5905
	Fax	575-397-6252
	2nd Fax	575-393-7259

District Manager	Robin Terrell	575-390-4816
Drilling Superintendent	Frosty Lathan	575-390-4103
	Bradley Bishop	575-390-6838
Drilling Foreman	Wesley Noseff	575-441-0729

Mewbourne Oil Company

Eddy County, New Mexico NAD 83

Oxbow 23/24 W0MP Fed Com #1H

Secs. 23 & 24, T25S, R28E

SL: 810' FSL & 215' FWL (23)

BHL: 330' FSL & 330' FEL (24)

Plan: Design #1

Standard Planning Report

21 December, 2018

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Oxbow 23/24 W0MP Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 2963.0usft (Original Well Elev)
Project:	Eddy County, New Mexico NAD 83	MD Reference:	WELL @ 2963.0usft (Original Well Elev)
Site:	Oxbow 23/24 W0MP Fed Com #1H	North Reference:	Grid
Well:	Secs. 23 & 24, T25S, R28E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 330' FSL & 330' FEL (24)		
Design:	Design #1		

Project	Eddy County, New Mexico NAD 83		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Oxbow 23/24 W0MP Fed Com #1H			
Site Position:		Northing:	403,988.00 usft	Latitude: 32.1103597
From:	Map	Easting:	624,168.00 usft	Longitude: -104.0658074
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence: 0.14 °

Well	Secs. 23 & 24, T25S, R28E			
Well Position	+N/-S	0.0 usft	Northing: 403,988.00 usft	Latitude: 32.1103597
	+E/-W	0.0 usft	Easting: 624,168.00 usft	Longitude: -104.0658074
Position Uncertainty	0.0 usft	Wellhead Elevation:	2,963.0 usft	Ground Level: 2,936.0 usft

Wellbore		BHL: 330' FSL & 330' FEL (24)			
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	12/21/2018	6.88	59.81	47,750

Design	Design #1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	92.43

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,685.0	0.00	0.00	2,685.0	0.0	0.0	0.00	0.00	0.00	0.00	
3,012.6	4.91	202.94	3,012.2	-12.9	-5.5	1.50	1.50	0.00	202.94	
8,795.5	4.91	202.94	8,773.8	-469.1	-198.5	0.00	0.00	0.00	0.00	
9,123.1	0.00	0.00	9,101.0	-482.0	-204.0	1.50	-1.50	0.00	180.00	KOP: 330' FSL & 10' F
9,863.9	88.98	89.71	9,578.0	-479.6	264.6	12.01	12.01	0.00	89.71	
19,692.1	88.98	89.71	9,753.0	-429.0	10,091.0	0.00	0.00	0.00	0.00	BHL: 330' FSL & 330'

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Oxbow 23/24 WOMP Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 2963.0usft (Original Well Elev)
Project:	Eddy County, New Mexico NAD 83	MD Reference:	WELL @ 2963.0usft (Original Well Elev)
Site:	Oxbow 23/24 WOMP Fed Com #1H	North Reference:	Grid
Well:	Secs. 23 & 24, T25S, R28E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 330' FSL & 330' FEL (24)		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
SL: 810' FSL & 215' FWL (23)									
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	0.00	0.00	2,100.0	0.0	0.0	0.0	0.00	0.00	0.00
2,200.0	0.00	0.00	2,200.0	0.0	0.0	0.0	0.00	0.00	0.00
2,300.0	0.00	0.00	2,300.0	0.0	0.0	0.0	0.00	0.00	0.00
2,400.0	0.00	0.00	2,400.0	0.0	0.0	0.0	0.00	0.00	0.00
2,500.0	0.00	0.00	2,500.0	0.0	0.0	0.0	0.00	0.00	0.00
2,600.0	0.00	0.00	2,600.0	0.0	0.0	0.0	0.00	0.00	0.00
2,685.0	0.00	0.00	2,685.0	0.0	0.0	0.0	0.00	0.00	0.00
2,700.0	0.23	202.94	2,700.0	0.0	0.0	0.0	1.50	1.50	0.00
2,800.0	1.73	202.94	2,800.0	-1.6	-0.7	-0.6	1.50	1.50	0.00
2,900.0	3.23	202.94	2,899.9	-5.6	-2.4	-2.1	1.50	1.50	0.00
3,000.0	4.73	202.94	2,999.6	-12.0	-5.1	-4.5	1.50	1.50	0.00
3,012.6	4.91	202.94	3,012.2	-12.9	-5.5	-4.9	1.50	1.50	0.00
3,100.0	4.91	202.94	3,099.3	-19.8	-8.4	-7.5	0.00	0.00	0.00
3,200.0	4.91	202.94	3,198.9	-27.7	-11.7	-10.5	0.00	0.00	0.00
3,300.0	4.91	202.94	3,298.5	-35.6	-15.1	-13.5	0.00	0.00	0.00
3,400.0	4.91	202.94	3,398.2	-43.5	-18.4	-16.5	0.00	0.00	0.00
3,500.0	4.91	202.94	3,497.8	-51.4	-21.7	-19.5	0.00	0.00	0.00
3,600.0	4.91	202.94	3,597.4	-59.3	-25.1	-22.5	0.00	0.00	0.00
3,700.0	4.91	202.94	3,697.1	-67.2	-28.4	-25.5	0.00	0.00	0.00
3,800.0	4.91	202.94	3,796.7	-75.0	-31.8	-28.5	0.00	0.00	0.00
3,900.0	4.91	202.94	3,896.3	-82.9	-35.1	-31.5	0.00	0.00	0.00
4,000.0	4.91	202.94	3,996.0	-90.8	-38.4	-34.5	0.00	0.00	0.00
4,100.0	4.91	202.94	4,095.6	-98.7	-41.8	-37.5	0.00	0.00	0.00
4,200.0	4.91	202.94	4,195.2	-106.6	-45.1	-40.5	0.00	0.00	0.00
4,300.0	4.91	202.94	4,294.9	-114.5	-48.5	-43.5	0.00	0.00	0.00
4,400.0	4.91	202.94	4,394.5	-122.4	-51.8	-46.5	0.00	0.00	0.00
4,500.0	4.91	202.94	4,494.1	-130.3	-55.1	-49.5	0.00	0.00	0.00
4,600.0	4.91	202.94	4,593.8	-138.1	-58.5	-52.5	0.00	0.00	0.00
4,700.0	4.91	202.94	4,693.4	-146.0	-61.8	-55.5	0.00	0.00	0.00
4,800.0	4.91	202.94	4,793.0	-153.9	-65.1	-58.5	0.00	0.00	0.00
4,900.0	4.91	202.94	4,892.7	-161.8	-68.5	-61.5	0.00	0.00	0.00
5,000.0	4.91	202.94	4,992.3	-169.7	-71.8	-64.5	0.00	0.00	0.00

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Oxbow 23/24 W0MP Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 2963.0usft (Original Well Elev)
Project:	Eddy County, New Mexico NAD 83	MD Reference:	WELL @ 2963.0usft (Original Well Elev)
Site:	Oxbow 23/24 W0MP Fed Com #1H	North Reference:	Grid
Well:	Secs. 23 & 24, T25S, R28E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 330' FSL & 330' FEL (24)		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,100.0	4.91	202.94	5,091.9	-177.6	-75.2	-67.5	0.00	0.00	0.00
5,200.0	4.91	202.94	5,191.6	-185.5	-78.5	-70.5	0.00	0.00	0.00
5,300.0	4.91	202.94	5,291.2	-193.4	-81.8	-73.5	0.00	0.00	0.00
5,400.0	4.91	202.94	5,390.8	-201.2	-85.2	-76.5	0.00	0.00	0.00
5,500.0	4.91	202.94	5,490.5	-209.1	-88.5	-79.5	0.00	0.00	0.00
5,600.0	4.91	202.94	5,590.1	-217.0	-91.9	-82.5	0.00	0.00	0.00
5,700.0	4.91	202.94	5,689.7	-224.9	-95.2	-85.5	0.00	0.00	0.00
5,800.0	4.91	202.94	5,789.4	-232.8	-98.5	-88.6	0.00	0.00	0.00
5,900.0	4.91	202.94	5,889.0	-240.7	-101.9	-91.6	0.00	0.00	0.00
6,000.0	4.91	202.94	5,988.6	-248.6	-105.2	-94.6	0.00	0.00	0.00
6,100.0	4.91	202.94	6,088.3	-256.5	-108.5	-97.6	0.00	0.00	0.00
6,200.0	4.91	202.94	6,187.9	-264.3	-111.9	-100.6	0.00	0.00	0.00
6,300.0	4.91	202.94	6,287.5	-272.2	-115.2	-103.6	0.00	0.00	0.00
6,400.0	4.91	202.94	6,387.2	-280.1	-118.6	-106.6	0.00	0.00	0.00
6,500.0	4.91	202.94	6,486.8	-288.0	-121.9	-109.6	0.00	0.00	0.00
6,600.0	4.91	202.94	6,586.4	-295.9	-125.2	-112.6	0.00	0.00	0.00
6,700.0	4.91	202.94	6,686.0	-303.8	-128.6	-115.6	0.00	0.00	0.00
6,800.0	4.91	202.94	6,785.7	-311.7	-131.9	-118.6	0.00	0.00	0.00
6,900.0	4.91	202.94	6,885.3	-319.6	-135.2	-121.6	0.00	0.00	0.00
7,000.0	4.91	202.94	6,984.9	-327.4	-138.6	-124.6	0.00	0.00	0.00
7,100.0	4.91	202.94	7,084.6	-335.3	-141.9	-127.6	0.00	0.00	0.00
7,200.0	4.91	202.94	7,184.2	-343.2	-145.3	-130.6	0.00	0.00	0.00
7,300.0	4.91	202.94	7,283.8	-351.1	-148.6	-133.6	0.00	0.00	0.00
7,400.0	4.91	202.94	7,383.5	-359.0	-151.9	-136.6	0.00	0.00	0.00
7,500.0	4.91	202.94	7,483.1	-366.9	-155.3	-139.6	0.00	0.00	0.00
7,600.0	4.91	202.94	7,582.7	-374.8	-158.6	-142.6	0.00	0.00	0.00
7,700.0	4.91	202.94	7,682.4	-382.7	-162.0	-145.6	0.00	0.00	0.00
7,800.0	4.91	202.94	7,782.0	-390.6	-165.3	-148.6	0.00	0.00	0.00
7,900.0	4.91	202.94	7,881.6	-398.4	-168.6	-151.6	0.00	0.00	0.00
8,000.0	4.91	202.94	7,981.3	-406.3	-172.0	-154.6	0.00	0.00	0.00
8,100.0	4.91	202.94	8,080.9	-414.2	-175.3	-157.6	0.00	0.00	0.00
8,200.0	4.91	202.94	8,180.5	-422.1	-178.6	-160.6	0.00	0.00	0.00
8,300.0	4.91	202.94	8,280.2	-430.0	-182.0	-163.6	0.00	0.00	0.00
8,400.0	4.91	202.94	8,379.8	-437.9	-185.3	-166.6	0.00	0.00	0.00
8,500.0	4.91	202.94	8,479.4	-445.8	-188.7	-169.6	0.00	0.00	0.00
8,600.0	4.91	202.94	8,579.1	-453.7	-192.0	-172.6	0.00	0.00	0.00
8,700.0	4.91	202.94	8,678.7	-461.5	-195.3	-175.6	0.00	0.00	0.00
8,795.5	4.91	202.94	8,773.8	-469.1	-198.5	-178.4	0.00	0.00	0.00
8,800.0	4.85	202.94	8,778.3	-469.4	-198.7	-178.6	1.50	-1.50	0.00
8,900.0	3.35	202.94	8,878.1	-476.0	-201.5	-181.1	1.50	-1.50	0.00
9,000.0	1.85	202.94	8,978.0	-480.2	-203.2	-182.6	1.50	-1.50	0.00
9,100.0	0.35	202.94	9,077.9	-481.9	-204.0	-183.3	1.50	-1.50	0.00
9,123.1	0.00	0.00	9,101.0	-482.0	-204.0	-183.3	1.50	-1.50	0.00
KOP: 330' FSL & 10' FWL (23)									
9,200.0	9.24	89.71	9,177.6	-482.0	-197.8	-177.2	12.01	12.01	0.00
9,300.0	21.25	89.71	9,273.9	-481.8	-171.6	-150.9	12.01	12.01	0.00
9,400.0	33.26	89.71	9,362.7	-481.6	-125.8	-105.3	12.01	12.01	0.00
9,500.0	45.27	89.71	9,439.9	-481.3	-62.7	-42.2	12.01	12.01	0.00
9,600.0	57.28	89.71	9,502.4	-480.9	15.2	35.6	12.01	12.01	0.00
9,700.0	69.29	89.71	9,547.2	-480.4	104.4	124.7	12.01	12.01	0.00
9,711.3	70.65	89.71	9,551.1	-480.4	115.0	135.3	12.01	12.01	0.00
FTP: 330' FSL & 330' FWL (23)									
9,800.0	81.30	89.71	9,572.6	-479.9	200.9	221.1	12.01	12.01	0.00
9,863.9	88.98	89.71	9,578.0	-479.6	264.6	284.7	12.01	12.01	0.00

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Oxbow 23/24 WOMP Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 2963.0usft (Original Well Elev)
Project:	Eddy County, New Mexico NAD 83	MD Reference:	WELL @ 2963.0usft (Original Well Elev)
Site:	Oxbow 23/24 WOMP Fed Com #1H	North Reference:	Grid
Well:	Secs. 23 & 24, T25S, R28E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 330' FSL & 330' FEL (24)		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
9,900.0	88.98	89.71	9,578.6	-479.4	300.6	320.7	0.00	0.00	0.00
10,000.0	88.98	89.71	9,580.4	-478.9	400.6	420.6	0.00	0.00	0.00
10,100.0	88.98	89.71	9,582.2	-478.4	500.6	520.5	0.00	0.00	0.00
10,200.0	88.98	89.71	9,584.0	-477.9	600.6	620.3	0.00	0.00	0.00
10,300.0	88.98	89.71	9,585.8	-477.3	700.6	720.2	0.00	0.00	0.00
10,400.0	88.98	89.71	9,587.5	-476.8	800.5	820.1	0.00	0.00	0.00
10,500.0	88.98	89.71	9,589.3	-476.3	900.5	919.9	0.00	0.00	0.00
10,600.0	88.98	89.71	9,591.1	-475.8	1,000.5	1,019.8	0.00	0.00	0.00
10,700.0	88.98	89.71	9,592.9	-475.3	1,100.5	1,119.7	0.00	0.00	0.00
10,800.0	88.98	89.71	9,594.7	-474.8	1,200.5	1,219.5	0.00	0.00	0.00
10,900.0	88.98	89.71	9,596.4	-474.3	1,300.4	1,319.4	0.00	0.00	0.00
11,000.0	88.98	89.71	9,598.2	-473.7	1,400.4	1,419.3	0.00	0.00	0.00
11,100.0	88.98	89.71	9,600.0	-473.2	1,500.4	1,519.2	0.00	0.00	0.00
11,200.0	88.98	89.71	9,601.8	-472.7	1,600.4	1,619.0	0.00	0.00	0.00
11,300.0	88.98	89.71	9,603.6	-472.2	1,700.4	1,718.9	0.00	0.00	0.00
11,400.0	88.98	89.71	9,605.4	-471.7	1,800.4	1,818.8	0.00	0.00	0.00
11,500.0	88.98	89.71	9,607.1	-471.2	1,900.3	1,918.6	0.00	0.00	0.00
11,600.0	88.98	89.71	9,608.9	-470.7	2,000.3	2,018.5	0.00	0.00	0.00
11,700.0	88.98	89.71	9,610.7	-470.1	2,100.3	2,118.4	0.00	0.00	0.00
11,800.0	88.98	89.71	9,612.5	-469.6	2,200.3	2,218.3	0.00	0.00	0.00
11,900.0	88.98	89.71	9,614.3	-469.1	2,300.3	2,318.1	0.00	0.00	0.00
12,000.0	88.98	89.71	9,616.0	-468.6	2,400.3	2,418.0	0.00	0.00	0.00
12,100.0	88.98	89.71	9,617.8	-468.1	2,500.2	2,517.9	0.00	0.00	0.00
12,200.0	88.98	89.71	9,619.6	-467.6	2,600.2	2,617.7	0.00	0.00	0.00
12,300.0	88.98	89.71	9,621.4	-467.0	2,700.2	2,717.6	0.00	0.00	0.00
12,400.0	88.98	89.71	9,623.2	-466.5	2,800.2	2,817.5	0.00	0.00	0.00
12,500.0	88.98	89.71	9,624.9	-466.0	2,900.2	2,917.4	0.00	0.00	0.00
12,600.0	88.98	89.71	9,626.7	-465.5	3,000.2	3,017.2	0.00	0.00	0.00
12,700.0	88.98	89.71	9,628.5	-465.0	3,100.1	3,117.1	0.00	0.00	0.00
12,800.0	88.98	89.71	9,630.3	-464.5	3,200.1	3,217.0	0.00	0.00	0.00
12,900.0	88.98	89.71	9,632.1	-464.0	3,300.1	3,316.8	0.00	0.00	0.00
13,000.0	88.98	89.71	9,633.8	-463.4	3,400.1	3,416.7	0.00	0.00	0.00
13,100.0	88.98	89.71	9,635.6	-462.9	3,500.1	3,516.6	0.00	0.00	0.00
13,200.0	88.98	89.71	9,637.4	-462.4	3,600.1	3,616.4	0.00	0.00	0.00
13,300.0	88.98	89.71	9,639.2	-461.9	3,700.0	3,716.3	0.00	0.00	0.00
13,400.0	88.98	89.71	9,641.0	-461.4	3,800.0	3,816.2	0.00	0.00	0.00
13,500.0	88.98	89.71	9,642.7	-460.9	3,900.0	3,916.1	0.00	0.00	0.00
13,600.0	88.98	89.71	9,644.5	-460.4	4,000.0	4,015.9	0.00	0.00	0.00
13,700.0	88.98	89.71	9,646.3	-459.8	4,100.0	4,115.8	0.00	0.00	0.00
13,800.0	88.98	89.71	9,648.1	-459.3	4,200.0	4,215.7	0.00	0.00	0.00
13,900.0	88.98	89.71	9,649.9	-458.8	4,299.9	4,315.5	0.00	0.00	0.00
14,000.0	88.98	89.71	9,651.6	-458.3	4,399.9	4,415.4	0.00	0.00	0.00
14,100.0	88.98	89.71	9,653.4	-457.8	4,499.9	4,515.3	0.00	0.00	0.00
14,200.0	88.98	89.71	9,655.2	-457.3	4,599.9	4,615.2	0.00	0.00	0.00
14,300.0	88.98	89.71	9,657.0	-456.8	4,699.9	4,715.0	0.00	0.00	0.00
14,400.0	88.98	89.71	9,658.8	-456.2	4,799.8	4,814.9	0.00	0.00	0.00
14,500.0	88.98	89.71	9,660.5	-455.7	4,899.8	4,914.8	0.00	0.00	0.00
14,600.0	88.98	89.71	9,662.3	-455.2	4,999.8	5,014.6	0.00	0.00	0.00
14,700.0	88.98	89.71	9,664.1	-454.7	5,099.8	5,114.5	0.00	0.00	0.00
14,800.0	88.98	89.71	9,665.9	-454.2	5,199.8	5,214.4	0.00	0.00	0.00
14,900.0	88.98	89.71	9,667.7	-453.7	5,299.8	5,314.2	0.00	0.00	0.00
15,000.0	88.98	89.71	9,669.5	-453.2	5,399.7	5,414.1	0.00	0.00	0.00
15,100.0	88.98	89.71	9,671.2	-452.6	5,499.7	5,514.0	0.00	0.00	0.00
15,200.0	88.98	89.71	9,673.0	-452.1	5,599.7	5,613.9	0.00	0.00	0.00

Planning Report



Database:	Hobbs	Local Co-ordinate Reference:	Site Oxbow 23/24 W0MP Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 2963.0usft (Original Well Elev)
Project:	Eddy County, New Mexico NAD 83	MD Reference:	WELL @ 2963.0usft (Original Well Elev)
Site:	Oxbow 23/24 W0MP Fed Com #1H	North Reference:	Grid
Well:	Secs. 23 & 24, T25S, R28E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 330' FSL & 330' FEL (24)		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
15,300.0	88.98	89.71	9,674.8	-451.6	5,699.7	5,713.7	0.00	0.00	0.00
15,400.0	88.98	89.71	9,676.6	-451.1	5,799.7	5,813.6	0.00	0.00	0.00
15,500.0	88.98	89.71	9,678.4	-450.6	5,899.7	5,913.5	0.00	0.00	0.00
15,600.0	88.98	89.71	9,680.1	-450.1	5,999.6	6,013.3	0.00	0.00	0.00
15,700.0	88.98	89.71	9,681.9	-449.5	6,099.6	6,113.2	0.00	0.00	0.00
15,800.0	88.98	89.71	9,683.7	-449.0	6,199.6	6,213.1	0.00	0.00	0.00
15,900.0	88.98	89.71	9,685.5	-448.5	6,299.6	6,313.0	0.00	0.00	0.00
16,000.0	88.98	89.71	9,687.3	-448.0	6,399.6	6,412.8	0.00	0.00	0.00
16,044.4	88.98	89.71	9,688.0	-447.8	6,444.0	6,457.2	0.00	0.00	0.00
PPP: 330' FSL & 1326' FWL (24)									
16,100.0	88.98	89.71	9,689.0	-447.5	6,499.6	6,512.7	0.00	0.00	0.00
16,200.0	88.98	89.71	9,690.8	-447.0	6,599.5	6,612.6	0.00	0.00	0.00
16,300.0	88.98	89.71	9,692.6	-446.5	6,699.5	6,712.4	0.00	0.00	0.00
16,400.0	88.98	89.71	9,694.4	-445.9	6,799.5	6,812.3	0.00	0.00	0.00
16,500.0	88.98	89.71	9,696.2	-445.4	6,899.5	6,912.2	0.00	0.00	0.00
16,600.0	88.98	89.71	9,697.9	-444.9	6,999.5	7,012.1	0.00	0.00	0.00
16,700.0	88.98	89.71	9,699.7	-444.4	7,099.5	7,111.9	0.00	0.00	0.00
16,800.0	88.98	89.71	9,701.5	-443.9	7,199.4	7,211.8	0.00	0.00	0.00
16,900.0	88.98	89.71	9,703.3	-443.4	7,299.4	7,311.7	0.00	0.00	0.00
17,000.0	88.98	89.71	9,705.1	-442.9	7,399.4	7,411.5	0.00	0.00	0.00
17,100.0	88.98	89.71	9,706.8	-442.3	7,499.4	7,511.4	0.00	0.00	0.00
17,200.0	88.98	89.71	9,708.6	-441.8	7,599.4	7,611.3	0.00	0.00	0.00
17,300.0	88.98	89.71	9,710.4	-441.3	7,699.3	7,711.1	0.00	0.00	0.00
17,400.0	88.98	89.71	9,712.2	-440.8	7,799.3	7,811.0	0.00	0.00	0.00
17,500.0	88.98	89.71	9,714.0	-440.3	7,899.3	7,910.9	0.00	0.00	0.00
17,600.0	88.98	89.71	9,715.7	-439.8	7,999.3	8,010.8	0.00	0.00	0.00
17,700.0	88.98	89.71	9,717.5	-439.3	8,099.3	8,110.6	0.00	0.00	0.00
17,800.0	88.98	89.71	9,719.3	-438.7	8,199.3	8,210.5	0.00	0.00	0.00
17,900.0	88.98	89.71	9,721.1	-438.2	8,299.2	8,310.4	0.00	0.00	0.00
18,000.0	88.98	89.71	9,722.9	-437.7	8,399.2	8,410.2	0.00	0.00	0.00
18,100.0	88.98	89.71	9,724.7	-437.2	8,499.2	8,510.1	0.00	0.00	0.00
18,200.0	88.98	89.71	9,726.4	-436.7	8,599.2	8,610.0	0.00	0.00	0.00
18,300.0	88.98	89.71	9,728.2	-436.2	8,699.2	8,709.9	0.00	0.00	0.00
18,400.0	88.98	89.71	9,730.0	-435.7	8,799.2	8,809.7	0.00	0.00	0.00
18,500.0	88.98	89.71	9,731.8	-435.1	8,899.1	8,909.6	0.00	0.00	0.00
18,600.0	88.98	89.71	9,733.6	-434.6	8,999.1	9,009.5	0.00	0.00	0.00
18,695.9	88.98	89.71	9,735.3	-434.1	9,095.0	9,105.2	0.00	0.00	0.00
PPP 2: 330' FSL & 1326' FEL (24)									
18,700.0	88.98	89.71	9,735.3	-434.1	9,099.1	9,109.3	0.00	0.00	0.00
18,800.0	88.98	89.71	9,737.1	-433.6	9,199.1	9,209.2	0.00	0.00	0.00
18,900.0	88.98	89.71	9,738.9	-433.1	9,299.1	9,309.1	0.00	0.00	0.00
19,000.0	88.98	89.71	9,740.7	-432.6	9,399.1	9,408.9	0.00	0.00	0.00
19,100.0	88.98	89.71	9,742.5	-432.0	9,499.0	9,508.8	0.00	0.00	0.00
19,200.0	88.98	89.71	9,744.2	-431.5	9,599.0	9,608.7	0.00	0.00	0.00
19,300.0	88.98	89.71	9,746.0	-431.0	9,699.0	9,708.6	0.00	0.00	0.00
19,400.0	88.98	89.71	9,747.8	-430.5	9,799.0	9,808.4	0.00	0.00	0.00
19,500.0	88.98	89.71	9,749.6	-430.0	9,899.0	9,908.3	0.00	0.00	0.00
19,600.0	88.98	89.71	9,751.4	-429.5	9,999.0	10,008.2	0.00	0.00	0.00
19,692.1	88.98	89.71	9,753.0	-429.0	10,091.0	10,100.1	0.00	0.00	0.00
BHL: 330' FSL & 330' FEL (24)									

Planning Report

Database:	Hobbs	Local Co-ordinate Reference:	Site Oxbow 23/24 W0MP Fed Com #1H
Company:	Mewbourne Oil Company	TVD Reference:	WELL @ 2963.0usft (Original Well Elev)
Project:	Eddy County, New Mexico NAD 83	MD Reference:	WELL @ 2963.0usft (Original Well Elev)
Site:	Oxbow 23/24 W0MP Fed Com #1H	North Reference:	Grid
Well:	Secs. 23 & 24, T25S, R28E	Survey Calculation Method:	Minimum Curvature
Wellbore:	BHL: 330' FSL & 330' FEL (24)		
Design:	Design #1		

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
SL: 810' FSL & 215' FWI - plan hits target center - Point	0.00	0.00	0.0	0.0	0.0	403,988.00	624,168.00	32.1103597	-104.0658074
KOP: 330' FSL & 10' FWI - plan hits target center - Point	0.00	0.00	9,101.0	-482.0	-204.0	403,506.00	623,964.00	32.1090361	-104.0664701
FTP: 330' FSL & 330' FV - plan hits target center - Point	0.00	0.01	9,551.1	-480.4	115.0	403,507.64	624,283.00	32.1090385	-104.0654398
PPP: 330' FSL & 1326' F - plan hits target center - Point	0.00	0.00	9,688.0	-447.8	6,444.0	403,540.22	630,612.00	32.1090831	-104.0449986
PPP 2: 330' FSL & 1326 - plan hits target center - Point	0.00	0.00	9,735.3	-434.1	9,095.0	403,553.87	633,263.00	32.1091009	-104.0364365
BHL: 330' FSL & 330' FE - plan hits target center - Point	0.00	0.00	9,753.0	-429.0	10,091.0	403,559.00	634,259.00	32.1091074	-104.0332197



Mewbourne Oil Company
Oxbow 23/24 W0MP Fed Com #1H
Secs. 23 & 24, T25S, R28E
SL: 810' FSL & 215' FWL (23)
BHL: 330' FSL & 330' FEL (24)

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	500'	13.375"	48	H40	STC	3.37	7.56	13.42	22.54
12.25"	0'	2685'	9.625"	36	J55	LTC	1.45	2.52	4.69	5.83
8.75"	0'	9711'	7"	26	P110	LTC	1.32	2.11	2.53	3.29
6.125"	9123'	19692'	4.5"	13.5	P110	LTC	1.75	2.04	2.37	2.96
BLM Minimum Safety Factor	1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet						

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	

Mewbourne Oil Company
Oxbow 23/24 W0MP Fed Com #1H
Secs. 23 & 24, T25S, R28E
SL: 810' FSL & 215' FWL (23)
BHL: 330' FSL & 330' FEL (24)

Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company
Oxbow 23/24 W0MP Fed Com #1H
Secs. 23 & 24, T25S, R28E
SL: 810' FSL & 215' FWL (23)
BHL: 330' FSL & 330' FEL (24)

2. Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	500'	13.375"	48	H40	STC	3.37	7.56	13.42	22.54
12.25"	0'	2685'	9.625"	36	J55	LTC	1.45	2.52	4.69	5.83
8.75"	0'	9711'	7"	26	P110	LTC	1.32	2.11	2.53	3.29
6.125"	9123'	19692'	4.5"	13.5	P110	LTC	1.75	2.04	2.37	2.96
BLM Minimum Safety Factor	1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet						

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	

Mewbourne Oil Company
Oxbow 23/24 W0MP Fed Com #1H
Secs. 23 & 24, T25S, R28E
SL: 810' FSL & 215' FWL (23)
BHL: 330' FSL & 330' FEL (24)

Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

3. Cementing Program

Casing	# Sks	Wt. lb/ gal	Yld ft ³ / sack	H ₂ O gal/ sk	500# Comp. Strength (hours)	Slurry Description
Surf.	210	12.5	2.12	11	10	Lead: Class C + Salt + Gel + Extender + LCM
	200	14.8	1.34	6.3	8	Tail: Class C + Retarder
Inter.	370	12.5	2.12	11	10	Lead: Class C + Salt + Gel + Extender + LCM
	200	14.8	1.34	6.3	8	Tail: Class C + Retarder
Prod. Stg 1	310	12.5	2.12	11	9	Lead: Class C + Salt + Gel + Extender + LCM
	400	15.6	1.18	5.2	10	Tail: Class H + Retarder + Fluid Loss + Defoamer
ECP/DV tool @ 3710'						
Prod. Stg 2	50	12.5	2.12	11	9	Lead: Class C + Salt + Gel + Extender + LCM
	100	14.8	1.34	6.3	8	Tail: Class C + Retarder
Liner	420	11.2	2.97	18	16	Class H + Salt + Gel + Fluid Loss + Retarder + Dispersant + Defoamer + Anti-Settling Agent

A copy of cement test will be available on location at time of cement job providing pump times & compressive strengths.

Casing String	TOC	% Excess
Surface	0'	100%
Intermediate	0'	25%
Production	2485'	25%
Liner	9123'	25%

Mewbourne Oil Company
Oxbow 23/24 W0MP Fed Com #1H
Secs. 23 & 24, T25S, R28E
SL: 810' FSL & 215' FWL (23)
BHL: 330' FSL & 330' FEL (24)

4. Pressure Control Equipment

BOP installed and tested before drilling which hole?	Size?	System Rated WP	Type		Tested to:
12-1/4"	13-5/8"	5M	Annular	X	2500#
			Blind Ram	X	5000#
			Pipe Ram	X	
			Double Ram		
			Other*		

*Specify if additional ram is utilized.

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

X	Formation integrity test will be performed per Onshore Order #2. On exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in
---	---

Mewbourne Oil Company
Oxbow 23/24 W0MP Fed Com #1H
Secs. 23 & 24, T25S, R28E
SL: 810' FSL & 215' FWL (23)
BHL: 330' FSL & 330' FEL (24)

	accordance with Onshore Oil and Gas Order #2 III.B.1.i.	
Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.	
	N	Are anchors required by manufacturer?
Y	A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested. <ul style="list-style-type: none"> Provide description here: See attached schematic. 	

5. Mud Program

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0'	500'	FW Gel	8.6-8.8	28-34	N/C
500'	2685'	Saturated Brine	10.0	28-34	N/C
2685'	9551'	Cut Brine	8.6-9.5	28-34	N/C
9551'	9753'	OBM	9.5-12.0	30-40	<10cc

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times. MW up to 13.0 ppg may be required for shale control. The highest MW needed to balance formation pressure is expected to be 12.0 ppg.

What will be used to monitor the loss or gain of fluid?	Pason/PVT/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing.	
X	Will run GR/CNL from KOP (9123') to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain

Mewbourne Oil Company
Oxbow 23/24 W0MP Fed Com #1H
Secs. 23 & 24, T25S, R28E
SL: 810' FSL & 215' FWL (23)
BHL: 330' FSL & 330' FEL (24)

	Coring? If yes, explain	
--	-------------------------	--

Additional logs planned	Interval	
X	Gamma Ray	9123' (KOP) to TD
	Density	
	CBL	
	Mud log	
	PEX	

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	6085 psi
Abnormal Temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers in surface hole.

Hydrogen Sulfide (H₂S) monitors will be installed prior to drilling out the surface shoe. If H₂S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

	H ₂ S is present
X	H ₂ S Plan attached

8. Other facets of operation

Is this a walking operation? If yes, describe.

Will be pre-setting casing? If yes, describe.

Mewbourne Oil Company
Oxbow 23/24 W0MP Fed Com #1H
Secs. 23 & 24, T25S, R28E
SL: 810' FSL & 215' FWL (23)
BHL: 330' FSL & 330' FEL (24)

Attachments

- ☐ Directional Plan
- ☐ Other, describe