•		RECEIVED									
Form 3160-5 (June 2015) DE Bi	UNITED STATES PARTMENT OF THE INT UREAU OF LAND MANAG	TERIOR BEB 19 2020		FORM AP OMB NO. Expires: Janu	1004-0137						
	NOTICES AND REPORT s form for proposition (APD)		TESIA	ease Serial No. MNM25866 Indian, Allonee or T	ribe Name						
SUBMIT IN	RIPLICATE - Other Instru	uctions on page 2	7. If	Unit or CA/Agreeme	mi, Name and/or No.						
1. Type of Well				ell Name and No.							
Oil Well B Gas Well Out One of Operator EOG Y RESOURCES INC		INA HUERTA peogresources.com	9, A	UDER ACN FEDEF PI Well No. 0-005-62283-00-5	• 						
3a. Address 105 SOUTH FOURTH STREE ARTESIA, NM 88210		3b. Phone No. (include area code) Ph: 575-748-4168	10. I P	ield and Pool or Exp ECOS SLOPE-A	koratory Area BO						
4. Location of Well (Footuge, Sec., T.	, R. M. or Survey Description)		11. (County or Parish, Stat	te						
Sec 22 T6S R26E NWNW 660	FNL 660FWL		c	CHAVES COUNTY, NM							
12. CHECK THE AF	PROPRIATE BOX(ES) T	O INDICATE NATURE O	NOTICE, REP	ORT, OR OTHE	R DATA						
TYPE OF SUBMISSION		TYPE OF	ACTION								
Notice of Intent	 Acidize Alter Casing 	 Deepen Hydraulic Fracturing 	Production (S Reclamation		□ Water Shut-Off □ Well Integrity						
Subsequent Report	Casing Repair	New Construction	C Recomplete		Other						
Final Abandonment Notice	Final Abandonment Notice Change Plans Plug and Abandon Tem Convert to Injection Plug Back Wate										
following completion of the involved testing has been completed. Final Ab determined that the site is ready for fi EOG Resources, Inc. plans to 1. MIRU all safety equipment 2. RIH with bit and scraper to 3. Set a CIBP at 4077 ft with 3 and tag. 4. Spot a 25 sx Class C ceme 5. Perforate at 972 ft. Attempt 972 ft - 610 ft. WOC. This will 6. Tag TOC. Perforate at 145 7. Spot a 25 sx Class C in/out 8. Back fill and or 1 inch as ne	andonment Notices must be filed nal inspection plug and abandon this well as needed. POOH with pro- 4097 ft. 55 ft Class C cement on top nt plug from 1812 ft - 1450 to establish circulation. Spr sover 8-5/8 inch shoe and 5 ft. Attempt to establish circu cement plug from 145 ft up	as follows: as follows: duction equipment. This will cover top of Abo p ft. This will cover Glorieta. V ot a 25 sx Class C cement p San Andres. TA C	ng reclamation, have perfs. WOC i i in	been completed and	the operator has	bailer. 2/21/20 d for record - NMOCD					
	Electronic Submission #50 For EOG Y RE nitled to AFMSS for process	1937 verificit by the BLM Well SOURCESINC, sent to the R Ing by MEIGHAN SALAS on 0	oswell 2/04/2020 (20MMS	0029\$E)							
Naine (Printed/Typed) TINA HUE		Title REGULA	TORY SPECIAL	151	<u> </u>						
Signature (Electronic S		Date 02/04/20									
	THIS SPACE FOR	FEDERAL OR STATE (FFICE USE								
Approved By Long Vo	Zm	Title Petro	eum Eng	ineer	Date 2/15/20						
Conditions of approval, if any, are attached certify that the applicant holds legal or equi which would entitle the applicant to conduc	Approval of this notice does no table title to those rights in the su operations thereon.	t warrant or bject lease Office CF	0								
Title 18 U.S.C. Section 1001 and Title 43 U States any false, fictitious or fraudulent st	J.S.C. Section 1212, make it a cru atements or representations as to	me for any person knowingly and any matter within its jurisdiction.	villfully to make to a	ny department or agen	ncy of the United						
(Instructions on page 2) ** BLM REV	SED ** BLM REVISED *	* BLM REVISED ** BLM			6						
			APPRO	val subj	IECT TO						

÷.,

. . . GENERAL REQUIREMENTS AND SPECIAL STIPULATIONS ATTACHED

Additional data for EC transaction #501937 that would not fit on the form

32. Additional remarks, continued

9. Cut off wellhead and install dry hole marker. Clean location as per regulated.

Wellbore schematics attached

COMMENTS	Buder AC	Ler ACN #1 Sec-TWN-RNG: Sec. 22-T6S-R25E FOOTAGES: 660' FNL & 660' FWL CURRENT					API: GL: KB:	30-005-62283 3,691'					
		See State		60929			053668857		označeni	and the second second		and design	7. H. M.
					G DETAL								
					HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	SxCmt	Chertoc	TOC Metho
				В	10"	8 5/8*	24#	K-55	0	922	.550	Surface	100/401/2
				C	7 7/8*	4 1/2"	13.5#	N-80	0	4,350	675	Surface	Visual
			<u> </u>										
	в				1								
				9895				S Starger	SELECTION OF	er og hersteller.	A STATE	的研究的研究	i seriere
				FORM	ATION TOPS								
						Formation	Тор						
						San Andrea	655	×					_
						Giorieta Abo	1,762	×					
													
	5 S S S						_						
				}							<u>├</u> -		
					+					·····			
		Sector Sector	3				_	ļ					
				A10512575	and the second second		Markar Colored	147210-1010-778	Treffer ann	eter the second second second	-0-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	and the second	and the second se
	200						****************		<u></u>		1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.		CALCULATION OF A
	「「「」			Plags								·····	
				1		R with 35 ft of CLS C (
				2	Spot a 25 SX (38	12 ft) CLS C cement plu	<u>α 3505 π - 3868</u>	R. NUC &	Tag Plug	This will plug the A	b0.		
	22			3	Spot a 25 SX (35	2 f) CLS C cement plu	n 1450 ft - 1812	e woca:	Tao Plun	This will nive the G	innete		
												0 8-972 8 WOC	& Tan Plun
				4		R. Altempt to establish 8 5/8*& San Andres							
				5	Will plug the Top	ft, Attempt to establish	Circuseson or sj	ot I/D, Rec	or centry	SX (1451) CLS C ce	ment plug D t	n - 145 ft. WOC &	Tag Pieg. Th
				6								· · · · · · · · · · · · · · · · · · ·	
				,		,							
	1964 1977			<u>+</u>	12.								
	20			в		•							
			964	9		· · · · · · · · · · · · · · · · · · ·							
			4		1								
		And the second second											
Perfect Abo @													
127-4135 (18 holes)		A CONTRACTOR	5										
			ACCENT		1								
		z											······································
	100					· · · · · · · · · · · · · · · · · · ·							
		and the second se			1								
				F									
	C C				1								
	C PBTD;	MD			1								

			an a								
						•					
	Buder ACN #1	(1997) - 2014년 - 2014년 - 2014년 - 2014년 - 2014년 - 1914년 - 1914년 - 2014년 - 2014년 - 2014년 - 2014년 - 2014년 - 2014년 - 2014년 - 2014년 - 2014년 - 2014년 - 2014년 - 2014년	Sec-TWN-RNG:	Sec. 22-T6S-R26	E		API:	30-005-6	2283		
COMMENTS			CURRENT	660' FNL & 660' I	FWL		GL: KB:	3,691'			
			California			642 (A)		5.575 (A)			
			CASING DETAIL			·······					
			# HOLE SIZE B 10*	SIZE	WGHT	GRADE	Top	Bottom	Sx Crnt	Circ/TOC	TOC Method
			B 10* C 77/8*	<u>8 5/8"</u> 4 1/2"	24#	K-55 N-80	0	922 4,350	<u>550</u> 675	Surface Surface	Visual
					10.07			••••••	0/5	SURCE	VISURN
l I	B		Second Second		and the second	-	w.m. 12444	4.1. Mar. 120.10.17	Constant of the other	and the second second	4. 10 Land 10 and 10 10 10 10
			FORMATION TOPS		and the second secon	A. A. P. Good and Street, St.	Second C.	S. S. Start (R. c.			16101130252400
				Formation	Estimated Top						
			· .	San Andres	655'	<u> </u>					_
				Giorietz	1,762 3,818	<u> </u>					
					-						
	22253									·····	
										······	
l						NS ROOM			in an		
ł			TUBING DETAIL	r							
			# Joints 126	Description J-65	Lenoth 4.090*	0D 23/8"	_10	Grade J-SS	WA (ILMO:	Top (ftKB):	8tm (ftKB):
				<i>8-03</i>	4,050	23/8					
			Rod Detail			an a	0-fairth	195	and the second	an a	17.19.19.19.19.19.19.19
			# Joints	Description	Length	OD	1D	Grade	WI (IB/II):	Top (ftKE):	Btm (ft/CB);
			And the first section of the state of the st		1. Charles to a stability to say						
			NAME OF COMPANY				1996				D. A. KITERIG
				l							
Packer & SN @ 4090'											
Perfed Abo @				1	·	1 1					
4127-4135 (16 holes)											-
			na internetienter						() () () () ()		in en
	c										
i i i i i i i i i i i i i i i i i i i	PBTD: 4,299 MD TD: 4,350 MD										
	10:1 4.350 MD				····			·····		·····	

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of pluggingmud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary. Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.

8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

à

i.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/am



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech 575-234-5909, 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Henryetta Price Environmental Protection Specialist 575-234-5951

Shelly Tucker Environmental Protection Specialist 575-234-5979

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612