UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED FEB 2.4 2020

FORM APPROVED OMB NO. 1004-0137

Expires: January 31, 2018

SUNDRY Do not use the abandoned we	nah III.		Serial No. IM04557 ian, Allottee or	Tribe Name			
SUBMIT IN TRIPLICATE - Other instructions on page				7. If Unit or CA/Agreement, Name and/or No. 891000326X			
Type of Well ☐ Gas Well ☐ Other				8. Well Name and No. BIG EDDY UNIT DI4B 274H			
Name of Operator XTO PERMIAN OPERATING LLC E-Mail: Cheryl_rowell@xtoenerg							
3a. Address 6401 HOLIDAY HILL ROAD BLDG 5 MIDLAND, TX 79707		3b. Phone No. (include area code) Ph: 432-571-8205			10. Field and Pool or Exploratory Area WILLIAMS SINK		
4. Location of Well (Footage, Sec., T)		11. Cou	11. County or Parish, State			
Sec 5 T20S R31E SWSE 720FSL 2065FEL				EDD	EDDY COUNTY, NM		
12. CHECK THE AI	PPROPRIATE BOX(ES)	TO INDICATE N	ATURE O	F NOTICE, REPOR	T, OR OTHE	ER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION					
☐ Notice of Intent	☐ Acidize	☐ Deepen		☐ Production (Start	Resume)	☐ Water Shut-Off	
	☐ Alter Casing	☐ Hydraulic	Fracturing	☐ Reclamation		■ Well Integrity	
Subsequent Report	☐ Casing Repair	☐ New Const	truction	☐ Recomplete '			
☐ Final Abandonment Notice	□ Change Plans	☐ Plug and A	bandon	☐ Temporarily Aba	ndon	Drilling Operations	
	□ Convert to Injection	Plug Back		■ Water Disposal			
13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection. ******* ******* ****** ***** *****							
14. I hereby certify that the foregoing is	true and correct. Electronic Submission #5	503449 vovisidel by th	o Di M Woll	Information System			
Com	For XTO PERMI mitted to AFMSS for proce	AN OPERATING LL	C. sent to the	e Carlsbad	8SF)		
Name (Printed/Typed) CHERYL I	Title						
				· · · · · ·		•	
Signature (Electronic S	Electronic Submission) Date			02/07/2020			
	THIS SPACE FO	R FEDERAL OF	STATE	OFFICE USE			
Approved By ACCEPT	Title	JONATHOI PETROLEI	N SHEPARD JM ENGINEER		Date 02/13/2020		
Conditions of approval; if any are attached. Approval of this notice does not warrant certify that the applicant holds legal or equitable title to those rights in the subject least			and the second second second second	manip processor suprement and account to the suprement of	Section Control of Con	Sika paramakan ing katharika da akamatan da katharika da akamata	
which would entitle the applicant to conduct operations thereon.			e Carlsbad				

(Instructions on page 2) ** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Additional data for EC transaction #502448 that would not fit on the form

32. Additional remarks, continued

05/23/2019 to 05/26/2019
Drill 10 5/8 inch hole to 4318 ft. Run 8 5/8, 32#, J-55 casing set at 4264 ft., Cement stage 1: 990 sxs Class C cement. Bump Plug. Inflate ECP, drop cancellation tool. Cement to surface. WOC. Test casing 1850 psi, 30 mins (good).

05/27/2019 to 06/06/2019
Drill 7 7/8 inch hole to 16400 ft, Run 5 1/2 inch, 20#, P-110 casing set @ 16400?. Cement casing with 480 sxs Class C and 390 sxs Class H. Bump plug. Spacer to surface. CTOC 2200?.

PBTD = 16398 FT

Rig Release 06/06/2019