

RECEIVED

FEB 21 2020

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-41032

5. Indicate Type of Lease

STATE ☐ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Cedar Canyon 15

8. Well Number #2H

9. OGRID Number 16696

10. Pool name or Wildcat
PIERCE CROSSING; BONE SPRING, EAST

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator OXY USA INC.

3. Address of Operator 5 GREENWAY PLAZA, SUITE 110, HOUSTON, TX, 77046

4. Well Location

Unit Letter M: 170 feet from the SOUTH line and 360 feet from the WEST line

Section 15 Township 24S Range 29E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: LINER, PERFOR, FRAC ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

OXY respectfully requests to run a liner, perforate, and frac the existing formation. Please see below proposed procedure and attached current and proposed wellbore diagrams.

- MIRU PU. Ensure well is dead
- ND wellhead. NU BOP
- POOH with beam equipment
- PU and RIH packer on 2-7/8" tubing and perform pressure test on casing
- RDMO PU
- Pump produced gas slug
- MIRU PU
- ND wellhead. NU BOP
- POOH with packer and tubing
- Cleanout to PBD
- RIH w/ 4.25" 13.1# expandable liner set @ approximately 8,400'-13,500'
- Perforate and frac in stages from approximately 12,800'- 8,550'
- Cleanout to PBD
- Flowback as needed
- Run artificial lift equipment
- RDMO PU

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Emily Messer TITLE REGULATORY LEAD DATE 02/19/2020

Type or print name EMILY MESSER E-mail address: EMILY_MESSER@OXY.COM PHONE: 713-497-2076

For State Use Only

APPROVED BY: [Signature] TITLE Staff DATE 2/24/20

Conditions of Approval (if any):

OXY USA Inc. Cedar Canyon 15 #2H – 30-015-41032

OXY USA Inc. - Current

Well Name: Cedar Canyon 15-2H

API: 30-015-41032

Loc: 170' FSL 360' FWL SEC 15, T24S, R29E

County/State: Eddy County, NM

11-3/4" 42# H-40 SA 334'
TOC at surface (Circulated)

8-5/8" 32# J55 SA 3101'
TOC at surface (Circulated)

ACP SA 2744'

5-1/2" 17# L80 SA 12,880'
TOC at 5450' (CBL)
1450 sx CMT

Perforation Interval: 8900' - 12,800' (3900' total)

KOP at ~7850' (MD)

TD: 12,960' MD; 8796' (TVD)
PBSD: 12,880' (MD); 8794' (TVD)

OXY USA Inc. Cedar Canyon 15 #2H – 30-015-41032

OXY USA Inc. - Proposed
Well Name: Cedar Canyon 15-2H
API: 30-015-41032

Loc: 170' FSL 360' FWL SEC 15, T24S, R29E
County/State: Eddy County, NM

