Form 3160-3 (June 2015) UNITED STATES DEPARTMENT OF THE I BUREAU OF LAND MAN	S NTERIOF	NECEIV MAR 1 II RD-OCE		RTES	FORM A OMB No Expires: Jar Lease Serial No.	APPROVED . 1004-0137 nuary 31, 2018
			1		0. If indian, Anotee C	n moe Name
Ia. Type of work: 🗹 DRILL 🗌 R	EENTER				7. If Unit or CA Agro	cement, Name and No.
lb. Type of Well: 🔽 Oil Well 🛄 Gas Well 🛄 Other					8. Lease Name and V	Well No.
1c. Type of Completion: Hydraulic Fracturing Single Zone 🖌 Multiple Z		lone		LEATHERNECK 30	129 FED COM	
2. Name of Operator MATADOR PRODUCTION COMPANY					9. API Well No. 30-01	5-46895-
3a. Address 5400 LBJ Freeway, Suite 1500 Dallas TX 75240	3b. Phone (972)371-	No. <i>(include ai</i> 5200	ea cod	code) 10. Field and Pool, or Exploratory AVALON / BONE SPRING EAST		
4. Location of Well (Report location clearly and in accordance with any State requirements *) 11. Sec., T. R. M. or Blk. and Survey of SEC 30 / T20S / R29E / NMP At surface LOT 3 / 1355 FSL / 280 FWL / LAT 32.5409843 / LONG -104.1217353 SEC 30 / T20S / R29E / NMP At proposed prod. zone NESE / 1650 FSL / 60 FEL / LAT 32.541694 / LONG -104.088801 SEC 30 / T20S / R29E / NMP				Blk. and Survey or Area 29E / NMP		
14. Distance in miles and direction from nearest town or post off 8 miles	ice*				12. County or Parish EDDY	13. State NM
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)	16. No of 2150.97	acres in lease		17. Spacir 317.32	ng Unit dedicated to th	iis well
 Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 	19. Proposed Depth 9110 feet / 19265 feet		20. BLM/ FED: NN	M/BIA Bond No. in file NMB001079		
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3236 feet	22. Appro 09/01/201	ximate date wo	rk will	start*	23. Estimated duration 65 days	on
	24. Atta	chments			· · · · · ·	
The following, completed in accordance with the requirements o (as applicable)	f Onshore O	il and Gas Orde	r No.	l, and the H	Iydraulic Fracturing ru	ile per 43 CFR 3162.3-3
1. Well plat certified by a registered surveyor.4. Bond to cover the operations unless covered by an existing bond on file2. A Drilling Plan.Item 20 above).			existing bond on file (see			
 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). 5. Operator 6. Such oth BLM. 			certific r site sj	cation. pecific infor	nation and/or plans as	may be requested by the
25. Signature (Electronic Submission)	Nan Bria	ne <i>(Printed/Typ</i> n Wood / Ph:	<i>ed)</i> (505)4	66-8120		Date 07/16/2019
Title President						
proved by (Signature) Nan Electronic Submission) Cod		Name <i>(Printed/Typed)</i> Cody Layton / Ph: (575)234-5959			Date 03/06/2020	
Title C Assistant Field Manager Lands & Minerals C		Office CARLSBAD				
Application approval does not warrant or certify that the applicat applicant to conduct operations thereon. Conditions of approval, if any, are attached.	nt holds lega	l or equitable ti	tle to t	hose rights	in the subject lease wh	nich would entitle the
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, r of the United States any false, fictitious or fraudulent statements	nake it a crii or represent	ne for any pers ations as to any	on kno mattei	wingly and within its	willfully to make to a jurisdiction.	ny department or agency
		TH CON	DIT	IONS		

novel

Approval Date: 03/06/2020

APPI

(Continued on page 2)

*(Instructions on page 2)

RW 3-20-20

INSTRUCTION\$

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM I: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the wen, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionary drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

ITEM 24: If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service wen or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record win be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM conects this information to anow evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Conection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

(Continued on page 3)

Additional Operator Remarks

Location of Well

 SHL: LOT 3 / 1355 FSL / 280 FWL / TWSP: 20S / RANGE: 29E / SECTION: 30 / LAT: 32.5409843 / LONG: -104.1217353 (TVD: 0 feet, MD: 0 feet) PPP: LOT 3 / 1647 FSL / 86 FWL / TWSP: 20S / RANGE: 29E / SECTION: 30 / LAT: 32.5417838 / LONG: -104.1223646 (TVD: 8728 feet, MD: 8757 feet) PPP: NWSE / 1650 FSL / 2640 FEL / TWSP: 20S / RANGE: 29E / SECTION: 30 / LAT: 32.54177 / LONG: -104.114322 (TVD: 9110 feet, MD: 11400 feet) BHL: NESE / 1650 FSL / 60 FEL / TWSP: 20S / RANGE: 29E / SECTION: 29 / LAT: 32.541694 / LONG: -104.088801 (TVD: 9110 feet, MD: 19265 feet)

BLM Point of Contact

Name: Sophia Cwiklinski Title: LIE Phone: 5752345972 Email: scwiklinkski@blm.gov

Approval Date: 03/06/2020

(Form 3160-3, page 3)

Review and Appeal Rights

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.

Geologic Conditions of Approval

:

The operator proposes to set surface casing at 400 feet which is below Karst and groundwater zones. BLM accepts this set point. If salt is encountered, set casing at least 25' above the salt. The operator proposes to set first and second intermediate casing to a depth of 1,200 feet and 3100 feet which isolates the Capitan Reef. BLM accepts these two set points for intermediate casing. Geophysical logs above the Tansill Dolomite do not exist for more than two miles from project area. Because of this lack of data there is no sure way to protect karst/shallow groundwater zones. All Rustler, Salt and bottom of salt picks are being gridded from wells three miles away. ENSURE THAT A FULL GEOPHYSICAL SUITE OF LOGS IS RUN FOR AT LEAST TWO OF THE WELLS ON THIS PAD.

Approval Date: 03/06/2020

(Form 3160-3, page 4)

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
LEASE NO.:	NMNM0003677
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 137H
SURFACE HOLE FOOTAGE:	1355'/S & 280'/W
BOTTOM HOLE FOOTAGE	1650'/S & 60'/E
LOCATION:	Section 30, T.20 S., R.29 E., NMP
COUNTY:	Eddy County, New Mexico

COA

H2S	• Yes	C No	
Potash	None	C Secretary	⊂ R-111-P
Cave/Karst Potential	C Low	C Medium	High
Cave/Karst Potential	Critical		
Variance	(None	• Flex Hose	C Other
Wellhead	Conventional	← Multibowl	🕫 Both
Other	✓ 4 String Area	Capitan Reef	∫ WIPP
Other	☐ Fluid Filled	☐ Cement Squeeze	F Pilot Hole
Special Requirements	□ Water Disposal	COM	└ Unit

A. HYDROGEN SULFIDE

A Hydrogen Sulfide (H2S) Drilling Plan shall be activated 500 feet prior to drilling into the **Cherry Canyon** and **Brushy Canyon** formations. As a result, the Hydrogen Sulfide area must meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.

B. CASING

Casing Design:

- 1. The 20 inch surface casing shall be set at approximately 400 feet (a minimum of 70 feet (Eddy County) into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after

Page 1 of 10

completing the cement job.

- b. Wait on cement (WOC) time for a primary cement job will be a minimum of <u>8</u>
 <u>hours</u> or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- d. If cement falls back, remedial cementing will be done prior to drilling out that string.
- 2. The 13-3/8 inch intermediate casing shall be set at approximately 1200 feet The minimum required fill of cement behind the 13-3/8 inch intermediate casing is:

Option 1 (Single Stage):

• Cement to surface. If cement does not circulate see B.1.a, c-d above. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- b. Second stage above DV tool:
 - Cement to surface. If cement does not circulate, contact the appropriate BLM office.
 Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.
- In <u>High Cave/Karst Areas</u> if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
- In <u>Capitan Reef Areas</u> if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
- Special Capitan Reef requirements. If lost circulation (50% or greater) occurs below the Base of the Salt, the operator shall do the following:

Page 2 of 10

- Switch to fresh water mud to protect the Capitan Reef and use fresh water mud until setting the intermediate casing. The appropriate BLM office is to be notified for a PET to witness the switch to fresh water.
- Daily drilling reports from the Base of the Salt to the setting of the intermediate casing are to be submitted to the BLM CFO engineering staff via e-mail by 0800 hours each morning. Any lost circulation encountered is to be recorded on these drilling reports. The daily drilling report should show mud volume per shift/tour. Failure to submit these reports will result in an Incidence of Non-Compliance being issued for failure to comply with the Conditions of Approval. If not already planned, the operator shall run a caliper survey for the intermediate well bore and submit to the appropriate BLM office.
- 3. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:

the lead cement slurry due to cave/karst or potash.

Option 1 (Single Stage):

Cement should tie-back at least 50 feet on top of Capitan Reef top. If cement does not circulate see B.1.a, c-d above.
 Wait on cement (WOC) time for a primary cement job is to include

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- c. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- d. Second stage above DV tool:
 - Cement should tie-back at least 50 feet on top of Capitan Reef top. If cement does not circulate see B.1.a, c-d above.
 Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.
- 4. The minimum required fill of cement behind the 5-1/2 inch production casing is:

Option 1 (Single Stage):

• Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

Page 3 of 10

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- b. Second stage above DV tool:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

C. PRESSURE CONTROL

- 1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
- 2.

Option 1:

- a. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **3000 (3M)** psi.
- b. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the intermediate casing shoe shall be **5000 (5M)** psi.

Option 2:

- 1. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000** (**5M**) psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.

Page 4 of 10

- d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

D. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. <u>When the Communitization Agreement number is known, it shall also be</u> on the sign.

Page 5 of 10

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)
 - Eddy County Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220, (575) 361-2822
 - Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575) 393-3612
- 1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
- 2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
- 3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

Page 6 of 10

A. CASING

- 1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
- <u>Wait on cement (WOC) for Potash Areas:</u> After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least <u>24</u> hours. WOC time will be recorded in the driller's log. The casing intergrity test can be done (prior to the cement setting up) immediately after bumping the plug.
- 3. <u>Wait on cement (WOC) for Water Basin:</u> After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least <u>8 hours</u>. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing intergrity test can be done (prior to the cement setting up) immediately after bumping the plug.
- 4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
- 5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
- 6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
- 7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
- 8. Whenever a casing string is cemented in the R-11 1-P potash area, the NMOCD requirements shall be followed.

Page 7 of 10

B. PRESSURE CONTROL

- 1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
- 2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
- 3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
- 4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- 5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including

Page 8 of 10

lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

Page 9 of 10

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

NMK03032020

Page 10 of 10

٦

PECOS DISTRICT SURFACE USE CONDITIONS OF APPROVAL

OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 113H
SURFACE HOLE FOOTAGE:	1575'/S & 250'/W
BOTTOM HOLE FOOTAGE	2310'/S & 30'/E
LOCATION:	Section 30, T.20 S., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 114H
SURFACE HOLE FOOTAGE:	1575'/S & 280'/W
BOTTOM HOLE FOOTAGE	987'/S & 60'/E
LOCATION:	Section 30, T.20 S., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 123H
SURFACE HOLE FOOTAGE:	1465'/S & 250'/W
BOTTOM HOLE FOOTAGE	2310'/S & 60'/E
LOCATION:	Section 30, T.20 S., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 124H
SURFACE HOLE FOOTAGE:	1465'/S & 280'/W
BOTTOM HOLE FOOTAGE	987'/S & 60'/E
LOCATION:	Section 30, T.20 S., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 127H
SURFACE HOLE FOOTAGE:	1245'/S & 250'/W
BOTTOM HOLE FOOTAGE	1650'/S & 60'/E
LOCATION:	Section 30, T.20 S., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 128H
SURFACE HOLE FOOTAGE:	1245'/S & 280'/W
BOTTOM HOLE FOOTAGE	330'/S & 60'/E
LOCATION:	Section 30, T.20 S., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 133H
SURFACE HOLE FOOTAGE:	1545'/S & 250'/W
BOTTOM HOLE FOOTAGE	2310 ² /S & 60 ² /E
LOCATION:	Section 30, T.20 S., R.29 E., NMP
COUNTY:	Eddy County, New Mexico

Page 1 of 26

OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 134H
SURFACE HOLE FOOTAGE:	1545'/S & 280'/W
BOTTOM HOLE FOOTAGE	987'/S & 60'/E
LOCATION:	Section 30, T.20 S., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 137H
SURFACE HOLE FOOTAGE:	1355'/S & 280'/Ŵ
BOTTOM HOLE FOOTAGE	1650'/S & 60'/E
LOCATION:	Section 30, T.20 S., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 138H
SURFACE HOLE FOOTAGE:	1325'/S & 280'/Ŵ
BOTTOM HOLE FOOTAGE	330'/S & 60'/E
LOCATION:	Section 30, T.20 S., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 207H
SURFACE HOLE FOOTAGE:	1356'/S & 250'/W
BOTTOM HOLE FOOTAGE	330'/S & 60'/E
LOCATION:	Section 30, T.20 \$., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 208H
SURFACE HOLE FOOTAGE:	1325'/S & 250'/W
BOTTOM HOLE FOOTAGE	330'/S & 60'/E
LOCATION:	Section 30, T.20 \$., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 223H
SURFACE HOLE FOOTAGE:	1435'/S & 250'/W
BOTTOM HOLE FOOTAGE	2310'/S & 60'/E
LOCATION:	Section 30, T.20 \$., R.29 E., NMP
COUNTY:	Eddy County, New Mexico
OPERATOR'S NAME:	MATADOR PRODUCTION COMPANY
WELL NAME & NO.:	LEATHERNECK 3029 FED COM 224H
SURFACE HOLE FOOTAGE:	1435'/S & 280'/W
BOTTOM HOLE FOOTAGE	987'/S & 60'/E
LOCATION:	Section 30, T.20 \$., R.29 E., NMP
COUNTY:	Eddy County, New Mexico

Page 2 of 26

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

General Provisions
Permit Expiration
Archaeology, Paleontology, and Historical Sites
Noxious Weeds
Special Requirements
Cave/Karst
Hydrology
Construction
Notification
Topsoil
Closed Loop System
Federal Mineral Material Pits
Well Pads
Roads
Road Section Diagram
Production (Post Drilling)
Well Structures & Facilities
Access Roads
Electric Lines
Interim Reclamation
Final Abandonment & Reclamation

Page 3 of 26

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

Page 4 of 26

V. SPECIAL REQUIREMENT(S)

Condition of Approval for High Karst:

Construction Mitigation

In order to mitigate the impacts from construction activities on cave and karst resources, the following Conditions of Approval will apply to this APD or project:

General Construction:

- No blasting
- The BLM, Carlsbad Field Office, will be informed immediately if any subsurface drainage channels, cave passages, or voids are penetrated during construction, and no additional construction shall occur until clearance has been issued by the Authorized Officer.
- All linear surface disturbance activities will avoid sinkholes and other karst features to lessen the possibility of encountering near surface voids during construction, minimize changes to runoff, and prevent untimely leaks and spills from entering the karst drainage system.
- All spills or leaks will be reported to the BLM immediately for their immediate and proper treatment.

Pad Construction:

- The pad will be constructed and leveled by adding the necessary fill and caliche no blasting.
- The entire perimeter of the well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad.
- The compacted berm shall be constructed at a minimum of 12 inches high with impermeable mineral material (e.g., caliche).
- No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad.
- The topsoil stockpile shall be located outside the bermed well pad.
- Topsoil, either from the well pad or surrounding area, shall not be used to construct the berm.
- No storm drains, tubing or openings shall be placed in the berm.
- If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.
- The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed.
- Any access road entering the well pad shall be constructed so that the integrity of the berm height surrounding the well pad is not compromised (i.e. an access road crossing the berm cannot be lower than the berm height).
- Following a rain event, all fluids will vacuumed off of the pad and hauled off-site and disposed at a proper disposal facility.

Road Construction:

- Turnout ditches and drainage leadoffs will not be constructed in such a manner as to alter the natural flow of water into or out of cave or karst features.
- Special restoration stipulations or realignment may be required if subsurface features are discovered during construction.

Buried Pipeline/Cable Construction:

• Rerouting of the buried line(s) may be required if a subsurface void is encountered during construction to minimize the potential subsidence/collapse of the feature(s) as well as the possibility of leaks/spills entering the karst drainage system.

Page 5 of 26

Powerline Construction:

- Smaller powerlines will be routed around sinkholes and other karst features to avoid or lessen the possibility of encountering near surface voids and to minimize changes to runoff or possible leaks and spills from entering karst systems.
- Larger powerlines will adjust their pole spacing to avoid cave and karst features.
- Special restoration stipulations or realignment may be required if subsurface voids are encountered.

Surface Flowlines Installation:

• Flowlines will be routed around sinkholes and other karst features to minimize the possibility of leaks/spills from entering the karst drainage system.

Drilling Mitigation

Federal regulations and standard Conditions of Approval applied to all APDs require that adequate measures are taken to prevent contamination to the environment. Due to the extreme sensitivity of the cave and karst resources in this project area, the following additional Conditions of Approval will be added to this APD.

To prevent cave and karst resource contamination the following will be required:

- Closed loop system using steel tanks all fluids and cuttings will be hauled off-site and disposed of properly at an authorized site
- Rotary drilling with fresh water where cave or karst features are expected to prevent contamination of freshwater aquifers.
- Directional drilling is only allowed at depths greater than 100 feet below the cave occurrence zone to prevent additional impacts resulting from directional drilling.
- Lost circulation zones will be logged and reported in the drilling report so BLM can assess the situation and work with the operator on corrective actions.
- Additional drilling, casing, and cementing procedures to protect cave zones and fresh water aquifers. See drilling COAs.

Production Mitigation

In order to mitigate the impacts from production activities and due to the nature of karst terrane, the following Conditions of Approval will apply to this APD:

- Tank battery locations and facilities will be berned and lined with a 20 mil thick permanent liner that has a 4 oz. felt backing, or equivalent, to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.
- Development and implementation of a leak detection system to provide an early alert to operators when a leak has occurred.
- Automatic shut off, check values, or similar systems will be installed for pipelines and tanks to minimize the effects of catastrophic line failures used in production or drilling.

Residual and Cumulative Mitigation

The operator will perform annual pressure monitoring on all casing annuli and reported in a sundry notice. If the test results indicated a casing failure has occurred, remedial action will be taken to correct the problem to the BLM's approval.

Plugging and Abandonment Mitigation

Upon well abandonment in high cave karst areas additional plugging conditions of approval may be required. The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

Page 6 of 26

Hydrology:

The entire well pad(s) will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. The compacted berm shall be constructed at a minimum of 12 inches with impermeable mineral material (e.g. caliche). Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed. Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion. Stockpiling of topsoil is required. The top soil shall be stockpiled in an appropriate location to prevent loss of soil due to water or wind erosion and not used for berming or erosion control. If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility. The berm would be maintained through the life of the wells and after interim reclamation has been completed.

Tank battery locations will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank or 24 hour production, whichever is greater. Automatic shut off, check valves, or similar systems will be installed for tanks to minimize the effects of catastrophic line failures used in production or drilling.

Any water erosion that may occur due to the construction of overhead electric line and during the life of the power line will be quickly corrected and proper measures will be taken to prevent future erosion. A power pole should not be placed in drainages, playas, wetlands, riparian areas, or floodplains and must span across the features at a distance away that would not promote further erosion.

Grazing Lease Stipulations:

An agreement between Matador Production Company and the active Akali Lake (#77020) allotment (grazing) lease holder must come to an agreement of a new water pipeline location. Matador will move the water pipeline a minimum of 30' away from any oil and gas infrastructure. Matador will also construct the new pipeline prior to disconnecting the old pipeline to ensure cattle will have a source of water through the entire pipeline and oil and gas infrastructure construction.

Page 7 of 26

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Page 8 of 26

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts

Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Page 9 of 26

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outsloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

400 foot road with 4% road slope: $\frac{400'}{4\%}$ + 100' = 200' lead-off ditch interval

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Page 10 of 26



Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

Page 11 of 26

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Page 12 of 26

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, <u>Shale Green</u> from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. OIL AND GAS RELATED SITES

STANDARD STIPULATIONS FOR OIL AND GAS RELATED SITES

A copy of the application (Grant/Sundry Notice) and attachments, including stipulations and map, will be on location during construction. BLM personnel may request to view a copy of your permit during construction to ensure compliance with all stipulations.

The holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer, BLM.

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant and for all response costs, penalties, damages, claims, and other costs arising from the provisions of the Resource Conservation and Recovery Act (RCRA), 42 U.S.C. Chap. 82, Section 6901 et. seq., from the Comprehensive Environmental Response, Compensation and Liability Act (CERCLA), 42 U.S.C. Chap. 109, Section 9601 et. seq., and from other applicable environmental statues.

2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976, as amended (15 U.S.C. 2601, et. seq.) with regard to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized by this grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation and Liability Act, Section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the Authorized Officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42

Page 13 of 26

U.S.C. 9601, et. seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et. seq.) on the right-of-way (unless the release or threatened release is wholly unrelated to the right-of-way holder's activity on the right-of-way). This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the site or related pipeline(s), any oil or other pollutant should be discharged from site facilities, the pipeline(s) or from containers or vehicles impacting Federal lands, the control and total removal, disposal, and cleanup of such oil of other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages to Federal lands resulting therefrom, the Authorized Officer may take such measures as deemed necessary to control and cleanup the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any liability or responsibility.

5. Sites shall be maintained in an orderly, sanitary condition at all times. Waste materials, both liquid and solid, shall be disposed of promptly at an appropriate, authorized waste disposal facility in accordance with all applicable State and Federal laws. "Waste" means all discarded matter including, but not limited to, human waste, trash, garbage, refuse, petroleum products, brines, chemicals, oil drums, ashes, and equipment.

6. The operator will notify the Bureau of Land Management (BLM) authorized officer and nearest Fish and Wildlife Service (FWS) Law Enforcement office within 24 hours, if the operator discovers a dead or injured federally protected species (i.e., migratory bird species, bald or golden eagle, or species listed by the FWS as threatened or endangered) in or adjacent to a pit, trench, tank, exhaust stack, or fence. (If the operator is unable to contact the FWS Law Enforcement office, the operator must contact the nearest FWS Ecological Services office.)

7. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" designated by the Rocky Mountain Five-State Interagency Committee. The color selected for this project is **Shale Green**, Munsell Soil Color Chart Number 5Y 4/2.

8. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on the holder's behalf, on public or Federal land shall be immediately reported to the Authorized Officer. The holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of

Page 14 of 26

evaluation and any decision as to the proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

9. A sales contract for removal of mineral material (caliche, sand, gravel, fill dirt) from an authorized pit, site, or on location must be obtained from the BLM prior to commencing construction. There are several options available for purchasing mineral material: contact the BLM office (575-234-5972).

10. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

11. Once the site is no longer in service or use, the site must undergo final abandonment. At final abandonment, the site and access roads must undergo "final" reclamation so that the character and productivity of the land are restored. Earthwork for final reclamation must be completed within six (6) months of the abandonment of the site. All pads and facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact. After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

12. The holder shall stockpile an adequate amount of topsoil where blading occurs. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles. The topsoil will be used for final reclamation.

13. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

(X) seed mixture 1	() seed mixture 3
() seed mixture 2	(X) seed mixture 4
() seed mixture 2/LPC	() Aplomado Falcon Mixture

14. In those areas where erosion control structures are required to stabilize soil conditions, the holder shall install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound management practices. Any earth work will require prior approval by the Authorized Officer.

Page 15 of 26

15. Open-topped Tanks - The operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps

16. The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an

impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

17. Open-Vent Exhaust Stack Exclosures – The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

18. Containment Structures - Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

19. Special Stipulations:

Hydrology:

Page 16 of 26

The entire well pad(s) will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. The compacted berm shall be constructed at a minimum of 12 inches with impermeable mineral material (e.g. caliche). Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed. Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion. Stockpiling of topsoil is required. The top soil shall be stockpiled in an appropriate location to prevent loss of soil due to water or wind erosion and not used for berming or erosion control. If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.

Tank battery locations will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank or 24 hour production, whichever is greater. Automatic shut off, check valves, or similar systems will be installed for tanks to minimize the effects of catastrophic line failures used in production or drilling.

Range:

Cattleguards

Where a permanent cattlegaurd is approved, an appropriately sized cattleguard(s) sufficient to carry out the project shall be installed and maintained at fence crossing(s). Any existing cattleguard(s) on the access road shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguard(s) that are in place and are utilized during lease operations. A gate shall be constructed on one side of the cattleguard and fastened securely to H-braces.

Fence Requirement

Where entry granted across a fence line, the fence must be braced and tied off on both sides of the passageway prior to cutting. Once the work is completed, the fence will be restored to its prior condition, or better. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fence(s).

Livestock Watering Requirement

Any damage to structures that provide water to livestock throughout the life of the well, caused by operations from the well site, must be immediately corrected by the operator. The operator must notify the BLM office (575-234-5972) and the private surface landowner or the grazing allotment holder if any damage occurs to structures that provide water to livestock.

<u>Karst:</u>

Page 17 of 26

Construction Mitigation

In order to mitigate the impacts from construction activities on cave and karst resources, the following Conditions of Approval will apply to this APD or project:

General Construction:

- No blasting
- The BLM, Carlsbad Field Office, will be informed immediately if any subsurface drainage channels, cave passages, or voids are penetrated during construction, and no additional construction shall occur until clearance has been issued by the Authorized Officer.
- All linear surface disturbance activities will avoid sinkholes and other karst features to lessen the possibility of encountering near surface voids during construction, minimize changes to runoff, and prevent untimely leaks and spills from entering the karst drainage system.
- All spills or leaks will be reported to the BLM immediately for their immediate and proper treatment.

Pad Construction:

- The pad will be constructed and leveled by adding the necessary fill and caliche no blasting.
- The entire perimeter of the well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad.
- The compacted berm shall be constructed at a minimum of 12 inches high with impermeable mineral material (e.g., caliche)
- No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad.
- The topsoil stockpile shall be located outside the bermed well pad.
- Topsoil, either from the well pad or surrounding area, shall not be used to construct the berm.
- No storm drains, tubing or openings shall be placed in the berm.
- If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.
- The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed.
- Any access road entering the well pad shall be constructed so that the integrity of the berm height surrounding the well pad is not compromised (i.e. an access road crossing the berm cannot be lower than the berm height).
- Following a rain event, all fluids will vacuumed off of the pad and hauled off-site and disposed at a proper disposal facility.

Road Construction:

• Turnout ditches and drainage leadoffs will not be constructed in such a manner as to alter the natural flow of water into or out of cave or karst features.

Page 18 of 26

• Special restoration stipulations or realignment may be required if subsurface features are discovered during construction.

Buried Pipeline/Cable Construction:

• Rerouting of the buried line(s) may be required if a subsurface void is encountered during construction to minimize the potential subsidence/collapse of the feature(s) as well as the possibility of leaks/spills entering the karst drainage system.

Powerline Construction:

- Smaller powerlines will be routed around sinkholes and other karst features to avoid or lessen the possibility of encountering near surface voids and to minimize changes to runoff or possible leaks and spills from entering karst systems.
- Larger powerlines will adjust their pole spacing to avoid cave and karst features.
- Special restoration stipulations or realignment may be required if subsurface voids are encountered.

Surface Flowlines Installation:

• Flowlines will be routed around sinkholes and other karst features to minimize the possibility of leaks/spills from entering the karst drainage system.

Drilling Mitigation

Federal regulations and standard Conditions of Approval applied to all APDs require that adequate measures are taken to prevent contamination to the environment. Due to the extreme sensitivity of the cave and karst resources in this project area, the following additional Conditions of Approval will be added to this APD.

To prevent cave and karst resource contamination the following will be required:

- Closed loop system using steel tanks all fluids and cuttings will be hauled offsite and disposed of properly at an authorized site
- Rotary drilling with fresh water where cave or karst features are expected to prevent contamination of freshwater aquifers.
- Directional drilling is only allowed at depths greater than 100 feet below the cave occurrence zone to prevent additional impacts resulting from directional drilling.
- Lost circulation zones will be logged and reported in the drilling report so BLM can assess the situation and work with the operator on corrective actions.
- Additional drilling, casing, and cementing procedures to protect cave zones and fresh water aquifers. See drilling COAs.

Production Mitigation

In order to mitigate the impacts from production activities and due to the nature of karst terrane, the following Conditions of Approval will apply to this APD:

• Tank battery locations and facilities will be bermed and lined with a 20 mil thick permanent liner that has a 4 oz. felt backing, or equivalent, to prevent tears or

Page 19 of 26

punctures. Tank battery berms must be large enough to contain 1 ¹/₂ times the content of the largest tank.

- Development and implementation of a leak detection system to provide an early alert to operators when a leak has occurred.
- Automatic shut off, check values, or similar systems will be installed for pipelines and tanks to minimize the effects of catastrophic line failures used in production or drilling.

Residual and Cumulative Mitigation

The operator will perform annual pressure monitoring on all casing annuli and reported in a sundry notice. If the test results indicated a casing failure has occurred, remedial action will be taken to correct the problem to the BLM's approval.

Plugging and Abandonment Mitigation

Upon well abandonment in high cave karst areas additional plugging conditions of approval may be required. The BLM will assess the situation and work with the operator to ensure proper plugging of the wellbore.

Grazing Lease Stipulations:

An agreement between Matador Production Company and the active Akali Lake (#77020) allotment lease holder must come to an agreement of new water pipeline location. Matador will move the water pipeline a minimum of 30' away from any oil and gas infrastructure. Matador will also construct the new pipeline prior to disconnecting the old pipeline to ensure cattle will have a source of water through the entire pipeline and well pad construction.

C. ELECTRIC LINES

STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.

2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on

Page 20 of 26

facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, <u>et seq</u>. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, <u>et seq</u>.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.

5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006. The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching deterrence shall be placed on all vertical poles that extend past the cross arms.

6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

7. The BLM serial number assigned to this authorization shall be posted in a permanent,

Page 21 of 26

conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.

8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply with those abandonment procedures as prescribed by the Authorized Officer.

9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.

10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

11. Special Stipulations:

- For reclamation remove poles, lines, transformer, etc. and dispose of properly.
- Fill in any holes from the poles removed.

Powerline Construction:

- Smaller powerlines will be routed around sinkholes and other karst features to avoid or lessen the possibility of encountering near surface voids and to minimize changes to runoff or possible leaks and spills from entering karst systems.
- Larger powerlines will adjust their pole spacing to avoid cave and karst features.
- Special restoration stipulations or realignment may be required if subsurface voids are encountered.

ELECTRIC LINE(S):

• Any water erosion that may occur due to the construction of overhead electric line and during the life of the power line will be quickly corrected and proper measures will be taken to prevent future erosion. A power pole should not be placed in drainages, playas, wetlands, riparian areas, or floodplains and must span across the features at a distance away that would not promote further erosion.

• Grazing Lease Stipulations:

An agreement between Matador Production Company and the active Akali Lake (#77020) allotment lease holder must come to an agreement of new water pipeline location. Matador will move the water pipeline a minimum of 30' away from any oil and gas infrastructure. Matador will also construct the new pipeline prior to

Page 22 of 26
disconnecting the old pipeline to ensure cattle will have a source of water through the entire pipeline and well pad construction.

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Page 23 of 26

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Page 24 of 26

Seed Mixture 1 for Loamy Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed shall be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed shall be planted using a drill equipped with a depth regulator to ensure proper depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture shall be evenly and uniformly planted over the disturbed area (small/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed shall be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre shall be doubled. The seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

~		•	
- N	n 0	01	00
			C.5
\sim	~ •	•••	ΨĻ

-	<u>lb/acre</u>
Plains lovegrass (Eragrostis intermedia)	0.5
Sand dropseed (Sporobolus cryptandrus)	1.0
Sideoats grama (Bouteloua curtipendula)	5.0
Plains bristlegrass (Setaria macrostachya)	2.0

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed

Page 25 of 26

Page 26 of 26



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT



Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Brian Wood		Signed on: 07/15/2019
Title: President		
Street Address: 37 Verano Loc	юр	
City: Santa Fe	State: NM	Zip : 87508
Phone: (505)466-8120		
Email address: afmss@permits	swest.com	
Field Representati	ve	
Representative Name:		
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Application Data Report

APD ID: 10400043718	Submission D	ate: 07/16/2019	Highlighted data
Operator Name: MATADOR PRODUCTION	N COMPANY	· .	reflects the most recent changes
Well Name: LEATHERNECK 3029 FED CC	M Well Number:	137H	Show Final Text
Well Type: OIL WELL	Well Work Typ	e: Drill	
Section 1 - General			
APD ID: 10400043718	Tie to previous NOS? N	Subm	iission Date: 07/16/2019
BLM Office: CARLSBAD	User: Brian Wood	Title: Presid	lent
Federal/Indian APD: FED	Is the first lease penetrated	for production Fede	eral or Indian? FED
Lease number: NMNM0003677	Lease Acres: 2150.97		
Surface access agreement in place?	Allotted?	eservation:	
Agreement in place? NO	Federal or Indian agreemen	t:	
Agreement number:	·		
Agreement name:			
Keep application confidential? NO			
Permitting Agent? YES	APD Operator: MATADOR P	RODUCTION COMP	ANY
Operator letter of designation:			
Operator Info			
Operator Organization Name: MATADOR	PRODUCTION COMPANY		
Operator Address: 5400 LBJ Freeway, Su	te 1500	7:	
Operator PO Box:		21p : 75240	
Operator City: Dallas State	: TX		
Operator Phone: (972)371-5200			
Operator Internet Address: amonroe@ma	tadorresources.com		
Section 2 - Well Inform	ation		
Well in Master Development Plan? NO	Master Developme	nt Plan name:	
Well in Master SUPO? NO	Master SUPO nam	e:	
Well in Master Drilling Plan? NO	Master Drilling Pla	n name:	
Well Name: LEATHERNECK 3029 FED CO	M Well Number: 137	H Well A	PI Number:
Field/Pool or Exploratory? Field and Pool	Field Name: AVAL	ON Pool N	lame: BONE SPRING
Is the proposed well in an area containing	g other mineral resources? USE	EAST ABLE WATER,NATU	IRAL GAS,OIL

_																			_
Operator Name: MATADOR PRODUCTION COMPANY																			
Wel	l Nan	ne: LE	EATH	ERNE	ЕСК З	8029 F	ED	сом		Well Nu	mber:	137H							
																			J
ls th	e pro	pose	d wel	ll in a	n are	a con	Itaini	ing othe	er mineral	resources	S? USE	EABLE	WATE	R,N	IATURAL	GAS	,OIL		
			•																
Is the proposed well in a Helium production area? N Use Existir										g Well	Pad?	NO	N	ew surfa	ce dis	turba	nce?		
Туре	e of V	Vell P	ad: M	1ULTI	PLE \	WELL			м	ultiple We	ll Pad	Name:		N	u mber: 3	/4			
Well	Clas	s: HC	RIZC	ΝΤΑ	L				LE N	EATHERN	ECK 30 _eas:	029 SL(1	от						
Well	Wor	к Тур	e: Dr	ill					-										
Well	Туре	e: OIL	WEL	.L															
Des	cribe	Well	Туре	:															
Well	sub-	Туре	: INFI	LL															
Dese	cribe	sub-1	ype:																
Dist	ance	to to	vn: 8	Miles	5 .			Distanc	e to neare	est well: 30) FT	I	Distan	ce t	o lease l	i ne : 2	80 FT		
Res	ervoi	r well	spac	ing a	ssigr	ned a	cres	Measur	ement: 31	7.32 Acres	6								
Well	plat:	L	N_13	7H_C	102_	etal_(0715	19_2019	07151540	15.pdf			•						
Well	work	(star	t Date	e: 09/	01/20	19			D	uration: 6	5 DAYS	5							
	6			14/-		4!		Table]					•					
	26	CTIO	13-	vve		cati	on	i adie											
Surv	ey Ty	/pe: F	RECT	ANG	JLAR														
Desc	cribe	Surve	∍у Ту	pe:															
Datu	im: N	AD83							Ve	ertical Dat	um: N/	AVD88							
Surv	ey nι	umbe	Survey number: 25116 Reference Datum:																
1		1	1	r—	r	6				1	1	1	I		1				-
																			duce
		2		2			-	Tract				-			ber				ll produce
lre	ot	licator	ot	dicator			c	VLot/Tract	<u>v</u>	epr			an	/pe	Number	no			s well produce
/ellbore	S-Foot	S Indicator	W-Foot	W Indicator	dsv	ange	ection	liquot/Lot/Tract	atitude	ongitude	ounty	late	eridian	ase Type	sase Number	levation		Q	/ill this well produce
Mellbore	toog-SN 135	NS Indicator	580 EW-Foot	EW Indicator	dsw1	B Range	Section	5 Aliquot/Lot/Tract	ephtitinde 32 54098	- Longitude	County	State	A Meridian	T Lease Type	Lease Number	Elevation	QW	0 TVD	Will this well produce from this lease?
S HL Feg	NS-Foot 132 2	LS Indicator	EW-Foot 580	R Hudicator	dsw1 20S	Range 29E	05 Section	S Aliquot/Lot/Tract	ep Ter 32.54098 43	epuiditinge	A Gunty A DD	IXEM State	Meridian Meridian	거 Lease Type	Lease Number MXWW 2000267	9 858 Elevation	O M O	o TVD	Will this well produce from this lease?
estimation of the second secon	NS-Foot 132 2	NS Indicator	тоо - М - Д 280	EW Indicator	dsw1 20S	Range 29E	05 Section	C Aliquot/Lot/Tract	ep Tatiting 132.54098 43	epnji Guo - 104.1217 353	Artuno EDD Y	State NEW NEW OO	O NAR Meridian	T T Lease Type	NMMM 000367 7	9 Elevation	<u>Пу</u> 0	0 0	Will this well produce from this lease?
estimate of the second	too_J-SN 135 5 164 7	NS Indicator	тоод- 280 53	T H T A EW Indicator	dsm1 20S 20S	egeneration 29E 29E	05 Section 05	ତ ହ ତ ହ Aliquot/Lot/Tract	ep nitite 32.54098 43 32.54098 43	- 104.1217 353 - 104.1217	County FDD Y EDD Y	NEM MAN State	Weridian MEM MEXI CO FIRS T	H Lease Type	Lease Number VMMM VMMNM VMMM VMNM VM0367	923 6 530	 0 856 3	0 853 7	Will this well produce from this lease?
endlipore SHL Leg #1 Leg #1	toou SN 135 5 164 7	NS Indicator	тоо 	T A EW Indicator	dsw1 20S 20S	abugy 29E 29E	00 Section 00 00	c p Aliquot/Lot/Tract	9 nite 32.54098 43 32.54098 43	- 104.1217 353 - 104.1217 353	Atuno EDD Y EDD Y	NEW NEM NAM OO IXAM OO IXAM OO	Meridian MEXI CO FIRS T PRIN	T Lease Type	Lease Number Lease NumM NMMM NMMM 000367 7	223 6 - 530 1	 0 856 3	0 853 7	Will this well produce from this lease?
eJoqlipote SHL Leg #1 PPP	135 5 164 7 165 0	SN FSL FSL	то 	EW Indicator	20S 20S 20S	^{ернеу} 29Е 29Е 29Е	u 30 30 30	Aliquot/Lot/Tract 2 Por 2 PODO 2 POD	9 32.54098 43 32.54098 43 32.54177	- 104.1217 353 - 104.1217 353 - 104.1217 353 - 104.1143	Atunoo EDD Y EDD Y EDD Y	NEW State NEW WEXI CO NEW WEXI	NEW MEXI CO FIRS T PRIN NEW MEXI	표 표 Type	NMNM Page V NMNM 000367 7 NMNM 000367 7 NMNM 095635	U 323 6 - 530 1 - 587	□ 0 856 3 114 00	0 853 7 911	Will this well produce from this lease?

Operator Name: MATADOR PRODUCTION COMPANY

Well Name: LEATHERNECK 3029 FED COM

Well Number: 137H

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
PPP	164	FSL	86	FW	20S	29E	30	Lot	32.54178	-	EDD	NEW	NEW	F	NMNM	-	875	872	
Leg	7			L				3	38	104.1223	Y	MEXI	MEXI		000367	549	7	8	
#1-2										646		co	co		7	2			
EXIT	165	FSL	60	FEL	20S	29E	29	Aliquot	32.54169	-	EDD	NEW	NEW	F	NMNM	-	192	911	
Leg	0							NESE	4	104.0888	Y	MEXI	MEXI		000367	587	65	0	
#1										01		co	co		7	4			
BHL	165	FSL	60	FEL	20S	29E	29	Aliquot	32.54169	-	EDD	NEW	NEW	F	NMNM	-	192	911	
Leg	0							NESE	4	104.0888	Y	MEXI	MEXI		000367	587	65	0	
#1										01		co	co		7	4			







FMSS

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT



03/09/2020

APD ID: 10400043718

Submission Date: 07/16/2019

Highlighted data reflects the most recent changes

Operator Name: MATADOR PRODUCTION COMPANY

Well Name: LEATHERNECK 3029 FED COM

Well Number: 137H

Show Final Text

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Geologic Formations

Formation			True Vertical	Measured			Producing
ID	Formation Name	Elevation	Depth	Depth	Lithologies	Mineral Resources	Formation
498438	RUSTLER	3236	165	165	ANHYDRITE	NONE	N
498437	TOP SALT	2970	265	265	SALT	NONE	N
498439	BASE OF SALT	2444	791	791	SALT	NONE	N
498434	YATES	2370	865	865	OTHER : Cave/Karst	NONE	N
498435	SEVEN RIVERS	1920	1315	1315	OTHER : Cave/Karst	NONE	N
498440	CAPITAN REEF	1845	1390	1390	OTHER : Capitan Aquifer	NONE	N
498436	CHERRY CANYON	250	2985	2985	SANDSTONE	NATURAL GAS, OIL	N
498441	BRUSHY CANYON	-710	3945	3945	SANDSTONE	NATURAL GAS, OIL	N
498442	BONE SPRING LIME	-2390	5625	5625	LIMESTONE	NATURAL GAS, OIL	N
498443	BONE SPRING 1ST	-3508	6743	6743	SANDSTONE	NATURAL GAS, OIL	Y _
498444	BONE SPRING 2ND	-3770	7005	7005	OTHER : Carbonate	NATURAL GAS, OIL	N
498445	BONE SPRING 2ND	-4246	7482	7482	SANDSTONE	NATURAL GAS, OIL	N
498432	BONE SPRING 3RD	-4633	7869	7869	OTHER : Carbonate	NATURAL GAS, OIL	N
498433	BONE SPRING 3RD	-5494	8730	8800	SANDSTONE	NATURAL GAS, OIL	Y

Section 2 - Blowout Prevention

Operator Name: MATADOR PRODUCTION COMPANY

Well Name: LEATHERNECK 3029 FED COM

Well Number: 137H

Pressure Rating (PSI): 5M

Rating Depth: 12000

Equipment: A 12,000' 5000-psi BOP stack consisting of 3 rams with 2 pipe rams, 1 blind ram, and one annular preventer will be utilized below intermediate 1 casing to TD. See attachments for BOP and choke manifold diagrams. An accumulator complying with Onshore Order #2 requirements for the pressure rating of the BOP stack will be present. A rotating head will also be installed as needed.

Requesting Variance? YES

Variance request: Matador requests a variance to have the option of running a multi-bowl wellhead assembly. The BOPs will not be tested again unless any flanges are separated or if the time between the setting of the intermediate casing and reaching within 500' from the top of the Wolfcamp formation exceeds 30 days per the CFO Drilling COAs. Matador requests a variance to drill this well using a co-flex line between the BOP and choke manifold. Certification for proposed co-flex hose is attached. The hose is not required by the manufacturer to be anchored. If the specific hose is not available, then one of equal or higher rating will be used. Matador requests a variance to have the option of batch drilling this well with other wells on the same pad. In the event that this well is batch drilled, the wellbore will be secured with a blind flange of like pressure. When the rig returns to this well and BOPs are installed, the operator will perform a full BOP test. Matador requests a variance for the use of a diverter along with a 2000-psi annular to be installed after running 20" casing. Matador requests the option to cut off 20" SOW wellhead and run 13-3/8" SOW multi-bowl wellhead system once 1st intermediate string is run and cemented. Testing Procedure: BOP will be inspected and operated as required in Onshore Order #2. Kelly cock and sub equipped with a full opening valve sized to fit the drill pipe and collars will be available on the rig floor in the open position. A third party company will test the BOPs. After setting intermediate casing, a minimum 5M BOPE system will be installed. Test pressures will be 250 psi low and 5000 psi high with the annular preventer being tested to 250 psi low and 2500 psi high before drilling below intermediate shoe. In the event that the rig drills multiple wells on the pad and any seal subject to test pressures are broken, a full BOP test will be performed when the rig returns and the 5M BOPE system is re-installed.

Choke Diagram Attachment:

LN_137H_5M_Choke_20190715160257.pdf

BOP Diagram Attachment:

LN_137H_5M_BOP_20190715160307.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	26	20.0	NEW	API	N	0	400	0	400	3236		400	J-55	94	BUTT	1.12 5	1.12 5	DRY	1.8	DRY	1.8
2	INTERMED IATE	17.5	13.375	NEW	API	N	0	1200	0	1200	3236		1200	J-55	54.5	BUTT	1.12 5	1.12 5	DRY	1.8	DRY	1.8
3	INTERMED IATE	12.2 5	9.625	NEW	API	N	0	3100	0	3100	3236		3100	J-55	40	BUTT	1.12 5	1.12 5	DRY	1.8	DRY	1.8
4	PRODUCTI ON	8.75	5.5	NEW	API	N	0	19265	0	9110	3236		19265	P- 110	20	OTHER - DWC/C-IS HT Plus	1.12 5	1.12 5	DRY	1.8	DRY	1.8

Operator Name: MATADOR PRODUCTION COMPANY Well Name: LEATHERNECK 3029 FED COM Well Num	mber: 137H
Casing Attachments	
Casing ID: 1 String Type:SURFACE Inspection Document:	
Spec Document:	
Tapered String Spec:	
Casing Design Assumptions and Worksheet(s):	
LN_137H_casing_design_assumptions_4string_BS_201907	15160338.pdf
Casing ID: 2 String Type:INTERMEDIATE Inspection Document:	
Spec Document:	
Tapered String Spec:	
Casing Design Assumptions and Worksheet(s):	
LN_137H_casing_design_assumptions_4string_BS_201907	15160350.pdf
Casing ID: 3 String Type:INTERMEDIATE Inspection Document: Inspection Document:	
Spec Document:	
Tapered String Spec:	
Casing Design Assumptions and Worksheet(s):	
LN_137H_casing_design_assumptions_4string_BS_201907	15160358.pdf

1

,

Operator Name: MATADOR PRODUCTION COMPANY Well Name: LEATHERNECK 3029 FED COM								ll Numł	ber: 13	37H	
Casing Attachme	ents										
Casing ID:	4	s	String 1	ype :P	RODU	CTION					
Inspection De	ocumer	nt:									
Spec Document:											
Tapered Strir	ng Spec	::									
Casing Desig	n Assu	Imptio	ns and	Work	sheet(:	s):					
LN_137	H_casir	ng_des	ign_as	sumpti	ons_4s	string_E	3S_201	190715	16042	5.pdf	
LN_Slot	34_Cas	sing_Sp	pec_5.6	5in_201	190715	16043	7.PDF				
									1		
Section	4 - Ce	emen	it						a.		
String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	400	0	0	0	0	0	None	None
SURFACE	Tail		0	400	1060	1.35	14.8	1424	100	Class C	5% NaCl + LCM
NTERMEDIATE	Lead	1500	0	1200	640	1.78	13.5	1132	50	Class C	5% NaCl + LCM
NTERMEDIATE	Tail		900	1200	260	1.35	14.8	347	50	Class C	5% NaCl + LCM
NTERMEDIATE	Lead	1500	0	3100	700	1.78	13.5	1254	50	Class C	Bentonite + 1% CaCL2 + 8% NaCl + LCM
NTERMEDIATE	Tail		2480	3100	240	1.35	14.8	325	50	Class C	5% NaCl + LCM
RODUCTION	Lead		1340	1926 5	910	2.22	11.5	2046	25	Class H	Fluid Loss + Dispersant + Retarder + LCM
RODUCTION	Tail		8062	1926 5	2630	1.35	13.2	3548	25	Class H	Fluid Loss + Dispersant + Retarder + LCM

.

.,

Operator Name: MATADOR PRODUCTION COMPANY Well Name: LEATHERNECK 3029 FED COM

Well Number: 137H

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: All necessary mud products for weight addition and fluid loss control will be on location at all times. Mud program subject to change due to hole conditions.

Describe the mud monitoring system utilized: An electronic Pason mud monitoring system complying with Onshore Order #2 will be used.

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (Ibs/gal)	Max Weight (Ibs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	Н	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	400	SPUD MUD	8.4	8.8							
1200	3100	OTHER : Fresh water	8.4	8.6							
3100	1926 5	OTHER : Cut brine/OBM	8.6	9.4							
400	1200	OTHER : Brine water	9.5	10.2							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

A 2-person mud logging program will be used from Kick-off point to TD. No electric logs are planned at this time. GR will be collected through the MWD tools from Intermediate casing to TD. CBL with CCL will be run as far as gravity will let it fall to top of curve.

List of open and cased hole logs run in the well:

CBL,GR

Coring operation description for the well:

No core or drill stem test is planned.

Operator Name: MATADOR PRODUCTION COMPANY **Well Name:** LEATHERNECK 3029 FED COM

Well Number: 137H

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 4453

Anticipated Surface Pressure: 2448.8

Anticipated Bottom Hole Temperature(F): 155

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geoharzards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

LN_Slot34_H2S_Plan_wMaps_20190715160608.pdf

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

LN_137H_horizontal_plan_20190715160751.pdf

Other proposed operations facets description:

Other proposed operations facets attachment:

LN_Slot34_full_wellhead_3string_20190715160758.pdf LN_137H_CoFlex_Certs_20190715160815.pdf LN_137H_20in_20.75_3M_SOW_20190715160823.pdf LN_137H_Anti_Collision_Report_20190715160830.pdf LN_137H_Drill_Plan_Revised_20200103103657.pdf

Other Variance attachment:

LN_137H_DVT_Tool_Variance_Request_20190715160643.pdf



λ	Exhibit E-1: BOP	
	JTI pntrol	RIG: 297
	Made by Cameron (Shaffer Spherical) Clone Annular	PATTERSON-UTI # PS2-628 STYLE: New Shaffer Spherical BORE 13 5/8" PRESSURE 5,000 HEIGHT: 48 ½" WEIGHT: 13,800 lbs PATTERSON-UTI # PC2-128 STYLE: New Cameron Type U BORE 13 5/8" PRESSURE 10,000 RAMS: TOP 5" Pipe BTM Blinds HEIGHT: 66 5/8" WEIGHT: 24,000 lbs
		Length40Outlets4" 10M DSA4" 10M x 2" 10M PATTERSON-UTI #PC2-228 STYLE:New Cameron Type U BORE13 5/8" PRESSURE10,000 RAMS:5" Pipe HEIGHT: _41 5/8" WEIGHT:13,000 lbs
	WING VALVES	
2" Check Valve 2" Manual Valve	2" Manual Valve	4" Manual Valve 4" Hydraulic Valve

Casing Design Criteria and Load Case Assumptions

Surface Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.43 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and an internal force equal to mud gradient of displacement fluid (0.52 psi/ft).

Burst: DF_b=1.125

 Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud gradient in which the casing will be run (0.43 psi/ft), which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (8.3 ppg).

Intermediate #1 Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.52 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft).

Burst: DF_b=1.125

- Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud gradient in which the casing will be run (0.52 psi/ft), which is a more conservative backup force than pore pressure.
- Gas Kick Profile: Internal burst force at the shoe will be Fracture Pressure at that depth. Surface burst
 pressure will be fracture gradient at setting depth less a gas gradient to equivalent height of 50 bbl kick
 with Drill Pipe inside casing and mud gradient with which the next hole section will be run above that
 (0.47 psi/ft). External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft),
 which is a more conservative backup force than pore pressure.
- Fracture at Shoe with 1/3 BHP at Surface: Internal burst force at the shoe will be Fracture Pressure at setting depth. Internal burst force at surface will be 1/3 of pore pressure at setting depth. External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft) which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (10.0 ppg).

Intermediate #2 Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.52 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned depths and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft).

Burst: DF_b=1.125

- Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud gradient in which the casing will be run (0.52 psi/ft), which is a more conservative backup force than pore pressure.
- Gas Kick Profile: Internal burst force at the shoe will be Fracture Pressure at that depth. Surface burst
 pressure will be fracture gradient at setting depth less a gas gradient to equivalent height of 50 bbl kick
 with Drill Pipe inside casing and mud gradient with which the next hole section will be run above that
 (0.47 psi/ft). External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft),
 which is a more conservative backup force than pore pressure.
- Fracture at Shoe with 1/3 BHP at Surface: Internal burst force at the shoe will be Fracture Pressure at setting depth. Internal burst force at surface will be 1/3 of pore pressure at setting depth. External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft) which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (8.4 ppg).

Production Casing

Collapse: DF_c=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.47 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and mud
 gradient in which the casing will be run above that (0.47 psi/ft) and an internal force equal to mud gradient
 of displacement fluid (0.43 psi/ft).

Burst: DF_b=1.125

- Pressure Test: 8000 psi casing test with an external force equal to the mud gradient in which the casing will be run (0.47 psi/ft), which is a more conservative backup force than pore pressure.
- Injection Down Casing: 9500 psi surface injection pressure plus an internal pressure gradient of 0.65 psi/ft with an external force equal to the mud gradient in which the casing will be run (0.47 psi/ft), which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (9.0 ppg).

Casing Design Criteria and Load Case Assumptions

Surface Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.43 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned depths and an internal force equal to mud gradient of displacement fluid (0,52 psi/ft).

Burst: DF_b=1.125

 Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud gradient in which the casing will be run (0.43 psi/ft), which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (8.3 ppg).

Intermediate #1 Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.52 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft).

Burst: DF_b=1.125

- Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud gradient in which the casing will be run (0.52 psi/ft), which is a more conservative backup force than pore pressure.
- Gas Kick Profile: Internal burst force at the shoe will be Fracture Pressure at that depth. Surface burst
 pressure will be fracture gradient at setting depth less a gas gradient to equivalent height of 50 bbl kick
 with Drill Pipe inside casing and mud gradient with which the next hole section will be run above that
 (0.47 psi/ft). External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft),
 which is a more conservative backup force than pore pressure.
- Fracture at Shoe with 1/3 BHP at Surface: Internal burst force at the shoe will be Fracture Pressure at setting depth. Internal burst force at surface will be 1/3 of pore pressure at setting depth. External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft) which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (10.0 ppg).

Intermediate #2 Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.52 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned depths and an internal force equal to mud gradient of displacement fluid (0,43 psi/ft).

Burst: DF_b=1.125

- Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud
 gradient in which the casing will be run (0.52 psi/ft), which is a more conservative backup force than pore
 pressure.
- Gas Kick Profile: Internal burst force at the shoe will be Fracture Pressure at that depth. Surface burst pressure will be fracture gradient at setting depth less a gas gradient to equivalent height of 50 bbl kick with Drill Pipe inside casing and mud gradient with which the next hole section will be run above that (0.47 psi/ft). External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft), which is a more conservative backup force than pore pressure.
- Fracture at Shoe with 1/3 BHP at Surface: Internal burst force at the shoe will be Fracture Pressure at setting depth. Internal burst force at surface will be 1/3 of pore pressure at setting depth. External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft) which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (8.4 ppg).

Production Casing

Collapse: DF_c=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.47 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and mud gradient in which the casing will be run above that (0.47 psi/ft) and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft).

Burst: DF_b=1.125

- Pressure Test: 8000 psi casing test with an external force equal to the mud gradient in which the casing will be run (0.47 psi/ft), which is a more conservative backup force than pore pressure.
- Injection Down Casing: 9500 psi surface injection pressure plus an internal pressure gradient of 0.65 psi/ft with an external force equal to the mud gradient in which the casing will be run (0.47 psi/ft), which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

 Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (9.0 ppg).

Casing Design Criteria and Load Case Assumptions

Surface Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.43 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and an internal force equal to mud gradient of displacement fluid (0 52 psi/ft).

Burst: DFb=1.125

 Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud gradient in which the casing will be run (0.43 psi/ft), which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (8.3 ppg).

Intermediate #1 Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.52 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and an internal force equal to mud gradient of displacement fluid (0,43 psi/ft).

Burst: DF_b=1.125

- Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud gradient in which the casing will be run (0.52 psi/ft), which is a more conservative backup force than pore pressure.
- Gas Kick Profile: Internal burst force at the shoe will be Fracture Pressure at that depth. Surface burst
 pressure will be fracture gradient at setting depth less a gas gradient to equivalent height of 50 bbl kick
 with Drill Pipe inside casing and mud gradient with which the next hole section will be run above that
 (0.47 psi/ft). External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft),
 which is a more conservative backup force than pore pressure.
- Fracture at Shoe with 1/3 BHP at Surface: Internal burst force at the shoe will be Fracture Pressure at setting depth. Internal burst force at surface will be 1/3 of pore pressure at setting depth. External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft) which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (10.0 ppg).

Intermediate #2 Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.52 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and an internal force equal to mud gradient of displacement fluid (0,43 psi/ft).

Burst: DFb=1.125

- Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud gradient in which the casing will be run (0.52 psi/ft), which is a more conservative backup force than pore pressure.
- Gas Kick Profile: Internal burst force at the shoe will be Fracture Pressure at that depth. Surface burst pressure will be fracture gradient at setting depth less a gas gradient to equivalent height of 50 bbl kick with Drill Pipe inside casing and mud gradient with which the next hole section will be run above that (0.47 psi/ft). External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft), which is a more conservative backup force than pore pressure.
- Fracture at Shoe with 1/3 BHP at Surface: Internal burst force at the shoe will be Fracture Pressure at setting depth. Internal burst force at surface will be 1/3 of pore pressure at setting depth. External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft) which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (8.4 ppg).

Production Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.47 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and mud gradient in which the casing will be run above that (0.47 psi/ft) and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft).

Burst: DF_b=1.125

- Pressure Test: 8000 psi casing test with an external force equal to the mud gradient in which the casing will be run (0.47 psi/ft), which is a more conservative backup force than pore pressure.
- Injection Down Casing: 9500 psi surface injection pressure plus an internal pressure gradient of 0.65 psi/ft with an external force equal to the mud gradient in which the casing will be run (0.47 psi/ft), which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (9.0 ppg).

Casing Design Criteria and Load Case Assumptions

Surface Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.43 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and an internal force equal to mud gradient of displacement fluid (0.52 psi/ft).

Burst: DF_b=1.125

 Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud gradient in which the casing will be run (0.43 psi/ft), which pressure.

Tensile: DFt=1.8

 Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (8.3 ppg).

Intermediate #1 Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.52 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft).

Burst: DF_b=1.125

- Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud
 gradient in which the casing will be run (0.52 psi/ft), which is a more conservative backup force than pore
 pressure.
- Gas Kick Profile: Internal burst force at the shoe will be Fracture Pressure at that depth. Surface burst
 pressure will be fracture gradient at setting depth less a gas gradient to equivalent height of 50 bbl kick
 with Drill Pipe inside casing and mud gradient with which the next hole section will be run above that
 (0.47 psi/ft). External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft),
 which is a more conservative backup force than pore pressure.
- Fracture at Shoe with 1/3 BHP at Surface: Internal burst force at the shoe will be Fracture Pressure at setting depth. Internal burst force at surface will be 1/3 of pore pressure at setting depth. External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft) which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (10.0 ppg).

Intermediate #2 Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.52 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and an internal force equal to mud gradient of displacement fluid (0.43 psi/ft).

Burst: DF_b=1.125

- Pressure Test: Casing test per Onshore Oil and Gas Order No. 2 with an external force equal to the mud gradient in which the casing will be run (0.52 psi/ft), which is a more conservative backup force than pore pressure.
- Gas Kick Profile: Internal burst force at the shoe will be Fracture Pressure at that depth. Surface burst pressure will be fracture gradient at setting depth less a gas gradient to equivalent height of 50 bbl kick with Drill Pipe inside casing and mud gradient with which the next hole section will be run above that (0.47 psi/ft). External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft), which is a more conservative backup force than pore pressure.
- Fracture at Shoe with 1/3 BHP at Surface: Internal burst force at the shoe will be Fracture Pressure at setting depth. Internal burst force at surface will be 1/3 of pore pressure at setting depth. External force will be equal to the mud gradient in which the casing will be run (0.52 psi/ft) which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (8.4 ppg).

Production Casing

Collapse: DFc=1.125

- Full Internal Evacuation: Collapse force equal to the mud gradient in which the casing will be run (0.47 psi/ft). The effects of axial load on collapse will be considered.
- Cementing: Collapse force equal to the gradient of planned cement slurries to planned depths and mud
 gradient in which the casing will be run above that (0.47 psi/ft) and an internal force equal to mud gradient
 of displacement fluid (0.43 psi/ft).

Burst: DF_b=1.125

- Pressure Test: 8000 psi casing test with an external force equal to the mud gradient in which the casing will be run (0.47 psi/ft), which is a more conservative backup force than pore pressure.
- Injection Down Casing: 9500 psi surface injection pressure plus an internal pressure gradient of 0.65 psi/ft with an external force equal to the mud gradient in which the casing will be run (0.47 psi/ft), which is a more conservative backup force than pore pressure.

Tensile: DFt=1.8

• Overpull: A downward force of 100,000 lbs is applied at the shoe along with the weight of the casing string utilizing the effects of buoyancy (9.0 ppg).

Hydrogen Sulfide Drilling Operations Plan Matador Resources

1 H2S safety instructions to the following:

- Characteristics of H2S
- Physical effects and hazards
- Principal and operation of H2S detectors, warning system and briefing areas
- Evacuation procedures, routes and first aid
- Proper use of safety equipment & life support systems
- Essential personnel meeting medical evaluation criteria will receive additional training on the proper use of 30min pressure demand air packs

2 H2S Detection and Alarm Systems:

- H2S sensor/detectors to be located on the drilling rig floor, in the base of the sub structure / cellar area, on the mud pits in the shale shaker area. Additional H2S detectors may be placed as deemed necessary
- An audio alarm system will be installed on the derrick floor and in the doghouse

3 Windsocks and / Wind Streamers:

- Windsocks at mud pit area should be high enough to be visible
- Windsock on the rig floor and / top of doghouse should be high enough to be visible

4 Condition Flags and Signs:

- Warning sign on access road to location
- Flags to be displayed on sign at entrance to location
 - Green Flag Normal Safe Operation Condition
 - Yellow Flag Potential Pressure and Danger
 - Red Flag Danger (H2S present in dangerous concentrations) Only H2S trained personnel admitted on location

5 Well Control Equipment:

• See Exhibit E-1

6 Communication:

- While working under masks chalkboards will be used for communications
- Hand signals will be used where chalk board is inappropriate
- Two way radio will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at most drilling foreman's trailer or living quarters.

- 7 Drilling Stem Testing:
 - No DST cores are planned at this time

8 Drilling contractor supervisor will be required to be familiar with the effects H2S has on tubulars good and other mechanical equipment

9 If H2S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H2S scavengers if necessary

11 Emergency Contacts

• See exhibit E-6

MRC ENERGY CO.'S

HYDROGEN SULFIDE CONTINGENCY PLAN Drilling, Testing, & Completion

MRC ENERGY CO.

Reviewers

------ Operations Manager ------ Operations Supt. ------ Staff RES ------ Field Supt. Blake Hermes---Engineering

H2S Contingency Plan # 0165

Revision#0

This H2S Contingency Plan is subject to updating

Effective date: July 8, 2015

MRC ENERGY CO.'S

TABLE OF CONTENTS

I.	INTRODUCTION	3
II.	PURPOSE	4
	A. Operating Procedures	5
	B. Procedures to be Initiated Prior to	reaching 6
	H2S Contingency Plan Compliance	e
	C. Drilling Below Contingency Plan	Depth 7
	D. Procedures program	7
III.	CONDITIONS & H2S EMERGENCY PI	ROCEDURES 10
	A. Definition of Operational "Condit	ions" 10
	B. H2S Emergency Procedures; In Se	cope Personnel 12
	C. Instructions for Igniting the Well	16
	D. Coring	17
	E. Normal Operations	<u> </u>
IV.	SAFETY EQUIPMENT	21
V.	TOXICITY OF VARIOUS GASES	23
VI.	PROPERTIES OF GASES	24
VII.	TREATMENT PROCEDURES FOR H2	S POISONING 25
VIII.	BREATHING AIR EQUIPMENT DRIL	LS ON/OFF DUTY 26
IX.	HYDROGEN SULFIDE TRAINING CU	RRICULUM 27
Χ.	FIT TEST	29
XI.	H2S EQUIPMENT LIST	30
XII.	EMERGENCY PHONE NUMBERS	32
XIII.	EVACUATION OF GENERAL PUBLIC	37
XIV.	SEPCO EMERGENCY PHONE NUMB DIRECTIONS TO WELL SITE	ERS AND 38
XV.	ROE MAP (RADIUS OF EXPOSURE)	39
XVI.	RESIDENCE LIST WITHIN ROE	40

INTRODUCTION

The H2S equipment will be rigged up 2 days prior to reaching a potential H2S containing zone. Drilling into any potential H2S zone shall not commence until the on-site MRC Drilling Supervisor has confirmed this plan in place.

The onsite Drilling Foreman will give Total Safety one week (7 days) notice to prepare for rig up of H2S equipment)

To be effective, the plan requires the cooperation and effort of each person participating in the drilling of an H_2S well. Each person must know his/her responsibilities and all emergency and safety procedures. He/she should thoroughly understand and be able to use with accuracy, all safety equipment while performing his/her normal duties, if the circumstance should arise. He/she should therefore familiarize himself/herself with the location of all safety equipment and check to see that it is properly stored, easily accessible at all times, and routinely maintained.

It is the intention of MRC ENERGY CO. and the Drilling Contractor to make every effort to provide adequate safeguards against harm to persons on the rig and in the immediate vicinity from the effects of hydrogen sulfide, which may be released into the atmosphere under emergency conditions. However, the initiative rests with the individual in utilizing the safeguards provided. The ideas and suggestions of the individuals involved in the drilling of this well are highly welcomed and act as a fundamental tool for providing the safest working conditions possible.

The drilling representative is required to enforce these procedures. They are set up for your safety and the safety of all others.

II. PURPOSE

It is MRC Energy Co.'s intent to provide a safe working place, not only for its employees, but also for other contractors who are aiding in the drilling of this well. The safety of the general public is of utmost concern. All precautions will be taken to keep a safe working environment and protect the public.

There is a possibility of encountering toxic hydrogen sulfide gas. Safety procedures must be adhered to in order to protect all personnel connected with the operations as well as people living within the area.

The MRC Energy Co. representative will enforce all aspects of the H2S Contingency Plan. This job will become easier by a careful study of the following pages and training and informing all personnel that will be working on responsibilities.

A. OPERATING PROCEDURES

DEFINITIONS:

For purpose of this plan, on-site personnel shall be referred to as "In Scope Personnel" or "Out of Scope Personnel", per the following definitions:

In Scope Personnel – Personnel who will be working or otherwise present in potential H2S release areas, including the rig floor, cellar, pits, and shaker areas.

Out of Scope Personnel – Personnel who will not be working or Otherwise present in potential H2S areas. Such personnel include rig Site visitor, delivery and camp services personnel.

GENERAL:

Before this H_2S contingency plan becomes operational, all regularly assigned In Scope Personnel (primarily the MRC, drilling contractor, and certain service personnel,) shall be thoroughly trained in the use of breathing equipment, emergency procedures, and responsibilities. Total Safety Technician or a designee assigned by the MRC Drilling Foreman shall keep a list of all personnel who have been through the on-site H_2S training program at the drill site.

All In Scope Personnel shall be given H2S training and the steps to be taken during H2S conditions under which the well may be drilled. General information will be explained about toxic gases, as well as the physiological effects of H_2S and the various classified operating conditions. In addition, the reader will be informed his/her general responsibility concerning safety equipment and emergency procedures.

The Total Safety H₂S Safety Technician or MRC on-site RSE Technician shall make available the H2S Contingency Plan for all personnel to review.

Without exception, all personnel that arrive on location must proceed directly to and sign-in with the on-site MRC RSE Technician. In Scope Personnel will be required to complete an on-site H2S training and respirator fit testing before starting work, or produce evidence that they have received equivalent training. Out of Scope Personnel will be required to complete a site H2S awareness and general safety briefing. This briefing will consist of a H2S hazard overview, alarm review and required response to alarms.

B. PROCEDURES TO BE INITIATED PRIOR TO H2S CONTINGENCY PLAN COMPLIANCE:

A list of emergency phone numbers and contacts will be on location and posted at the following locations:

- 1. MRC ENERGY CO.'S Representative's Office
- 2. Drilling Contractor's, Toolpusher Office
- 3. Living Quarters Area

All safety equipment and H₂S related hardware must be set up as required by MRC Energy Co. with regard to location of briefing areas, breathing equipment, etc. All safety equipment must be inspected periodically (at least weekly) with particular attention to resuscitators and breathing equipment.

In Scope Personnel working in the well site area will be assigned breathing apparatus. Operator and drilling contractor personnel required to work in the following areas will be provided with Self Contained Breathing Apparatus:

- 1. Rig Floor
- 2. Mud Pits
- 3. Derrick
- 4. Shale Shaker
- 5. Cellar

The Total Safety H_2S Safety Technician will be responsible for rigging up all H_2S continuous monitoring-type detectors. The Total Safety Technician will monitor and bump test the detector units periodically (at least at least once a week to test alarm function during drilling conditions. In the event H_2S is detected, or when contain H_2S , the units shall be bump tested at least once every 24 hours. A bump test/calibration log will be kept on location. All results will be reported to the MRC on-site Drilling Foreman.

All Total Safety H2S equipment will be maintained and inspected by a Total Safety Technician on at least a Weekly basis.

C. DRILLING BELOW CONTINGENCY PLAN DEPTH

H2S response drills will be held at least once per week if possible or as often as necessary to acquaint the crews and service company personnel of their responsibilities and the proper procedures to shut-in a well. Initial drills will be performed until crews demonstrate competency donning and working under mask. After the MRC Energy Co.'s representative is satisfied with initial blowout drill procedures, a drill will be conducted weekly with each crew, as necessary. The H2S Safety Technician or designee will conduct safety talks and maintain the safety equipment, consult and carry out the instructions of the drilling supervisor. All personnel allowed in the well work area during drilling or testing operations will be instructed in the use of breathing equipment until supervisory personnel are satisfied that they are capable of using it.

After familiarization, each person must perform a drill with breathing equipment. The drill should include getting the breathing equipment, donning the breathing apparatus, and performing expected duties for a short period. A record shall be kept of all personnel drilled and the date of the drill. H2S training records will be kept on location for all personnel.

Rig crews and service company personnel shall be made aware of the location of spare air bottles, resuscitation equipment, portable fire extinguishers, H_2S monitors and detectors. Knowledge of the location of the H_2S monitors and detectors are vital in determining as our gas location and the severity of the emergency conditions.

After any device has initially detected H2S, all areas of poor ventilation shall be inspected periodically by means of a portable H_2S detector instrument. The buddy system will be utilized. (When an alarm sounds, personnel will don an SCBA, shut the well in, and proceed to SBA for roll call. The H2S Technician or designee will mask up, with a buddy and will verify source of H2S and report back to the on-site MRC Foreman.)

D. PROCEDURES PROGRAM

- 1. Drill Site
 - a. The drilling rig will be located to allow prevailing winds to blow across the reserve pit.
 - b. A Safe Briefing Area will be provided with a breathing air cascade trailer and or 30-minute SCBA's at the Primary Area. Personnel will assemble at the most up-wind station under alarm conditions, or when so ordered by the MRC Energy Co. representative, the Contractor representative, or
the Total Safety H₂S Safety Technician. Windsocks or streamers will be anchored to various strategic places on a pole about 10 feet high, so it is in easy view from the rig floor at all times.

- c. Warning signs will be posted on the perimeters. "No Smoking" signs will be posted by MRC Energy Co.as well.
- d. One multi-channel automatic H₂S monitor will be provided by Total Safety and the detector heads will be at the shale shaker, bell nipple, mud pits, rig floor, and quarter's area. The monitor will be located inside HSE or Company man trailer. Should the alarm be shut off to silence the sirens, the blinker light must continue to warn of H₂S presence. The Total Safety H2S Safety Technician or designee will continuously monitor the detectors and will reactivate the alarm if H₂S concentrations increase to a dangerous level.
- e. A method of escape will be open at all times.
- f. If available, land line telephone service will be provided or cell phones provided. (Primary communications provided)
- g. A rig communication system will be provided, as needed.
- h. A gas trap, choke manifold, and degasser will be installed.
- i. A kill line, securely anchored and of ample strength, will be laid to the well-head from a safe location. This line is to be used only in an emergency.

General

- a. The MRC Energy Co. representative and/or the Contractor's Toolpusher will be available at all times. The drilling supervisor, while on duty, will have complete charge of the rig and location operations and will take whatever action is deemed necessary to insure personnel safety, to protect the well, and to prevent damage.
 - A Mud Engineer will be on location at all times when drilling takes place at the depth H₂S may be expected. The mud engineer will be able to verify the presence or absence of H2S.

III. CONDITIONS AND EMERGENCY PROCEDURES A. DEFINITION OF OPERATIONAL "CONDITIONS"

CONDITION I Warning Flags Alarms	"POSS	SIBLE I Green No Ala	DANGER" rm. Less than 10 ppm
Characterized By:		Drilling contain remain it becon	g operations in zones that may hydrogen sulfide. This condition s in effect unless H ₂ S is detected and mes necessary to go to Condition II.
General Action:		a.	Be alert for a condition change
		b.	Check all safety equipment for availability and proper functioning.
		c.	Perform all drills for familiarization and proficiency.
CONDITION II Warning Flags	"MOE	DERAT Yellow	E DANGER"
Alarms:		Actuate light.	es at 10 ppm. Continuous flashing
Characterized By:		Drilling hydrog remain the mu sulfide Condit	g operations in zones containing en sulfide. This condition will in effect until adding chemicals to d system neutralizes the hydrogen or it becomes necessary to go to ion III.
General Action:		a.	Be alert for a condition change
		b.	WHEN DRILLING AHEAD - Driller and designated crewmember will don 30 min SCBA, shut-in the well and immediately proceed to the Safe Briefing Area.
			WHEN TRIPPING – Driller and two designated crewmembers will don 30 min SCBA, shut in the well and immediately proceed to the Safe Briefing Area. The Derrickman will

don a 5-minute escape pack, descend to the rig floor, don a 30-min SCBA (if necessary) and immediately proceed to the Safe Briefing Area.

- c. All In Scope Personnel will proceed directly to the appropriate Safe Briefing Area.
- d. Remain in safe briefing area, take roll call and wait for instructions
- e. Contact the Total H2S Technician if not on location.
 - Personnel shall ensure that their breathing apparatus is properly fitted and operational before entering an H₂S contaminated area to provide assistance to anyone who may be injured or overcome by toxic gases.
- g. All Out of Scope Personnel will report to the appropriate Safe Briefing Area.

CONDITION III Warning Flags

Characterized by:

General Action:

Alarms

"EXTREME DANGER" Red

f.

Actuate at 15 ppm. Continuous Sirens and Flashing Lights

Critical well operations which pose an immediate threat of H₂S exposure to on-site personnel and a potential threat to the public.

a. WHEN DRILLING AHEAD -Driller and designated crewmember will don 30 min SCBA, shut-in the well and immediately proceed to the Safe Briefing Area.

WHEN TRIPPING – Driller and two designated crewmembers will don 30

min SCBA, shut in the well and immediately proceed to the Safe Briefing Area. The Derrickman will don a 5-minute escape pack, descend to the rig floor, don a 30-min SCBA (if necessary) and immediately proceed to the Safe Briefing Area.

- All In Scope Personnel should don SCBA if nearby and immediately proceed to Safe Briefing Area. If SCBA in not nearby at time of alarm, DO NOT GO TOWARDS RIG AREA, but proceed directly to the Safe Briefing Area
- c. All out of Scope Personnel shall evacuate the location.
- d. Remain in the Safe Briefing Area, take roll call and wait for instructions.
- e. Contact the Total H2S Technician if not on location.
- f. Personnel shall ensure that their breathing apparatus is properly fitted and operational before entering an H₂S contaminated area to provide assistance to anyone who may be injured or overcome by toxic gases. Use the buddy system.
- g. Remain in safe briefing area, take roll call and wait for instructions.
- h. A cascade breathing air systems shall be mobilized and utilized to conduct any additional on rig work required to correct the H2S release condition.
- i. If well is ignited do not assume area is safe. SO2 is hazardous and not all H2S will burn.
- 13

H₂S EMERGENCY PROCEDURES; IN \$COPE PERSONNEL

A. Day To Day Drilling Operations

- 1. Upon discovering a release of H₂S gas in the ambient air by warning alarms or in any other way **Do Not Panic**.
- 2. Hold your breath donning the nearest Self Contained Breathing Apparatus and rapidly move up or across-wind away from the areas where H₂S sensing devices are in place, to the closest available safe briefing area. Continue to use breathing apparatus until it has been determined that the exposure of H₂S gas in the ambient air no longer exists. **Do Not Panic**!
- 3. Utilize the "Buddy System", i.e.; select and pair up each person participating in the drilling of an H₂S well prior to an emergency situation.
- 4. Help anyone who is overcome or affected by the H₂S gas by taking him/her up-wind out of the contaminated area. (This should be done utilizing an SCBA and with a buddy.)
- 5. Take necessary steps to confirm the release of the H_2S gas into the ambient air.
 - When an H2S alarm activates, two designated personnel using the buddy system, while wearing their self contained breathing apparatus, will determine by the read-out on the fixed monitor which sensing device has detected the release of the H₂S gas.
 - They will utilize the hand held sniffer type device at the particular sensing point disclosed on the fixed monitor to corroborate the fact that H₂S gas has actually been released. This will rule out the possibility of a false alarm. This will be done with a buddy and under mask after reporting to the Safe Briefing Area for roll call and instructions by on-site MRC Foreman.
- 6. Refer to the Emergency Phone Numbers and call emergency personnel.
- 7. Take the necessary steps to suppress the release of H_2S gas into the ambient air. Comply with the MRC Energy Co. Representative to physically suppress the release of H_2S gas at the actual release point.

8. Check all of MRC Energy Co.'s monitoring devices and increase gasmonitoring activities with the portable hand-operated H₂S and gas detector units.

Do Not Panic!

The MRC Energy Co. representative will assess the situation and with assistance of the Contractor's Representative and Total Safety's H₂S Safety Technician or on site designee, will assign duties to each person to bring the situation under control.

B. RESPONSIBILITIES OF WELL-SITE PERSONNEL

In the event of a release of potentially hazardous amounts of H₂S, all personnel will immediately don their protective breathing apparatus, the well will be shut in and personnel will proceed upwind to the nearest designated safe briefing area for roll call and instructions by MRC Foreman. Consideration will be given to evacuating Out of Scope Personnel, as situation warrants.

1. MRC ENERGY CO.'S Well-site Representatives

- a. If MRC Energy Co.'s well-site representative is incapacitated or not on location, this responsibility will fall to the Toolpusher/Driller.
- b. Immediately upon assessing the situation, set this plan into Action by initiating the proper procedures to contain the gas and notify the appropriate people and agencies.
- c. Ensure that the alarm area indicated by the fixed H₂S Monitor is checked and verified with a portable H₂S detector. (Safety Technician if on location or MRC assigned designee with a buddy utilizing SCBA's)
- d. Consult Pusher/driller of remedial actions as needed.
- e. Ensure that non-essential personnel proceed to the safe briefing area.
- f. Ensure location entrance barricades are positioned. Keep the number of persons on location to a minimum during hazardous operations.

- g. Consult each contractor, Service Company and all others allowed to enter the site, that H2S gas may be encountered and the potential hazards that may exist.
- h. Authorize the evacuation of local residents if H₂S threatens Their safety.
 - i. Non essential personnel should be evacuated from location if Situation warrants.

2. Toolpusher

a. Toolpusher/Driller will assume responsibilities of MRC Energy Co.'s well-site representative if that person is incapacitated or not on location.

Ensure that the alarm area indicated by the fixed H₂S monitor is checked and verified with a portable H₂S gas detector. (Alarm area indicated by the monitor will be Checked by the H2S Technician and a buddy, under mask.) This will be done after checking in and roll call at the Upwind Safe Briefing Area.

- c. Confer with MRC Energy Co.'s well-site representative or superintendent and direct remedial action to suppress the H_2S and control the well.
- d. Ensure that personnel at the safe briefing area are instructed on emergency actions required.
- e. Ensure that personnel at the drill floor area are instructed on emergency actions required.
- f. Ensure that all personnel observe the appropriate safety and emergency procedures.
- g. Ensure that all persons are accounted for and provided emergency assistance as necessary.

3. Mud Engineer

- a. Run a sulfide check on the flowline mud.
- b. Take steps to determine the source of the H_2S and suppress it. Lime and H_2S scavenger shall be added to the mud as necessary.

4. Total H₂S Safety Technician, if on location, or MRC Designee

- a. H2S Safety Technician or designee don nearest SCBA and report to Safe Briefing Area for roll call, take a buddy masked up and check monitor and verify with a portable H₂S detector the alarm area indicated by the fixed H₂S monitor. Advise the Toolpusher/Driller and MRC Energy Co.'s well-site representative of findings. Record all findings.
- b. If H₂S is flared, check for sulfur dioxide (SO₂) near the flare as necessary. Take hourly readings at different perimeters, log readings and record on location.
- c. Ensure that personnel at the safe briefing area are instructed on emergency actions required.
- d. Ensure that the appropriate warning flags are displayed.
- e. Ensure that all personnel are in S.C.B.A. as necessary.
- f. Ensure that all persons are accounted for and provide emergency assistance as necessary.
- g. Be prepared to evacuate rig if order is issued.

5. General Personnel & Visitors

a. All In Scope Personnel, if not specifically designated to shut the well in or control the well, shall proceed to the (upwind) safe briefing area. All Out of Scope Personnel shall immediately proceed to the appropriate (upwind) safe briefing area or evacuate the site as conditions warrant.

- b. During any emergency, use the "buddy" system to prevent anyone from entering or being left in a gas area alone, even wearing breathing apparatus.
- c. Provide assistance to anyone who may be injured or overcome by toxic gases. Personnel shall ensure that their breathing apparatus is properly fitted and operational before entering a potentially H₂S contaminated area.
- d. Remain in safe briefing area and wait for instructions.

C. INSTRUCTIONS FOR IGNITING THE WELL

1. The Toolpusher/Driller will confer with MRC Energy Co.'s wellsite representative who will secure the approval of the "Texas Wells Delivery Manager, prior to igniting the well, if at all possible.

> The Toolpusher/Driller will be responsible for igniting the well in the event of severe well control problems. This decision should be made only as a last resort in situations where it is clear that:

- a. Human life and property are endangered, or
- b. There is no hope of controlling the well under current conditions.
- 2. Once the decision has been made, the following procedures should be followed:
 - a. Two people wearing self-contained breathing apparatus will be needed for the actual lighting of the well. They must first establish the flammable perimeter by using an explosimeter. This should be established at 30% to 40% of the lower flammable limits.
 - b. After the flammable perimeter has been established and everyone removed from the area, the ignition team should select a site upwind of the well from which to ignite the well. This site should offer the maximum protection and have a clear path for retreat from the area.

c.

- The ignition team should have safety belts and lifeline attached and manned before attempting ignition. If the leak is not ignited on the first attempt, move in 20 to 30 feet and fire again. Continue to monitor with the explosimeter and NEVER fire from an area with over 75% of the Lower Explosive Limit (LEL). If having trouble igniting the well, try firing 40 degrees to 90 degrees on either side of the well.
- d. If ignition is not possible due to the makeup of the gas, the toxic perimeter must be established and evacuation continued until the well is contained.

e. All personnel must act only as directed by the person in charge of the operations.

NOTE: After the well is ignited, burning hydrogen sulfide (H_2S) will convert to sulfur dioxide (SO_2) , which is also a highly toxic gas.

DO NOT ASSUME THE AREA IS SAFE AFTER THE WELL IS IGNITED

D. CORING PROCEDURES

Only essential personnel shall be on the rig floor. Ten (10) stands prior to retrieving core barrel; all personnel on drill floor and in derrick shall confirm self-Contained breathing apparatus available and ready for use.

A Total H2S Technician will don a SCBA with a buddy assigned from the rig crew, and continuously monitor for H2S at each connection. Any levels detected will require operations to be shut down and all involved personnel to don SCBAs. Precautions will remain in place until barrel is laid down.

All involved personnel will don SCBAs when removing the inner barrel from the outer barrel. SCBAs can be removed once the absence of H2S in confirmed by the Total H2S Technician.

Cores will be appropriately marked and sealed for transportation.

Normal Operations

1. Responsibilities of well-site personnel a. Well-site Representative

- 1. Notify H₂S Technician of expected date to reach Contingency Plan implementation depth (Two (2) days prior to reaching suspected H₂S bearing zone) or prior to starting well work.
- 2. Ensure H₂S Safety Technician completes rig-up procedures prior to reaching Contingency Plan effective depth.
- 3. Restrict the number of personnel at the drilling rig or well site to a minimum while drilling, starting well work, testing or coring.
- 4. Ensure weekly H₂S drills/training are performed, if possible.

B. Toolpusher

- 1. Ensure that necessary H_2S safety equipment is provided on the rig, and that it is properly inspected and maintained.
- 2. Ensure that all personnel that work in the well area, are thoroughly trained in the use of H₂S safety equipment and periodic drills are held to maintain an adequate level of proficiency.

C. In Scope Personnel

- 1. Remain clean-shaven. Beards and long sideburns do not allow a proper facepiece seal.
- 2. Receive H_2S safety training on location, or confirm prior training by certification that is one year within date.
- 3. Familiarize yourself with the rig's Contingency Plan.
- 4. Inspect and practice putting on your breathing apparatus.

- 5. Know the location of the "safe briefing areas".
- 6. Keep yourself "wind conscious". Be prepared to quickly move upwind and away in the event of any emergency involving release of H₂S.

D. Total Safety H₂S Safety Technician or MRC Designee

- 1. Conduct training as necessary to ensure all personnel working in well area are familiar with the contingency procedures and the operation of emergency equipment.
- 2. Check all H_2S safety equipment to ensure that it is ready for emergency use:
 - Check pressure weekly for each shift on breathing apparatus (both 30-minute and hippacks) to make sure they are charged to full volume.
 - Check pressure on cascade air bottles, if on location, to see that they are capable of recharging breathing apparatus.
 - Check oxygen resuscitator, if on location, to ensure that it is charged to full volume.
 - Check H₂S detectors weekly for each shift (fixed and portable), and explosimeter, to ensure they are working properly.
- 3. Provide a weekly report to MRC Energy Co.'s wellsite representative documenting:
 - Calibrations performed on H₂S detectors.
 - Proper location and working order of H₂S safety equipment.
 - Attendance of all personnel, trained or retrained, and their company.
 - Weekly drills, if held and a list of personnel participating and summary of actions.

OUT OF SCOPE PERSONNEL

MRC Energy Co. policy will not require Out of Scope Personnel to be clean shaven, have processed medical questionnaires, fit testing, or have certified H2S Training.

SAFETY EQUIPMENT

All respirators will be designed, selected, used and maintained in conformance with ANSI Z88.2, American National Standard for respiratory protection.

Personal protective equipment must be provided and used. Those who are expected to use respiratory equipment in case of an emergency will be carefully instructed in the proper use and told why the equipment is being used. Careful attention will be given to the minute details in order to avoid possible misuse of the equipment during periods of extreme stress.

Self-contained breathing apparatus provides complete respiratory and eye protection in any concentration of toxic gases and under any condition of oxygen deficiency. The wearer is independent of the surrounding atmosphere because he/she is breathing with a system admitting no outside air. It consists of a full face mask, breathing tube, pressure demand regulator, air supply cylinder, and harness. Pure breathing air from the supply cylinder flows to the mask automatically through the pressure demand regulator which reduces the pressure to a breathing level. Upon inhalation, air flows into the mask at a rate precisely regulated to the user's demand. Upon exhalation, the flow to the mask stops and the exhaled breath passes through a valve in the face piece to the surrounding atmosphere. The apparatus includes an alarm & gauge which warns the wearer to leave the contaminated area for a new cylinder of air or cylinder refill.

The derrickman is provided with a full face piece unit attached to a 5– minute escape cylinder. He will also have his own self-contained 30-minute unit breathing apparatus located on the drilling floor. He will use the 5-minute unit to exit the derrick to the floor, donning the 30-minute unit located on the floor, if needed.

All respiratory protective equipment, when not in use, should be stored in a clean, cool, dry place, and out of direct sunlight to retard the deterioration of rubber parts. After each use, the mask assembly will be scrubbed with soap and water, rinsed thoroughly, and dried. Air cylinders can be recharged to a full condition from a cascade system.

Personnel in each crew will be trained in the proper techniques of bottle filling.

The primary piece of equipment to be utilized, should anyone be overcome by hydrogen sulfide, is the oxygen resuscitator, if on location.

When asphyxiation occurs, the victim must be moved to fresh air and immediately given artificial respiration. In order to assure readiness, the bottles of oxygen will be checked at regular intervals and an extra tank kept on hand.

Hand-operated pump-type detectors incorporating detector tubes will give more accurate readings of hydrogen sulfide. The pump-type draws air to be tested through the detector tube containing lead acetate-silica gel granules. Presence of hydrogen sulfide in the air sample is shown by the development of a dark brown stain on the granules, which is the

MRC ENERGY CO.'S

scale reading of the concentration of hydrogen sulfide. By changing the type of detector tube used, this detector may also be used for sulfur dioxide (SO_2) detection when hydrogen sulfide (H_2S) is being burned in the flare area.

Provisions must be made for the storage of all safety equipment as is evident from the foregoing discussion. All equipment must be stored in an available location so that anyone engaged in normal work situations is no more than "one breath away' from a mask.

V – TOXICITY OF VARIOUS GASES

	Chemical	Specific			
Lethal Common Name ppm⁴	Formula	Gravity ¹	PEL (O	SHA)²	STEL ³
Hydrogen Cyanide 300	HCN	0.94	10	1	150
Hydrogen Sulfide 600 Note: The ACGIH(7) re	H_2S ecommends a TW	1.18 ′A(6) value of 10	20 opm as the T	Pea FLV(5) for	ak- 50ppm H2S and an STEL of
^{15ppm.} Sulfur Dioxide 1000	SO ₂	2.21	2		5 ppm
Chlorine	CL ₂	2.45	1		
Carbon Monoxide 1000	CO	0.97	35	i	200/1 Hour
Carbon Dioxide 10%	CO2	1.52	50	00	5%
Methane	CH₄	0.55	90	000	

¹ Air = 1.0

² **Permissible -** Concentration at which is believed that all workers may repeatedly be exposed, day after day, without adverse effect.

³ **STEL -** Short Term Exposure Limit. A 15-minute time weighted average.

⁴ Lethal - Concentration that will cause death with short-term exposure.

TLV – Threshold Limit Value; a concentration recommended by the American Conference of Governmental Industrial Hygienists (ACGIH)

TWA – Time Weighted Average; the average concentration of contaminant one can be exposed to over a given eight-hour period.

ACGIH – (American Conference of Governmental Industrial Hygienists) is an organization comprised of Occupational Health Professionals believed by many to be the top experts in the field of Industrial Hygiene. They are recognized as an expert rexource by OSHA. The ACGIH releases a biannual publication "Threshold Limit Values and Biological Indices" that many safety professionals consider to be the authoritative document on airborne contaminants.

Reference: API RP-49, September 1974 - Reissued August 1978

VI. PROPERTIES OF GASES

A. <u>CARBON DIOXIDE</u>

1. Carbon Dioxide (CO₂) is usually considered inert and is commonly used to extinguish fires. It is 1.52 times heavier than air and will concentrate in low areas of still air. Humans cannot breathe air containing more than 10% CO₂ without losing conscience or becoming disorientation in a few minutes. Continued exposure to CO₂ after being affected will cause convulsions, coma, and respiratory failure.

2. The threshold limit of CO_2 is 5000 ppm. Short-term exposure to 50,000 ppm (5%) is reasonable. This gas is colorless, odorless, and can be tolerated in relatively high concentrations.

B. <u>HYDROGEN SULFIDE</u>

1. Hydrogen Sulfide (H₂S) is a colorless, transparent, flammable gas. It is heavier than air and, hence, may accumulate in low places.

2. Although the slightest presence of H_2S in the air is normally detectable by its characteristic "rotten egg" odor, it is dangerous to rely on the odor as a means of detecting excessive concentrations because the sense of smell is rapidly lost, allowing lethal concentrations to be accumulated without warning. The following table indicates the poisonous nature of H_2S .

CONCENTRATION		RATION	EFFECTS
% H ₂ S	PPM	GR/100 SCF1	
0.001	10	.65	Safe for 8 hours without respirator. Obvious and unpleasant odor.
0.0015	15	0.975	Safe for 15 minutes of exposure without respirator.
0.01	100	6.48	Kills smell in 3-15 minutes; may sting eyes and throat.
0.02	200	12.96	Kills smell quickly; stings eyes and throat.
0.05	500	32.96	Dizziness; breathing ceases in a few minutes; need prompt artificial respiration.
0.07	700	45.92	Rapid Unconsciousness; death will result if not rescued promptly
0.1	1000	64.80	Instant unconsciousness, followed by death within minutes.

¹ Grains per 100 Cubic Feet

VII. Treatment Procedures for Hydrogen Sulfide Poisoning

- A. Remove the victim to fresh air.
- B. If breathing has ceased or is labored, begin resuscitation immediately.

Note: This is the quickest and preferred method of clearing victim's lungs of contaminated air; however, under disaster conditions, it may not be practical to move the victim to fresh air. In such instances, where those rendering first aid must continue to wear masks, a resuscitator should be used.

- C. Apply resuscitator to help purge H_2S from the blood stream.
- D. Keep the victim at rest and prevent chilling.
- E. Get victim under physician's care as soon as possible.

C. <u>SULPHUR DIOXIDE</u>

- 1. Sulfur Dioxide (SO₂) is a colorless, non-flammable, transparent gas.
- 2. SO₂ is produced during the burning of H₂S. Although SO₂ is heavier than air, it can be picked up by a breeze and carried downwind at elevated temperatures. Since SO₂ is extremely irritating to the eyes and mucous membranes of the upper respiratory tract, it has exceptionally good warning powers in this respect. The following table indicates the toxic nature of SO₂:

CONCEN	TRATION	EFFECTS
% SO ₂	PPM	
0.0005	3 to 5	Pungent odor, normally a person can detect SO_2 in this range.
0.0012	12	Throat irritation, coughing, constriction of the chest, tearing and smarting of eyes.
0.015	150	So irritating that it can only be endured for a few minutes.
.05	500	Causes a sense of suffocation, event with the first breath.

VIII. BREATHING AIR EQUIPMENT DRILLS FOR ON & OFF DUTY PERSONNEL

An H₂S Drill and Training Session must be given once a week to ALL on-duty personnel with off duty personnel. On-duty and Off-duty personnel will reverse roles on alternate drills.

An H2S drill and training session must be given once a week to all off-duty personnel in coincidence with on-duty personnel reversing roles on alternate drills.

The purpose of this drill is to instruct the crews in the operation and use of breathing air and H_2S related emergency equipment and to allow the personnel to become acquainted with using the equipment under working conditions. The crews should be trained to put on the breathing air equipment within one minute when required or requested to do so.

The following procedure should be used for weekly drills. The MRC supervisor must be satisfied that the crews are proficient with the equipment.

- 1. All personnel should be informed that a drill will be held.
- 2. The Total H2S Safety Technician or a designee assigned by the MRC Drilling Foreman should initiate the drill by signaling as he/she would if H2S was detected.
- 3. Personnel should don their breathing apparatus.
- 4. Once the breathing air equipment is on, the H2S Technician should check all personnel to insure proper operation.

A training and information session will be conducted after each drill to answer any H₂S related questions and to cover any gaps identified from one of the following topics:

- Condition II, and III alerts and steps to be taken by all personnel.
- The importance of wind direction when dealing with H₂S.
- Proper use and storage of all types of breathing equipment.
- Proper use and storage of oxygen resuscitators.
- Proper use and storage of H₂S detectors (Mini Checks or equivalent).
- The "buddy system" and the procedure for rescuing a person overcome by H_2S .
- Responsibilities and duties.
- Location of H₂S safety equipment.
- Other parts of the "H₂S Contingency Plan" that should be reviewed.

NOTE: A record of attendance must be kept for weekly drills and training sessions.

IX. HYDROGEN SULFIDE TRAINING CURRICULUM

(FOR EMPLOYERS, VISITORS, AND CONTRACTORS) EACH PERSON WILL BE INFORMED ON THE RESTRICTIONS OF HAVING BEARDS AND CONTACT LENS. THEY WILL ALSO BE INFORMED OF THE AVAILABILITY OF SPECTACLE KITS.

AFTER THE H2S EQUIPMENT IS RIGGED UP, ALL IN SCOPE PERSONNEL WILL BE H2S TRAINED AND PUT THROUGH A DRILL. ANY DEFICIENCIES WILL BE CORRECTED.

Training Completion cards are good for one year and will indicate date of completion or expiration. Personnel previously trained on another facility and visiting, must attend a "supplemental briefing" on H2S equipment and procedures before beginning duty. Visitors who remain on the location more than 24 hours must receive full H2S training given all crew members. A "supplemental briefing" will include but not be limited to: Location of respirators, familiarization with safe briefing areas, alarms with instruction on responsibilities in the event of a release and hazards of H2S and (SO2, if applicable). A training and drill log will be kept.

Topics for full H2S training shall include the following equipment if on location, but not be limited to the following:

- 1. **Brief Introduction on H2S**
 - A. Slide or Computer presentation (If Available)
 - B. H2S material will be distributed
 - C. Re-emphasize the properties, toxicity, and hazards of H2S
 - D. Source of SO2 (if applicable)
- 2. **H2S Detection**
 - A. Description of H2S sensors
 - B. Description of warning system (how it works & it's location)
 - C. Actual location of H2S sensors
 - D. Instruction on use of pump type detector (Gastec)
 - E. Use of card detectors, ampoules, or dosimeters
 - F. Use of combustible gas detector
 - G. Other personnel detectors used
 - H. Alarm conditions I & II,
 - I. SO2 alarms (if applicable)

3. H2S Protection

- A. Types of breathing apparatus provided (30-minute SCBA & 5-minute SCBA (with voice diaphragms for communication if supplied)
- B. Principle of how breathing apparatus works
- C. Demonstration on how to use breathing apparatus
- D. Location of breathing apparatus

4. Cascade System

- A. Description of cascade system
- B. How system works
- C. Cascade location of rig with reference to briefing areas
- D. How to use cascade system (with 5-minute hose work line units & refill, if supplied)
- E. Importance of wind direction and actual location of Windsocks
- F. Purpose of compressor/function (if one is on site)

5. H2S Rescue and First Aid

- A. Importance of wind direction
- B. Safe briefing area
- C. Buddy system
- D. H2S symptoms
- E. Methods of rescue

6. Hands on Training

- A. Donning/familiarization of SCBA 30-minue unit
- B. Donning/familiarization of SKADA 5- MIN. Packs
- C. Familiarization of cascades
- D. Use of O2 resuscitator
- E. Alarm conditions upwind briefing areas, etc...
- F. Duties and responsibilities of all personnel
- G. Procedures for evacuation
- H. Search and Rescue teams

7. Certification

A. Testing on material covered

TOTAL SAFETY US INC., FIT TEST

X. EMPLOYEE INFORMATION				
Employee Name:			_Date:	
Date of Employee Medical Evalua	tion:			
Medical Status (circle): Unres Authorized	tricted	Limitations	on Use	Use Not
RESPIRATOR INFORMATIOIN				
Respirator Type (Dustmask, SCBA	A, etc):			·
Brand:				
Size: (circle): XS	S	М	L	XL
FIT TEST INFORMATION				
Type of Fit Test Performed:				
Porta Count Fittester 3000			Fit Factor:_ Fit Factor:_	
<u>Qualitative</u> Irritant Smoke Isoamyl Acetate (Ba Saccharin Bitrex	nana Oil)		Passed / Fa Passed / Fa Passed / Fa Passed / Fa	iiled iiled iiled iiled
hereby certify that this fittest was condu rotocols found in Appendix A of 1910.1	icted in acc 34.	cordance wi	th the OSH	A Fit Testing
it Tester Name (Print):				
ignature:	·		_ Date:	
	31			

XI. H₂S SAFETY SERVICES

HYDROGEN SULFIDE SAFETY PACKAGE – Contained on location in Total Safety H2S Equipment Trailer, unless otherwise noted:

RESPIRATORY SAFETY SYSTEMS

QTY DESCRIPTION

- 12 30-Minute Pressure Demand SCBA (4-Primary Safe Briefing Area, 4-Secondary Safe Briefing Area, 4-floor with one of these for derrick man)
- 9 Hose Line 5-minute Work Unit w/Escape Cylinder (1 in derrick, 6 on drill floor, 1 in mud pit wt area, 1 in shaker area)

The following shall be part of the package if requested by the MRC Foremen (at least one trailer with cascade system is required to be located in the MRC Magnolia asset for use as needed)

- 1 Breathing air cascade of 10 bottles w/regulator
- 2 Refill lines to refill 30-minute units on location
- 1 6-Man manifold that can be rigged up to work area on floor, if needed
- 6 25 foot hose lines
- 2 50 foot hose lines
- 100 Feet of hose line to rig cascade up to 12 man manifold on floor
- 12 30-minute Self Contained Breathing apparatus

DETECTION AND ALARM SAFETY SYSTEM

- H2S Fixed Monitor w/8Channels (Loc determined at rig up) suggested.
 (Mud pit area, shaker area, bell nipple area, floor/driller area, & outside quarters)
- 5 H2S Sensors
- 3 Explosion Proof Alarms (Light and Siren)
 - (1 on floor, 1 in work area, 1 in trailer area where quarters are located)
- 2 Personal H2S monitors
- 1 Portable Tri-Gas Hand Held Meter (O2, LEL, H2S)
- 1 Sensidyne/Gastech Manual Pump Type Detector
- 8 Boxes H2S Tubes Various Ranges
- 2 Boxes SO2 Tubes Various Ranges
- 1 Calibration Gas
- 1 Set Paper Work for Records: Training, Cal, Inspection, other

32 、

ADDITIONAL SAFETY RELATED EQUIPMENT

QTY DESCRIPTION

- 2 Windsocks with Pole and Bracket
- 1 Set Well Condition Sign w/Green, Yellow, Red Flags
- 1 Primary Safe Briefing Area Sign
- 1 Secondary Safe Briefing Area Sign
- 6 Operating Condition Signs for Work Areas & Living Quarters

TRAILER WITH BREATHING AIR CASCADE WILL ALSO INCLUDE THE FOLLOWING:

This equipment will be part of the H2S equipment stored in the trailer, when on location

- 1 First aid kit
- 1 Fire Blanket
- 1 Eye wash station
- 2 Safety Harness w/150' safety line

.

XII. EMERGENCY PHONE NUMBERS (Updated March 18, 2009)

EMERGENCY PHONE NUMBERS

MRC Energy Co. Emergency Phone # MRC Energy Co. Permian Operations Phone------MRC Energy Co. Production 113 Daw Rd Mansfield LA 71052

Title	Names	Phone	Cell
Operations Manager			
Operation Supt.			
Operations			
Supervisor			
Operations			
Supervisor			
Office Supervisor			
HSE			
Scheduler Planner			

Hydrogen Sulfide Safety Consultants

	1	
Total Safety W. Bender	575-392-2973	After Hours 24 Hour Call
Blvd. Hobbs, NM		Center Through Office
		Number
Tommy Throckmorton	575-392-2973	940-268-9614
Operations Manager		
Rodney Jourdan Sales	575-392-2973	432-349-3928
Contact		

MRC Energy Co. MEDICAL RESPONSE PLAN AND IT'S MEDICAL PROTOCOLS WILL BE FOLLOWED

MEDICAL COORDINATOR # -----

Emergency Numbers & Directions

Hospitals (911)

Artesia General Hospital		
702 N. 13 th St.	Main Phone Number	575-748-3333
Artesia, NM 88210		
Nor-Lea General Hospital		
1600 N. Main Ave.	Main Phone Number	575-396-6611
Lovington, NM 88260		
Lea Regional Medical		
Center	Main Phone Number	575-492-5260
5419 N. Lovington Hwy		
Hobbs, NM 88240		
Carlsbad General Hospital		
2430 W. Pierce St.	Main Phone Number	575-887-4100
Carlsbad, NM		
Lovelace Regional Hospital		
117 E. 19 th St	Main Phone Number	575-627-7000
Roswell, NM 88201		
Winkler Co. Memorial		
Hospital	Main Phone Number	432-586-8299
821 Jeffee Dr.		
Kermit, Texas 79745		
Reeves County Hospital		
2323 Texas St.	Main Phone Number	432-447-3551
Pecos, Texas 79772		

MRC ENERGY CO.'S

State Police (911)	·	
Texas DPS Loving co.		
225 N.Pecos	Office Number	432-377-2411
Mentone, Texas 79754		
Texas DPS Winkler Co.		
100 E Winkler	Office Number	432-586-3465
Kermit, Texas 79745		
Texas DPS Pecos Co.		
148 N I-20 Frontage RD	Office Number	432-447-3532
Pecos, Texas 79772		
New Mexico State Police		
3300 W. Main St	Office Number	575-748-9718
Artesia, NM		
New Mexico State Police		
304 N. Canyon St	Office Number	575-885-3137
Carlsbad, NM 88220		
New Mexico State Police		
5100 Jack Gomez Blvd.	Office Number	575-392-5588
Hobbs, NM 88240		

Local Law Enforcement (911) (Sheriff)

Reeves Co. Sheriff		
500 N. Oak ST	Office Number	432-445-4901
Pecos, Texas 79722		
Winkler Co. Sheriff		
1300 Bellaire St.	Office Number	432-586-3461
Kermit, Texas 79745		
Loving Co. Sheriff		
Courthouse	Office Number	432-377-2411
Mentone, Texas		
Lea Co. Sheriff		
1417 S. Commercial St.	Office Number	
Lovington, NM 88260		
Eddy Co. Sheriff		
305 N 7th St.	Office Number	575-766-9888
Artesia, NM 88210		
Eddy Co. Sheriff		
305 N 7th St.	Office Number	575-746-9888
Carlsbad, NM 88220		1

Federal & State Agencies

OSHA Lubbock Area Office 1205 Texas Av. Room 806 Lubbock, Texas 79401	Main Number	806-472-7681 EXT 7685
New Mexico Environment Department 400 N Pennsylvania Roswell, NM 88201	Joe Fresquez	575-623-3935
Texas Railroad Commission Midland, Texas	Main Number	844-773-0305
BLM Carlsbad, NM Field Office 620 E. Green ST Carlsbad, NM 88220	Main Number	575-234-5972
BLM Hobbs Field Station 414 W. Taylor Rd. Hobbs, NM 88240	Main Number	575-393-3612
BLM Roswell District Office 2909 W. Second St. Roswell, NM 88201	Main Number	575-627-0272
TECQ Texas Commission on Environmental Quality	Main Number	800-832-8224
New Mexico OCD		
U.S. Environmental Protection Agency Region 6 Texas/New Mexico	Main Number	214-655-2222
National Response Center Toxic Chemicals & Oil Spills	Main Number	800-424-8802

Rig Company

· · · · · · · · · · · · · · · · · · ·		
	·	

XIII. EVACUATION OF THE GENERAL PUBLIC

The procedure to be used in alerting nearby persons in the event of any occurrence that could pose a threat to life or property will be arranged and completed with public officials in detail, prior to drilling into the hydrogen sulfide formations.

In the event of an actual emergency, the following steps will be immediately taken:

- 1. The MRC Energy Co.'s representative will dispatch sufficient personnel to immediately warn each resident and transients down-wind within radius of exposure from the well site. Then warn all residence in the radius of exposure. Additional evacuation zones may be necessary as the situation warrants.
- 2. The MRC Energy Co.'s representative will immediately notify proper authorities, including the Sheriff's Office, Highway Patrol, and any other public officials as described above and will enlist their assistance in warning residents and transients in the calculated radius of exposure.
- 3. The MRC Energy Co.'s representative will dispatch sufficient personnel to divert traffic in the vicinity away from the potentially dangerous area. A guard to the entrance of the well site will be posted to monitor essential and non essential traffic.
- 4. General:
 - A. The area included within the radius of exposure is considered to be the zone of maximum potential hazard from a hydrogen sulfide gas escape. Immediate evacuation of public areas, in accordance with the provisions of this contingency plan, is imperative. When it is determined that conditions exist which create an additional area (beyond the initial zone of maximum potential hazard) vulnerable to possible hazard, public areas in the additional hazardous area will be evacuated in accordance with the contingency plan.
 - B. In the event of a disaster, after the public areas have been evacuated and traffic stopped, it is expected that local civil authorities will have arrived and within a few hours will have assumed direction of and control of the public, including all public areas. MRC Energy Co. will cooperate with these authorities to the fullest extent and will exert every effort by careful advice to such authorities to prevent panic or rumors.
 - C. MRC Energy Co. will dispatch appropriate management personnel at the disaster site as soon as possible. The company's personnel

D.

will cooperate with and provide such information to civil authorities as they might require.

One of the products of the combustion of hydrogen sulfide is sulfur dioxide (SO₂). Under certain conditions this gas may be equally as dangerous as H_2S . A pump type detector device, which determines the percent of SO₂ in air through concentrations in ppm, will be available. Although normal air movement is sufficient to dissipate this material to safe levels, the SO₂ detector should be utilized to check concentrations in the proximity of the well once every hour, or as necessary and the situation warrants. Also, if any low areas are suspected of having high concentrations, personnel should be made aware of these areas, and steps should be taken to determine whether or not these low areas are hazardous.

MRC ENERGY CO.'S

Exhibit E-6: H2S Contingency Plan Emergency Contacts Matador Resources Company

Company Office			
Matador Resources Company	(972)-371-5200		
Key Personnel			
Name	Title	Office	Mobile
Billy Goodwin	Vice President Drilling	972-371-5210	817-522-2928
Gary Martin	Drilling Superintendent		601-669-1774
Dee Smith	Drilling Superintendent	972-371-5447	972-822-1010
Blake Hermes	Drilling Engineer	972-371-5485	713-876-8558
	Construction Superintendent		
	Construction Superintendent		
<u>Artesia</u>			
Ambulance		911	
State Police		575-746-2703	
City Police		575-746-2703	
Sheriff's Office		575-746-9888	
Fire Department		575-746-2701	
Local Emergency Planning Committee		575-746-2122	
New Mexico Oil Conservation Division		575-748-1283	-
Carlsbad			
Ambulance		911	
State Police		575-885-3137	
City Police		575-885-2111	
Sheriff's Office		575-887-7551	
Fire Department		575-887-3798	
Local Emergency Planning Committee		575-887-6544	
New Mexico Oil Conservation Division		575-887-6544	-
<u>Santa Fe</u>			
New Mexico Emergency Response Comiss	ion (Santa Fe)	505-476-9600	
New Mexico Emergency Response Comiss	ion (Santa Fe) 24 hrs	505-827-9126	
New Mexico State Emergency Operations	Center	505-476-9635	
<u>National</u>			
National Emegency Response Center (Was	shington, D.C.)	800-424-8802	-
Medical			
Flight for Life- 4000 24th St.; Lubbock, TX		806-743-9911	
Aerocare- R3, Box 49F; Lubbock, TX		806-747-8923	
Med Flight Air Amb- 2301 Yale Blvd S.E., D	3; Albuquerque, NM	505-842-4433	
SB Air Med Service- 2505 Clark Carr Loop	S.E.; Albuquerque, NM	505-842-4949	l
<u>Other</u>			
Boots & Coots IWC		800-256-9688	or 281-931-8884
Cudd Pressure Control		432-699-0139	or 432-563-3356
Haliburton		575-746-2757	
B.J. Services		575-746-3569	

1 1 1		THEFA, IL IS N. CIT	Safe in uma life	ALMID	12101 744 PPA	4 15.41	Pri Dist.	
	10000			Barran -		<u>`</u> ®'	LUN AC	
<u>.</u>		- 2H 1. 644		Qui grue	Totes Pet	Gil	S Yestellum	
5	tendure	ن <u>م</u> ع	12.1411.14	Parabour re	Pto, pit-	8 11-200 	Ta _18-00 to nu.	1
TANT		4 Cu 2 40 mm U + ε L + 1 2 μ 3 Cm ² → V 1 4 μ	CTIOI - J-G	ALL CLOSE		(2.000) Ppcl.)	9716 (MAL)	
190_5				YATE FEE.	_55	Ang Sandhing MA University - Reed,	J.L WI ADDON	福
		6 U 1			TE MAY Set		PI+ Spreite Viel	
L.Fr	tront and	internetionale States / endernet		(D)	- 2 S. Williamy 1979	[7.00.Frd."	1. More 20	2
Here a	I (Manuary Front)	Barriston and	hill with main main	<u>н ут</u>	Project Fel 5/2	d Lakorana ()		1.15
2 101	Bit alle Mentenerikanisterit	Yot	HES FICH. SALET	Tetes Pet	Lotal	H.E.YOTHE		[]29
241.	100000 0 000000 0000000000000000000000	C.H. Stoliz m	1165	011055	Teris Pat ata		03617 4,950.@	
<u>.</u>	TOTAL AND	1 1 Stav	21 4 740 5 Yora#		(Corgenetin 6am)	Cutes Sed	E artos	1
÷#-	Tarner Carting Cil	2 7445 5-0 101-10	TDOOT		15			
100	Sthaster tas an In Star fiel			1 9-10	0.0	S CALL	1 1000	1
	16 983 Heats (Manophres)		Crew Street	8,94:172.1	20 Shimaraka	COG 09-	21	1
₽:	ALL Ventures A. THERE'S STO	P Fridlig	TO ICH Startero En.			Hereiro Lin.		4
			N.E. Yol (1) PTOLE	1498 D	reilers) Bri	10101 11 11 11 11 11 11 11 11 11 11 11 1		<u>ل</u> ه ا
	9-1-1016 - Covers Strate	in a is	A Cont (Zink	04	Stebbing"		\mathbf{N}	
-	10 10 10 10 10 10 100 100	BLYSHIS		Cioni-			Veter in	
	9.85DE	TC-12-27	323	11 Jan	Shirt Shirt		1	
	INTERN ALLARS	Hit.	Starters 1 2011	34	、(1.1.12165) 人 ⁽¹)、(人、42677	Triga Fo	עווי ס	Į
2	10 73 41 4 4 W 1 1 7 7 1 4 1 7 9 9 9	Ser- (dui	apona corp.	Liningero	1073000	1 T- 39 48P	1 Sotes Bat	
	The state of the s			Anorbo Courter	1077 TP 1190	CA13 6 44 1 4 14		
mai	The said a will a start a	Status Instantia				200 Heren	Teras 241 24	
N ₁₀			4 49 10 1304 4				1000 PC PS4 540	
3	there is there is the suit		30 - a		− 29		28 Stock Stone	ገሚ
6	ALL	E in Printer-30		104201-00 C	HLTOTIAL	Leatherneck Fed	្ត ាន ដ	
	Leatherneck Fed		, <u>, , , , , , , , , , , , , , , , , , </u>	94	aji PJOTT	Com #113H BHL	i Vetes Pet.	<u> </u>
Ø\$	a bit soften		L PERSONS	Orecond	1 Calapy 10 Dorg	l.	1 Aquine Sign	Yor
		4 (2000) TE	調整の天	H E.Yotos	♦ 357 1554		1 114 5 31-86	
		- <u></u>	A company	a/etoner	10 11 10 10 10 10 10 10 10 10 10 10 10 1	Surl Ville	1.3. 1.4	
	Liter Distance	1.5		l } <u>+</u> −	201 2031	Paulie Paulier	TIS FIOL	T .
		a personale an	Ide torres SME		93125 396		kon et	
26			iau pri l'opera			Black Steel		
	The Property Street	l¶G , i ≦islanaman,		Какр	.1	1 August 10-10 45012		. 8
	A AND AND A A COLD P LOOK			1	₩ ·	Think of Think	Yotes	8
1			E San Feel	Yelenen vil F	<u>لي الم</u>		Yotas Joint - Character	
1 1		CB. CB. CB. CB. CB. CB. CB. CB.	Farmer Laborer	Yelenergy all F		Totra Pet	Total	
	A STATE		Menicurit	Yelenene (1. 6)		rota Peter	3 perce (14) (14	-
		GB.	Mendeuran)	^ү й ү түүү (). F М	Cinerol Instance	riotra Peter Internet Peter Internet Peter Internet Peter Internet Peter	John Votes John Votes John Viel Ga. Vielssi Matzgirt	
P	AND & AND		I (Menideurrit) I (Menideurrit) I (Menideurrit) I (Menideurrit) I (Menideurrit) I (Menideurrit) I (Menideurrit) I (Menideurrit) I (Menideurrit)	Y # 2	Superior and a superior	roha Arta roha Arta IPD Jacob Arta IPD Jacob Arta IPD Jacob IPD Jacob	Join Port	
н. Ц.	MIDLAND &		I (Anna Lita) Feel I (Anna Lita) Feel I (Anna Lita) Feel I (Anna Lita) Feel Store	Y PT	Cinerol last	rote Att	A prime free free free free free free free fr	3
ц. Ц.	MIDLAND S.		I (Anna Lita) Fed (Anna Lita) Fed (Ann	Y	Cineral line Digo: filorit Stene Wher Line for 4420 for 4420 for 4420 for 1000 for 10000 for 1000 for 1000		CALL AND	
н 1 1 1 1 1	MIDLAND C. MICHANNEL		(Membeurin) (Membe	YPE	Anti-		A provide a prov	
e Mey	MIDLAND MIDLAND	2 7736 2 7736 4 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Finance Later Frei Finance Later Frei (Mersteuron) 14875 Selly Buter 116 alger st. 2/87.8	YPE	Hint Stene unber inter filmt Stene unber inter far 4521 Steller U.I. Ftill ISCH FILES SRBI 050		A Character of the second seco	2 2 1 4 5 5 2 1 1 4 5 5 2 1 1
e Mey L/2	MIDLAND TIBES TOTAL ATTEN TO LOSSE TO LOSSE TO LOSSE TO LOSSE TO LOSSE TO LOSSE TO LOSSE MIDLAND TO LOSSE TO LOSSE TO LOSSE MIDLAND TO LOSSE TO LOSSE	274 GB GB GB GB GB GB GB GB GB GB GB GB GB G	(Mendeuron) (Mende	Vierney II. F	Hint Stene unber (20) Hint Stene unber (20) far 4x20 Stene Unber (20) tar 4x20 Stene Unber (20) tar 4x20 Stene Stene Unber (20) SRBI QS G 9.1.4		A Case of the second se	5 21) 1455 É 7 ¹⁷ 374 jai
r Mev L/z	MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MISSING MIS	27156 2746 17199 17199	1 (Mendeuron) 1 (Men	YPETER I. F	til Cardoni Ritard Stene Var 4420 U.1. Ptri 1920 SRBI Q60 9-1-40 Outpus		Yorka Y	6121 3.425 (1425 (1425 (1425 (1425 (1426 (14)
er Trev L/2	MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MISSING MIS	27736 27.46 27736 27.46 1793	1 (Meniacuran) 1 (Meniacuran)	203720 11 203720 11	Anti- An		Angle	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
e Nev Lani: Lau	MOLANO MICLAND	27736 2746 64 0105115 64 0100000000000000000000000000000000000	I Former Interfeet	Viteration of the second secon	Hint Stone unber int filers Stone unber int filers Stone unber int filers Stone unber int filers Stone filers Stone filers Stone SRBI OSG Stoppas st	117 10 11 10 10 1170 11 10 10 1170 1170 10 1170 10	Japino Peri Japino Peri Ga. Property Ga. Property Japino Peri Japino Peri Japino Peri Japino	21) 1435 E 7" 24) 24) 24) 24) 24) 24) 24) 24) 24) 24)
	MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MISCON M		1 (Mendeurint) 1 (Mendeurint) 1 (Mendeurint) 1 (Mendeurint) 1 (Mendeurint) 4 (Mendeurint)	Viteration of the second secon	Anti- Selosi filerit Stene unber (207 filerit Stene Sterbur for 4420 tui- tui- SRBI OSG 9-1 - 40 000015 17 17 17 17 17 17 17 17 17 17	11-12-12-12-12-12-12-12-12-12-12-12-12-1	John Champion Ga. Wiges Ga. Wiges Ga. Wiges Marson John Marson Jiffet John Jo	
	MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MISSING MIS		I (Mendeurint) I (Mendeurint) I (Mendeurint) I (Mendeurint) I (Mendeurint) Autor	Volumentalit. E Volumentalit. E Ionech Trings I - Earzi I - Earzi I - Sarzi I - Sarzi - Sarzi I - Sarzi I	Ineral Int. SIGN Ineral Int. Ineral Stene Ineral Stene Ineral Stene Ineral Stene Ineral Stene Ineral Stene SREI OSG SREI OSG S.I. IN ORDAN IN IN IN IN IN IN IN IN IN I	11-70-11-70-11-11-11-11-11-11-11-11-11-11-11-11-11	1014	
	MIDLAND ALT DIAN MIDLAND ALT DIAN MIDLAND ALT DIAN MIDLAND ALT DIAN MIDLAND ALT DIAN MISSING ALT DIAN ALT DIAN AL		I (Mendeurint) I (Mendeurint) I 14872 Setty Sutor 116 Setty Sutor 116 Setty Sutor Setty	Viterenzielle Viterenzielle Ionch Trings I Solz Solz Solz Solz Solz Solz Solz Solz	Ineral Internet Stene Stener Law Ineral Stene Stener Stellar Ineral Astan Inter	11-10-11-10-10-10-10-10-10-10-10-10-10-1	Join Company of the second sec	est f
in the work of the second seco	MIDLAND ATTACK AND ATTACK AN	27736 27746 27736 27746 27736 27746 27736 27746 27736 27746 27736 27747 27747 27777 27777 27777 27777 27777 27777 277777 277777 277777 277777 2777777 277777777	I (Manuacurar) I (Manuacurar) I 14872 Setty Suter 116 Setty Suter 116 Setty Suter Setty	Vitering Vitering Vitering Vitering Solution Sol	Ineroi lant Signa Stene unber in ineroi Stene unber in ineroi Stene unber in ineroi Stene unber in ineroi Stene ineroi Stene ineroi Stene Signa Stene SREI OS G 9-1 - 40 ogogas it it it it it it it it it it	(1) 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10 10	Join Contract Join Contract Join Contract Ca. Deposit Deposit Join Contract Join Contr	est to
r Meyer Lyz Douit Same	MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MISSING MIS	C	I (Manualeurine) I (Manualeur	203728 4 203728 4 203748 4 203748 203748 4 203748 4 203748 4 203748 4 203748 4 203748 4 20375	Ineroi lan Selor iar 4420 iar 44200 iar 4420 iar 44	roha Art Poha Art Poha Art IPoha Art	A Constant Parts A Constant Parts C. Constant Par	
The way and the second se	MIDLAND ALT DE LE	C. C	I (Manuacurine) I (Manuacurine) I JART25 Gettig Buter III Older He J'St B Constant Constant Constant III III III III III III III I	20720 V 20720 V 207	Inerol Int. Selori Inerol Stene Weber (2007) Inerol Stene Weber (2007) Inerol Stene Weber (2007) Inter Stene Weber (2	(1) 10 10 10 10 10 10 10 10 10 10 10 10 10	A Constant of the second secon	
	AT 11 10000 AT 11	C. C	I (Membeurint) I (Membeurint) I JARTS Gerly Buter III Gerly Buter III Gerly III Gerly III Gerly III Gerly III Gerly III Gerly III Gerly III Gerly III III Gerly III III III III III III III I	20720 2070 2070	Inerol latit Selo ² filerit Stene wohr (20) filerit Stene wohr (20) filerit Stene wohr (20) filerit Stene wohr (20) filerit Stene wohr (20) SRBI OS G g-1 - ip oggjas if if oggjas if if oggjas filerit Cal oggjas if if oggjas if if oggjas if if oggjas if if oggjas if if if if if if if if oggjas if oggjas if if if if if if if if if if	Totra Person Potra Person Po	A Constant of the second secon	
	MIDLAND AND	C. C	In the set of the set	20728 Viterricht F Viterricht F Ionch Tring I - 50121 0572 of 3 ist ISt I ISt	Inerol lett Selor Sel	Tota Att Pota A	A Constant of the second of th	
	ATTING AND STREET AND	2 7736 7746 6 77356 7746 6 70355157 7 7739 7 7759 7 7759	I Farmer Lauffed I Farmer Lauffed I Harmieumn) I Harts Buter Hit Off of Jense Cons Amer. Cons	20728 Viterricht F Viterricht F Viterricht F Innch Tring I - E0121 0572 1 - E0121 0572 1 - E0121 0572 1 - E0121 0572 1 - E0121 1 - E0121	Inerol lett Andra Stone wober (20) filent Stone wober (20) filent Stone wober (20) filent Stone wober (20) filent Stone Stone Stone filent Stone Stone Stone SRBI OS G 9-1 - 40 SRBI OS G 9-	Totra Art Potra Art	A Case of the second se	

1 inch = 3,000 feet

Feet 0 7501,500 3,000 Map Prepared by: agreen Date: April 18, 2019 filename: OneMileRadius_Plat Sources: IHS Energy: Midland Map Company; Environmental Systems Research Institute [ESRI];

r T	50 317 1 1 1 1 1 1 1 1	THEFT	fo lafa a ferti a t mil.	12141 F/4 Pro	L.O.C. 4 (1-A)	Gel Dist.	
	Bizielo . 63 616 62 625 6116		THE SOM DOM	110 0 ¹ 10 mar			jet.
Sie Me	Yendure		Trace of the series	J 17 WW	A 11-223	16 Sectolly also	ъя,
Ø	1 0745 AT 175 AT 1754747	an a	Autor Annu Annu	overne i sta		10)	2
the s		i Baa				IL WI LEVER	谮
		6 blee bourne e of forth, Me	, 1	Se water	Chillen and an and a second second		Į۲.
. sh		in internet jouter fictor		* FOR	1.0.0.F	1. Harris 2Ct	X
	A (Proveriad)	B grant	bilant Arrows	Espinart P	el 5/2 dualer	ana Corp.] COG	LT S
<u> </u>	11 . L. Went west Manufacture	Yohes Pri	· Filmt · · · · · · · · · · · · · · · · · · ·	Petekal	H.E.Y	ניושרע איז	
A12	Actor 5 (1798-12,050 -1)	C.H.Stolitz testing Histories N	ાય થયો કે ગા	95 Tales Pr	t, etci		
	ALL AND LA PART CAAS	2. 31114		Coronada	Service Continues		
100	St 16. "6 Bei Sen	no-of on starta '	*	640 CP		116571 10024	
- 6	Y'ctaval - 20 Mainstree	「読ったー」 小説 ファ	TTE CELLARAS	20 Sharaca	i	21	_
6	the Ventures At	P Forder and the loss	Still SUZATI AND CRAMES		it 2015	Ūn, i	-4
		(H.E.Yo	I CIVIE TOLE IN	no (in relians)	6-1 1-1-1012		3 **
	3-1-1016 ADDWET	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	Corp.) 2 Mp (144	08/00/F25 (407 10:78-64 8165000	and the second	(
24	Haster Mason	Sint Vistors				U.I Souce	
75,1	1 APT LORY	TC-227	STATE CONTRACT	11.5	THE A		-
	all the HBF	THE YOTAS, etc	A State	5"3 IA 616	17 Trie	participation (r.)	
		Tarangina Calapana Ca	rp.: fr. (Unling 677	To Tomo	- 10 1799 - House	HOP Ness fet.	
	Store	IN DOB 1944 COLOR DOD	5-04-0 C	P1-1 2022. *** 1990	CAN THE CA	eter Pet. Silles Tak	
		The sea	20 N/:			Soon RI Coor	Ye
3	25 Hitty and	30-		29		-28 Prosect state	۶.
51	A Level a Line to 1 & Line to 060	HUWSaurne Vitted		Cetenal HETer	es,etal Jaiapena	េះ ខ្លាមដ្ឋ	
19 an	Leatherneck Fed		× 71	94635 83877	niber Pa	Yotes Pet.	
e ş	A BA SCATTON THE COLOR		DIEDEN	nG 3457 idatagy ha i	Leatherneck f	ed 1 Aguline Trans	i Yisi C
1 · 84		a Granding Sterbing	HE.Yote	11 2.2	Com #114H Br	"! 1045-31-65 ↓	
			Centre 14		5 a105 Y	fei bet 92 12	
		A LAN	115 - 12 Min	1000 1000 1000 1000 1000 1000 1000 100	D;(q)⊮ /P(■	NBP - Martin	-
k,	fine Stephen States				- j Alack '9	Cont Las and N Trans	
	1/7 (872) (74) (0= 7 620(6-2) 7407	and interest in the		الحد	11 y 10-4 450	AND YATES	
	115-12	100 100 100 100 100 100 100 100 100 100	La Fest Vite 10	Arg. 1. hit Fact		Loter - Advertis	
1	36				rotaPe	3 3pene And	
}	TO 1659	inter and the	Wieurmi	Maneroj (116, Carp	1155-116 / 155 ²	1047361# (P125)	
		3200	4875	March Strene 35	ber (17) (1883) Ref Gee		
на • г	MDLAC	Barer .		49 3 MA .LE	-Dari		
	STe or			ų <i>i</i> .	*		
					MARKAN BURCH AN	TANK DATE STATE	- 20
mey	vipurne R.S.Vrigg 9-4	60 010515	a anga anga anga anga anga anga anga an	SRB		Sape 1 Bes	ss É
6/2	HBP BE Mrs. Slanche		Mrs.Blonch_Tri	9	ំ នេះ ដែល ដែ	Anna Decasts (Richar	el fac
	17973 5 5 1 50 C	° N I I	(∰) ²² 9 / 1 €017 * 060577	z)-1 0	âŭ Ju a	5 1 71 1	197
2/51-2	a 702 Charles 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	A of Ch	at at	5	ന് മ്ദ്		æ
Eit.	🕹 🛛 📲 🗛 Elemente		e E only Unit		(feelististon)	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	فتترزر
			12150 12 0 68	177	· 5:19:49:81 - /		
Ann.	-Buy bun	्रत्तमा चित्र ।ऽ । २४ दे लो-सी	14 3	QiG	0 Grien (165	Line and the second	лъ ₁ к
Altin	1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1 (1			ate: Destate: Ded	toy & Hosping, ether	Crai Sidion Coman	ų
ine y					htin full	+ - M" +	 4
1	, 18 M	41. BALE 1024 (FA 5.2 BAR)	FINI 18 Mar - FIRT - 1			OF	
19 1. yr	Martin J2 Min Ol	iG.etal Hap	24 C2334	7.1.5402	lafel /	S	~ H
Ň	10 70 M 10	iG.etol HAP BLDSPE	65 PCA	64933C		»»، الا ت	
N N	40.78 M 1950	Gertal Hap BLOSTE	66 Pro	649336 5-1- 2463 5-1- 2463		a and a constant of the second s	
	AL 28 AL Martin Com 32 Min Co 1 4 30 1 1 40 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Get of HBP BLDSPE	2000 30 X000.0724,0 44 1 C2334 44 1 NBU 65 244 1 1 1 1 1 1 1 1 1 1 1 1 1	7 - 1 - 3162 e 6933e		Matado	

Map 3-2

1 inch = 3,000 feet

Feet 0 7501,500 3,000

Map Prepared by: agreen Date: April 18, 2019 filename: OneMileRadius_Piat Sources: IHS Energy: Midland Map Company; Environmental Systems Research Institute [ESRI];



ĝγ]	A	1.03				1/1		· · ·	ILER ST. PPR	· · · · ·	4	- ADM		
	njova rusha.	••••••••••••••••••••••••••••••••••••••	ີຊຸ່ງ <u>ເຈົ້</u>	· ·	5) <u></u>	201001 C	- J Pit		- 48 - 848 - 1 ₁₁	100	എ (6-A) വല്	O THE	ا ايو لا	tion Cial
	Garle) p	۵.35 (19- س ¹ الدر ¹⁹	ទទួកខ្លាំង ភូមាន		. Desi.	TAR	HL V. (PAR)	-F 1	Dillar Yates		มีตั้งระบากร	945 4174 8		
()	- 11,e-	-1-1-15	19 - Stentur		▝▀╵॔▃┤₿▖▖┉	47.401 VER	A 14 HTT) I	7 Willia	many.	041 8 13-202	1 6 1	isctuliu min	ЧŅ
0			514713	1. 2.0. 2.1. A		17.10113.07	A LAND	r pié		419	- ^{3• A} Et 2	et in a la vie	A 1 4 34-	2
T/RINT	67	¥ • 7.0	· ·			TIO .	AL	(+ <u>- 1</u> 5	C	(Landi Fo	1.5 [340]	7*416	-8:1
1997 5	IP. ST	677		· ··· ····	<u>.</u>	-165769 : 45	Yettle	đ\$		6354	Service States	1.5 Mi	∷⊀29547 °°°0. ⊵. 9 46	
	SE JUST	·	ጋ ከሮ		Concerning	5	A DACE	t De i	ે તે તે સુધાર જેટ			Bit State		. .
.	ലം ഉത പെടിയും		er 67 1 43 /5	Marntha .			NLY TRE-	GØ "	Port, Mil. Statificano		7.06 Fr	d gc Org	20	l X
20. T		<u> </u>	- Tricken	4 151 APA		Contraction of the second	Minth.		£64	1011		0.9 104710994		
	a', (****	ra hed i	ar - 1	<u> </u>	Yotes 70	blow tour tr'	tetes	Peteta	Explorent Fe	1.672		ena Corp.)	11-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1	15
-		1797 V. 18	ONS,	Min M. Canta	HOP		+iBP		ina)-G		THE THE PART AND	(12677) - (12677)	1 1, 950, 9	TC-1 D/ai
272	ner: +	100 12 - 22.	<u>1000</u>	- Control	Հ ՀՀՈՒԾ 5-5-5-5-5-5-5-5-5-5-5-5-5-5-5-5-5-5-5-	। ୫.୧% ଗୀ≤	g 0 116	1	Todas Pet	. etai				
	Kozak ar	- Auto	<u>S.</u>		55.44	ota -	f r	, <u> </u>	(Corponado	(. rezà	(7:1123-5		C. 11 1 102	
	- 9	Tipener Serie	- Charles Col	1 - O 114		ID SOT			15577			P S	11257	1
110A.3	TEMASTER 1			2		B41	1 100		1.1-2010		10.2 A	204 10 13 23	1 000	
	10463	- 24	(Taun true		- 맛뮋드고	Cinc as 0	20310 024	+ '	20 Sharera i	a	NO 00.	2)		
6	LLJ Ventures	A 3	5-1-20 LO	P Fredhul and	2 X X	B HI SUZZED	5	\$# <u></u>		-	1 2011	'n		- ₽'
	CEC 797				(8.E.Yo	1. 19 2018	2°97	che itu		Bri	1.1.2022		44	
- 1	SUSTICION THE	، مەھەر بىر ئانىر			9 18 77	- 100 H-*	17,24			•			2000	91
	0 9 1 1016 JA				1 a 3000 T	(1998) 2° Mil	1.1.1	178.61	31 6315		THE REAL STREET		1 - 47	F :
20	1945.14		13504	Concilia Fred			Million					U.	64600	F
		1		70.227		a2a-	Par 41			SHL.			3.11	h
[∳		F	7.51		Shorte	· ··· 2014	1878 J		19.1.192 11.192	TES) 17	í Trja	a Family K.		
F		Licens 1	10557 77231 51793980	THERE I	պայանն է։ Հմակցերու Հա	пр. Х.А	Linkson .	`- 0 -`) V	10 - 10 - 10 - 10 - 10 - 10 - 10 - 10 -	• <	V. N. Triss	Last Ir 🗿 🖏		
# -1		Chim IT		and the second	gz	577 × X°	400	Ι.	33-7 - 04-64- - 118. - 7.8 (1997)		10165: 0	Zaite A		
	7790		Shoke	114 868 1944	taics back	14 OF	Sho be City	111 8087	1 · · · · · · ·			ster Pet. 18	IN THE	
291		4-14-1A			ormania angle	്ര് \				1		rtus () - Yertus (?) Sobre ()		
문문의		36	الحد ببلطها (**************************************	0 2304 4	V '_'	1 - 1		•				រន៍
34	NOB 32 M	د ع منگ بر کا	(1,4477,3 9445) 1	4	30 - : 1 Witter	rrrr tssar Nefederiji	AL E SITA	hitted		المعاد ا		20 ° 1 5 0	sel Storig	[² .]
	* * * * *	6 . E C	1 State Goal	1 6mjo-30	19.19	50 g .	110020	first sta		C 4, C F UP	Jeropener			
	24Lp		Leatherneck Fed			≝ ¢.	{ ·····	85635	1 93677		10973637	i vele	Pet.	
es	64.5	Film []				LIVING	L CT-THE	34 97	i datage)	to Da	Leatherneck Fe	d i Agul		į γω
		····	We do the	ALL	· · ·	郡主義	1.2	¢.,	-16.3	Ċ	Com #124H BH	1 3.7	14 JI-66	
ľ		- 10.4 17.45		- 21.2.1	Jeeboo		E.Yotol		- n2		<u>भाग</u>	J.S.		
		and the second secon		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		Cescor	1.		Shirt Street		S -116 YS	te i Det 92	1 I	
		and the second s		1 Cia A41	* `` البر	an 207/	MHI.		2401		Datan na B	VINDE TO RECENT	Hube	
4.14	[\]	(AG) T L'are Etcele		and the second	16.19	TS SAR	N i	9	3175 383 -	1	8	4478	Comparison Constant Co	
5,G	$\vdash \Lambda$:	5.00	1079999	- ¹ 24	100 - 20	- TP546	\mathbf{N}				Black Sf	مرجد منتوا واجر	- 14	
	Xates	Ç	2016 1.5467		ipeno	• Ý	E	م اير -	<u> </u>		TTY NT LOW	ີ ເ <u>ສ</u> ີ.	Zatas	
	🔶 a 🔨		Sie 6		er jes		\mathbf{V}_{1}		••				Zeneral	e l
4	CHIERS	3.5		2.2494			<u> </u>		32		t and a	3 3040	Trad_	
	15-94 TO 16598		30-r		Hil /	- 		Liner	oiles, Corp		1. 2. 100	.ets.	1.25	1
r I		34 3 4			1111	(Mecurinti Anno A			1025 ·		1122 63129	19 67 80	4. F.	
		0 ²	- <u>R</u>		P	4672	6	, file	and shear way	ber (174) Ty Cre			ŗ	
на. 1	. DLAN			1. X.	st Bater			4	1 Marta			2	1	1
ľ	Le	ا مد م		1			Į.	1 u	ι <i>j_</i>	19 1	I -	a parate	4. F	
					116					4				
1.1) and 10	2767 4	17.44 8 77 0	2 21:56	7.46 4 27	जन्म अ	27.128	11111	រាណ៍ 🔊	THE	. 1.X.T	RE 187	3,31,42	ΞŊ
Mew	aligneting a		<u>6.5.7 nigg 9</u>	1 60 DL0515	, 	4		4	SREA	Q5.9	ام ام	ana 0,5_4 ₆ — _	الع العادي مشريكية	455 E 7
1.676	.~* ∂ ⊔≣n> A	25,7 9 S	Mes Sloath	17 104	5	Mrs. B	lanch Trìo	å i		't sas	2)´ °	A	inis (Richa	and Sau
	17050		9 50	ບີ	:	Q ^{ka} a i	1 - 50121		e (20 54 5		5-1-71		-
in the second	a Fud Cara"		CSOSTE	<u>v</u> 1		- C6	0572	Ă	-		ار خا	SUSSES 1		6197 •
Lown	이 것	Bla26 A£	a 11.∎	*ស៊ី វ	e e	មា ភ្នំពាទភ	(1	1	(7 7)	1	- 5		п	q 7 -
Sil.				61 N -	Ę,	g E day U.	nář	ų.		16	clinkistone.		Bin Frida	م ر ز
				s î { {	فخر	it- 4- €8	4	1 1	0		15 20 21			· .
Sec.		Bo.23 d	7 ×6 ⁻	`**,#*** —µ4	€د:	148	5	٩ ٦ -٩٩	្បើរៀ ។			R. Statt. 1	- 4 3 J	15
\$ ²	1.70		152	um CeC,etal				at at	8 I '	3 4 7	220	erei R	a la fat	6
M. Hope			. 1	a 69 797 1				059	inte Judi	byÿ Hor	erg, etcy	464107 S LI	PI369',	4
14	16121	7 0 70 ~ N	₽ +	- +- 1- 4	MIN THE				 	TES M	in 1 2007 -	J Se win	PAGAIN	4
No wi	NS-COP-CLO	1051.57	32 Min (G. et al 👖	HAP	200 AC 7/8	un. (* 3,64, 41) 2,334		2-1-\$166	1056		F.	g	9 ⁷² (1
N	7 4 4 -	يقتدعه	HUP	N 1	BLOSVE	75	HBU	l	e 68336	6692	1 3/		AFTIGE	ч. XQ
U.S.	10.0		060573	\mathcal{H}		OF NO				L	A Car		<u>ن</u> د	,
	ه موره			M		ж:,				- Xe	21 132 Mill.	<i>∴Z,</i> ∎∎	atad	Or
		i ¢ni		· · · · · · · · · · · · · · · · · · ·	1 2 - 7				44	<u>ب</u>	1 ET CT	- Inst	RESDURCES CO	
نے			42. 5					1	0			<u> </u>		
								1						

1 inch = 3,000 feet

Feet 0 7501,500 3,000 Map Prepared by: agreen Date: April 18, 2019 Filename: OneMi eRadius_Plat Sources: IHS Energy; Midland Map Company; Environmental Systems Research Institute [ESR]; ,

T.		62 (¢ 1)	ESEA	5 3966 MILER	TELENIO	11161 775	ra 1	4 (6A)	Cel D.	51. Ma r
	intelo al 416 of el	5 6 1161			H Chrol	2 10 0 ar - Yo		្រើ 📔 រាត់ភាពលាលេ	00 700 AC	
		Yensures.	2,4, 3	- 10	T AND FO	. 17 M	ding (mgray). Ding (mgray).	611 # 17-222 - 31-8 minutes	166 58 ⊌arts una	2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
100		i servi Reservati	[k]2		AL U-DIALX	·	SHALL Tates	Si bwill (annull Find	ian son i 🖉	Ø (16 0+1 €;
RO C		5	· · · · · · · · · · · · · · · · · · ·		The sec	SE SMONSS	2016-0-54	Maria Caracteria	505-1 105-1 6 Made	
Í.	່ອ ¹ 8 ¹¹ 816 100333 00126 00126	10315	internerseite		y - 70 198 - 70	F 1. 6. 4		"T.2.6.Fra	Pi+ Searer	" " "
2.7°	of Piteric Fred				H MP	Jerniora	64 (1) 1	J. Laborat	igi noonogoo 12 Coro 1	
A DL	11 0		Martin Exating	ones For start	Tetes P +iSP	e tantal (rea)-56		H.E.Yor	95,2704 075.77	11-1-19776 Per
512 -	10000 4 UPRA- (2.870 H)		-0.4,9:002 -//01[5	ଅଭୟର ଅଧ୍ୟ ମହିଥିୟ	01105	J toles	Prt, etsi	UT SOL	1	Print
		100 CH	2 2 2	r førde State 10501 i		10.0	, in the second s		ሳ. <u></u> ስድናርን	19-1 2018 19-1 2018
يەتتى مەت	ithetic the		··· - ·	10	131-15 T	- 20 - ¹⁻¹⁻¹	07. <u>r</u>	ie, single Size	PET PET	000
- A	10 512 India India	unetre: L'1010		A Same School Of D	रुप्रमुख । भर स इ. ीविक क्रिक्ट (१२	555	72	COG Op. [1:2013	21	
	79660497	<u>21,310</u>		(H.E. Yol ch) 19 tots	504 / 1005 / P)	And the second sec	11.1015		44.
	PI 1010 MONTO STO		Sth. 2	9 36 77 Notice 33 Corp.) 2 34 f	1763677 04-0 770 1401 1844 19410	Brenn	ring"		\mathbf{i}	
a¢ ∣	104510 - 10 350	і. И.З.	IFL YEARS		Lister -				u.)	Coscola
1	L' A OAY	! [H.K.	Erz de l'arter :	G020-		WETES!	(Trian	Formation Ter 1	
	ALTER LACON 17721	19390	NAC YOTES,	eto : n E vin De etali ulupena ĉiripi : Anjo	alinarro.	-6", 16, ¢ ∞∞cor	2677	H T- 37	int in Saladi Sapi	
	requer at				Corpo yorbo Cort	1. 2022 Te 1956			1826 7 1826 - 1	
			State Land						Sobry B	Ğ,
생태	25 14	Mu >∞) Mu m,9041.£U		30		- 29	-,		-28	al Stead 5
	A Contractory of the second se	mty OBU	HUVSource		LA E. YOLGA	NITED H.EY	cittelal	Leatherneck Fed		ាមដ 📘
	Leather	rneck Fed 27H SHL		Met Cons	ILC Y-ENAS	494 P26	······	Com #127H BHL	J yeles	Pet.
195 04			H. HEYMAN	1. Mar 547.	Drecente 1		in mining		1 1990/1 11:175 1 014 5	
			- 11-1-1- - 11-1-1-1-1-1-1-1-1-1-1-1-1-1	ebbine His	S/ECOTE	11 11 11		Sil rt	F.S.	
	iter and	ا ا <u>ح</u> ا	Standar A	- Erist	Ŋ; <u>↓</u>			Estate Par	FI HET 72 	f
4.6	Care steers wares		and and a solution of the second s	His Jorrs Star	IX	93175 33	12	t i		Confe fini
2.0	eine Calt.	lu= 2-5487	bioper		GHL			113 "10-4 4500" 113 "10-4 4500"		Yujus
	ar Site	U I	1994. 1994.	17 Farma Lastfed	Y					Cherois
		ĺ			f			roim Pet	Spurse	ANC PROCE
ľ		-		Mewleurie)		24021	r	112.0	iestrei	F
-	OLAND -		1 2000	- gelig Bater		Blogs Stene Nor 4530	Printer Corp.		1	
	NRUO-			i i i i i i i i i i i i i i i i i i i		trj.	- P		E Person	ri
								County (Million) (s Tracting of the		
mew	roparrie 18.5.7	9.14 9.17 19.19 9.11	2 11 55 11X		4 T	si si	RE OLS		1998) 	21 Bess
"	uller all birg.	al anna T	199	້ ສະຫຼັດ- 1. B	lench Tring	,	9.1.481 090143	3) 1	Asnosa,	FIS Richards
inst-	Fue Cars	605TL	N I	101 J	0572	i			<u>5-1-7</u> 1 NJU\$t4 <u> </u>	PL9
Louis		111 ⁴ 	1	600 Amer.	n¶ ⊈ sil		1 . -		а г – 1	~ IT 4
100				TO 12150		177	1 H	edînkîstona. Hişi tasl	<u>}</u>	Big Eddy 🦈
Res.	- Bur tan	×6	AH-4	14 5	⁴ ۴	- MARIA	uri U Grien (Third 2	-4 5 J /
A Line	17/ac	102 Mit	1. L.S. 6, 199 (1) 1. 747 L		r I	ate: bigner	? و [مەن ∂يونۇرى	erg.ethy	ef ei Maion i Co	(};0)96./ ∞684. 948.
		an akan "" "		er. decietar ta M	a.016.etel	Releadera Gil	- 			Page stor
Γ.		(Bb) C Milli (160		HAP ME O	1934 1984	7 - 1 - 344 e ¢0392	E Bro		с — — —	60 ⁷²
	1977 Tan 1991 1 4	1057) - 1 1 1 1		BENGO ACEMAN	· · ·		لِيْ)] مَعْمَ			
· A							Č.	5 89 1		RESOURCES COMPANY
	and the second sec	12.5	• 11	<u>U.S</u>			<u> 88 /</u>	- 449707	- 11	
1 in	h = 3.000 feet									

1 inch = 3,000 feet

Feet 0 7501,500 3,000

Map Prepared by: agreen Date: April 18, 2019 filename: OneMileRadius_Plat Sources: IHS Energy; Midland Map Company; Environmental Systems Research Institute [ESRI];
ru T		02 °TH (SF4,	1112 12 2012	5966 M 160 2 160	111012	12:41	744 The 3-60	4 (S.A)	Cel De	st. dawn
8 1	Gertelo gel (10 gertelo	5 6 116 ¹ L c.1			H Deroj	10 in	Yntes Pet	្រុ ៨ វាគឺគឺចលាក	OF FURAT	
SIL AT		Yentures			TIN BUT) I 7	Williamson.	Q41 # 11 22 3	15 🕱	ctall _M all of the
۹		14.12.4	Week razie		RE LI - D Mater	ne :			1	· · · · · · · · · · · · · · · · · · ·
600 -	PL 57		104	70101 H#C	Trail	1. 5	10:232	Sectorial Products	LAND TE WI	annach Teil
1		51571	🧯 🖓 ស្រៃអ្នងល ្អូខ ស៊ី ហៅហៅ	W.72.es	24 Mar.	The second se	\$\$ 5 B		9 Water P24 States	Part
. si		A83 25 1 40	Auroria de Ca taras / au Jano - A		(D)	S. 1	Mil And The State	7.00.Fr	1ª ge groot	2012
14	al (Ptry's fred)			tiberter e	- H (4)		increa Fel. 672		na Corp.]	COL 11
E III	11 of Low ST Standaris		. Yate 	6 761. F/mt	Tetes: HBP	etata (WI)	6	H.E.YU	10 s. 21 21	11-1-19977 Fee
en. 872	News & LEAST (3.050 FC)	20.	M.ŞPƏİrz mənəi Gərmə	\$∋ ગુમ્યમ¥તી*ડ	ំ អាចដ៏	T	ates Pet, etc.		r ∖!⊴n '. .	
ц. 1	an ins it an Oak		7 18 35 44	70184	l I	to	or 20 Ado 6271 .) :		-4-a	
	ar jb. "6		04 19 4	4 IV201 +	4 F		(d) Ope-		DE E	116571 00025
Ψ P	-rictival 24	5.1.356			01-8 <u>1</u>	- 20:	Sharorase.	010 01	2)	
р: -	alld Ventures	4.2010 3.970		1000 - 10		#	······	pr- 2015		4
	250107		R) F	E. Yel et / 19 2015	14050	9h-c.3873)	eri.	i r tota		AN.
	3-1-1010 ADDAVETS	Gh		93677 	(17934) (1993) (1993) (1993)	3	ir estaring "			
-6	1034 Jap 76		atta			75.03				Yo WIL
	3 850	W. Y	C1227	12.1	8.2.11		THE		16-2 	<u></u>
	LOTES A HBP		C Yongs etc	Shertero : 4 61 9000 V	87 8 7		4.1.10165	fTrjeg	Pagily Tr.)	, 🖡
5798) 24	to re an icent 17721	1723970 574 Last 172	ian Cuulop	ens Corp.	ر بر ماین ا	13		, N Trap		ns fter
	Stand Stranger Stranger	99e 141	196254	I E 1211	Shorto	1-1-20 2 7.	1150		stat Pet. 10	
EN C			The way in the	- 195 (d)					Sobry Pl	XOT
AM)				49 - 0 - 304 4-3	/	- 20-			28	
51	His 32 Mile (Line to a la	mt.064	uwsair w T	initia fot stal at a	4 5. XELOS	Yitte	H.C.Y.eter.efal	Jeiapene C	ក្នុង (អ្នក ក្នុង (អ្នក	
المراط	Jun 719 Leather	rneck Fed		75735	10333	12005	e (65) 73877	n 4755CJV		
a 93	Com #1	28H SHL		H.L.Yepper	AC Y-Stell	3497	I damase (10 Corps)	Leatherneck Fe		Part. Per Trans. You
. 84			E Yur	語語の来	12	4	\sim	Com #128H BHL	1 11.175 104 5	1 at 1
			1.2.17 11.5		31 et 5 ma	الأخاط م	<u> </u>	Su ri	F.3.	
	i ter ipi is			+ Cense		٩ (ا <u>کت</u>	<u></u>	Sall Pay	411 Her 72 - 7 1999 - 7,86 - 10	F
a Ka			ا معد المعادمة المع المعادمة المعادمة الم	La lorra Ser	(M)	93:72	306 2	р Г	NBA -	Carp chal
Ωú į					LENI.			Glock Sfa	94	
	A Annual State	/ ⁵⁺⁰⁷	CD i	a Y	\mathbf{k}			TTY NT WH.	سي ا	
			041 1617	Forege LattFed	Y	F#d	**	.		Zer
			n i san i			SZ Minerai In	v. Caro	roinaPet ⊪⊃orina inac		Percel
r I	10 10 M		19129	(Mewkeurine)		24025	·····	ritis Gales	Ind Tages	
ĿÌ	Cine .	***	1 322. 6	14825 Mg		filens S	rene water (trip D Santa			
	MIDL		ఎల్ క్	1771		10 10.0.1			S. THERE WAS	
	57= 67			116 <u></u>		ui.			⁷⁷ 77/***	
	1'11 11 1 11 11 A 12.50	277 G 14 2 1	36 17.46	4 27 98 1 21 21 3	70120	fetil #	R.H. THES	784 9	er tex	SHEE Y
Mey	Apparente 18.5.7	rigg 9-1-64 0	10515			<u> </u>	SREI OGG		1990) 10.0 خ	ii Ì Bess€ ⊈iz∺ y™
	रोस्के के सुध्य∵ं रिक्लाफे के	SlongheTrigg	12743	ិ _្ត្រីក្មេះ.B	onch Trige		ថ្ន√ី្រ ដូβ។ ភពព + គ គ	3)	Amora	is (Richard La
	17973 (1. 17 16.10.11	1 60 60 G		ε <u>ο</u> ί σει	9572		÷ at at a		Kirjingi Nantara	e397
Land	្រាំ រដ្ឋាល អា	ान औ	a t	Eng Amer	d .	x 1	⊢ i≇	\$ \$	12	*п* d ²
Eller,	d in the second s	1. A.		Eig Edny Un	ář –		ζ. Έ	incretering	، با	م مسترج به بعد جو به ا
		· · · · · · · · · · · · · · · · · · ·		340 (2° 0° 68	ا خر		- 2			
	ни юл		n un Caluti	145	13° 1	O 10	0 Grien (187 International Internatio	TONE TO	ا ^{ردر} اردر⊈≊ ۱۰ کاملامی
A Range	201	1	v, krei			ate:	Destination (* 1997) Destination (* 1996	enalativa I	chat staton i Co	aas (
	this - the second se						17 M	-+ /32+ +	Z ⊐ 2 ²⁰ ⊥ 1 ²⁰ Z ⊃re winti	786 stol
20 1 - 1 - 1	Married 9 1051 Fm. 3	2 Min OEG, et a	r`₩ <mark>Parma</mark> ro	915 77 <mark>1976 1</mark> 04	a. (7 3(4), 610 2336	2-1	saius (Öéğ ⊧Saius i efe	1 7		630 ⁷⁷ B
N		15P 16573	M Pr	1957E	HBU	e \$6:	176 6697 (21	1 1/	-	Arviar ^{as} , I
	high 🗍 🖬 hitt 🔤	14. MY 1434	. /Me ∷.	Jeren .	Í	1	Ē	51,12 Min.	- 2 m²	tador
			14 N 19 P			ł	C	9 <u>82</u> 1		RESOURCES COMPANY
		1:5	· H	0.5			<u> </u>	- 433797		

1 inch = 3,000 feet

0 7501,500 3,000

Nap Prepared by: agreen Date: April 18, 2019 Filename: OneMileRadius_Plat Sources: IHS Energy: Midland Map Company; Environmental Systems Research Institute [ESRI];

.

? ``		THEEA. IN STREET	160	241693	11'ct 1/5 Pro	A 12.43	C Cel Des	
				A Pito		െറ്റ്റ്റ്റ്റ്റ്റ്റ്റ്റ്റ്റ്റ്റ്റ്റ്റ്റ്	D Savie jiela	- Size N
		STORE NOT BOSS			10 IS TOTES PET	Minimberring 6	45 6171 '@	
Electron and		· · · · · · · · · · · · · · · · · · ·			17 Williamster	8 17-222	6 Strait and	
19	100 m to 43 6 47 6 13 10 10 1	are i are of the set	A A D A	RI LI -DIDEA	104- 3 MURAL			4
12040	The second second	and the second s	Stata: Hat	ther		(a strate Figal)	Ind A	100
1 97 - 1				THE REAL	5	MA COMPANY - April	TOG - TE. 2.84	្តត្រា
, 1		0.010	71, 1865 - 18 BARHIEL				Pit Spectie - Pat	\mathbf{N}
	Auffin en and an and an and	D 110 cl / cl / cl / cl		D	- " S. Willington	1.26.Frd	. J. Moor 20	82
HT I		Des Barriston and			Fraincest Cal 4 M		- / I FOR	
2.01	a il went net dentaurie	Yon Yon	Els Figl. Simil	Tetes Pet	and		a strail lis-l-dept	1.0
K		CO.H. SHOITZ CON	65	្រុ ។ស្រ បំផុតទី	(PE)-01	Test Ste	0.950.0	10.0
<u>87</u> 2-		i - voirs	ચાર્ચ જેવી"≲		Taties Print etc.	(HK SPEA	. Romino	
122	Tayner (Carta Cal	2 514	:0788 16307		10.00	W 730-2	-a (91.0)	
utts.	Stiften ter sie in ficht und bei enter	£⊶Ф 0л.⊶3л⊶	÷	Í	600 Cpor.		11212 1002	
- -	"" ctural = - 7 a this said	1. Mana manana iku	<u></u>	ans 🔽	20 Shararasa	1 <u>5</u> 56A	21	
	10 513 Harry Law Sel-2017		1	2721013246 27.5656442.0047	1-1-9-19-1	COG OF.	-	11
<u>[</u> _	CE0797		TOTICAL STATES En.	ALL		112012	ke	.]¥1
	the second				aci) Ici	1244 25 31	process	<i>ъ</i> .
	17-1-1016 ACONCT3 11-110		mpera Corp.) 2.44	- 11 - 12 - 12 - 12 - 12 - 12 - 12 - 12	Steamor"		NY T	1
5.6	104514 10 3504	HILLYBHAS		E.I.		1	1 Yo 175 (
	2.850	TC-PP7	1.7.		Ski	.» 		
[*	YAO Y	H.E.	Sperig 0 1-41 9015	GOT DE	ill.E.¥efas}	(Trical	Family Tr.)	F
F -1	107	THAC TOTAL, C'C	Mana Serge State		//) [//////////////////////////////	H.T-SH	ir Trig, stall	
-		- midd	52677	Curph	SCHOT BLANDE	10.41	ALTER ALTER	
	Tracian Shore	184 8 6 8 1754 tales	Les Ziels	3 40-6 0 (01-1-2	077	CAT I CAT I	181 Per. 1998 1. TA	<u>ti</u>
1 1		This way	- 19 O Y			•	Sater Pl -	il al
142		1	70 + 304 · *					日義
<u>थि</u> ।	A Contraction of the second se		Yom Patentin			1	መርጫ የአውር ይየወብሩ 1 1 ዓ.ም ቀንም	[¹ 2.]
	Part Parts		9-1-2-203 4	19913 p	(in) - 81	Leatherneck Fed	5 A Baa	
	Leatherneck Fed		> ₩ 🖤 🔨	1	33 P367T	Com #133H BHL	1 yetes Pet.	
6 3			Bride Ser.	Brebearts 34	idatagrigt Dorg.	<u>1</u>	i Agoline Tran	Y Ward
<u>,</u> षमं	Barson I Water		1. N. 7. 7 - 7		1.5		1045 31-65	
			01212	Versimer >	1-	şuri	F.S.	-
	1000 30.14	1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 -	- Center		<u></u>	teratin Yote teratin Pasi	i Per 72 22	
		the character of	PETS PTC Z	(MIL)	93172 306 90	н	Br - Care -	
μĶ.	The Stort Common	a an ar an ann an an Sea	Period			ij Edi	78 Y- 101 FD	хI I
~ u	e 195 and Tall, Ins	and ² Julaperno ¹		SEHL		Att 1 40 - 4500	AND VITE	
	A Name Site			· · · · · · · · · · · · · · · · · · ·	<u> </u>	d of the state.		
	Tailins	0 1 2 M 10 10 1 1817	FarmingFeel	Verence of Fac			This is a second second	ግ
	36			1	JZ	Contract 13	ia. Des	C
ř 1	TE ISTA	2,225	(Menacurine)		tati Manta tan k	rtE	1047281***	
			14875		Blogs Stene Suber (17)	Las al a	1 T	
er 1	10LACC		reng later		Har Har A- U.S.	1	1. I	
F"	AND .		ن ي		· · · · · · · · · · · · · · · · · · ·	1	Concerner a	
		Company and	116			ب النظار ويبين	n o : Minco danna (- 1
	115 C6 / 27 67 617.84 8 27 68	N 2 1156 TT.46	4 77 1 1 1 1 1	7:57 20 1111	til Philip Plates	7.84 18	in the state	22
Mey	Cipeirrie 16.5. Triss 9-1	60 060515 B	·····	<u> </u>	SREI OGG		ا (1996 ا سر 0.650 م⊱ –	Bess E
1 62		17 184	7 6 U-1 R		5 9.1.48	ա՝ Պ.	Signi En S	uged (a)
1		5 22	^{و ا} و	i Goizi -	0900A	- 12	3106.0	
ing the s	- Fue Caus	<u>N</u> 1 -	06	0,528	<u>і</u> -		Justa t	17971
L ow		× 1	Ega Amer	Te Th	at at	ø 1		ď
24.		57N	Eig Eddy Ur	ii i	, î	eclisterone:	Ain Car	م مشتر زیر
		i	20 12 0 68		100		ماما بومند بر سمهارین مدینه سا	'Y A
1. Second			ياله، کې	15° 14] 3	FIAMIST THE		الد 5 مسترس الجليوني ج	- A S
Ass.	2017 - 43 D0.20 of 150							
4 ²	-Тик мал 19/170 (32 М	in. CsC, etal			ate: 3	220 0	Tet Farmer	
2 A hip	ана дала ала ала ала ала ала ала ала ала а	611. CG G, etal 61797 1		0	ate: esunt Dediey ? Ho	220 etay	Hots Fors and Fors an	4 4
A tup	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	ins. CigG, efail 19797		a. O s.G. etail R	atori Symm Dodiev vo	iorg.ethy tin function	1010- 10005,0101 60107 1 Coman (2) 1 101360 30 win.1786, 6101	4 4
Kair 2 Mary Mary Mary Mary Mary Mary Mary Mary	(32 ki (32 ki (33 ki	101. CAG, etal 1479797 14 6G, etal	CEG, etal 1 - 24	n. O 5 G, 01 01 R 9 3 4	atori Samari Budiey vo Isberdeen Dil 2.1. Statt	220 torg, etwy Lin.	1945 (Bors, atal) 1947 (Bors, atal) 1910 (Bors, atal) 1911 (Bors,	
	(32 k) (32 k)	(ns. Ch.G. et al 19797	Uto, etor tat ad tap and to taste	a. 0 5 6, 01 01 R 2 3 34 HBU	afoi 3 in 7 in 1 in 1	220 torg.etwy Lin. 1534 1 1 1 2 2	Hat Bars, atal 60107 1 Coman 201 1 THISAD 201 1 THISAD 201 Win Mag ata	
	(32 b) (32 b)	ins. Ch.G. et al 19797 19797 19. et al 19. et al 1	CRC, etor tat Adi	0 016,0101 R 2334 HBU	4101 4101 2007 2017 2007 2007 2007 2007 2007 2	220 tors, etcy tin. 1 4 7 7 7 7 7 7 7 7 7 7 7 7 7	Constantiation (Constantiation)	87" H
	(32 b) (32 b)	ins. Ch.G. efail Ex797 EG. et of B C C C C C C C C C C C C C	URC, etor tar ad tap the contract of tapste	6. 0 46, 61 al R 9 3 4 14 BU	4101 4101 4101 211 21111 2111 2111 2111 2111 2111 2111 2111 2111 2111			2,7 H
	(32 b) (32 b)	ins. Cis.G. efail E9797 EG. et of B	UBC, ETOI Jac Adi Iap Mari O LOSTE	6.0 56, 61 01 R 9 34 1484	4101 3 101 3 101 2 11 200 201 2 11 2462 10 6 6 9 9 20 6 7 9 20 6 7 9 20 6 7 9 20 6 7 9 20 7 9	and a set of the set o		87 H

1 inch = 3,000 feet

Feet 0 7501,500 3,000 Map Prepared by: agreen Date: April 18, 2019 filename: DneWieRadius_Plat Sources: IHS Energy: Midland Map Company; Environmental Systems Research Institute [ESRI];

Ĩ	50			·	A PARTY OF	59 61 t o (1)	HL.			**** *## ^{P1}	- 8- 9 6	4 (1-A)	De Cel	Dias.	-
	Grete) p s	11 6 10	¢ 2 5 5 1	16 ¹ C		26 7		н. (Р)сэл (Р)	<u> </u>		¥~; ;, ~t†		- ይሆ የጋራል 1945 ፈንግላ ካ		isiai Www. France
	de d⊥n,≪	ᆕ뵍ᅪᆧ 음년 음년	Yenti		3	1 0		d a an	0.704	1 7 / ///	in ornson Inte	011 8 11-22-3 - 7 P. cm	15) satie====		10 - 1 0
1250 Il Marvill	Ö,	₩ 47.8	ef and	म्ब्यू क् ज_बर्ड	Nacheszi Fales	C LAsto	2		2	<u>∔</u> `—-`	SHIPPEL.	, gi by r (astroll Fo	ali (Mati	24	4
199 ₆ 7	Rea guidea	ا ۳۲ م نبد که ا			1044 . •	្ម	100 245	Y IL	944. s		286654	San Canadiana San Canadiana - Agai	1.E 101 101	1411 (1420) 5461 5 - 17 6 6 (2420) - 14 6 6 6 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	
, r	្រ ភូមិ ^ដ ្ឋារី ស ភូមិស		16 68 193	25		iciil (Xe) Yeke : 7 7 8	s is an inter NGC - 2 T	19 te 1	FOR	1.6. M		"T.06.Fr	P24.58± •••.5° 3℃ 0,00	- 10 Or	<u>الا</u>
		<u> </u>					1000	P. 1. 14			1	<u> </u>	U.S. Breidly	1967 C.34	4
En.		ार्ग्य सम्बद्ध सम्बद्धाः सम्बद्धाः		1 2.00	Yo	hes Fict. Size Hor	race, i Cat	τ ε† ₽. +iΒ	s Petaka P	7 2.0749 779 (-20 (101)-0	Fe9.972	1.181007 H.E.Yi	កាត់ Gorpi) ភ្លាំម៉ាត់ ឆ្នាំទៅ	11-1-01-0	
EMA	news +	LE RAY		- C.H 	.ștoitz m stra	⊭ី65 រូ⊀។	Mil's	0 ia	95 	j totali	tet., etci		ಟ್ಟ್ ಛಾಯ್ರಾಕಾರ ಜ್ಯಾಗಿ	1 8, 950. s	- -
		t Data	Q			Yofe IDad			۲ ۱	Corena Ver USE	øn (277) .)	W Sa		10 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
-5-	Sthuster 1	5e 96; 14 a		ў. <u>С</u> -Р	0.4 <u>1</u> 9	1- 1 4	•	19.0-0	1	(40 C	····		C PIZZI G PIZZI	002	-
		- - 2 /	Hate Point to				C 07 0	2751:172	н. (20 Shar 54	обе. — 29	COB OF.	2)	i l	- 10- 10-
₽ <u>:</u> ,	killi Ventures escanar	1. AN	N			in E Voleti	eru En. Pru En.	3	<u> </u>		Nillinina (traiters 1	Ľñ,		, †
-1		<u>است</u> الانتر				91477	131 PC		8291 Pelly 3681 / Col 1467 / Col	ຕ) ່ ໃຈແມ່ນນີ				, [64 ,	<u>.</u>
-1	¢€11	POWET3	Chartel PP Flor.	In Vol		whene an Corp		144	5 58 63	Sr e ha				vo ten	
	2 853=1		11 33 4. 3.		12 87	-1-1-1-3 21-1-1-1-3	1111 1111	8.2.4 - T	-/-	<u></u>	THE	<u> </u>		141-0	
[₩	intrest,		OAY HBP		Yofas.e	Norte 2		8787	/. ₂ 05	ુગાદ કોસ્ટ્રેલ્	Netasi 1617	í Trig			ţ
		icum l	1772) - 51921 	10	່ ເລັມໄ 11.	G2677	÷ Keriste	د ایش ا	eno 👘	1937 3000 3737 304 4 317	-		16P)	1. 1.	
		- 67 E	shore 1: 3 Contraction	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	nali. Buliza cale		~ `\	SAD DO C	0 A I I I 2000 A	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	• ± f	CAN TIS CAN Qrindram	ster @et.		<u>.</u>
	1.788	وا ، با هر نو نو به	ود بكتراري		1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -		ړ (Sobry	P54	01
a)	1000 3.2 Mi	ie				30	in sign Hain sat		na Yuted	29		- teisenna	28 4	Sincl Store	
	1 WAT125	ð leir	Leatherneck F	ed and	North L	9-1-2-2-1	¢. [6525	5 Gel sta 9 - 2003		с. с.к. с.нш.	Alberten -	5		
		nna an taon an tao ang Galana ji	Com #134H SH		1	96 92 H L.Yex	e 1	IC YON	95633 19 19 19	idama		L an ab a mus all E		les Pet. d'ac Trait	yur
, BH		π. ι 1		<u>م</u>	1	24 BH 212	*		÷	42.5	Ċ	Com #134H BH	L !	1784 5-31-65	
					1.2.17 /	15		a/ et om	ا حاد که			Surf	1.3.		┞╁
		I-BIT	A State		ан <u>к'</u>	1 1 K	197	ios an		2001 - 5001 - 2001 - 2001 - 2001 - 2001 - 2001 - 2001 - 2001 - 2001 - 2001 - 2001 - 2001 - 2001 - 2001 - 2001 - 2001 - 2001 -		Farth Pa	NBP - PS	rioil Huge	
4.7		inger Gebolier Storet	1. C.1.1.1.1.1	# s	andres - Transa - Frank Transa - Frank	He Jorrs		Λ	y.	3:24 395	-	n Filozá Si	c 41,76 (1996 - Kuno M		а Г
	- Juny	1751015 	- 写具も、10= 「おとり氏」から4日	· ·	Joloperno	, 15		EHA	ر این د-			TEN 10-11 450	ها خ	AND VILLE	
	4		\$15. ⊡			Fannie	diffed.	Yester and	ж . 16 ғ. а	!.			وري. اولا تولي ا	A	÷:
		36			L'H					52	- — ·	rotra Pel	3304	orif Des	E.
ľ	110 113 94	<u>.</u>			915265	Mervile	เกากไ ค			1021).		160 6129	172	(G) T	
	AL 3 14	0 -			200	ूः उपराद कृत्मेद् सन्दर्भत	-		ក្រីដ ខេត្ត	at a set	the state		1	F	
10 P	MALO-	.		2	÷ +	ξ μ3				,	\$			THE STATE	
			ر المحاقق	م الد		116							ángungin ter 2 Million Alfred a State		
Nev	inder v Abbeitrie	2767	127.19 1920 18.5.7 rigg	9-1-68 061	SIS	: 3 27:59-	4193.96 1	1.71.70	Tree is	SR	ษาวิธีรัง	، میسیدہ <u>،</u>			8455 E
1 2	्न र स≣र्ष्ट छ	26 24	S Mars,5logt	te Trigg	194	5	er Mrs.Bl	anch <u>T</u> r		۶	9	(?) ⁷ (?)	Amoun	COSIS RIC	n and fai
	- 54 6 a T	і.	5 - 1 - E C6051			୍ଡି	' 9 (68	1 * %800 95528			د عر ښېن		5-1-71 8-330+4 F	:	¢397I
Ecture	ан <u>-</u>	1 0.20	11 ⁴ 11 ⁴		•	e Ega A	ለት ጥድት	đ	1	at .	វ	18 5 	đ,	~ * 1*	ď
و ملتح	C. and			N .		12 12 13 12 131 6T	ម្មាម ប្រ ខ្ល	6 r			ſ	eningistona:		°₽ig Ect	منبر (م
Kan	×	20.23	e 🚓		-6	ه−ي محج ان ⁴ وي	4	جی	Man	្បាននៅ <u> </u>	4		2. Here	لد گان گرم	s.
1 ²			Į.	2 6633 (JQC	,etal		-		41	8	0 97 999 1 40 7 1 40 7	220	cret	Rossial J	i L
	Marsi	10 70 ***	.4 <u>م</u> مربع	0 69 747	Ъ₽	a de e	.+				પ્લાસ્ટγંર મધ્ય પ્રાવસ્થ		بالمجرح ا	191349'2	
يبرينا	ម្នារ ខេត្ត	Re LA	19. 32 Min	Off, et al.	N Free	нар им	45 Xii 41 - ¢	n. (7 \$6.9 2334	n CU Braile	erosea (;) 7 - 1 - 34()	ေ <u>၂၀</u> ရှိ(¥ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~ ~		©‴₿
Ng Trea	##	איבוי	060573		N I	BLOSFE T	l I IE rs e.	H B ¥		£ 88336	0 637	1 th	المحير ال	۰ ۱ ,	
	مين. موجير	** *	4		/ W 🕄		l Estanador			L	ર્જે	21 12 Min.	< 1 , 1	Tatao	lor
		¢n1	12.5		· • •	7 Y					us >	469707		-	

1 inch = 3,000 feet

.

Feet 0 7501,500 3,000

Map Propared by: agreen Date: April 18, 2019 filename: OneMileRadius_Plat Sources: IHS Energy; Midland Map Company; Environmental Systems Research Institute [ESRI];

eu T		THE REAL OF 13 YOU WANT	3964 % HONY 1601	141 MID	10 1/4 Pra	4 (s-A)	, Cel Dist.	
	BR1419 31 93 410 95 923 6 196				10 Mar Tates Pet	Nowbourny 045		
0		an Ningaran Mingaran	(7.10) 1.7 	ALL-ONICA	All Carl	3'A TEA)	A # 18-A 2 74-	14
ю <u>,</u>			2007973 (1#2) 	The state	10:32	Angenderi Angenderi Angenderi	1.5 WI 1. 2006	ŢΗ
6	1811 14 01 0 11 17. 18 0 1 10 11 10 11 10 10 10 10 10 10 10 10	ie Unterintigenet		Yo ter root		"TOG.Frd."	Pit Serelie Jet	Ì٨
	al Citras reduce	A; ††ji sine G ΩΨΓ	w timbarar	Cinital Dilat	Zapinrani Fel. 4/2	U.S. · Uskazena C	rp.) COL	
	11 all.) Mert west Grandwing	C.H.5+0itz 3	186 - 197. Skart 1884 1955	16785 -910 +8P 0065	(191)-00- 1910-100-	H.E.Yotha	1920) 1920) 1920, 1920	1723 DAI:
472	COLUMN LA CAL	C / D IS W	s 4 Mil's Yafaa		icoronado exercitor	(ALC ARE.) (TXQ) OUTES CEA.a	Pipinos	1
Fili-ii UTAA	thater the	2 7145 04 9	St IDaor I		65177 600 Cper-		(2) (9-1-2016 (2) (9-2-2016 (3) (9-2-2016) (3) (9-2-2016) (9-1-20)	
	10.942 - 2.4 Canachres	City - K	9	1994 20946 (98-6	20 Shimaraka	COG Op.	20	
<u>.</u>	CEC 797		H.E. YEI CT. 19 TOLE			storbro Lin. Introtz	41	*
	DIVERSION CAUL	The it is	93677 93677 2368) 2368	17930 ATT - 5 C	and shares			4
a∳'	10310 10310 10350 10350 10350 10350 10350 10350			1			Vota 1	
4	L'I AF OAY	H.E.	Personal State	CC387	H.E. Netres)	(Trjqa Fee	rily Tr	Π
		There (duly	C2677	turinaeno Ruebo				
Mari	Transfer a WAY 2 Strate	14068 Pres tales		300+b- Cr1+ 20	97. TO 11950	chillis 44 Fater	Perl. Colari Ville	;
N.		14 14 144 14 14 144	2 40 FD 2304 4		://///₩ • 00 -		Sater HI Fild Car	
3	A Day a Mile (Line to) Limb 060	Hilwseurne		HE WORDS THE	B H.CYcies, etcl B H.CYcies, etcl	Jeriopene Co.	1 19:005 Steel	
	Leatherneck Fed		75735	9563 9563		Araterbu	l yetes Pet.	
.85 		1884 - 1965 Yuders - 75 1884 - 1965 Yuders - 75 1884 - 1966 - 1967 - 197	W NUT OF	Brebenne Ø	I CONSCIENTS	Leatherneck Fed Com #137H BHL	1 Hourse stag	
		- 212.10 Jrd. - 200 []-2.17 /]	bias Carrier		71.01	Sinn Feiligen Yater	1.3. Iet 92 192	
	A start and a start and a start				12 1 2007 13 1 2007 13 175 385	Datath (Pauline NBP	T. 85 CIOIT HUCK	
4) A 5 C		n an Ersenhauten, Fran 19 9 St		RHI		Black Marek	1- 1- 1- 1 MA	5
	Annual 21-2016 A-24187	GD.		3		C NOT LODAL		
	A Se	2 41 X 10 10 10 10 10 10 10 10 10 10 10 10 10			32	rotra Pet 's	The Fred	
	TU ISM		(Mexileurin)	241	CHERRY CATP	160 160 161	19473 (1+ 175)	
-	MOLAND *		Gellg Bater		ilandi ditene sang ing kar ditan ta 1 Milan			
	Trem		ن . 116 میں میں میں ا		te á-			
-6	3 15 66 1 27 68 427.50 STOR	2 1156 17.46	4 27 36 3 191 X	70728 Het	SPH 064	7.84 184		ass f
172	and Mrs Sloathe	17 (174)	T Mrs.B	anch Trips	9-1-48	2) ⁷¹ 0		r _∓ atbeg
2em a	17923 51 11600 • Fed Const 000572		(O) ⁵¹ 9 06	1 601111 9572	0,90 ja 2	i ⊊~i Istat		¢785
Loture	jana ana ana ana ana ana ana ana ana ana		Egga Amer.	d f 5 €	- 1 2 4 - 1 2 4 	s	1 1	8
			TO 12150		10	62]72(57070) - 19-242(/	\$ 'Big Edd	منز ^م رکا
2. 2	28 0 20 20 8 12 12 - Aux 20 7 - Aux 20 7	ि तन भा ⊤⊮त Int CsC,etal	is inte	S NGI	1.6 1997 16 1997 1997	165 F 106 37 h	Horseist,	15
M Rope		169797		0	STATE DUSING YOU	erg etty Sidi	07 1 [0max 12] 1 [01340]	4 4
¹⁰ ويو ريز با	Ber Galager - 12 Min C	G. et al BZM	NORGistal is all Hap the c	n.O3G.4101 Ra 2334			. Der Wilm. Frag, stol G	20 ⁷⁷ ∦3
N.	060573		SOSFE TA	164	440434 L (2)	"Like	arriar'	
					මි			
	12 S	1	U.S		<u></u>	- 1969707 [3-**	* 16-	

1 inch = 3,000 feet

Feet 0 7501,500 3,000

_ /

Map Prepared by: agreen Date: April 18, 2019 filename: OneMileRadius_Plat Sources: IHS Energy: Midand Map Company; Environmental Systems Research Institute [ESRI];

Eddy	Count	y, Ne	W W	exico
Contraction of the local division of the loc				the second s

,

2	half acroal 6, 4.754		THE THE THE TO OTHE	5986'to 11812' 0'	(4.2 Mil.)	BC	4 (1-A) Hù 🖉 🛛 🔘	, DelDisc sinte 01,G. 106 Note -₩
	nd)90 36 34	15 19 1 Venture		10 (T 10) (MD)	QIH-BZEN	17 Williamson-	Mowbcarne 055 011 8 27:7013	6 Westally B
) O		70 40	INEL 24 Mackenzi	(2 2 Mij.)167 Marbob-0-6	Mebourne III-LI-Glack	J H.Hill ?	3-A (T x0) -	₩ (2·A) 2 3N
Q4/1		Kaser		Yorrs HAL 	Yatas.Fod.	5 DA6-1564	Senederi Shilkamoon-Fed	TOG - Fed 9 AN
571	AC (8 ¹² 18 1	TO 1078 1 6858	C Marathonia	1070, 01165	Yutes Fed		"TO.GFed."	P34 Beselle - Frd.
12.014	of (Strata fr	adl	L DI TOUBOO	Mewbourne'		Explorers Pet.N/2	U.S.	orp.) COG
5)IL	960 illi Ventures Osa797 Jampan Z	Merbourns' 91-2016 16570	COH.Stallz o	TES PET Glock HBP 1165	101€3 Pety H8P 01165	(ND) -CE	H.E.Yotes,	eto) 115270 1 03677 2,500.00
272- 2.92	Fod Abstr.		1 Yafes 7 El 3245	N H Wills Yates	r -	_ j Yatus Prt., et al (Caramodo Expl.) HAC	(HE "dtms) (rxp) (ryptes Ferd.	tromo
40 n)	Schupter plat	ner Diempic Dil	r ∳ n/4 1-20	5 ¹⁰⁹⁰⁷ ¢	1 1	03677 COG Oper. 1:1:2022	WT Disc DiP	8 1:6571
ip 8°,	- V-ckeret	24 Unsa Use	ا، - +	9		20 Sharbrofn -	COG Op.	21
<u>,</u>	LLJ Ventures 42	1 Thene		101018 Shorbro En. H. E. Yates /11-2072	51-H Stephins		Sharbro En. 1-1-2022	411-
	Mewbourne Gutt	13 51 010		09677 gtapena Corp.)	Mesa Refailer Stebbins - Fe	ra) Id "Stebbins"		
õ¢'	116570	10 3504 U.S.	Cilis-Fed	U.S. SSECTOR	DIA 10 - 23 - 62	U.S	U S	Yotes / Gazelle Bill 17
75.1		OXY with flug	H.E.	1 COG OA 1+1012 Shorter C ++ 1012	C06 Op. 11 2012	(H.E. Yates)	(Trigg Fo	wily Tr.)
24	PTC 201 Lever	+ 17721-11707	Per- (de)	openo Corp.)	(Jalapeno Corp	Mantano Saya Paunate	U H. Trigg HBP	totes fet.
- The second		Strata 22- DXY) ? (iberty) H	134868 19 K coles		Sharborn-1-1-2	022 10 11950	O/A 5 15 64 Y oter	Yajes Pet.
t we	1287 - PERCE	25 (FIMI)	m DATITA	2 00 103385 07	/_:::-	- 29		Socor BEE Pas two
3	CALL MILE	Liberty DEG	Mewbourne	Yetes Pet etui	A E Yates Yat	teoni H.E.Yotes,etal etal: H.B.P	Jalapenn Co.	fiom 4530
(5)	STUDETH STUDETH	10196 C T0199521-H 1 T/A 9 6 89 "Cee F perf "	S C Leatherneck 3029 Fed Co	3499 4	9-1-20 956 956 34	95 03677	0473817	Yotes Pet.
85 . 88		Wenzen	2014 H #138H SHL	TO STATIST		1 1,1 1,1 1,1 1,1 1,1 1,1 1,1 1,1 1,1 1	Leatherneck	101784 0/45-31-66
	1 5,596 DA991 - 04	U.S Wennut	- 04, 11-10.77 /		57666778 3	····· 43 ③	3029 Fed Com #138H BHL	। । দু স্কু
		A Sec	La DYA INON	1075 149 -	•	93176 390 99	(Payline HBP	Trigg etail Huber
4 y2 LG	- 16eo 1 - 16fore - 110101	B 15/0/	ID THE Laborer	Formie Yotes	Comport		Hlack Store fram 4500	to T. Mus
	tinepered.	9 r 2m8 7 5487 \$15 55	SAR Co.	S Y	0412 19 59	5	to T Mise	Come Later
		36	yotel	SI Tamie Loured		- 32	Yotes Pet V2	33peno Ard.
	TD 11896	S S Sm	912005 9551	(Mewbourne)		O4B/S autor are	H8P (14928	0479917
-	MIDLAND			Gelly Bates		black Stone totes Fed om 4500 Site Disc to Miss		
	State		₩÷ +÷			u.s		
15	2 25 66 1 27.83	6 ¹ 27.61 3 ¹ 27.60	W 2127.56 127.46	a 27.39 3'27.31	2 27 20 1 27	112 8726.51 3726.83 SDDI 06 0	272638 7 1636	17676 372537
Men E/2	Pourne de 20	R.S. Trigg 9-	1 60 060515	3 6 ⁺	7 ⁴ 0	5 5 5 60	n d-	- 0.0.0.0.0 5.9.1.60 060915 IRich
	15095	MES. BIONCHC 9 - 1 - 60(040677	2)		1 60(2)	060515	Am S∕l	
Excon	Po 20	11 ⁴ 11 ⁴	10 5	Pan Amer	10 5	124 11	10 ^{1 3}	
				819 Eddy Un 10 12150 04 12: 4-88	•T	(2)	eatherstone) 5-10 2021	*Big Edd
Brand	191 16 40 20	· /* ***	- 1+ H -10	13 ⁺ 14 5	15 16 32	Minis Ha	06G 32	
A.Kerry	Flat."	132 A	117.066,8101			et àt 3-13-2 69707 Oudley G. Use	ozo ery etal	07 Cowon (2) T01340'
14	20 78 Bos	$-\frac{1}{10} = -\frac{1}{10} = -\frac{1}{10}$	6G. et al	n. Obg, etal 30 Mi	n.O&G, et al R	ichordson Oil 132 M	lin. Lust	32 Min. ObG, et al
187		Eddy Unit HUP		060572 K 1	казан НВП -	069550 0697((1)		067145
18	Com. 1 40.20	15	erraa (Med	Berço Big Eddy			2 32 Mill.	Big Eddy "
	ока (Риз) фл	i	- S. A.	U.S.,		U.S.		1,
			atal A	32 Mm.OQG et	ol ja	12 Min. ObG, etal/ az N	tin.086.2	latadı
	<u> </u>	SZ MIR UBU	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	<u> </u>		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		

Veri	nson Shuckellard (Remyda) - G For Angel 1 - Ada Talido - O- u an
1 050 TT AD FOR THE TOTAL	ar TOG Fed G
31 51 - 51 - 51 - 51 - 51 - 51 - 51 - 51	Del Disc Siete OLG. 105 Red.e # Siets
And go 33 1 4 0 1 1 LLJ THE LEAST OF THE TRANSFORMED OF THE PER NOT THE TRANSFORMED OF THE PER NOT THE	16 Westallin Brief
(2 2 Mil) 16/ Mondarna (1 2 2 Mil) 16/ Mana (1 2 2 Mil) 16/ Mana (1 2 2 2	100 (1-AJ 2 3H - 2)
any is the total of total of the total of the total of	TOG - Fed 9.446 101
THAC 68 12 18 1 TO GRA MAGE 29 1 CHARGE 199 1 CHARGE 199 1 CHARGE 199 1 TO G.G. Fed. 1 S. W. M.	Joorgigor 2012
of (Strata frad) Bamp Yates Pet Mewlourne' Yotes Pet Mewlourne' Yotes Peters Peters Peters Via Users	Corp.) COG LCE
HBP HBP (ND)-05 HISTO (HISTO (HIS	0.3677 2,500.9 D/AI
At Ford Abstrill Correspondent States (Gorean de Evel.) (Vices ford (1 1 1 1 2075) A United Evel.) (Correspondent States) (Corresponden	CrownOff 91-2016
icis schupter etn. Cos Oper. Ale to the state of the stat	116571 1021 8007
00 10 10 10 10 10 10 10 10 10 10 10 10 1	21
050797 (H.E. Yates) 1-2022 (H.E. Yates) - 2022	4H-
9-12-7016 Howers scalo 10-70-70-70-543 Lee Fed. Stebbins Stebbins Stebbins	Votes
0 H16570 - TD 3504U.S Ellis Fod U.S Ellis Fod U.S	Gorolle
K, Bull-o Jahres - + HBP 27:14 Triage - + H.E. Shorts o Entertore	amily Tr.) (rigg.etal)
12 - 12 - 12 - 12 - 12 - 12 - 12 - 12 -	
	1 Yoles Pot. 311
2 (1 1 25 (More See and)	28 Histack State (
Bull D/A 2196 (Control 1 - 2 Control 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2	
85 S S S S S S S S S S S S S S S S S S S	Yotes Pet. Pouline Trigg Vut
In the state of th	1 DIA 5 31 66
Part Attack of the Devon Person (Paul	Pet 12 2
4 1/2 (100) 9 (100) 100 (1	Corpetor
fram 4500 for Mile John Star Star Control of Star Star Star Star Star Star Star Star	And Yotes
Folling 36 Hun Parsel Farmer Loufed Pennistik ed	Theno Ard.
To 11056 Minerokiny Corp. (Hewbourne)	0470017
AND Getty 04825 Bluck Stone tores for the form	
m Miller work to a work the work with the wo	IC particular
16 1'25 66 1 27.83 d'27.60 1 2'27.56 427.86 427.39 3'27.31 2'27 20 1/ 27.12 d'26.51 3'26 83 2'26 68 1 16	6 47676 372632 272
Mewbourtle $R S. Frigg 9.1 co ocosis 7E/2 d d zo zo s $	- 3000 a 355 E
Har Mrs. Blonche irigg 17095 9 1 - 60(2) 0605(5 5 060572 060572	1.71 03926
Testing red com. 10 20 12 11 10 51 12 10 51 12 10 51 12 11 10 51	125 - IT IT
To 12150 DA 12 0 68 (7)	Big Eddy
Rear burton 16 00 20 13 10 11 11 11 11 11 11 11 11 11 11 11 11	Minte 143 1 15
a Kumper 2 069707 Oudley G Ussery etal	2) TUI340
14 10 20 18 132 Min. O&G, et al 32 Min. O&G, et al 32 Min. O&G, et al 32 Min. O&G, et al 812 Min. O&G, et al 132 Min. O&G, et	✓ 32 Min.OaG, et al
060572 1 HBU 063550 063707 30 060572 060572 060577 0 060572 060572	067145 AH PRB * Big Eddu ? (Big E
	SAL <u>INTERIO</u> .
	'Y Natadon
32 Min. OAG. et al 060572 (all sec) 060572 067145 063516	RESOURCES COMPANY

ļ

V 911- 5 d 64 97 14	65072		49 (36)	IN DA		Doyo Op BHL	NerseyLip	arathon	Yates Pet 01165 BUL	T/A 1379 J.C.W.	liamson Sha (Ren t-11 to0 ₹01445 701	skettard giggi	1N-824
TY YOR	050797	(73) (73) (73) (73) (73) (73) (73) (73)	0 10924 61 10924 10 10924	H-BIEH		Marathen_	Typhs Fee	c) ș	Yates Pet. Williomson	BHL Fed	19	Fed	Yo Ger
i i	internation 38	4554 — € ³⁵ 6 €31 €16 €3 €31 € 6	675 538HL	\$\$ \$	(0)	4 4 10 4 4 10 1.8 Mile	un Oir/0		Yotes Pet	Mowbcurne	0554771 .	G. 5 ₩'	Siet: Huro
0	Cred-U.		P Ventures			Yotes fed. (2 2 Mil.)16	Mohou	1	7 Williamson- Fed Bitt	011 8 27-7015 3-A (TX)	∦ 16 αيرز∷⊈	AJ 2 3N	5
nmrm GNI ::		636 070 044 51 €	"RUSECH				TX0)	nd. 5	Yofes Votes	i (2 Mill Field	1000 1007	illiamson Fed	
1	AC 612		10 1 Serv 10 1 73 828 1455 2917	é (Nearathó	Miwbau 1-15-1070	0165	HI YE TES	F C	MIRACES-BC	"T0.6Fee	P34 Buse	The sol	
17.01	4.41 21 97 ji	rata fred	Bul	D. TOINGOO		- MBWIANUEDE	QIH-MP	(Explorers Pet. N/2	Luciane	ng Corp.)		
BHL	968 (LL) Vi Johnson Z	0197 91-2016		Ço H.Ştali	Yates HBI Iz OII6	Pet. Glock P 5	Y0*es H8P 0116	Pet, chai 5	(ND) -CE -69	H.E.Yo	tes, etal 03677	11-1-2017- 115270 1 2,500.99	Fed. 1011 D/A1
(¥2- 0.9).	Fed Abstr.	÷	P40	Yorge	3245	NH Wills Yates	ſ	/	Yotas Prt., et al (Caronnaa Exul.) 	(HE'dtes (TXO) (Votes Fe	-4-A	Crownon	
Fern) icus	Schuster	10 101 10 101 101 101 101 101 101 101 1	Cont corp.	r¢°ni ≷	4 ⁷⁻ 10-63	(USU) 4			COG Oper.	12 20 73 1 A. A. A. A.	(XP/8) -19(22) XP(1)	800 m	
8°, 01,	10 387 LLJ Venture	s Al fitall	, -	r 99 Promity		COG Op.		ndor N/ns	U Sharbroth	COG Op. I-1- 2022 Sharbro Fr	21		ý.
	050797 Mewbourne	Gatt			(H. E 0	E. Yates) ^{11.2072} 9671	b ¹⁺⁴ Mesa Ret	nilers)		1-1-2022		411- AHG	
-	9-1-2016 0-1-0	TO DA 3 TO DA 3	504	Yotes Filie-Fed	t to log	peno Corp.)	Stebbin TD1402 DIA 10-23	s-fed 3-62	"Stebbins"	1	1 N.A.X. 44	Yotes /	F
75-4	2,850 2	OX1	U.S. Nem plug (sen D., sta	- TOI227	U. I.E. 19	5. 06 0p 111017	C06 Op.	U.	(H.E.Yates)	Ciria	Formily Tr	111 - C?	
4, 6H 17 M 26	No TO TO	+ HBF	1 29. 74	THAC YO	luciape	HEYONA etal no Corp.)	(Jotaper	· · · · · · · · · · · · · · · · · · ·	IL 03677 Monzono Sona Pounde	J H. Triggedu Erd	ine ine.ele	si) otes flet	
1. (1)	Libert 25	• (0XY) 2	strata 22.	134868 134868 135,500 1 4	t cates robuic DD		Shørborn.	11 2022	70 11950	DIAD IS 64 Y	stes Pet. 6		
E S	in the second	25	Along (-sc)		ουν 10 ² - 2 - 2 5 C	₩ ¥03385 ↔		2	9	C TUPE	28 07	Fine (wes)	
3			Liberty DEG	Alevibour	<u>• Ĭ</u> ¥	tes Pet, etul - A -1-2005 95635	A E Yata A Steppin	Pet etal	H.E.Yotes,eta NBP	Jalapenn Ci	5. I 44 I 4	0m 4500	
65 		And "Leets	TIAS 6 89	Ca Leath 3029 F #208H	erneck ≂ed Corn ISHL	3499 Ye - H E.Yates Hotes Pet. 1	+E Yater Brebbine	95635 3499	Usiciapeno Carp.		Yote Poul	s Pet. ine Trigg	Vat
. өл	Lange De La	1	ganion .	Seeburgs	N 42 N		· d' LE Vater Stebbind	4 337 5775	<i>us</i>	Leatherned 3029 Fed C	k 0/A5	3 66	
	- All and a second	() ^{'''}	-	Mentbourne Liberty M	A. 1	Devon 14700140	¢ ¹ 10	3	Devuri 1 2007	#208H BHL	et fo	Huber	
4 ½ EG		(w) Y IGeo Elzetola (Stote)	ioca and	The yold	enter H	L Yores E Nia		66	176 390 🧐	o Mack Sta		from4500	
		1014117 Ki 16 9120 1914/00/ \$	11, Inc. 18 7 5487 15 65	2 ³⁰⁰ 10	apento 144 20. 1		DAIZ 19 59	***		fram 4500, to T Mise			
	Folling	36		- Start	173817 1 "	Fannie Loufed	1.65 6.02.2	Fed	2	Yotes Prt	- Jala-	Led.	
ł	YD 11896			19	2005	(Mewbourne)		Minero D4	n inv.Corp.	H8P 04828	0470	7 (F325)	
22	MIDLAN	40			1 8ai	lly tes		10	4500 Stone Pores Fed			1	
	<u>.</u>	Statz				ιj •6		Ľ.	·				
is Mev	ja zasida i i r vibipur ne	27.83 6°27. R.	61 3'27.60 i S. Trigg 9-1-	2 27.56	27.46	a 27.39 3'27.31	2127 20	1 27.12	SRBI OEG	2176 68 11	1.16 1.16 X	5 3726.52 161 1 8a	- <u>7</u> '7 255 Ei
E/2	:# ; ;5855	40 20 5	s. BloncheT	T7 [278			7" Itonch Trig 1 + 60(2)	8	5 9 1 60 060515	ญ้ ตั้	Amoco	50 C 2915 (Richa	7' ndsor
iusti.	L Fed Com	10.70 IF	060572			e oe	10572 18	5	12* 11*	* 5	5-1-71 H33826 1	- n+	03926 N
Encor English	1)** #1					" Pan Amer. Big Eddy U 10 12150	nit		F	entherstone)	1 1	`Big Eddy	سيز م
Bran	n) di la la	ao 20 13 ⁺	*6	·	i 1	14 12: 4:68 3 ⁺ 14 5	15+	(2) 16 37 Mi	nu u	1	32 Mint	ia 3 +	片
A Kin	Flat.		132 Mi	n.06(G,etal 9707 N				e1 (1 06 970	1 3-13-2 07 Oudley G. Usi	ozo ery etal	ef of R c 69707 1 C (2) . T	385,etal / awan D1340',	10
14		0 20 - 18 - Bass Ent.		G, et al	32 Min. 0	AG, etal 32 M	in OaG, et	at Richo	rdson Oil 132 M	in. Eusky	7 32 Min	OAG, et of	~ ^ 172 PH
0	AE # wo	TOSTIO	HBP 060572	\mathbb{N}	060	1572 74 1 BErgo	HBU		69550 0697		, •	067145 Bin Frank	i ar Ibre
44	Com	40.20 15 		\mathbb{N}		Big Cady Uf			હિ			19 E 00 9	(96) (14)
	ан (РИВ)	10.62	U. S.			U.S.,		┼ ╋───	U.S.	- 061	 }₽	ade	
1	ب ^ع ر	3	12 Min.O&G. 060572 ^{(a}	etal Il sec)	\mathbb{N}	060572		32 M	lin.066,etal 32 N 167145	lin.O&G.			
· - E	p. anto						ID C Base)	<u> </u>					

	A	e ji i ći	BEER, LIGHT SCOTT	166	ALMI J	Pro fa Pro	A	Cel Dier	
				<u>3969 Politik</u>	TPILO a		្រឹល់ 🖓 ប័		e i
	PROFILE STATE		Sal TAC			io isar Yates Pet	Nowbearing - of	15 6 77 1 '0' D	")
EIL M		" "Theniures	·			T Millionsort	A 17-202		7
୲୭		6 4	Ligo Weeterzu	Astos 00.	AL U - MALL	HURL	9 bwith	BY 200 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	¢'
10-MIN		T Ale Scerie			frix@F	TD:232	r (1990)) Forts	LE ALLADER	14
197,5	TR UNCLU GA	. t: 5. 7				5	anta Consecutions - March	TCG-YCD. P. BASS P	5
[r	ั้ส์ยี่ในเดีย ไ	3 1 1 TS	o () "1 S fatarenes Side (*)	(***), 1865 (************************************	Yn tyn 190		р В Чтог и 19	Pl+ Poserie -	
-	up in 1 ¹¹ 21	IC GR T SARE			Ð	- 2 5. Willight 10.74	1,500.***4." Als	Jun Hoper - Ziet	<u> </u>
H.	A Prese Front	1	B	h h h h h h h h h h h h h h h h h h h		Frainant Fet Sit	L.L. alcono a	Loren 1 EQU	r 5
≥n.	il) Mint and Man		Yot Yot	Tes Tot. Start	Teres Pet	akal	H.E.Ygie	s that interes ?	29
2 40		Groff.	C.H.5+0872 - 20	1155	1 0 10 10 10 10 10 10 10 10 10 10 10 10	Lash-us	Time Pres	13877 1,950 B	ŇĚ
672-	Containing the second sec		- Yolfs,	4 4 4 d 's		Tailes Privets;		. Rominos	
1		(2) 0.40 (2) 0.40	2.2	70780 16907			W Factor	-A 191 2010	
1.57	Se sk.		10-45 Dat 20	· · · ·		\$49 Cpu-		PIZ2 660	
- هت		CH33.366	and the second second second second	a <u>2016 c</u>	and T	20 Shore 2022	4 · 504041	2)	
	10-912	al Tampitres *		Car Car of U	ang si 192 si Si kasa na na n	21.3.124	COG Op.		ú-
* :-	allu Venturch And . The Lorendon	1. 2.310		TO LES SIMPORE En.	31000.0		trante de		۳ ا
				A.E. Yol city in LOLD	1 Mar. 90	(1) (r)	1942 10 213	er er e lanere e de la	
	9-1-1010 Johnwerts		Bh .	գրություն անվերություններին՝ 2004-ն		Srestorna"			
-1	AL- 10343	er fan	ALL VERTS		- / we			Yo MR	-
	2 853-		Configuration	1.7		IKL	V.	Searche	
15		OAY .	ιά, Η.Ε.	1 202 00 1 2 2013	CC0702	H.E. Netres	Trian		
<u>e'</u>	all a little	18-	LINE TOTOL OF	o në veretali		(1) IA 63617	17994 1997 - 1997 - 1997	ir ir igi sidil	
	A CALL STORE		a state i Cault	C2677	Corba	37-7 TOPO 37-7 TOP OF	1 1 H	il intes fit	
	2	shore	6-63892563 84049	LE 1311	500+1-0 GP1-1-1	077. TO 1990	GA 16 44 18 1	er ert dinen Tak	
mail			15.00 Grame	- 1935 - V				D Teras Pri 20 0	
N.A	10 · · · · · · · · · · · · · · · · · · ·			1 44 70 2304 4	(· · · · · ·	ta Coulterf 🖤		**************************************	끮
5	25	(MATT BOALL		30		_29 ā	4 — 164997 "B"	28 Stock Stone	۲Ż.
זין		Pislim to OSU	httiw begar ve		101 C 00 (100 C)	stal H.L Yeres, E	Leatherneck Fed	ាម ្ល	1
E.	1007192 2/2000	Leatherneck Fed		1 25735	10989 B.1.2	9387T	Com #223H BHL		
	616 6 - C - 2 -	Com #223H SHL	P	H.L. YAND	ICTING 34	57 Hatteritt Dora		A Police Pet.	Yest
	A CAR CAR	17:00	14. 85 Yorn . 14.				1	12.1784	
1		100 million	- Carponie - See	na an sinar an an	E.yetos	35 1 2 2	Surt	E C]
			E T (264) (- E 17 /)	115	AND CALCUMPT -		the second se		
	N 1		Service of Street				And using Yorks	Per to the	
	- Inter	1 Sec.					Calle Paule	Per 72 TH	
		All and		HE WORK SHE			Column Yate Doub Payle Ni Cate	a Def Y2 The state	
4 Ka 50		A State	A DE AND		200 - 11	93175 385 -	Courter Yote Courter (Pourte Ni Class Start		
4 Ka 50			Lingerno				Diack Steel Clark (Paule Ni Clack Steel Clack Steel (Try from 4500)	ther Y2 to To	
4 K 5,0		114 117 117 117 117 117 117 117 117 117			CONTRACTOR	93172 332 -	Black State Calle Pagin H Black State Call State	And Yorks	
4 Ka 5,0	Antonio C	10-14 1-15 1-15 1-15 1-15 1-15 1-15 1-15 1	and an A			93172 332 -	Callie Vote Note Provide All Callie Provide All Callson Assoc	Linia-	
4 K. 40		10.14 1.15 1.1.10 1.1.10 1.2.016 1.2.016 1.2.1407 1.2.15 1	diaperno Gillione Constanting		BHL Ye Yang Sill Fa	2) 1 2007 93172 332 = 32 32 Perol Inst. Carp	Contract State	There yes rively and the second secon	
4 Ma 50		7.11. Inc *2.06 +5.407 \$15.91	And	international	BHL Yelen Chil Fa	2.1 2007 93172 335 = 32 rerol lies, Carp	Constant of the second	Thomas and the second s	
4 Ma 6 D		ζ21, he ζ21, he ν206 / ζ40/ ξ/5.g	diada A	International International International International International International	BHL Velence Dit Fa	S. 1 2907 93172 3325 - 93172 3325 - Bank Carp Suprimers Steere water tark	Constant of the second	Thomas and the second s	
a Ke Ki	John States	ζη 1. Ins ζη 1. Ins ν 2016 - γς 4407 ξιδ. gr		International In	BHL Velence Dit Fa	3172 3335 - 3172 3335 - 32 	Constant of the second	Thomas and the second s	
4 Ke 1900 1911	MIOLAND S	ζή 1. Ins ζή 1. Ins ν 2016 γ 5407 ξίδ. g	A A A A A A A A A A A A A A A A A A A	International In	BHL BHL Yelener yit Fa	3172 3335 - 3172 3335 - 32 14 32 15 16 16 16 16 16 16 16 16 16 16	Control 3	The Proving the Pr	
	MIOLAND STATE	ζή 1, log ζή 1, log ½200 ½20	A A A A A A A A A A A A A A A A A A A	Anterna antern		Status Status	Constant of the second	The Y2 The Top roll The Top roll Top roll	
	MIOLAND S	1 3		Line and the second sec		3172 3335 - 3172 3335 - 32 Perol link Corp Saper ing 4320 ing 4320 in	Calle Play Black Steel Higher S	A Det Y2 A Case of a Case	
	MIOLAND S.	1 1		International	AND	32 32 337 337 337 337 337 337 33	Calle Play Black Steel High Aspects High Asp	ALC VIELAND	
	MIDLAND S	1 1	Trase	International Alter and a second and a second a		32 32 32 32 32 32 32 32 32 32		ALC Y2 ALC Y2	
	MIOLAND S	11.00 7.11.00 2.206 / 540 505.91 505.91 1.5.5 / 1.50 Mrs. Stanthel 9.1.50 1.50	A da and A addaption Co. Co. Co. Co. Co. Co. Co. Co. Co. Co.	International Autor A	MU BHL Viteratic Fa Mu Viteratic Fa Mu Mu Mu Mu Mu Mu Mu Mu Mu Mu Mu Mu Mu	3172 3335 - 3172 3335 - 32 32 32 32 32 32 32 32 32 32		AND THE PART OF TH	ייין דיי דיי
	MIDLAND S	11.00 11.00 12.00 12.00 15.00 15.00 15.00 15.00 15.00 10	A diagene Co. Co. Co. Co. Co. Co. Co. Co. Co. Co.	Converse Line of the second se	10 10 10 10 10 10 10 10 10 10	3172 3335 - 3172 3335 - 32 32 32 32 32 32 32 32 32 32		AND THE PARTY OF T	11 5 £ 1 5 £
a Ka E C Mey Zama	MIDLAND S	11.00 7.11.00 2.206 / 5401 \$15.50 15.5 / 1502 Mrs. Stantel Mrs. Stantel Mrs. Stantel 1.602 C605T2 1.1	And A	Hand Americ	2017 BHL 1017 1	S. 1 2007 9.1 2007 9.172 335 = 32 persiles, Carp 2007 107 320 = 500 free 107 320 107 30 107 30		AND THE PROPERTY OF THE PROPER	21) 5 £ 7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
A Na GG T T T T T T T T T T T T T T T T T T	MICLANC STATE	11.14 11.14 11.14 12.14 12.14 15.5 14.5 15.5 14.5 15.5 14.5 15.5 14.5 15.5 1	2 Pras 2 Pras 2 Pras 1 Pras	Anter Jan Start		S. 1 2007 9.1 2007 9.172 335 = 32 merol lev. Carp 2007 films. Strone suber (27) films. St		AND A STATE OF A STATE	
A Na GG SG SG SG SG SG SG SG SG SG SG SG SG	MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND MIDLAND	ALL AND ALL AN	Andream Angeler and Angeler an	Constant Consta		S. 1 2007 9.1 2007 9.172 335 = 32 merol les, Carp Mark Stone Suber (27) films, Stone Suber		AND A STATE OF A STATE	
A Ka SC Meyer Erection Contrast Contrast Contrast Contrast Contrast Contrast Contrast	MIDLAND MIDLAN	ALL AND ALL AN	2 1136 An and A Sublement CCS. Statistics of the second second second se	Constant Consta		Sell 2007 93172 335 - 93172 335 - 1000 Strone suber (27) 1000 Strone suber (27) 101 St		AND	
A Ka AL Meyer Al College Al Colle	MIDLAND MIDLAN	11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2 2736 2 2746 2 276 2 276 2 276 2 276 2 276 2 276 2 276 2	Constant Consta		S. 1 2007 9.1 2007 9.172 335 = 1.1 2007 9.172 335 = 1.1 2007 9.172 335 = 1.1 2007 1.1 20	Clark Vite Clark Vite Clark Vite Clark Vite Clark Vite Clark Vite Clark Vite Clark Vite Vite Clark Vite Vite Clark Vite Vite Clark Vite Vite Clark Vite Vite Clark Vite Vite Clark Vite Vite Clark Vite Vite Clark Vite Vite Clark Vite Vite Vite Clark Vite	AND A STATE OF A STATE	
A Ka A C B C C C C C C C C C C C C C C C C C C	MICLANO Sand Case Sand Cas	11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2 2736 2 2736 2 7736 2 7736 2 7736 2 7736 1 2746 1 2746	Constant Consta			Clark Steel Clark	Def Y2 Tory risk Cap risk C	
A Ka SC T T T T T T T T T T T T T T T T T T	MIDLAND MIDLAN	11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	2 2736 2746 A BARNER 2 2736 2746 A BARNER 2 7736 2746 A BARNER 4 2 7736 1 2 7746 1 2 774	Alter Start Start		A Constant of the second of th		Def Y2 Fig riol Auge	
A Ka SLC Intervention Country	MIOLANO MIOLAN	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	A diagento a diagento Co. Co. Co. Co. Co. Co. Co. Co	Alter Start Start Alter Start Start Alter Start Start Alter Start		3172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 93172 3332 9317 3332 9317 3332 9317 3332 9317 3332 9317 3332 9317 3332 9317 3332 9317 3332 9317 3332 9317 3332 9317 3332 9317 3332 9317 3332 9317 3332		i Det Y2 If T. P5 riol Auge Auto View Table The Case Table To an and the Case Table The Case Table The Case Table The Case Table	
A Ka Contraction of the second s	MIOLANO MIOLAN	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Constant Consta	Alter Stand		3172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 93172 3335 9317 3335 9317 3355 9317 3355 9317 3355 9317 3355 9317 3355 9317 3355 9317 3355 9317 3355 9317 3355 9317 3355 9317 3355 9317 3355 9317 3355		i Det Y2 If T. P5 riol Auge The T. P5 riol Auge The T. P5 riol Auge The T. P5 riol Auge The T. P5 riol Auge T. J. T. P5 riol Aug T. J. T. P5 riol Aug T. J. T. P5 riol Aug T. J. T. P5 riol Auge T. J. T. P5 riol Aug T. J. T. P5 riol Aug T. J. T.	
A Ka C		Tat L Inc 2397 Tat L Inc 22016 - 75407 SID ST 105 ST Mrs. Slongther Mrs. Slongther 1 - Eocc C60572 10 10 10 10 10 10 10 10 10 10	Constant Consta	Alter Stand		3172 3335 3172 3335 32 3335 337 3335 337 3335 337 3335 337 3335 337 3335 337 3335 337 3335 338 3335 338 3335 338 3335 338 3335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335 338 335		i Det Y2 I Carp rist Response Res	
A KA		THE AND A THE A THE AND A THE	A the second sec	Constant Consta	20 10 10 10 10 10 10 10 10 10 1	3172 3335 3172 3335 32 3335 337 3335 337 3335 337 3335 337 3335 337 3335 337 3335 337 3335 337 3335 338 335 <t< td=""><td>Clark Steel Clark /td><td>ARC VOIL ALLON ALL</td><td></td></t<>	Clark Steel Clark	ARC VOIL ALLON ALL	
A KA		Tel 1. Inc. Tel 1. Inc. F2016 - F3407 S10. S1 S10. S1 Mrs. Sloather Mrs. Sloather Scostz 10 10 10 10 10 10 10 10 10 10	A de la serie de l	ALCONTRACTOR	200720 W F	3172 3335 3172 3335 32 33 34 35 36 37 37 37 37 37 37 37 37 37 37 37 37 37 37 37 38 37 38 38 39 39 39 39 39 39 39 39 39 39 39 39 39 39 39 39 <td< td=""><td>Clack Stern Clack Stern Stern Clack Stern Clack Stern</td><td>ARE VERSION ALLON /td><td></td></td<>	Clack Stern Clack Stern Stern Clack Stern Clack Stern	ARE VERSION ALLON	

1 inch = 3,000 feet

0 7501,500 3,000

Map Prepared by: agreen Date: April 18, 2019 filename: OneMileRadius_Plat Sources: IHS Energy; Midland Map Company; Environmental Systems Research Institute [ESRI];