

RECEIVED

FEB 26 2020

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

EMNRD-OCD ARTESIA

WELL API NO.
30-015-30934

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

HARROUN 15

8. Well Number #010

9. OGRID Number

16696

10. Pool name or Wildcat

CEDAR CANYON; DELAWARE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

OXY USA INC

3. Address of Operator

PO BOX 4294, HOUSTON, TX 77210

4. Well Location

Unit Letter K : 1700 feet from the SOUTH line and 2310 feet from the WEST line

Section 15 Township 24S Range 29E NMPM County EDDY

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

2920'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐CLOSED-LOOP SYSTEM ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/6/20 MIRU.

2/7/20 POOH with rods and pump. NU and function test BOP. Release TAC and POOH with tubing.

2/10/20 Continue to POOH with tubing. RIH and set CIBP at 5202'.

2/11/20 Pumped 35sx class c cement on top of CIBP. POOH and WOC.

2/12/20 RIH and tag cement at 4710'. Notified NMOCD. POOH, EOT at 3020'. Pumped 40sx class c cement. POOH and WOC.

2/13/20 RIH and tag cement at 2386'. Notified NMOCD. RU wireline. RIH and shot perfs at 650'. RD wireline.

Break circulation and switch to cement, saw cement through surface casing. Notified NMOCD and confirmed new plan. Pumped 23sx class c cement from 448' to 221'. Pumped 28sx class c cement to surface. Confirmed with NMOCD. RDMO.

Approved for plugging of well bore only.
Licensee under bond is retained pending receipt
of OCS Subsequent Report of Well Plugging
which may be found at OCD Web Page under
Forms, www.emnrd.state.nm.us/oed.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE REGULATORY ADVISOR

DATE 2/20/20

Type or print name

LESLIE REEVES

E-mail address: LESLIE_REEVES@OXY.COM

PHONE: 713-497-2492

For State Use Only

APPROVED BY:

TITLE

Staff mg

DATE 2/27/20

Conditions of Approval (if any):

7