

Office

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1283

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3811

1220 S. St. Francis Dr., Santa Fe, NM

87505

Energy, Minerals and Natural Resources

RECEIVED

FEB 24 2020

CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

EMNRD-OCDARTESIA

WELL API NO.
30-015-30951

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

HARROUN 15

8. Well Number #011

9. OGRID Number
1669610. Pool name or Wildcat
CEDAR CANYON DELWARE

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

OXY USA INC.

3. Address of Operator

PO BOX 4294, HOUSTON, TX 77210

4. Well Location

Unit Letter O : 800 feet from the SOUTH line and 1900 feet from the EAST lineSection 15 Township 24S Range 29E NMPM County EDDY

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

2923'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐CLOSED-LOOP SYSTEM ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☒CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/29/20 MIRU. POOH with rods and pump.

1/30/20 Continue to POOH with rods and pump. RU BOP and function test, good test. (0# tbq psi) Pump 70bbls hot fresh water down tubing. POOH with tubing.

2/3/20 RIH and set CIBP @ 5196'. Pumped 35sx class c cement on top of CIBP. EOT @2983'. WOC.

2/4/20 RIH and tagged cement at 4800', POOH. Confirmed with NMOCD, Gilbert Cordero. RU wireline, RIH and perforated 6 holes at 2980'. POOH with perf gun and RD wireline. RIH with EOT at 3078', pumped 65sx class c cement 1.32 yield. WOC. RIH and tagged cement 2096'. RU wireline and RIH with perf gun to 613', perforate 6 holes. POOH and RD wireline. Pumped 4bbls and saw cement out of surface casing.

2/6/20 NDBOP. Pumped 178sx (42bbls) class c cement 1.32 yield from 613' to surface. RDMO.

Spud Date:

Rig Release Date:

2/6/20

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 / Subsequent Report of Well Plugging
which may be found at OCD Web Page under
www.emnrd.state.nm.us/oecd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE REGULATORY ADVISOR

DATE 2/20/20

Type or print name LESLIE REEVES

E-mail address: LESLIE_REEVES@OXY.COM PHONE: 713-497-2492

For State Use Only

APPROVED BY:

TITLE

DATE 2/27/20

Conditions of Approval (if any):

76